Release65:NWChem Documentation

__NOTITLE__

NWChem 6.5 User Documentation

Overview __NOTITLE__

- Comprehensive Suite of Scalable Capabilities
- Compiling NWChem
- Getting Started
- Top-level Directives
- NWChem Architecture
- Running NWChem

System Description __NOTITLE__

- Charge
- Geometry
- Basis Sets
- Effective Core Potentials
- Relativistic All-electron Approximations

Quantum Mechanical Methods __NOTITLE__

- Hartree-Fock (HF) Theory
- Density Functional Theory (DFT)
- Excited-State Calculations (CIS, TDHF, TDDFT)
- Real-time TDDFT
- Plane-Wave Density Functional Theory (plane-wave DFT)
- Tensor Contraction Engine: CI, MBPT, and CC
- MP2
- Coupled Cluster Calculations
- Multiconfiguration SCF
- Selected CI

Classical Methods __NOTITLE__

- Prepare
- Molecular Dynamics
- Analysis

Hybrid Approaches __NOTITLE__

- COSMO Solvation Model
- Solvation Model Based on Density (SMD) Model
- Vertical Excitation or Emission (VEM) Model
- Hybrid Calculations with ONIOM
- Combined Quantum and Molecular Mechanics (QM/MM)

• External Charges (Bq)

Potential Energy Surface Analysis __NOTITLE__

- Constraints for Optimization
- Geometry Optimization (Minimization & Transition State Search)
- Hessians & Vibrational Frequencies
- Nudged Elastic Band (NEB) and Zero Temperature String Methods

Electronic Structure Analysis __NOTITLE__

- Molecular Properties
- Electrostatic Potential Charges
- DPLOT

Other Capabilities __NOTITLE__

- Electron Transfer Calculations
- VSCF
- Dynamical Nucleation Theory Monte Carlo
- Correlation Consistent Composite Approach (ccCA)
- Controlling NWChem with Python
- Interfaces to Other Programs

Examples __NOTITLE__

- Sample input files
- Examples of geometries using symmetry

Supplementary Information

- Global Arrays^[1]
- ARMCI^[2]
- ParSoft ^[3]

References

- [1] http://www.emsl.pnl.gov/docs/global/
- [2] http://www.emsl.pnl.gov/docs/parsoft/armci/index.html
- [3] http://www.emsl.pnl.gov/docs/parsoft/tools.html

Overview

Release65:Capabilities

__NOTITLE__

Comprehensive Suite of Scalable Capabilities

NWChem provides many methods for computing the properties of molecular and periodic systems using standard quantum mechanical descriptions of the electronic wavefunction or density. Its classical molecular dynamics capabilities provide for the simulation of macromolecules and solutions, including the computation of free energies using a variety of force fields. These approaches may be combined to perform mixed quantum-mechanics and molecular-mechanics simulations.

The specific methods for determining molecular electronic structure, molecular dynamics, and pseudopotential plane-wave electronic structure and related attributes are listed in the following sections.

Molecular Electronic Structure

Methods for determining energies and analytic first derivatives with respect to atomic coordinates include the following:

- Hartree-Fock (RHF, UHF, high-spin ROHF)
- Gaussian orbital-based density functional theory (DFT) using many local and non-local exchange-correlation potentials (LDA, LSDA)
- second-order perturbation theory (MP2) with RHF and UHF references
- complete active space self-consistent field theory (CASSCF).

Analytic second derivatives with respect to atomic coordinates are available for RHF and UHF, and closed-shell DFT with all functionals.

The following methods are available to compute energies only:

- iterative CCSD, CCSDT, and CCSDTQ methods and their EOM-CC counterparts for RHF, ROHF, and UHF references
- active-space CCSDt and EOM-CCSDt approaches
- completely renormalized CR-CCSD(T), and CR-EOM-CCSD(T) correction to EOM-CCSD excitation energies
- locally renormalized CCSD(T) and CCSD(TQ) approaches
- non-iterative approaches based on similarity transformed Hamiltonian: the CCSD(2)T and CCSD(2) formalisms.
- MP2 with RHF reference and resolution of the identity integral approximation MP2 (RI-MP2) with RHF and UHF references
- selected CI with second-order perturbation correction.

For all methods, the following may be performed:

• single point energy calculations

- geometry optimization with constraints (minimization and transition state)
- molecular dynamics on the fully ab initio potential energy surface
- automatic computation of numerical first and second derivatives
- normal mode vibrational analysis in Cartesian coordinates
- ONIOM hybrid calculations
- Conductor-Like Screening Model (COSMO) calculations
- electrostatic potential from fit of atomic partial charges
- spin-free one-electron Douglas-Kroll calculations
- electron transfer (ET)
- vibrational SCF and DFT.

At the SCF and DFT level of theory various (response) properties are available, including NMR shielding tensors and indirect spin-spin coupling.

Quantum Mechanics/Molecular Mechanics (QM/MM)

The QM/MM module in NWChem provides a comprehensive set of capabilities to study ground and excited state properties of large-molecular systems. The QM/MM module can be used with practically any quantum mechanical method available in NWChem. The following tasks are supported

- single point energy and property calculations
- excited states calculation
- optimizations and transition state search
- dynamics
- free energy calculations.

Pseudopotential Plane-Wave Electronic Structure

The NWChem Plane-Wave (NWPW) module uses pseudopotentials and plane-wave basis sets to perform DFT calculations. This method's efficiency and accuracy make it a desirable first principles method of simulation in the study of complex molecular, liquid, and solid-state systems. Applications for this first principles method include the calculation of free energies, search for global minima, explicit simulation of solvated molecules, and simulations of complex vibrational modes that cannot be described within the harmonic approximation.

The NWPW module is a collection of three modules:

- PSPW (PSeudopotential Plane-Wave) A gamma point code for calculating molecules, liquids, crystals, and surfaces.
- Band A band structure code for calculating crystals and surfaces with small band gaps (e.g. semi-conductors and metals).
- PAW (Projector Augmented Wave) a gamma point projector augmented plane-wave code for calculating molecules, crystals, and surfaces.

These capabilities are available:

- constant energy and constant temperature Car-Parrinello molecular dynamics (extended Lagrangian dynamics)
- LDA, PBE96, and PBE0, exchange-correlation potentials (restricted and unrestricted)
- SIC, pert-OEP, Hartree-Fock, and hybrid functionals (restricted and unrestricted)

- Hamann, Troullier-Martins, Hartwigsen-Goedecker-Hutter norm-conserving pseudopotentials with semicore corrections
- geometry/unit cell optimization, frequency, transition-states
- fractional occupation of molecular orbitals for metals
- AIMD/MM capability in PSPW
- constraints needed for potential of mean force (PMF) calculation
- wavefunction, density, electrostatic, Wannier plotting
- band structure and density of states generation

Molecular Dynamics

The NWChem Molecular Dynamics (MD) module can perform classical simulations using the AMBER and CHARMM force fields, quantum dynamical simulations using any of the quantum mechanical methods capable of returning gradients, and mixed quantum mechanics molecular dynamics simulation and molecular mechanics energy minimization.

Classical molecular simulation functionality includes the following methods:

- single configuration energy evaluation
- energy minimization
- molecular dynamics simulation
- free energy simulation (MCTI and MSTP with single or dual topologies, double-wide sampling, and separation-shifted scaling).

The classical force field includes the following elements:

- effective pair potentials
- first-order polarization
- self-consistent polarization
- smooth particle mesh Ewald
- twin-range energy and force evaluation
- periodic boundary conditions
- SHAKE constraints
- constant temperature and/or pressure ensembles
- dynamic proton hopping using the Q-HOP methodology
- advanced system setup capabilities for biomolecular membranes.

Compiling NWChem

__NOTITLE__

Compiling NWChem from source

On this page, a step-by-step description of the build process and necessary and optional environment variables is outlined. In addition, based on the experiences of developers and users how-to's for various platforms have been created. These how-to's will be updated with additional platforms and better environment variables over time.

Setting up the proper environment variables

• **NWCHEM_TOP** defines the top directory of the NWChem source tree, e.g.

% setenv NWCHEM_TOP <your path>/nwchem

• NWCHEM_TARGET defines your target platform, e.g.

% setenv NWCHEM_TARGET LINUX64

NWCHEM_TARGET	Platform	OS/Version	Compilers
LINUX	x86 ppc	RedHat, MDK, SLES YD2.1, SLES	GNU, Intel, PGI GNU, xlf
LINUX64	ia64 x86_64 ppc64	RedHat SLES, RedHat SLES, RedHat	Intel GNU, PGI, PathScale, Intel xlf
BGL BGP	Bluegene/L Bluegene/P	SLES	blrts_xlf bgxlf
LAPI LAPI64	IBM SP	AIX/LAPI	
IBM IBM64	IBM RS/6000	AIX	
MACX MACX64	Apple MacOSX	OSX, Lion	GNU, xlf, Intel
CYGWIN WIN32	Intel x86	Windows with Cygwin Windows	GNU Compaq
SGI_N32 SGITFP	SGI 64 bit OS using 32 bit integers SGI 64 bit OS	IRIX	
HPUX HPUX64	PA-RISC PA-RISC, ia64	HPUX	

The platforms that available are:

• **ARMCI_NETWORK** must be defined in order to achieve best performance on high performance networks, .e.g.

% setenv ARMCI_NETWORK OPENIB

For a single processor system, this environment variable does not have to be defined.

ARMCI_NETWORK	NWCHEM_TARGET	Network	Protocol
OPENIB	LINUX, LINUX64	InfiniBand	OpenIB
MPI-MT	LINUX64	Myrinet MX, Infiniband	MPI2
MPI-SPAWN			
MPI-TS	any	any network with MPI	MPI
MELLANOX	LINUX, LINUX64	InfiniBand	VAPI
GM	LINUX, LINUX64	Myrinet	GM
DMAPP	LINUX64	Cray Gemini & Aries	DMAPP
GEMINI	LINUX64	Cray Gemini	Gemini
PORTALS	LINUX64	Cray SeaStar/HyperTransport	PORTALS
BGMLMPI	BGL	IBM BlueGene Torus	BGLMPI
DCMFMPI	BGP	Global Tree/Interrupt	DCMF, MPI
VIA	LINUX	Giganet/CLAN	VIA

Supported combination of ARMCI_NETWORK and NWCHEM_TARGET variables:

Some more information can be found on the global arrays/armci web page ^[1].

• **MPI variables needed to compile.** For a single processor system, these environment variables do not have to be defined.

USE_MPI	Set to "y" to indicate that NWChem should be compiled with MPI
USE_MPIF	Set to "y" for the NWPW module to use for tran-bindings of MPI (Generally set when $\ensuremath{\text{USE_MPI}}$ is set)
USE_MPIF4	Set to "y" for the NWPW module to use Integer*4 for tran-bindings of MPI. (Generally set when USE_MPI is set on most platforms)
LIBMPI	Name of the MPI library that should be linked with -l (eglmpich)
MPI_LIB	Directory where the MPI library resides
MPI_INCLUDE	Directory where the MPI include files reside

The output of the command

mpif90 -show

can be used to extract the values of LIBMPI, MPI_LIB and MPI_INCLUDE $% \label{eq:limit}$

E.g. for MPICH2, this might look like:

```
$ mpif90 -show
f95 -I/usr/local/mpich2.141p1/include -I/usr/local/mpich2.141p1/include
-L/usr/local/mpich2.141p1/lib \
-lmpichf90 -lmpichf90 -lmpich -lopa -lmpl -lrt -lpthread
```

The corresponding environment variables are

```
% setenv USE_MPI y
% setenv LIBMPI "-lmpich -lopa -lmpl -lpthread -lmpichf90 -lfmpich
```

-lmpich"
% setenv MPI_LIB /usr/local/mpich2.141p1/lib
% setenv MPI INCLUDE '/usr/local/mpich2.141p1/include

Note: a script is available in NWChem 6.5 to extract the environment variables listed above \$NWCHEM TOP/contrib/distro-tools/getmpidefs nwchem

For some specific implementations the settings for MPI_LIB, MPI_INCLUDE, and LIBMPI look like:

MPI Implementation	Environment variables
MPICH	setenv MPI_LOC /usr/local #location of mpich installation setenv MPI_LIB \$MPI_LOC/lib
	setenv MPI_INCLUDE \$MPI_LOC/include
	setenv LIBMPI "-lfmpich -lmpich -lpmpich"
MPICH2	setenv MPI_LOC /usr/local #location of mpich2 installation
	setenv MPI_LIB \$MPI_LOC/lib
	setenv MPI_INCLUDE \$MPI_LOC/include
	setenv LIBMPI "-lmpich -lopa -lmpl -lrt -lpthread"
OPENMPI	setenv MPI_LOC /usr/local #location of openmpi installation
	setenv MPI_LIB \$MPI_LOC/lib
	setenv MPI_INCLUDE \$MPI_LOC/include
	setenv LIBMPI "-lmpi f90 -lmpi f77 -lmpi -ldl -Wl,export-dynamic
	-lnsl -lutil"

Note:

When MPI is used, the appropriate MPI run command should be used to start an NWChem calculation, e.g.

% mpirun -np 8 \$NWCHEM_TOP/bin/\${NWCHEM_TARGET}}/nwchem h2o.nw

When all nodes are connected via shared memory and the ch_shmem version of MPICH is installed and used, NWChem can be called directly, e.g.

```
% $NWCHEM_TOP/bin/${NWCHEM_TARGET}/nwchem -np 8 h2o.nw
```

• **NWCHEM_MODULES** defines the modules to be compiled, e.g.

% setenv NWCHEM_MODULES "all python"

The following modules are available:

Module	Description
all	Everything useful
all python	Everything useful plus python
qm	All quantum mechanics modules
md	MD only build

Note that additional environment variables need to be defined to specify the location of the Python libraries, when the python module is compiled. See the optional environmental variables section for specifics.

Adding optional environmental variables

USE_NOFSCHECK can be set to avoid NWChem creating files for each process when testing the size of the scratch directory (a.k.a. creation of junk files), e.g.

% setenv USE_NOFSCHECK TRUE

USE_NOIO can be set to avoid NWChem 6.5 doing I/O for the ddscf, mp2 and ccsd modules (it automatically sets USE_NOFSCHECK, too). It is strongly recommended on large clusters or supercomputers or any computer lacking any fast and large local filesystem.

% setenv USE_NOIO TRUE

LIB_DEFINES can be set to pass additional defines to the C preprocessor (for both Fortran and C), e.g.

% setenv LIB_DEFINES -DDFLT_TOT_MEM=16777216

Note: -DDFLT_TOT_MEM sets the default dynamic memory available for NWChem to run, where the units are in doubles. Instead of manually defining these one can optionally use the "getmem.nwchem" script in the \$NWCHEM_TOP/contrib directory. This script should be run after an initial build of the binary has been completed. The script will assess memory availability and make an educated guess, recompile the appropriate files and relink.

MRCC_THEORY can be set to request the multireference coupled cluster capability to be included in the code, e.g.

% setenv MRCC_THEORY TRUE

Setting Python environment variables

Python programs may be embedded into the NWChem input and used to control the execution of NWChem. To build with Python, Python needs to be available on your machine. The software can be download from http://www.python.org . Follow the Python instructions for installation and testing. NWChem has been tested with Python versions 1.x and 2.x.

The following environment variables need to be set when compiling with Python:

```
% setenv PYTHONHOME /usr/local/Python-1.5.1
```

```
% setenv PYTHONVERSION 1.5
```

Note that the third number in the version should not be kept: 2.2.3 should be set as 2.2 The following env. variables might be required

```
% setenv USE_PYTHON64 y
% setenv PYTHONLIBTYPE so
% setenv PYTHONCONFIGDIR config-x86_64-linux-gnu
```

USE_PYTHON64 is needed on platforms were the Python library is found under the /usr/lib64 tree instead of /usr/lib (e.g. 64-bit RHEL6: /usr/lib64/python2.6/config/libpython2.6.so).

PYTHONLIBTYPE=so needs to be set when static libraries are not present, and shared libraries needs to be used, instead (/usr/lib64/python2.6/config/libpython2.6.a vs /usr/lib64/python2.6/config/libpython2.6.so).

PYTHONCONFIGDIR needs to be set when the name of the subdirectory containing the Python library is not config (e.g. config-x86_64-linux-gnu instead of config).

To run with Python, make sure that PYTHONHOME is set as mentioned above. You will also need to set PYTHONPATH to include any modules that you are using in your input. Examples of Python within NWChem are in the \$NWCHEM_TOP/QA/tests/pyqa and \$NWCHEM_TOP/contrib/python directories.

Using optimized math libraries

By default NWChem uses its own basic linear algebra subroutines (BLAS). To include faster BLAS routines, the environment variable BLASOPT needs to be set before building the code. For example, with ATLAS

% setenv BLASOPT "-L/usr/local/ATLAS -llapack -lf77blas -latlas"

Good choices of optimized BLAS libraries on x86 (e.g. LINUX and LINUX64) hardware include:

OpenBLAS	[2]
GotoBLAS	[3]
Intel MKL	[4]
AMD ACML	[5]
ATLAS	http://math-atlas.sf.net
Cray LibSci	Available only on Cray x86 64 hardware, it is automatically linked when compiling on Cray
	XT and XE computers.

NWChem can also take advantage of the ScaLAPACK library ^[6] if it is installed on your system. The following environment variables need to be set:

```
% setenv USE_SCALAPACK y
```

% setenv SCALAPACK "location of Scalapack and BLACS library"

WARNING: In the case of 64-bit platforms, most vendors optimized BLAS libraries cannot be used. This is due to the fact that while NWChem uses 64-bit integers (i.e. integer*8) on 64-bit platforms, most of the vendors optimized BLAS libraries used 32-bit integers. The same holds for the ScaLAPACK libraries, which internally use 32-bit integers.

A method is now available to link against the libraries mentioned above, using the following procedure:

```
% cd $NWCHEM_TOP/src
% make clean
% make 64_to_32
% make USE_64T032=y BLASOPT=" optimized BLAS"
```

E.g., for IBM64 this looks like

% make USE_64T032=y BLASOPT="-lessl -lmass"

Notes:

• GotoBLAS2 can be installed with 64bit integers. This is accomplished by compiling the GotoBLAS2 library after having by edited the GotoBLAS2 Makefile.rule file and

un-commenting the line containing the INTERFACE64 definition. In other words, the line

```
#INTERFACE64 = 1
```

needs to be changed to

INTERFACE64 = 1

ACML and MKL can support 64-bit integers if the appropriate library is chosen. For MKL, one can choose the ILP64 Version of Intel® MKL and the correct recipe can be extracted from the website https://software.intel.com/en-us/articles/intel-mkl-link-line-advisor.
 For ACML the int64 libraries should be chosen, e.g. in the case of ACML 4.4.0 using a PGI compiler /opt/acml/4.4.0/pgi64_int64/lib/libacml.a

Linking in NBO

The current versions of NBO provide a utility to generate source code that can be linked into computational chemistry packages such as NWChem. To utilize this functionality, follow the instructions in the NBO package to generate an nwnbo.f file. Linking NBO into NWChem can be done using the following procedure:

```
% cd $NWCHEM_TOP/src
% cp nwnbo.f $NWCHEM_TOP/src/nbo/.
% make nwchem_config NWCHEM_MODULES="all nbo"
% make
```

One can now use "task nbo" and incorporate NBO input into the NWChem input file directly:

nbo \$NBO NRT \$END ... end

task nbo

Building the NWChem binary

Once all required and optional environment variables have been set, NWChem can be compiled:

```
% cd $NWCHEM_TOP/src
% make nwchem_config
% make >& make.log
```

The make above will use the standard compilers available on your system. To use compilers different from the default one can either set environment variables:

```
% setenv FC <fortran compiler''>
% setenv CC <c compiler>
```

Or one can supply the compiler options to the make command, e.g:

% make FC=ifort CC=icc

For example, on Linux FC could be set either equal to ifort, gfortran or pgf90

Note 1: If in a Linux environment, FC is set equal to anything other than the tested compilers, there is no guarantee of a successful installation, since the makefile structure has not been tested to process other settings. In other words, please avoid make FC="ifort -O3 -xhost" and stick to make FC="ifort", instead

Note 2: It's better to avoid redefining CC, since a) NWChem does not have C source that is a computational bottleneck and b) we typically test just the default C compiler. In other words, the recommendation is to compile with make FC=ifort

Note 3: It's better to avoid modifying the values of the FOPTIMIZE and COPTIMIZE variables. The reason is that the default values for FOPTIMIZE and COPTIMIZE have been tested by the NWChem developers (using the internal QA suites, among others), while any modification might produce incorrect results.

How-to: Build_nwchem script

The build_nwchem script is an auto-compile tool. It guesses the configuration of your machine based on the results of a number of tests and compiles a corresponding binary. It is of course possible that the script guesses something wrong in which case that setting can be corrected by manually specifying the corresponding environment variable. See the other platform how-to's for details on those variables. The only requirement to use the script is that the MPI compiler wrappers (e.g. mpif90, mpicc and mpiCC) should be in your path, and that if your machine uses the "module" software you should have all modules you want to use loaded. If these requirements are met then simply run

```
% cd <your path>/nwchem
```

% ./contrib/distro-tools/build_nwchem | tee build_nwchem.log

In the file build_nwchem.log you will find under "Building NWChem" a report on what platform the script thinks you are using.

How-to: Linux workstation platforms

- Common environmental variables for building in serial or in parallel with MPI
- % setenv NWCHEM_TOP <your path>/nwchem
- % setenv NWCHEM_TARGET LINUX64
- % setenv NWCHEM_MODULES all

Common environmental variables for building with MPI

The following environment variables need to be set when NWChem is compiled with MPI:

```
% setenv USE_MPI y
% setenv USE_MPIF y
% setenv USE_MPIF4 y
% setenv MPI_LOC <your path>/openmpi-1.4.3 (for example, if you
are using OpenMPI)
% setenv MPI_LIB <your path>/openmpi-1.4.3/lib
% setenv MPI_INCLUDE <your path>/openmpi-1.4.3/include
% setenv LIBMPI "-lmpi_f90 -lmpi_f77 -lmpi -lpthread"
```

• Compiling the code once all variables are set

```
% cd $NWCHEM_TOP/src
```

- % make nwchem_config
- % make FC=gfortran >& make.log

How to: Mac platforms

Compilation of NWChem 6.3 release on Mac OS X 10.7

- Download and unpack latest NWChem tarball to the directory of your choosing, say /Users/johndoe/nwchem
- Download XCode from the App store ^[7]
- From within Xcode install command line tools
- Download gfortran 4.6.2 ^[8] from http://gcc.gnu.org/wiki/GFortranBinaries#MacOS
- To compile serial version of NWChem 6.1.1 set (unset) the following environmental variables

```
unsetenv USE_MPI
setenv NWCHEM_MODULES all
setenv OLD_GA yes
setenv NWCHEM_TARGET MACX
setenv NWCHEM_TOP /Users/johndoe/nwchem
```

• Go to your source directory, configure, and compile

```
cd /Users/johndoe/nwchem/src
make nwchem_config
make
```

• That is it !

Compilation of NWChem 6.5 release on Mac OS X 10.9 x86_64

- Download and unpack latest NWChem tarball to the directory of your choosing, say /Users/johndoe/nwchem
- Install Homebrew as described at http://brew.sh

ruby -e "\$(curl -fsSL https://raw.github.com/Homebrew/homebrew/go/install)"

• Use Homebrew to install mpich2

brew install mpich2

• As usual, set the env. variables

```
setenv USE_MPI y
setenv NWCHEM_MODULES all
setenv NWCHEM_TARGET MACX64
setenv NWCHEM_TOP /Users/johndoe/nwchem
```

• Important: set the following env. variable (GA will not compile otherwise)

```
setenv CFLAGS_FORGA "-DMPICH_NO_ATTR_TYPE_TAGS"
```

• Go to your source directory, configure, and compile

```
cd /Users/johndoe/nwchem/src
make nwchem_config
make
```

How-to: Cray platforms

Common environmental variables for building and running on the Cray XT and XE:

```
% setenv NWCHEM_TOP <your path>/nwchem
% setenv NWCHEM_TARGET LINUX64
% setenv NWCHEM_MODULES all
% setenv USE_MPI y
% setenv USE_MPIF y
% setenv USE_MPIF4 y
% setenv USE_SCALAPACK y
% setenv USE_64T032 y
% setenv LIBMPI " "
```

• Portals, e.g. XT3, XT4, XT5

Set the following environmental variable for compilation:

```
% setenv ARMCI_NETWORK PORTALS
```

• Gemini, e.g. XE6

Load the onsided module by executing the command

```
% module load onesided
```

Note: Preferred version of onesided is 1.5.0 or later ones.

Set the environmental variable for compilation:

- % setenv ARMCI_NETWORK GEMINI
 % setenv ONESIDED_USE_UDREG 1
- % setenv ONESIDED_UDREG_ENTRIES 2048

Aries, e.g. XC30

Compilation instructions for GNU compilers:

```
% module swap PrgEnv-intel PrgEnv-gnu
```

(assuming that was loaded PrgEnv-intel, this might not necessary be the case \dots)

Might need to execute

```
% module load craype-hugepages64M
```

Strongly recommended: replace ga-5-3 with GA/ARMCI developed by Cray folks. The software is hosted on github at https://github.com/ryanolson/ga^[9]. Instructions:

```
% cd $NWCHEM_TOP/src/tools
% wget https://github.com/ryanolson/ga/archive/cray.zip -0 cray.zip
% unzip cray.zip
% setenv GA_DIR ga-cray
```

Set the environmental variable for compilation:

```
% setenv ARMCI_NETWORK DMAPP
% setenv USE_SCALAPACK y
% setenv SCALAPACK -lsci_gnu
% setenv SCALAPACK_LIB -lsci_gnu
% setenv BLASOPT -lsci_gnu
% setenv BLAS_LIB -lsci_gnu
% setenv LAPACK_LIB -lsci_gnu
% setenv USE 64T032 y
```

in the PBS script, add the following env. variables definitions

% setenv HUGETLB_MORECORE yes
% setenv HUGETLB DEFAULT PAGE SIZE 8M

• Compiling the code on Cray once all variables are set

% cd \$NWCHEM_TOP/src

% make nwchem_config

```
% make 64_to_32
```

```
% make FC=ftn >& make.log
```

How-to: Intel Xeon Phi

• Compiling NWChem on hosts equipped with Intel Xeon Phi Knights Corner HW

NWChem 6.5 offers the possibility of using Intel Xeon Phi hardware to perform the most computationally intensive part of the CCSD(T) calculations (non-iterative triples corrections).

Required for compilation: Intel Composer XE version 14.0.3 (or later)

Environmental variables required for compilation

% setenv USE_OPENMP 1

```
% setenv USE_OFFLOAD 1
```

Environmental variables needed at run-time.

OMP_NUM_THREADS is needed for the thread-level parallelization on the Xeon CPU hosts

% setenv OMP_NUM_THREADS 4

MIC_USE_2MB_BUFFER greatly improve communication between host and Xeon Phi card

% setenv MIC_USE_2MB_BUFFER 16K

Examples of configurations: ...

How-to: IBM platforms

• Compiling NWChem on BLUEGENE/L

The following environment variables need to be set

```
% setenv NWCHEM TOP <your path>/nwchem
 % setenv NWCHEM TARGET BGL
 % setenv ARMCI NETWORK BGMLMPI
 % setenv BGLSYS DRIVER /bgl/BlueLight/ppcfloor
 % setenv BGLSYS ROOT ${BGLSYS DRIVER}/bglsys
 % setenv BLRTS GNU ROOT ${BGLSYS DRIVER}/blrts-gnu
 % setenv BGDRIVER ${BGLSYS DRIVER}
 % setenv BGCOMPILERS ${BLRTS GNU ROOT}/bin
 % setenv USE MPI y
 % setenv LARGE FILES TRUE
 % setenv MPI_LIB ${BGLSYS ROOT}/lib
 % setenv MPI INCLUDE ${BGLSYS ROOT}/include
 % setenv LIBMPI "-lfmpich .rts -lmpich.rts -lmsglayer.rts -lrts.rts
-ldevices.rts"
 % setenv BGMLMPI_INCLUDE /bgl/BlueLight/ppcfloor/bglsys/include
 % setenv BGMLLIBS /bgl/BlueLight/ppcfloor/bglsys/lib
```

To compile, the following commands should be used:

```
% cd $NWCHEM_TOP/src
% make nwchem_config
```

% make FC=blrts_xlf >& make.log

• Compiling NWChem on BLUEGENE/P

The following environment variables need to be set

```
% setenv NWCHEM TARGET BGP
 % setenv ARMCI NETWORK DCMFMPI
 % setenv MSG COMMS DCMFMPI
 % setenv USE MPI y
 % setenv LARGE FILES TRUE
 % setenv BGP INSTALLDIR /bgsys/drivers/ppcfloor
 % setenv BGCOMPILERS /bgsys/drivers/ppcfloor/gnu-linux/bin
 % setenv BGP_RUNTIMEPATH /bgsys/drivers/ppcfloor/runtime
 % setenv ARMCIDRV ${BGP_INSTALLDIR}
 % setenv BGDRIVER ${ARMCIDRV}
 % setenv MPI LIB ${BGDRIVER}/comm/lib
 % setenv MPI INCLUDE ${BGDRIVER}/comm/include
 % setenv LIBMPI "-L${MPI_LIB} -lfmpich_.cnk -lmpich.cnk
-ldcmfcoll.cnk -ldcmf.cnk -lpthread -lrt -L${BGP RUNTIMEPATH}/SPI
-lSPI.cna"
 % setenv BGMLMPI_INCLUDE ${MPI_INCLUDE}
```

To compile, the following commands should be used:

```
% cd $NWCHEM_TOP/src
```

```
% make nwchem_config
```

```
% make FC=bgxlf >& make.log
```

• Compiling NWChem on BLUEGENE/Q

The following environment variables need to be set

```
% setenv NWCHEM_TARGET BGQ
% setenv USE_MPIF y
% setenv USE_MPIF4 y
% setenv USE_MPIF4 y
% setenv MPI_INCLUDE /bgsys/drivers/ppcfloor/comm/xl/include
% setenv LIBMPI " "
% setenv BLASOPT "/opt/ibmmath/essl/5.1/lib64/libesslbg.a -llapack
-lblas -Wl,-zmuldefs "
% setenv BLAS_LIB "/opt/ibmmath/essl/5.1/lib64/libesslbg.a -zmuldefs
"
% setenv BLAS_SIZE 4
% setenv USE_64T032 y
% set path=(/bgsys/drivers/ppcfloor/gnu-linux/bin/ $path)
% setenv ARMCI_NETWORK MPI-TS
% setenv DISABLE_GAMIRROR y
```

To compile, the following commands should be used:

```
% module load bgq-xl
% make nwchem_config
% make 64_to_32 >& make6t3.log
% make >& make.log
```

WARNING: This is just a baseline port that we have tested and validated against our QA suite. There is large room for improvement both for serial performance (compiler options) and parallel performance (use of alternative ARMCI NETWORKS other than MPI-TS)

Compiling NWChem on IBM PowerPC architectures

The following environment variables should be set:

```
% setenv NWCHEM_TOP <your path>/nwchem
% setenv NWCHEM_TARGET IBM64
% setenv ARMCI_NETWORK MPI-MT
% setenv OBJECT_MODE 64
% setenv USE_MPI y
% setenv LARGE_FILES TRUE
% setenv MPI_LIB /usr/lpp/ppe.poe/lib
% setenv MPI_LIDE /usr/lpp/ppe.poe/include
% setenv LIBMPI "-lmpi -lpthreads"
```

To compile, the following commands should be used:

```
% cd $NWCHEM_TOP/src
```

```
% make nwchem_config
```

```
% make FC=xlf >& make.log
```

How-to: Commodity clusters with Infiniband

Common environmental variables for building and running on most Infiniband clusters are:

```
% setenv NWCHEM_TOP <your path>/nwchem
% setenv NWCHEM_TARGET LINUX64
% setenv NWCHEM_MODULES "all
% setenv USE_MPI y
% setenv USE_MPIF y
% setenv USE_MPIF4 y
% setenv MPI_LIB <Location of MPI library>/lib
% setenv MPI_INCLUDE <Location of MPI library>/include
% setenv LIBMPI <MPI library, e.g -lmtmpi or -lmpich>
```

• On Infiniband clusters with the OpenIB software stack, the following environment variables should be defined

```
% setenv ARMCI_NETWORK OPENIB
% setenv IB_INCLUDE <Location of Infiniband libraries>/include
% setenv MSG_COMMS MPI
```

• On Infiniband clusters that do not support OpenIB, such as Myrinet MX, the MPI2 protocol can be used

```
% setenv ARMCI_NETWORK MPI-MT
```

• Compiling the code on an Infiniband cluster once all variables are set

```
% cd $NWCHEM_TOP/src
```

% make nwchem_config

```
% make >& make.log
```

How-to: Windows Platforms

The current recommended approach for building a NWChem binary for a Windows platform is to build within Cygwin with make, perl, and gcc/gfortran version 4 installed.

```
% setenv NWCHEM_TOP <your path>/nwchem
% setenv NWCHEM_TARGET CYGWIN
% setenv NWCHEM_MODULES all
% cd $NWCHEM_TOP/src
% make nwchem_config
% make >& make.log
```

It used to be possible to build a version for native Windows using the Compaq Visual Fortran compiler. This has not been tested for the last couple of releases as the NWChem.

```
% setenv NWCHEM_TOP <your path>/nwchem
% setenv NWCHEM_TARGET WIN32
% setenv NWCHEM_MODULES all
```

To start the compilation, start the Microsoft makefile utility from the top level source directory by typing "nmake". Reminder: For Compaq visual fortran don't forget to execute the "dfvars" script.

General site installation

The build procedures outlined above will allow use of NWChem within the NWChem directory structure. The code will look for the basis set library file in a default place within that directory structure. To install the code in a general, public place (e.g., /usr/local/NWChem) the following procedure can be applied:

- Determine the local storage path for the install files. (e.g., /usr/local/NWChem).
- Make directories

```
mkdir /usr/local/NWChem
mkdir /usr/local/NWChem/bin
mkdir /usr/local/NWChem/data
```

• Copy binary

```
cp $NWCHEM_TOP/bin/${NWCHEM_TARGET}/nwchem /usr/local/NWChem/bin
cd /usr/local/NWChem/bin
chmod 755 nwchem
```

• Set links to data files (basis sets, force fields, etc.)

```
cd $NWCHEM_TOP/src/basis
cp -r libraries /usr/local/NWChem/data
```

cd \$NWCHEM_TOP/src/ cp -r data /usr/local/NWChem

cd \$NWCHEM_TOP/src/nwpw
cp -r libraryps /usr/local/NWChem/data

• Each user will need a .nwchemrc file to point to these default data files. A global one could be put in /usr/local/NWChem/data and a symbolic link made in each users \$HOME directory is probably the best plan for new installs. Users would have to issue the following command prior to using NWChem: ln -s /usr/local/NWChem/data/default.nwchemrc \$HOME/.nwchemrc

Contents of the default.nwchemrc file based on the above information should be:

```
nwchem_basis_library /usr/local/NWChem/data/libraries/
nwchem_nwpw_library /usr/local/NWChem/data/libraryps/
ffield amber
amber_1 /usr/local/NWChem/data/amber_s/
```

```
amber_2 /usr/local/NWChem/data/amber_q/
amber_3 /usr/local/NWChem/data/amber_x/
amber_4 /usr/local/NWChem/data/amber_u/
spce /usr/local/NWChem/data/solvents/spce.rst
charmm_s /usr/local/NWChem/data/charmm_s/
charmm x /usr/local/NWChem/data/charmm x/
```

Of course users can copy this file instead of making the symbolic link described above and change these defaults at their discretion.

It is can also be useful to use the NWCHEM_BASIS_LIBRARY environment variable when testing a new installation when an old one exists. This will allow you to overwrite the value of nwchem_basis_library in your .nwchemrc file and point to the new basis library. For example:

```
% setenv NWCHEM_BASIS_LIBRARY "$NWCHEM/data-5.0/libraries/"
```

Do not forget the trailing "/".

References

- [1] http://www.emsl.pnl.gov/docs/global/support.shtml
- [2] https://github.com/xianyi/OpenBLAS
- [3] http://www.tacc.utexas.edu/tacc-projects/gotoblas2
- [4] http://www.intel.com/software/products/mkl
- [5] http://developer.amd.com/?s=acml
- [6] http://www.netlib.org/scalapack/
- [7] http://itunes.apple.com/us/app/xcode/id497799835?mt=12
- [8] http://quatramaran.ens.fr/~coudert/gfortran/gfortran-4.6.2-x86_64-Lion.dmg
- [9] https://github.com/ryanolson/ga

Release65:Getting Started

__NOTITLE__

Getting Started

This section provides an overview of NWChem input and program architecture, and the syntax used to describe the input. See Simple Input File and Water Molecule Input for examples of NWChem input files with detailed explanation.

NWChem consists of independent modules that perform the various functions of the code. Examples of modules include the input parser, SCF energy, SCF analytic gradient, DFT energy, etc.. Data is passed between modules and saved for restart using a disk-resident database or dumpfile (see NWChem Architecture).

The input to NWChem is composed of commands, called directives, which define data (such as basis sets, geometries, and filenames) and the actions to be performed on that data. Directives are processed in the order presented in the input file, with the exception of certain start-up directives (see Input File Structure) which provide critical job control information, and are processed before all other input. Most directives are specific to a particular module and define data that is used by that module only. A few directives (see Top-level Directives) potentially affect all modules, for instance by specifying the total electric charge on the system.

There are two types of directives. Simple directives consist of one line of input, which may contain multiple fields. Compound directives group together multiple simple directives that are in some way related and are terminated with an END directive. See the sample inputs (Simple Input File and Water Molecule Input) and the input syntax specification (Input Format and Syntax for Directives).

All input is free format and case is ignored except for actual data (e.g., names/tags of centers, titles). Directives or blocks of module-specific directives (i.e., compound directives) can appear in any order, with the exception of the TASK directive (see Input File Structure and Tasks) which is used to invoke an NWChem module. All input for a given task must precede the TASK directive. This input specification rule allows the concatenation of multiple tasks in a single NWChem input file.

To make the input as short and simple as possible, most options have default values. The user needs to supply input only for those items that have no defaults, or for items that must be different from the defaults for the particular application. In the discussion of each directive, the defaults are noted, where applicable.

The input file structure is described in the following sections, and illustrated with two examples. The input format and syntax for directives is also described in detail.

.nwchemrc for environment variables and libraries

Each user should have a .nwchemrc file to point to default data files, such as basis sets, pseudopotentials, and MD potentials.

Contents of the default.nwchemrc file based on the above information should be:

```
nwchem_basis_library <location of NWChem
installation>/src/basis/libraries/
nwchem_nwpw_library <location of NWChem
installation>/src/nwpw/libraryps/
ffield amber
amber_1 <location of NWChem installation>/src/data/amber_s/
amber_2 <location of NWChem installation>/src/data/amber_q/
amber_3 <location of NWChem installation>/src/data/amber_x/
amber_4 <location of NWChem installation>/src/data/amber_u/
spce <location of NWChem
installation>/src/data/solvents/spce.rst
charmm_s <location of NWChem installation>/src/data/charmm_s/
charmm x <location of NWChem installation>/src/data/charmm_s/
```

It is can also be useful to use the NWCHEM_BASIS_LIBRARY environment variable when testing a new libraries in your own directory. This will allow you to overwrite the value of nwchem_basis_library in your .nwchemrc file and point to the new basis library. For example:

```
% setenv NWCHEM_BASIS_LIBRARY "$NWCHEM/data-5.0/libraries/"
```

Do not forget the trailing "/".

Input File Structure

The structure of an input file reflects the internal structure of NWChem. At the beginning of a calculation, NWChem needs to determine how much memory to use, the name of the database, whether it is a new or restarted job, where to put scratch/permanent files, etc.. It is not necessary to put this information at the top of the input file, however. NWChem will read through the entire input file looking for the start-up directives. In this first pass, all other directives are ignored.

The start-up directives are

```
START
RESTART
SCRATCH_DIR
PERMANENT_DIR
MEMORY
ECH0
```

After the input file has been scanned for the start-up directives, it is rewound and read sequentially. Input is processed either by the top-level parser (for the directives listed in Top-level Directives, such as TITLE, SET, ...) or by the parsers for specific computational modules (e.g., SCF, DFT, ...). Any directives that have already been processed (e.g., MEMORY) are ignored. Input is read until a TASK directive (see Tasks) is encountered. A

TASK directive requests that a calculation be performed and specifies the level of theory and the operation to be performed. Input processing then stops and the specified task is executed. The position of the TASK directive in effect marks the end of the input for that task. Processing of the input resumes upon the successful completion of the task, and the results of that task are available to subsequent tasks in the same input file.

The name of the input file is usually provided as an argument to the execute command for NWChem. That is, the execute command looks something like the following

nwchem input_file

The default name for the input file is nwchem.nw. If an input file name input_file is specified without an extension, the code assumes .nw as a default extension, and the input filename becomes input_file.nw. If the code cannot locate a file named either input_file or input_file.nw (or nwchem.nw if no file name is provided), an error is reported and execution terminates. The following section presents two input files to illustrate the directive syntax and input file format for NWChem applications.

Simple Input File --SCF geometry optimization

A simple example of an NWChem input file is an SCF geometry optimization of the nitrogen molecule, using a Dunning cc-pvdz basis set. This input file contains the bare minimum of information the user must specify to run this type of problem -- fewer than ten lines of input, as follows:

```
title "Nitrogen cc-pvdz SCF geometry optimization"
geometry
    n 0 0 0
    n 0 0 1.08
end
basis
    n library cc-pvdz
end
task scf optimize
```

Examining the input line by line, it can be seen that it contains only four directives; TITLE, GEOMETRY, BASIS, and TASK. The TITLE directive is optional, and is provided as a means for the user to more easily identify outputs from different jobs. An initial geometry is specified in Cartesian coordinates and Angstrøms by means of the GEOMETRY directive. The Dunning cc-pvdz basis is obtained from the NWChem basis library, as specified by the BASIS directive input. The TASK directive requests an SCF geometry optimization.

The GEOMETRY directive defaults to Cartesian coordinates and Angstrøms (options include atomic units and Z-matrix format). The input blocks for the BASIS and GEOMETRY directives are structured in similar fashion, i.e., name, keyword, ..., end (In this simple example, there are no keywords). The BASIS input block must contain basis set information for every atom type in the geometry with which it will be used. Refer to Sections 7 and 8, and Appendix A for a description of available basis sets and a discussion of how to define new ones.

The last line of this sample input file (task scf optimize) tells the program to optimize the molecular geometry by minimizing the SCF energy. (For a description of possible tasks and

the format of the TASK directive, refer to Tasks)

If the input is stored in the file n2.nw, the command to run this job on a typical UNIX workstation is as follows:

nwchem n2

NWChem output is to UNIX standard output, and error messages are sent to both standard output and standard error.

Water Molecule Sample Input File

A more complex sample problem is the optimization of a positively charged water molecule using second-order Møller-Plesset perturbation theory (MP2), followed by a computation of frequencies at the optimized geometry. A preliminary SCF geometry optimization is performed using a computationally inexpensive basis set (STO-3G). This yields a good starting guess for the optimal geometry, and any Hessian information generated will be used in the next optimization step. Then the optimization is finished using MP2 and a basis set with polarization functions. The final task is to calculate the MP2 vibrational frequencies. The input file to accomplish these three tasks is as follows:

```
start h2o freq
charge 1
geometry units angstroms
0
         0.0 0.0 0.0
Н
         0.0
             0.0
                  1.0
н
         0.0 1.0 0.0
end
basis
H library sto-3g
0 library sto-3g
end
scf
uhf; doublet
print low
end
title "H2O+ : STO-3G UHF geometry optimization"
task scf optimize
basis
H library 6-31g**
0 library 6-31g**
end
title "H2O+ : 6-31g** UMP2 geometry optimization"
task mp2 optimize
mp2; print none; end
scf; print none; end
title "H2O+ : 6-31g** UMP2 frequencies"
task mp2 freq
```

The START directive (START/RESTART tells NWChem that this run is to be started from the beginning. This directive need not be at the beginning of the input file, but it is commonly

placed there. Existing database or vector files are to be ignored or overwritten. The entry h2o_freq on the START line is the prefix to be used for all files created by the calculation. This convention allows different jobs to run in the same directory or to share the same scratch directory SCRATCH_DIR/PERMANENT_DIR, as long as they use different prefix names in this field.

As in the first sample problem, the geometry is given in Cartesian coordinates. In this case, the units are specified as Angstrøms. (Since this is the default, explicit specification of the units is not actually necessary, however.) The CHARGE directive defines the total charge of the system. This calculation is to be done on an ion with charge +1.

A small basis set (STO-3G) is specified for the initial geometry optimization. Next, the multiple lines of the first SCF directive in the scf ...end block specify details about the SCF calculation to be performed. Unrestricted Hartree-Fock is chosen here (by specifying the keyword uhf), rather than the default, restricted open-shell high-spin Hartree-Fock (ROHF). This is necessary for the subsequent MP2 calculation, because only UMP2 is currently available for open-shell systems (see Section 4). For open-shell systems, the spin multiplicity has to be specified (using doublet in this case), or it defaults to singlet. The print level is set to low to avoid verbose output for the starting basis calculations.

All input up to this point affects only the settings in the runtime database. The program takes its information from this database, so the sequence of directives up to the first TASK directive is irrelevant. An exchange of order of the different blocks or directives would not affect the result. The TASK directive, however, must be specified after all relevant input for a given problem. The TASK directive causes the code to perform the specified calculation using the parameters set in the preceding directives. In this case, the first task is an SCF calculation with geometry optimization, specified with the input scf and optimize. (See Tasks for a list of available tasks and operations.)

After the completion of any task, settings in the database are used in subsequent tasks without change, unless they are overridden by new input directives. In this example, before the second task (task mp2 optimize), a better basis set (6-31G**) is defined and the title is changed. The second TASK directive invokes an MP2 geometry optimization.

Once the MP2 optimization is completed, the geometry obtained in the calculation is used to perform a frequency calculation. This task is invoked by the keyword freq in the final TASK directive, task mp2 freq. The second derivatives of the energy are calculated as numerical derivatives of analytical gradients. The intermediate energies and gradients are not of interest in this case, so output from the SCF and MP2 modules is disabled with the PRINT directives.

Input Format and Syntax for Directives

This section describes the input format and the syntax used in the rest of this documentation to describe the format of directives. The input format for the directives used in NWChem is similar to that of UNIX shells, which is also used in other chemistry packages, most notably GAMESS-UK. An input line is parsed into whitespace (blanks or tabs) separating tokens or fields. Any token that contains whitespace must be enclosed in double quotes in order to be processed correctly. For example, the basis set with the descriptive name modified Dunning DZ must appear in a directive as "modified Dunning DZ", since the name consists of three separate words.

Input Format

A (physical) line in the input file is terminated with a newline character (also known as a `return' or `enter' character). A semicolon (;) can be also used to indicate the end of an input line, allowing a single physical line of input to contain multiple logical lines of input. For example, five lines of input for the GEOMETRY directive can be entered as follows;

```
geometry

0 0 0 0

H 0 1.430 1.107

H 0 -1.430 1.107

end
```

These same five lines could be entered on a single line, as

geometry; 0 0 0 0; H 0 1.430 1.107; H 0 -1.430 1.107; end

This one physical input line comprises five logical input lines. Each logical or physical input line must be no longer than 1023 characters.

In the input file:

- a string, token, or field is a sequence of ASCII characters (NOTE: if the string includes blanks or tabs (i.e., white space), the entire string must be enclosed in double quotes).
- \ (backslash) at the end of a line concatenates it with the next line. Note that a space character is automatically inserted at this point so that it is not possible to split tokens across lines. A backslash is also used to quote special characters such as whitespace, semi-colons, and hash symbols so as to avoid their special meaning (NOTE: these special symbols must be quoted with the backslash even when enclosed within double quotes).
- ; (semicolon) is used to mark the end of a logical input line within a physical line of input.
- # (the hash or pound symbol) is the comment character. All characters following # (up to the end of the physical line) are ignored.
- If any input line (excluding Python programs, Section 38) begins with the string INCLUDE (ignoring case) and is followed by a valid file name, then the data in that file are read as if they were included into the current input file at the current line. Up to three levels of nested include files are supported. The user should note that inputting a basis set from the standard basis library (Basis Sets) uses one level of include.
- Data is read from the input file until an end-of-file is detected, or until the string EOF (ignoring case) is encountered at the beginning of an input line.

Format and syntax of directives

Directives consist of a directive name, keywords, and optional input, and may contain one line or many. Simple directives consist of a single line of input with one or more fields. Compound directives can have multiple input lines, and can also include other optional simple and compound directives. A compound directive is terminated with an END directive. The directives START (see START/RESTART) and ECHO (see ECHO) are examples of simple directives. The directive GEOMETRY (see Release64:Geometry) is an example of a compound directive.

Some limited checking of the input for self-consistency is performed by the input module, but most defaults are imposed by the application modules at runtime. It is therefore usually

impossible to determine beforehand whether or not all selected options are consistent with each other.

In the rest of this document, the following notation and syntax conventions are used in the generic descriptions of the NWChem input.

- a directive name always appears in all-capitals, and in computer typeface (e.g., GEOMETRY, BASIS, SCF). Note that the case of directives and keywords is ignored in the actual input.
- a keyword always appears in lower case, in computer typeface (e.g., swap, print, units, bqbq).
- variable names always appear in lower case, in computer typeface, and enclosed in angle brackets to distinguish them from keywords (e.g., <input_filename>, <basisname>, <tag>).
- \$variable\$ is used to indicate the substitution of the value of a variable.
- () is used to group items (the parentheses and other special symbols should not appear in the input).
- || separate exclusive options, parameters, or formats.
- [] enclose optional entries that have a default value.
- <> enclose a type, a name of a value to be specified, or a default value, if any.
- $\$ is used to concatenate lines in a description.
- ... is used to indicate indefinite continuation of a list.

An input parameter is identified in the description of the directive by prefacing the name of the item with the type of data expected, i.e.,

- string an ASCII character string
- integer integer value(s) for a variable or an array
- logical true/false logical variable
- real real floating point value(s) for a variable or an array
- double synonymous with real

If an input item is not prefaced by one of these type names, it is assumed to be of type ``string.

In addition, integer lists may be specified using Fortran triplet notation, which interprets lo:hi:inc as lo, lo+inc, lo+2*inc, ..., hi. For example, where a list of integers is expected in the input, the following two lines are equivalent

```
7 10 21:27:2 1:3 99
7 10 21 23 25 27 1 2 3 99
```

(In Fortran triplet notation, the increment, if unstated, is 1; e.g., 1:3 = 1:3:1.)

The directive VECTORS (Section 10.5) is presented here as an example of an NWChem input directive. The general form of the directive is as follows:

This directive contains three optional keywords, as indicated by the three main sets of square brackets enclosing the keywords input, swap, and output. The keyword input allows the user to specify the source of the molecular orbital vectors. There are two mutually exclusive options for specifying the vectors, as indicated by the || symbol separating the option descriptions;

The first option, (<string input_movecs default atomic>), allows the user to specify an ASCII character string for the parameter input_movecs. If no entry is specified, the code uses the default atomic (i.e., atomic guess). The second option, (project <string basisname> <string filename>), contains the keyword project, which takes two string arguments. When this keyword is used, the vectors in file <filename> will be projected from the (smaller) basis

basisname> into the current atomic orbital (AO) basis.

The second keyword, swap, allows the user to re-order the starting vectors, specifying the pairs of vectors to be swapped. As many pairs as the user wishes to have swapped can be listed for <integer vec1 vec2 ... >. The optional keywords alpha and beta allow the user to swap the alpha or beta spin orbitals.

The third keyword, output, allows the user to tell the code where to store the vectors, by specifying an ASCII string for the parameter output_movecs. If no entry is specified for this parameter, the default is to write the vectors back into either the user- specified MO vectors input file or, if this is not available, the file \$file_prefix\$.movecs.

A particular example of the VECTORS directive is shown below. It specifies both the input and output keywords, but does not use the swap option.

```
vectors input project "small basis" small_basis.movecs \
    output large_basis.movecs
```

This directive tells the code to generate input vectors by projecting from vectors in a smaller basis named "small basis", which is stored in the file small_basis.movecs. The output vectors will be stored in the file large_basis.movecs.

The order of keyed optional entries within a directive should not matter, unless noted otherwise in the specific instructions for a particular directive.

Release65:Top-level

__NOTITLE__

Top-level Directives

Top-level directives are directives that can affect all modules in the code. Some specify molecular properties or other data that should apply to all subsequent calculations with the current database. However, most top-level directives provide the user with the means to manage the resources for a calculation and to start computations. As the first step in the execution of a job, NWChem scans the entire input file looking for start-up directives, which NWChem must process before all other input. The input file is then rewound and processed sequentially, and each directive is processed in the order in which it is encountered. In this second pass, start-up directives are ignored.

The following sections describe each of the top-level directives in detail, noting all keywords, options, required input, and defaults.

START /RESTART

The START or RESTART directive define the start-up mode and are optional keywords. If one of these two directives is not specified explicitly, the code will infer one, based upon the name of the input file and the availability of the database. When allowing NWChem to infer the start-up directive, the user must be quite certain that the contents of the database will result in the desired action. It is usually more prudent to specify the directive explicitly, using the following format:

The START directive indicates that the calculation is one in which a new database is to be created. Any relevant information that already exists in a previous database of the same name is destroyed. The string variable <file_prefix> will be used as the prefix to name any files created in the course of the calculation.

E.g., to start a new calculation on water, one might specify

```
start water
```

which will make all files begin with "water.".

If the user does not specify an entry for <file_prefix> on the START directive (or omits the START directive altogether), the code uses the base-name of the input file as the file prefix. That is, the variable <file_prefix> is assigned the name of the input file (not its full pathname), but without the last "dot-suffix". For example, the input file name /home/dave/job.2.nw yields job.2 as the file prefix, if a name is not assigned explicitly using the START directive.

The user also has the option of specifying a unique name for the database, using the keyword rtdb. When this keyword is entered, the string entered for rtdb_file_name is used

as the database name. If the keyword rtdb is omitted, the name of the database defaults to file_prefix.db in the directory for permanent files.

If a calculation is to start from a previous calculation and go on using the existing database, the RESTART directive must be used. In such a case, the previous database must already exist. The name specified for <file_prefix> usually should not be changed when restarting a calculation. If it is changed, NWChem will not be able to find needed files when going on with the calculation.

In the most common situation, the previous calculation was completed (with or without an error condition), and it is desired to perform a new task or restart the previous one, perhaps with some input changes. In these instances, the RESTART directive should be used. This re-uses the previous database and associated files, and reads the input file for new input and task information.

The RESTART directive looks immediately for new input and task information, deleting information about previous incomplete tasks. For example, when doing a RESTART there is no need to specify geometry or basis set declaration because the program will detect this information since it is stored in the run-time database.

If a calculation runs out of time, for example because it is on a queuing system, this is another instance where doing a RESTART is advisable. Simply include nothing after the RESTART directive except those tasks that are unfinished.

To summarize the default options for this start-up directive, if the input file does not contain a START or a RESTART directive, then

- the variable <file_prefix> is assigned the name of the input file for the job, without the suffix (which is usually .nw)
- the variable <rtdb_file_name> is assigned the default name, file_prefix.db

If the database with name file_prefix.db does not already exist, the calculation is carried out as if a START directive had been encountered. If the database with name file_prefix.db does exist, then the calculation is performed as if a RESTART directive had been encountered.

For example, NWChem can be run using an input file with the name water.nw by typing the UNIX command line,

nwchem water.nw

If the NWChem input file water.nw does not contain a START or RESTART directive, the code sets the variable <file_prefix> to water. Files created by the job will have this prefix, and the database will be named water.db. If the database water.db does not exist already, the code behaves as if the input file contains the directive,

start water

If the database water.db does exist, the code behaves as if the input file contained the directive,

restart water

PERMANENT_DIR

This start-up directive allows the user to specify the directory location of permanent files created by NWChem. NWChem distinguishes between permanent (or persistent) files and scratch (or temporary) files, and allows the user the option of putting them in different locations. In most installations, however, permanent and scratch files are all written to the current directory by default. What constitutes "local" disk space may also differ from machine to machine.

The PERMANENT_DIR directives enable the user to specify a single directory for all processes or different directories for different processes. The general form of the directive is as follows:

```
(PERMANENT_DIR) [(<string host&>||<integer process>):]
  <string directory> [...]
```

SCRATCH_DIR

This start-up directive allows the user to specify the directory location of scratch files created by NWChem. NWChem distinguishes between permanent (or persistent) files and scratch (or temporary) files, and allows the user the option of putting them in different locations. In most installations, however, permanent and scratch files are all written to the current directory by default. What constitutes "local" disk space may also differ from machine to machine.

The conventions for file storage are at the discretion of the specific installation, and are quite likely to be different on different machines. When assigning locations for permanent and scratch files, the user must be cognizant of the characteristics of the installation on a particular platform. To consider just a few examples, on clusters, machine-specific or process-specific names must be supplied for both local and shared file systems, while on SMPs it is useful to specify scratch file directories with automated striping across processors with round-robin allocation. On SMP clusters (a.k.a. constellations), both of these specifications are required.

The SCRATCH_DIR enables the user to specify a single directory for all processes or different directories for different processes. The general form of the directive is as follows:

```
(SCRATCH_DIR) [(<string host&>||<integer process>):]
<string directory> [...]
```

Directories are extracted from the user input by executing the following steps, in sequence:

- Look for a directory qualified by the process ID number of the invoking process. Processes are numbered from zero. Else,
- 2. If there is a list of directories qualified by the name of the host machineAs returned by util_hostname() which maps to the output of the command hostname on Unix workstations., then use round-robin allocation from the list for processes executing on the given host. Else,
- **3**. If there is a list of directories unqualified by any hostname or process ID, then use round-robin allocation from this list.

If directory allocation directive(s) are not specified in the input file, or if no match is found to the directory names specified by input using these directives, then the steps above are executed using the installation-specific defaults. If the code cannot find a valid directory name based on the input specified in either the directive(s) or the system defaults, files are automatically written to the current working directory (".").

The following is a list of examples of specific allocations of scratch directory locations:

• Put scratch files from all processes in the local scratch directory (Warning: the definition of "local scratch directory" may change from machine to machine):

scratch_dir /localscratch

• Put scratch files from Process 0 in /piofs/rjh, but put all other scratch files in /scratch:

```
scratch_dir /scratch 0:/piofs/rjh
```

• Put scratch files from Process 0 in directory scr1, those from Process 1 in scr2, and so forth, in a round-robin fashion, using the given list of directories:

scratch_dir /scr1 /scr2 /scr3 /scr4 /scr5

• Allocate files in a round-robin fashion from host-specific lists for processes distributed across two SGI multi-processor machines (node names coho and bohr):

```
scratch_dir coho:/xfs1/rjh coho:/xfs2/rjh coho:/xfs3/rjh
bohr:/disk01/rjh bohr:/disk02/rjh bohr:/disk13/rjh
```

MEMORY

This is a start-up directive that allows the user to specify the amount of memory PER PROCESSOR CORE that NWChem can use for the job. If this directive is not specified, memory is allocated according to installation-dependent defaults. The defaults should generally suffice for most calculations, since the defaults usually correspond to the total amount of memory available on the machine.

The general form of the directive is as follows:

```
MEMORY [[total] <integer total_size>] \
    [stack <integer stack_size>] \
    [heap <integer heap_size>] \
    [global <integer global_size>] \
    [units <string units default real>] \
    [(verify||noverify)] \
    [(nohardfail||hardfail)]
```

NWChem recognizes the following memory units:

- real and double (synonyms)
- integer
- real and double (synonyms)
- integer
- byte
- kb (kilobytes)
- mb (megabytes)
- mw (megawords, 64-bit word)

In most cases, the user need specify only the total memory limit to adjust the amount of memory used by NWChem. The following specifications all provide for eight megabytes of total memory (assuming 64-bit floating point numbers), which will be distributed according to the default partitioning:

memory 1048576
memory 1048576 real
memory 1 mw
memory 8 mb
memory total 8 mb
memory total 1048576

In NWChem there are three distinct regions of memory: stack, heap, and global. Stack and heap are node-private, while the union of the global region on all processors is used to provide globally-shared memory. The allowed limits on each category are determined from a default partitioning (currently 25% heap, 25% stack, and 50% global). Alternatively, the keywords stack, heap, and global can be used to define specific allocations for each of these categories. If the user sets only one of the stack, heap, or global limits by input, the limits for the other two categories are obtained by partitioning the remainder of the total memory available in proportion to the weight of those two categories in the default memory partitioning. If two of the category limits are given, the third is obtained by subtracting the two given limits from the total limit (which may have been specified or may be a default value). If all three category limits are specified, it must be larger than the sum of all three categories. The code will abort if it detects an inconsistent memory specification.

The following memory directives also allocate 8 megabytes, but specify a complete partitioning as well:

memory total 8 stack 2 heap 2 global 4 mb
memory stack 2 heap 2 global 4 mb

The optional keywords verify and noverify in the directive give the user the option of enabling or disabling automatic detection of corruption of allocated memory. The default is verify, which enables the feature. This incurs some overhead (which can be around 10% increase in walltime on some platforms), which can be eliminated by specifying noverify.

The keywords hardfail and nohardfail give the user the option of forcing (or not forcing) the local memory management routines to generate an internal fatal error if any memory operation fails. The default is nohardfail, which allows the code to continue past any memory operation failure, and perhaps generate a more meaningful error message before terminating the calculation. Forcing a hard-fail can be useful when poorly coded applications do not check the return status of memory management routines.

When assigning the specific memory allocations using the keywords stack, heap, and global in the MEMORY directive, the user should be aware that some of the distinctions among these categories of memory have been blurred in their actual implementation in the code. The memory allocator (MA) allocates both the heap and the stack from a single memory region of size heap+stack, without enforcing the partition. The heap vs. stack partition is meaningful only to applications developers, and can be ignored by most users. Further complicating matters, the global array (GA) toolkit is allocated from within the MA space on distributed memory machines, while on shared-memory machines it is separate. This is because on true shared-memory machines there is no choice but to allocate GAs from within a shared-memory segment, which is managed differently by the operating system.

On distributed memory platforms, the MA region is actually the total size of stack+heap+global. All three types of memory allocation compete for the same pool of memory, with no limits except on the total available memory. This relaxation of the memory category definitions usually benefits the user, since it can allow allocation requests to succeed where a stricter memory model would cause the directive to fail. These implementation characteristics must be kept in mind when reading program output that relates to memory usage.

Standard default for memory is currently 400 MB.

ECHO

This start-up directive is provided as a convenient way to include a listing of the input file in the output of a calculation. It causes the entire input file to be printed to Fortran unit six (standard output). It has no keywords, arguments, or options, and consists of the single line:

ECH0

The ECHO directive is processed only once, by Process 0 when the input file is read.

TITLE

Specify job title.

This top-level directive allows the user to identify a job or series of jobs that use a particular database. It is an optional directive, and if omitted, the character string containing the input title will be empty. Multiple TITLE directives may appear in the input file (e.g., the water example file) in which case a task will use the one most recently specified. The format for the directive is as follows:

TITLE <string title>

The character string <title> is assigned to the contents of the string following the TITLE directive. If the string contains white space, it must be surrounded by double quotes. For example,

```
title "This is the title of my NWChem job"
```

The title is stored in the database and will be used in all subsequent tasks/jobs until redefined in the input.

PRINT /NOPRINT

The PRINT and NOPRINT directives allow the user to control how much output NWChem generates. These two directives are special in that the compound directives for all modules are supposed to recognize them. Each module can control both the overall print level (general verbosity) and the printing of individual items which are identified by name (see below). The standard form of the PRINT directive is as follows:

```
PRINT [(none || low || medium || high || debug) default medium]
[<string list_of_names ... >]
```

NOPRINT <string list_of_names ... >

The default print level is medium.

Every output that is printed by NWChem has a print threshold associated with it. If this threshold is equal to or lower than the print level requested by the user, then the output is generated. For example, the threshold for printing the SCF energy at convergence is low. This means that if the user-specified print level on the PRINT directive is low, medium, high, or debug, then the SCF energy will be printed at convergence.

The overall print level specified using the PRINT directive is a convenient tool for controlling the verbosity of NWChem. Setting the print level to high might be helpful in diagnosing convergence problems. The print level of debug might also be of use in evaluating problem cases, but the user should be aware that this can generate a huge amount of output. Setting the print level to low might be the preferable choice for geometry optimizations that will perform many steps which are in themselves of little interest to the user.

In addition, it is possible to enable the printing of specific items by naming them in the PRINT directive in the <list_of_names>. Items identified in this way will be printed, regardless of the overall print level specified. Similarly, the NOPRINT directive can be used to suppress the printing of specific items by naming them in its <list_of_names>. These items will not be printed, regardless of the overall print level, or the specific print level of the individual items.

The list of items that can be printed for each module is documented as part of the input instructions for that module. The items recognized by the top level of the code, and their thresholds, are:

Name	'Print Level;'	Description
"total time";	medium	Print cpu and wall time at job end
"task time"	high	Print cpu and wall time for each task
"rtdb"	high	Print names of RTDB entries
"rtdbvalues"	high	Print name and values of RTDB entries
"ga summary"	medium	Summarize GA allocations at job end
"ga stats"	high	Print GA usage statistics at job end
"ma summary"	medium	Summarize MA allocations at job end
"ma stats"	high	Print MA usage statistics at job end
"version"	debug	Print version number of all compiled routines
"tcgmsg"	never	Print TCGMSG debug information

Top Level Print Control Specifications

The following example shows how a PRINT directive for the top level process can be used to limit printout to only essential information. The directive is

print none "ma stats" rtdb

This directive instructs the NWChem main program to print nothing, except for the memory usage statistics (ma stats) and the names of all items stored in the database at the end of the job.

The print level within a module is inherited from the calling layer. For instance, by specifying the print to be low within the MP2 module will cause the SCF, CPHF and gradient modules when invoked from the MP2 to default to low print. Explicit user input of print thresholds overrides the inherited value.

SET

This top-level directive allows the user to enter data directly into the run-time database. The format of the directive is as follows:

```
SET <string name> [<string type default automatic>]
<type data>
```

The entry for variable <name> is the name of data to be entered into the database. This must be specified; there is no default. The variable <type>, which is optional, allows the user to define a string specifying the type of data in the array <name>. The data type can be explicitly specified as integer, real, double, logical, or string. If no entry for <type> is specified on the directive, its value is inferred from the data type of the first datum. In such a case, floating-point data entered using this directive must include either an exponent or a decimal point, to ensure that the correct default type will be inferred. The correct default type will be inferred for logical values if logical-true values are specified as .true., true, or t, and logical-false values are specified as .false., false, or f. One exception to the automatic detection of the data type is that the data type **must** be explicitly stated to input integer ranges, unless the first element in the list is an integer that is not a range. For example,

set atomid 1 3:7 21

will be interpreted as a list of integers. However,

set atomid 3:7 21

will not work since the first element will be interpreted as a string and not an integer. To work around this feature, use instead

```
set atomid integer 3:7 21
```

which says to write three through seven, as well as twenty-one.

The SET directive is useful for providing indirection by associating the name of a basis set or geometry with the standard object names (such as "ao basis" or geometry) used by NWChem. The following input file shows an example using the SET directive to direct different tasks to different geometries. The required input lines are as follows:

```
title "Ar dimer BSSE corrected MP2 interaction energy"
geometry "Ar+Ar"
```
```
Ar1 0 0 0
Ar2 0 0 2
end
geometry "Ar+ghost"
Ar1 0 0 0
Bq2 0 0 2
end
basis
Ar1 library aug-cc-pvdz
Ar2 library aug-cc-pvdz
Bq2 library Ar aug-cc-pvdz
end
set geometry "Ar+Ar" task mp2
scf; vectors atomic; end
set geometry "Ar+ghost" task mp2
```

This input tells the code to perform MP2 energy calculations on an argon dimer in the first task, and then on the argon atom in the presence of the "ghost" basis of the other atom.

The SET directive can also be used as an indirect means of supplying input to a part of the code that does not have a separate input module (e.g., the atomic SCF). Additional examples of applications of this directive can be found in the sample input files, and its usage with basis sets and geometries. Also see database section for an example of how to store an array in the database.

UNSET

Delete data in the RTDB.

This directive gives the user a way to delete simple entries from the database. The general form of the directive is as follows:

UNSET <string name>[*]

This directive cannot be used with complex objects such as geometries and basis sets. Complex objects are stored using a structured naming convention that is not matched by a simple wild card. A wild-card (*) specified at the end of the string <name> will cause all entries whose name begins with that string to be deleted. This is very useful as a way to reset modules to their default behavior, since modules typically store information in the database with names that begin with module:. For example, the SCF program can be restored to its default behavior by deleting all database entries beginning with scf:, using the directive

```
unset scf:*
```

Section -sec:fragguess- has an example using unset on a water dimer calculation.

The following example makes an entry in the database using the SET directive, and then immediately deletes it using the UNSET directive:

```
set mylist 1 2 3 4
unset mylist
```

STOP

Terminate processing.

This top-level directive provides a convenient way of verifying an input file without actually running the calculation. It consists of the single line,

STOP

As soon as this directive is encountered, all processing ceases and the calculation terminates with an error condition.

TASK

The TASK directive is used to tell the code what to do. The input directives are parsed sequentially until a TASK directive is encountered, as described in Input File Structure. At that point, the calculation or operation specified in the TASK directive is performed. When that task is completed, the code looks for additional input to process until the next TASK directive is encountered, which is then executed. This process continues to the end of the input file. NWChem expects the last directive before the end-of-file to be a TASK directive. If it is not, a warning message is printed. Since the database is persistent, multiple tasks within one job behave exactly the same as multiple restart jobs with the same sequence of input.

There are four main forms of the the TASK directive. The most common form is used to tell the code at what level of theory to perform an electronic structure calculation, and which specific calculations to perform. The second form is used to specify tasks that do not involve electronic structure calculations or tasks that have not been fully implemented at all theory levels in NWChem, such as simple property evaluations. The third form is used to execute UNIX commands on machines having a Bourne shell. The fourth form is specific to combined quantum-mechanics and molecular-mechanics (QM/MM) calculations.

By default, the program terminates when a task does not complete successfully. The keyword ignore can be used to prevent this termination, and is recognized by all forms of the TASK directive. When a TASK directive includes the keyword ignore, a warning message is printed if the task fails, and code execution continues with the next task. An example of this feature is given in the sample input file.

The input options, keywords, and defaults for each of these four forms for the TASK directive are discussed in the following sections.

TASK Directive for Electronic Structure

This is the most commonly used version of the TASK directive, and it has the following form:

```
TASK <string theory> [<string operation default energy>]
[ignore]
```

The string <theory> specifies the level of theory to be used in the calculations for this task. NWChem currently supports ten different options. These are listed below, with the corresponding entry for the variable <theory>:

- scf Hartree-Fock
- dft Density functional theory for molecules

- sodft Spin-Orbit Density functional theory
- mp2 MP2 using a semi-direct algorithm
- direct_mp2 MP2 using a full-direct algorithm
- rimp2 MP2 using the RI approximation
- ccsd Coupled-cluster single and double excitations
- ccsd(t) Coupled-cluster linearized triples approximation
 - 1. ccsd+t(ccsd)# Fourth order triples contribution
- mcscf Multiconfiguration SCF
- selci Selected configuration interaction with perturbation correction
- md Classical molecular dynamics simulation
- pspw Pseudopotential plane-wave density functional theory for molecules and insulating solids using NWPW
- band Pseudopotential plane-wave density functional theory for solids using NWPW
- tce Tensor Contraction Engine

The string <operation> specifies the calculation that will be performed in the task. The default operation is a single point energy evaluation. The following list gives the selection of operations currently available in NWChem:

- energy Evaluate the single point energy.
- gradient Evaluate the derivative of the energy with respect to nuclear coordinates.
- optimize Minimize the energy by varying the molecular structure. By default, this geometry optimization is presently driven by the Driver module, but the Stepper module may also be used.
- saddle Conduct a search for a transition state (or saddle point) using either Driver module (the default) or Stepper.
- hessian Compute second derivatives. See hessian section for analytic hessians.
- frequencies or freq Compute second derivatives and print out an analysis of molecular vibrations. See vibration section for controls for vibration calculations.
- vscf Compute anharmonic contributions to the vibrational modes. See the vibrational SCF section for options.
- property Calculate the properties for the wave function.
- dynamics Perform classical molecular dynamics.
- thermodynamics Perform multi-configuration thermo-dynamic integration using classical MD

NOTE: See PSPW Tasks for the complete list of operations that accompany the NWPW module.

The user should be aware that some of these operations (gradient, optimize, dynamics, thermodynamics) require computation of derivatives of the energy with respect to the molecular coordinates. If analytical derivatives are not available (Capabilities), they must be computed numerically, which can be very computationally intensive.

Here are some examples of the TASK directive, to illustrate the input needed to specify particular calculations with the code. To perform a single point energy evaluation using any level of theory, the directive is very simple, since the energy evaluation is the default for the string operation. For an SCF energy calculation, the input line is simply

task scf

Equivalently, the operation can be specified explicitly, using the directive

task scf energy

Similarly, to perform a geometry optimization using density functional theory, the TASK directive is

task dft optimize

The optional keyword ignore can be used to allow execution to continue even if the task fails, as discussed above. An example with the keyword ignore can be found in the DFT example.

TASK Directive for Special Operations

This form of the TASK directive is used in instances where the task to be performed does not fit the model of the previous version (such as execution of a Python program), or if the operation has not yet been implemented in a fashion that applies to a wide range of theories (e.g., property evaluation). Instead of requiring theory and operation as input, the directive needs only a string identifying the task. The form of the directive in such cases is as follows:

TASK <string task> [ignore]

The supported tasks that can be accessed with this form of the TASK directive are listed below, with the corresponding entries for string variable <task>.

- python Execute a Python program.
- rtdbprint Print the contents of the database.
- cphf Invoke the CPHF module.
- property Perform miscellaneous property calculations.
- dplot Execute a DPLOT run.

This directive also recognizes the keyword ignore, which allows execution to continue after a task has failed.

TASK Directive for Bourne Shell

This form of the TASK directive is supported only on machines with a fully UNIX-style operating system. This directive causes specified processes to be executed using the Bourne shell. This form of the task directive is:

```
TASK shell [(<integer-range process = 0>||all)] <string
command>
```

The keyword shell is required for this directive. It specifies that the given command will be executed in the Bourne shell. The user can also specify which process(es) will execute this command by entering values for process on the directive. The default is for only process zero to execute the command. A range of processes may be specified, using Fortran triplet notation. Alternatively, all processes can be specified simply by entering the keyword all. The input entered for command must form a single string, and must consist of valid UNIX command(s). If the string includes white space, it must be enclosed in double quotes.

For example, the TASK directive to tell process zero to copy the molecular orbitals file to a backup location /piofs/save can be input as follows:

task shell "cp *.movecs /piofs/save"

The TASK directive to tell all processes to list the contents of their /scratch directories is as follows:

task shell all "ls -l /scratch"

The TASK directive to tell processes 0 to 10 to remove the contents of the current directory is as follows:

task shell 0:10:1 "/bin/rm -f *"

Note that NWChem's ability to quote special input characters is very limited when compared with that of the Bourne shell. To execute all but the simplest UNIX commands, it is usually much easier to put the shell script in a file and execute the file from within NWChem.

TASK Directive for QM/MM simulations

This is very similar to the most commonly used version of the TASK directive, and it has the following form:

```
TASK QMMM <string theory> [<string operation default
energy>] [ignore]
```

The string <theory> specifies the QM theory to be used in the QM/MM simulation. If theory is "md" this is not a QM/MM simulation and will result in an appropriate error. The level of theory may be any QM method that can compute gradients but those algorithms in NWChem that do not support analytic gradients should be avoided (see Functionality).

The string <operation> is used to specify the calculation that will be performed in the QM/MM task. The default operation is a single point energy evaluation. The following list gives the selection of operations currently available in the NWChem QM/MM module;

- energy single point energy evaluation
- optimize minimize the energy by variation of the molecular structure.
- · dynamics molecular dynamics using nwARGOS

Here are some examples of the TASK directive for QM/MM simulations. To perform a single point energy of a QM/MM system using any QM level of theory, the directive is very simple. As with the general task directive, the QM/MM energy evaluation is the default. For a DFT energy calculation the task directive input is,

task qmmm dft

or completely as

task qmmm dft energy

To do a molecular dynamics simulation of a QM/MM system using the SCF level of theory the task directive input would be $\label{eq:model}$

task qmmm scf dynamics

The optional keyword ignore can be used to allow execution to continue even if the task fails, as discussed above.

TASK Directive for BSSE calculations

NWChem computes the basis set superposition error (BSSE) when two or more fragments are interacting by using the counterpoise method. This directive is performed if the BSSE section is present. Single point energies, energy gradients, geometry optimizations, Hessians and frequencies, at the level of theory that allows these tasks, can be obtained with the BSSE correction. The input options for the BSSE section are:

BSSE

```
MON <string monomer name> <integer natoms>
[INPUT [<string input>]]
[INPUT_WGHOST[<string input>]]
[CHARGE [<real charge>]]
[OFF]
[ON]
END
```

MON defines the monomer's name and its atoms; <string monomer name> defines the name of the monomer, <integer atoms> is the list of atoms corresponding to the monomer (where such a list is relative to the initial geometry). This information is needed for each monomer. With the tag INPUT the user can modify any calculation attributes for each monomer without ghost. For example, the iterations number and the grid can be changed in a DFT calculation (see the example of the interaction between Zn^{2+} and water). INPUT_WGHOST is the same than INPUT but for the monomer with ghost. The input changes will be applied within this and for the following calculations, you should be cautious reverting the changes for the next monomers. CHARGE assigns a charge to a monomer and it must be consistent with the total charge in the whole system (see Section -sec:charge-). The options OFF and ON turns off and on any BSSE calculation.

The energy evaluation involves 1 + 2N calculations, i.e. one for the supermolecule and two for the N monomers. [S. Simon, M. Duran, J. J. Dannenberg, J. Chem. Phys., 105, 11024 (1996)] NWChem stores the vector files for each calculation (<string monomer name>.bsse.movecs), and one hessian file (<string monomer name>.bsse.hess). The code does not assign automatically the basis set for the ghost atoms, you must assign the corresponding bqX for each element, instead.

Examples

```
The dimer (FH)<sub>2</sub>
title dimer
start dimer
geometry units angstrom
symmetry c1
F 1.47189 2.47463 -0.00000
H 1.47206 3.29987 0.00000
F 1.46367 -0.45168 0.00000
H 1.45804 0.37497 -0.00000
end
basis "ao basis"
F library 6-31G
```

```
H library 6-31G
  bqF library F 6-31G
  bqH library H 6-31G
end
dft; xc slater 1.0 vwn_5 1.0; direct; end
bsse
 mon first 1 2
 mon second 3 4
end
task dft energy
Changing maxiter for a specific monomer: Zn^{2+}(H_2O)
title znwater
start znwater
echo
geometry noautoz units angstrom
  symmetry cl
  Zn -1.89334 -0.72741 -0.00000
  0 -0.20798 0.25012 0.00000
  H -0.14200 1.24982 -0.00000
  H 0.69236 -0.18874 -0.00000
end
basis "ao basis"
  0 library 6-31G
  Zn library 6-31G
  H library 6-31G
  bq0 library 0 6-31G
  bqZn library Zn 6-31G
  bqH library H 6-31G
end
charge 2
scf; direct; end
mp2; end
bsse
 mon metal 1
 charge 2
 input_wghost "scf\; maxiter 200\; end"
 mon water 2 3 4
end
task mp2 optimize
```

ECCE_PRINT

The ECCE_PRINT directive allows the user to print out a file, usually called ecce.out, that will allow the calculation and its results to be imported into Ecce (see http://ecce.pnl.gov).

ECCE_PRINT <string name>

The entry for variable <name> is the name of the file that will contain the Ecce import information and should include the full path to the directory where you want that file. For example

ecce_print /home/user/job/ecce.out

If the full path is not given and only the file name is given, the file will be located in whatever directory the job is started in. For example, if the line

ecce_print ecce.out

is in the input file, the file could end up in the scratch directory if the user is using a batch script that copies the input file to a local scratch directory and then launches NWChem from there. If the system then automatically removes files in the scratch space at the end of the job, the ecce.out file will be lost. So, the best practice is to include the full path name for the file.

Release65:Nwarch

_NOTITLE__

NWChem Architecture

As noted above, NWChem consists of independent modules that perform the various functions of the code. Examples include the input parser, self-consistent field (SCF) energy, SCF analytic gradient, and density functional theory (DFT) energy modules. The independent NWChem modules can share data only through a disk-resident database, which is similar to the GAMESS-UK dumpfile or the Gaussian checkpoint file. This allows the modules to share data, or to share access to files containing data.

It is not necessary for the user to be intimately familiar with the contents of the database in order to run NWChem. However, a nodding acquaintance with the design of the code will help in clarifying the logic behind the input requirements, especially when restarting jobs or performing multiple tasks within one job.

As described above (Input File Structure), all start-up directives are processed at the beginning of the job by the main program, and then the input module is invoked. Each input directive usually results in one or more entries being made in the database. When a TASK directive is encountered, control is passed to the appropriate module, which extracts relevant data from the database and any associated files. Upon completion of the task, the module will store significant results in the database, and may also modify other database entries in order to affect the behavior of subsequent computations.

Database Structure

Data is shared between modules of NWChem by means of the database. Three main types of information are stored in the data base: (1) arrays of data, (2) names of files that contain data, and (3) objects. Arrays are stored directly in the database, and contain the following information:

- 1. the name of the array, which is a string of ASCII characters (e.g., "reference energies")
- 2. the type of the data in the array (i.e., real, integer, logical, or character)
- 3. the number (N) of data items in the array (Note: A scalar is stored as an array of unit length.)
- 4. the N items of data of the specified type

It is possible to enter data directly into the database using the SET directive. For example, to store a (64-bit precision) three-element real array with the name "reference energies" in the database, the directive is as follows:

```
set "reference energies" 0.0 1.0 -76.2
```

NWChem determines the data to be real (based on the type of the first element, 0.0), counts the number of elements in the array, and enters the array into the database.

Much of the data stored in the database is internally managed by NWChem and should not be modified by the user. However, other data, including some NWChem input options, can be freely modified.

Objects are built in the database by storing associated data as multiple entries, using an internally consistent naming convention. This data is managed exclusively by the subroutines (or methods) that are associated with the object. Currently, the code has two main objects: basis sets and geometries. GEOMETRY and BASIS present a complete discussion of the input to describe these objects.

As an illustration of what comprises a geometry object, the following table contains a partial listing of the database contents for a water molecule geometry named "test geom". Each entry contains the field test geom, which is the unique name of the object.

Contents of RTDB h2o.db	
Entry	Type[nelem]
<pre>geometry:test geom:efield geometry:test geom:coords geometry:test geom:ncenter geometry:test geom:charges geometry:test geom:tags</pre>	double[3] double[9] int[1] double[3] char[6]

Using this convention, multiple instances of objects may be stored with different names in the same database. For example, if a user needed to do calculations considering alternative geometries for the water molecule, an input file could be constructed containing all the geometries of interest by storing them in the database under different names.

The runtime database contents for the file h2o.db listed above were generated from the user-specified input directive,

```
geometry "test geom"

0 0.00000000 0.0000000 0.00000000

H 0.00000000 1.43042809 -1.10715266

H 0.00000000 -1.43042809 -1.10715266

end
```

The GEOMETRY directive allows the user to specify the coordinates of the atoms (or centers), and identify the geometry with a unique name.

Unless a specific name is defined for the geometry, (such as the name "test geom" shown in the example), the default name of geometry is assigned. This is the geometry name that computational modules will look for when executing a calculation. The SET directive can be used in the input to force NWChem to look for a geometry with a name other than geometry. For example, to specify use of the geometry with the name "test geom" in the example above, the SET directive is as follows:

set geometry "test geom"

NWChem will automatically check for such indirections when loading geometries. Storage of data associated with basis sets, the other database resident object, functions in a similar fashion, using the default name "ao basis".

Persistence of data and restart

The database is persistent, meaning that all input data and output data (calculation results) that are not destroyed in the course of execution are permanently stored. These data are therefore available to subsequent tasks or jobs. This makes the input for restart jobs very simple, since only new or changed data must be provided. It also makes the behavior of successive restart jobs identical to that of multiple tasks within one job.

Sometimes, however, this persistence is undesirable, and it is necessary to return an NWChem module to its default behavior by restoring the database to its input-free state. In such a case, the UNSET directive can be used to delete all database entries associated with a given module (including both inputs and outputs).

Release65:Running

__NOTITLE__

Running NWChem

The command required to invoke NWChem is machine dependent, whereas most of the NWChem input is machine independent.

Sequential execution

To run NWChem sequentially on nearly all UNIX-based platforms simply use the command nwchem and provide the name of the input file as an argument. This does assume that either nwchem is in your path or you have set an alias of nwchem to point to the appropriate executable.

Output is to standard output, standard error and Fortran unit 6 (usually the same as standard output). Files are created by default in the current directory, though this may be overridden in the input.

Generally, one will run a job with the following command:

```
nwchem input.nw >& input.out &
```

Parallel execution on UNIX-based parallel machines including workstation clusters using TCGMSG

These platforms require the use of the TCGMSGD.2 parallel command and thus also require the definition of a process-group (or procgroup) file. The process-group file describes how many processes to start, what program to run, which machines to use, which directories to work in, and under which userid to run the processes. By convention the process-group file has a .p suffix.

The process-group file is read to end-of-file. The character **#** (hash or pound sign) is used to indicate a comment which continues to the next new-line character. Each line describes a cluster of processes and consists of the following whitespace separated fields:

userid hostname nslave executable workdir

- userid The user-name on the machine that will be executing the process.
- hostname The hostname of the machine to execute this process. If it is the same machine on which parallel was invoked the name must match the value returned by the command hostname. If a remote machine it must allow remote execution from this machine (see man pages for rlogin, rsh).
- nslave The total number of copies of this process to be executing on the specified machine. Only "clusters" of identical processes specified in this fashion can use shared memory to communicate. If no shared memory is supported on machine <hostname> then only the value one (1) is valid.
- executable Full path name on the host <hostname> of the image to execute. If <hostname> is the local machine then a local path will suffice.
- workdir Full path name on the host <hostname> of the directory to work in. Processes execute a chdir() to this directory before returning from pbegin(). If specified as a "".""

then remote processes will use the login directory on that machine and local processes (relative to where parallel was invoked) will use the current directory of parallel.

For example, if your file "nwchem.p" contained the following

d3g681 pc 4 /msrc/apps/bin/nwchem /scr22/rjh

then 4 processes running NWChem would be started on the machine pc running as user d3g681 in directory "/scr22/rjh". To actually run this simply type:

parallel nwchem big_molecule.nw

N.B. : The first process specified (process zero) is the only process that

- opens and reads the input file, and
- opens and reads/updates the database.

Thus, if your file systems are physically distributed (e.g., most workstation clusters) you must ensure that process zero can correctly resolve the paths for the input and database files.

Parallel execution on UNIX-based parallel machines including workstation clusters using MPI

To run with MPI, parallel should not be used. The way we usually run nwchem under MPI are the following

- using mpirun: mpirun -np 8 \$NWCHEM TOP/bin/\$NWCHEM TARGET/nwchem input.nw
- If you have all nodes connected via shared memory and you have installed the ch_shmem version of MPICH, you can do
 \$NWCHEM TOP/bin/\$NWCHEM TARGET/nwchem -np 8 h2o.nw

Parallel execution on MPPs

All of these machines require use of different commands in order to gain exclusive access to computational resources.

System Description

Release65:Charge

__NOTITLE__

CHARGE

This is an optional top-level directive that allows the user to specify the total charge of the system. The form of the directive is as follows:

CHARGE <real charge default 0>

The default chargeThe charge directive, in conjunction with the charges of atomic nuclei (which can be changed via the geometry input, cf. Section -sec:cart-), determines the total number of electrons in the chemical system. Therefore, a charge n specification removes "n" electrons from the chemical system. Similarly, charge -n adds "n" electrons. is zero if this directive is omitted. An example of a case where the directive would be needed is for a calculation on a doubly charged cation. In such a case, the directive is simply,

charge 2

If centers with fractional charge have been specified the net charge of the system should be adjusted to ensure that there are an integral number of electrons.

The charge may be changed between tasks, and is used by all wavefunction types. For instance, in order to compute the first two vertical ionization energies of LiH, one might optimize the geometry of LiH using a UHF SCF wavefunction, and then perform energy calculations at the optimized geometry on LiH^+ and LiH^{2+} in turn. This is accomplished with the following input:

geometry; Li 0 0 0; H 0 0 1.64; end basis; Li library 3-21g; H library 3-21g; end scf; uhf; singlet; end task scf optimize charge 1 scf; uhf; doublet; end task scf charge 2 scf; uhf; singlet; end task scf

The GEOMETRY, BASIS, and SCF directives are described below (Geometry, Basis and SCF respectively) but their intent should be clear. The TASK directive is described above (TASK).

Release65:Geometry

__NOTITLE___

Geometries

The GEOMETRY directive is a compound directive that allows the user to define the geometry to be used for a given calculation. The directive allows the user to specify the geometry with a relatively small amount of input, but there are a large number of optional keywords and additional subordinate directives that the user can specify, if needed. The directive therefore appears to be rather long and complicated when presented in its general form, as follows:

```
GEOMETRY [<string name default geometry>] \
          [units <string units default angstroms>] \
          [(angstrom to au || ang2au) ∖
                 <real angstrom_to_au default 1.8897265>] \
          [print [xyz] || noprint] \
          [center || nocenter] \
          [bqbq] \
          [autosym [real tol default 1d-2] || noautosym] \
          [autoz || noautoz] \
          [adjust] ∖
          [(nuc || nucl || nucleus) <string nucmodel>]
   [SYMMETRY [group] <string group name> [print] \
          [tol <real tol default 1d-2>]]
   [ LOAD [format xyz||pdb] [frame <int frame>] \
          [select [not] \
               [name <string atomname>] \
               [rname <string residue-name>]
               [id <int atom-id>|<int range
atom-id1:atom-id2> ... ]
               [resi <int residue-id>|<int range</pre>
residue-id1:residue-id2> ... ]
   <string filename> ]
  <string tag> <real x y z> [vx vy vz] [charge <real</pre>
charge>] ∖
          [mass <real mass>] \
          [(nuc || nucl || nucleus) <string nucmodel>]
   ...]
   [ZMATRIX || ZMT || ZMAT
        <string tagn> <list of zmatrix variables>
        . . .
        [VARIABLES
             <string symbol> <real value>
             ...]
```

```
[CONSTANTS
             <string symbol> <real value>
             ...]
    (END || ZEND)]
    [ZCOORD
         CVR SCALING <real value>
         BOND
                 <integer i> <integer j> \
                  [<real value>] [<string name>] [constant]
         ANGLE
                 <integer i> <integer j> \
                      [<real value>] [<string name>]
[constant]
         TORSION <integer i> <integer j> <integer k>
<integer l > \setminus
                  [<real value>] [<string name>] [constant]
     END]
     [SYSTEM surface <molecule polymer surface crystal default
molecule>
          lat a <real lat a> lat b <real lat b> lat c
<real lat c>
          alpha <real alpha> beta <real beta> gamma
<real gamma>
     END1
  END
```

The three main parts of the GEOMETRY directive are:

- keywords on the first line of the directive (to specify such optional input as the geometry name, input units, and print level for the output)
- symmetry information
- Cartesian coordinates or Z-matrix input to specify the locations of the atoms and centers
- lattice parameters (needed only for periodic systems)

The following sections present the input for this compound directive in detail, describing the options available and the usages of the various keywords in each of the three main parts.

Keywords on the GEOMETRY directive

This section presents the options that can be specified using the keywords and optional input on the main line of the GEOMETRY directive. As described above, the first line of the directive has the general form,

```
GEOMETRY [<string name default geometry>] \
    [units <string units default angstroms>] \
    [bqbq] \
    [print [xyz] || noprint] \
    [center || nocenter] \
    [autosym [real tol default 1d-2] || noautosym] \
    [autoz || noautoz] \
    [adjust] \
```

[(nuc || nucl || nucleus) <string nucmodel>]

All of the keywords and input on this line are optional. The following list describes all options and their defaults.

- <name> user-supplied name for the geometry; the default name is geometry, and all NWChem modules look for a geometry with this name. However, multiple geometries may be specified by using a different name for each. Subsequently, the user can direct a module to a named geometry by using the SET directive (see the example in Section 5.7) to associate the default name of geometry with the alternate name.
- units keyword specifying that a value will be entered by the user for the string variable <units>. The default units for the geometry input are Angstrøms (Note: atomic units or Bohr are used within the code, regardless of the option specified for the input units. The default conversion factor used in the code to convert from Angstrøms to Bohr is 1.8897265 which may be overidden with the angstrom_to_au keyword described below.). The code recognizes the following possible values for the string variable <units>:
 - angstroms or an -- Angstroms , the default (converts to A.U. using the Angstrom to A.U. conversion factor)
 - au or atomic or bohr -- Atomic units (A.U.)
 - nm or nanometers -- nanometers (converts to A.U. using a conversion factor computed as 10.0 times the Angstrom to A.U. conversion factor)
 - pm or picometers -- picometers (converts to A.U. using a conversion factor computed as 0.01 times the Angstrom to A.U. conversion factor)
- angstrom_to_au may also be specified as ang2au. This enables the user to modify the conversion factors used to convert between Angstrom and A.U.. The default value is 1.8897265.
- bqbq keyword to specify the treatment of interactions between dummy centers. The default in NWChem is to ignore such interactions when computing energies or energy derivatives. These interactions will be included if the keyword bqbq is specified.
- print and noprint complementary keyword pair to enable or disable printing of the geometry. The default is to print the output associated with the geometry. In addition, the keyword print may be qualified by the additional keyword xyz, which specifies that the coordinates should be printed in the XYZ format of molecular graphics program XMol
- center and nocenter complementary keyword pair to enable or disable translation of the center of nuclear charge to the origin. With the origin at this position, all three components of the nuclear dipole are zero. The default is to move the center of nuclear charge to the origin.
- autosym and noautosym keyword to specify that the symmetry of the geometric system should be automatically determined. This option is on by default, but can be turned off with noautosym. Only groups up to and including O_h are recognized. Occasionally NWChem will be unable to determine the full symmetry of a molecular system, but will find a proper subgroup of the full symmetry. The default tolerance is set to work for most cases, but may need to be decreased to find the full symmetry of a geometry. Note that autosym will be turned off if the SYMMETRY group input is given (See Symmetry Group Input). Also note that if symmetry equivalent atoms have different tags in the geometry they will not be detected as symmetry equivalent by the autosym capability. The reason for this is that atoms with different tags might be assigned different basis sets, for

example, after which they are no longer symmetry equivalent. Therefore autosym chooses to make the save choice.

- noautoz by default NWChem (release 3.3 and later) will generate redundant internal coordinates from user input Cartesian coordinates. The internal coordinates will be used in geometry optimizations. The noautoz keyword disables use of internal coordinates. The autoz keyword is provided only for backward compatibility. See Forcing internal coordinates for a more detailed description of redundant internal coordinates, including how to force the definition of specific internal variables in combination with automatically generated variables.
- adjust This indicates that an existing geometry is to be adjusted. Only new input for the redundant internal coordinates may be provided (Forcing internal coordinates). It is not possible to define new centers or to modify the point group using this keyword. See Forcing internal coordinates for an example of its usage.
- nucleus keyword to specify the default model for the nuclear charge distribution. The following values are recognized:
 - point or pt -- point nuclear charge distribution. This is the default.
 - finite or fi -- finite nuclear charge distribution with a Gaussian shape. The RMS radius of the Gaussian is determined from the nuclear mass number A by the expression $r_{\rm RMS} = 0.836 * A^{1/3} + 0.57$ fm.

NOTE: If you specify a finite nuclear size, you should ensure that the basis set you use is contracted for a finite nuclear size.

The following examples illustrate some of the various options that the user can specify on the first input line of the GEOMETRY directive, using the keywords and input options described above.

The following directives all specify the same geometry for H_2 (a bond length of 0.732556 Å):

geometry	geometry units nm
h 0 0 0	h 0 0 0
h 0 0 0.732556	h 0 0 0.0732556
end	end
geometry units pm	geometry units atomic
h 0 0 0	h 0 0 0
h 0 0 73.2556	h 0 0 1.3843305
end	end

SYMMETRY --Symmetry Group Input

The SYMMETRY directive is used (optionally) within the compound GEOMETRY directive to specify the point group for the molecular geometry or space group for the crystal structure. The general form of the directive, as described above within the general form of the GEOMETRY directive, is as follows:

```
[SYMMETRY [group] <string group_name><integer group number> [setting <integer setting>] [print] \
```

[tol <real tol default 1d-2>

The keyword group is optional, and can be omitted without affecting how the input for this directive is processed. However, if the SYMMETRY directive is used, a group name must be

specified by supplying an entry for the string variable <group_name> or <group number>. The latter is useful for the space groups discussed in the section below. The group name should be specified as the standard Schöflies symbol. Examples of expected input for the variable group_name include such entries as:

- c2v for molecular symmetry C_{2v}
- d2h for molecular symmetry D_{2h}
- Td for molecular symmetry T_d
- d6h for molecular symmetry D_{6h}

The SYMMETRY directive is optional. The default is no symmetry (i.e., C_1 point group). Automatic detection of point group symmetry is available through the use of autosym in the GEOMETRY directive main line (discussed in Keywords on the GEOMETRY directive). Note: if the SYMMETRY directive is present the autosym keyword is ignored.

If only symmetry-unique atoms are specified, the others will be generated through the action of the point group operators, but the user if free to specify all atoms. The user must know the symmetry of the molecule being modeled, and be able to specify the coordinates of the atoms in a suitable orientation relative to the rotation axes and planes of symmetry. Appendix C lists a number of examples of the GEOMETRY directive input for specific molecules having symmetry patterns recognized by NWChem. The exact point group symmetry will be forced upon the molecule, and atoms within 10^{-3} A.U. of a symmetry element (e.g., a mirror plane or rotation axis) will be forced onto that element. Thus, it is not necessary to specify to a high precision those coordinates that are determined solely by symmetry.

The keyword print gives information concerning the point group generation, including the group generators, a character table, the mapping of centers, and the group operations.

The keyword tol relates to the accuracy with which the symmetry-unique atoms should be specified. When the atoms are generated, those that are within the tolerance, tol, are considered the same.

Names of 3-dimensional space groups

Web resources:

- "A Hypertext Book of Crystallographic Space Group Diagrams and Tables" Birkbeck College, University of London [1]
- NRL Crystal Lattice Structures [2]
- Three-Dimensional Space Groups from Steven Dutch, Natural and Applied Sciences, University of Wisconsin - Green Bay [3]
- REPRES, Space Group Irreducible Representations [4]

For many of the space groups there are multiple choices of symmetry transformations. They are denoted as settings for each of the groups. By default, the code will use the first setting. By defining "setting <integer setting>" on the symmetry input line (see above), you can tell the code to choose a different setting/symmetry transformation.

Triclinic space groups (group numbers: 1-2)

P-1

P1

Monoclinic space groups (group numbers: 3-15)

		P2	P2_1	C2
Pm	Pc	Cm	Cc	P2/m
P2 1/m	C2/m	P2/c	P2 1/c	C2/c

Orthorhombic space groups (group numbers: 16-74)

P222	P222_1	P2_12_12	P2_12_12_1	C222_1
C222	F222	I222	I2_12_12_1	Pmm2
Pmc2_1	Pcc2	Pma2	Pca2_1	Pnc2
Pmn2_1	Pba2	Pna2_1	Pnn2	Cmm2
Cmc2_1	Ccc2	Amm2	Abm2	Ama2
Aba2	Fmm2	Fdd2	Imm2	Iba2
Ima2	Pmmm	Pnnn	Pccm	Pban
Pmma	Pnna	Pmna	Pcca	Pbam
Pccn	Pbcm	Pnnm	Pmmn	Pbcn
Pbca	Pnma	Cmcm	Cmca	Cmmm
Cccm	Cmma	Ccca	Fmmm	Fddd
Immm	Ibam	Ibca	Imma	

Tetragonal space groups (group numbers: 75-142)

				P4
P4_1	P4_2	P4_3	I4	I4_1
P-4	I-4	P4/m	P4_2/m	P4/n
P4_2/n	I4/m	I4_1/a	P422	P42_12
P4_122	P4_12_12	P4_222	P4_22_12	P4_322
P4_32_12	I422	I4_122	P4mm	P4bm
P4_2cm	P4_2nm	P4cc	P4nc	P4_2mc
P4_2bc	I4mm	I4cm	I4_1md	I4_1cd
P-42m	P-42c	P-42_1m	P-42_1c	P-4m2
P-4c2	P-4b2	P-4n2	I-4m2	I-4c2
I-42m	I-42d	P4/mmm	P4/mcc	P4/nbm
P4/nnc	P4/mbm	P4/mnc	P4/nmm	P4/ncc
P4_2/mmc	P4_2/mcm	P4_2/nbc	P4_2/nnm	P4_2/mbc
P4_2/mnm	P4_2/nmc	P4_2/ncm	I4/mmm	I4/mcm
I4 1/amd	I4 1/acd			

Trigonal space groups (group numbers: 143-167)

	P3	P3_1	P3_2
P-3	R-3	P312	P321
P3_121	P3_212	P3_221	R32
P31m	P3c1	P31c	R3n
P-31m	P-31c	P-3m1	P-3c1
R-3c			
	P-3 P3_121 P31m P-31m R-3c	P3 P-3 R-3 P3_121 P3_212 P31m P3c1 P-31m P-31c R-3c F	P3 P3_1 P-3 R-3 P312 P3_121 P3_212 P3_221 P31m P3c1 P31c P-31m P-31c P-3m1 R-3c

Hexagonal space groups (group numbers: 168-194)

		P6	P6_1	P6_5
P6_2	P6_4	P6_3	P-6	P6/m
P6_3/m	P622	P6_122	P6_522	P6_222
P6_422	P6_322	P6mm	P6cc	P6_3cm
P6_3mc	P-6m2	P-6c2	P-62m	P-62c
P6/mmm	P6/mcc	P6 3/mcm	P6 3/mmc	

Cubic space groups (group numbers: 195-230)

				P23	
F23	I23	P2_13	I2_13	Pm-3	
Pn-3	Fm-3	Fd-3	Im-3	Pa-3	
Ia-3	P432	P4_232	F432	F4_132	
I432	P4_332	P4_132	I4_132	P-43m	
F-43m	I-43m	P-43n	F-43c	I-43d	
Pm-3m	Pn-3n	Pm-3n	Pn-3m	Fm-3m	
Fm-3c	Fd-3m	Fd-3c	Im-3m	Ia-3d	

LOAD

```
[ LOAD [format xyz||pdb] [frame <int frame>] \
        [select [not] \
            [name <string atomname>] \
            [rname <string residue-name>]
        [id <int atom-id>|<int range
atom-id1:atom-id2> ... ]
        [resi <int residue-id>|<int range
residue-id1:residue-id2> ... ]
        ]
        <string filename> ]
```

LOAD directive allows users to load Cartesian coordinates from external pdb or xyz files with the name <filename>. This directive works in addition to the explicit Cartesian coordinate declaration and can be repeated and mixed with the latter. This allows for complex coordinate assemblies where some coordinates are loaded from external files and some specified explicitly in the input file. The ordering of coordinates in the final geometry will follow the order in which LOAD statements and explicit coordinates are specified. NOTE that PDB file has to end with "END" keyword!

- The actual file from which coordinates will be loaded is presumed to be located in the run directory (the same place where input file resides). Its name cannot coincide with any of the keywords in the LOAD statement. To keep things simple it is advised to specify it either at the beginning or the end of the LOAD directive.
- **format** xyz || pdb specifies format of the input file. The only formats that are supported at this point are pdb and xyz. Either one can contain multiple structures, which can be selected using the frame directive. Note that in case of PDB file multiple structures are expected to be separated by END keyword. If the format directive is not provided the format will be inferred from file extension .xyz for xyz files and .pdb for pdb files

- **frame** <int frame> specifies which frame/structure to load from multiple structure xyz or pdb files. In the absence of this directive the 1st frame/structure will be loaded
- **select** ... this directive allows to selectively load parts of the geoemtry in the file within aspecified frame. Selections can be based on atom index (**id**), atom name (**name**), and for pdb files can also include residue index (**resi**) and residue name (**rname**). Atom and residue name selection are based on an *exact* single name match. Atom and residue index allow both multiple single number and multiple range selection. For example

select id 2 4:6 9

will result in the selection of atom id's 2 4 5 6 9.

The effect of multiple selection differs depending on on whether these selections are within a given class (say atom id) or between different classes (e.g. atom id and name). Multiple selection for within given class are always combined as OR. For example

select id 2 id 3

will select atoms whose id is 2 OR 3.

Multiple selection between different classes are always combined as AND. For example

select id 2 id 3 name 0

will select atoms whose id is (2 OR 3) AND name is O.

Each selection criteria can be inverted by prepending **not** keyword. For example

select not name 0 id 2:4

will select all atoms that are not named **O** and whose id/index is between 2 and 4.

Cartesian coordinate input

The default in NWChem is to specify the geometry information entirely in Cartesian coordinates, and examples of this format have appeared above (e.g, Water Molecule Input). Each center (usually an atom) is identified on a line of the following form:

```
<string tag> <real x y z> [vx vy vz] \
    [charge <real charge>] [mass <real mass>] \
    [(nuc || nucl || nucleus) <string nucmodel>]
```

The string <tag> is the name of the atom or center, and its case (upper or lower) is important. The tag is limited to 16 characters and is interpreted as follows:

- If the entry for <tag> begins with either the symbol or name of an element (regardless of case), then the center is treated as an atom of that type. The default charge is the atomic number (adjusted for the presence of ECPs by the ECP NELEC directive ; see Section 8). Additional characters can be added to the string, to distinguish between atoms of the same element (For example, the tags oxygen, O, o34, olonepair, and Oxygen-ether, will all be interpreted as oxygen atoms.).
- If the entry for <tag> begins with the characters bq or x (regardless of case), then the center is treated as a dummy center with a default zero charge (Note: a tag beginning with the characters xe will be interpreted as a xenon atom rather than as a dummy center.). Dummy centers may optionally have basis functions or non-zero charge.

It is important to be aware of the following points regarding the definitions and usage of the values specified for the variable < tag > to describe the centers in a system:

- If the tag begins with characters that cannot be matched against an atom, and those characters are not BQ or X, then a fatal error is generated.
- The tag of a center is used in the BASIS and ECP directives to associate functions with centers.
- All centers with the same tag will have the same basis functions.
- When using automatic symmetry detection, only centers with the same tag will be candidates for testing for symmetry equivalence.
- The user-specified charges (of all centers, atomic and dummy) and any net total charge of the system are used to determine the number of electrons in the system.

The Cartesian coordinates of the atom in the molecule are specified as real numbers supplied for the variables x, y, and z following the characters entered for the tag. The values supplied for the coordinates must be in the units specified by the value of the variable <units> on the first line of the GEOMETRY directive input.

After the Cartesian coordinate input, optional velocities may be entered as real numbers for the variables vx, vy, and vz. The velocities should be given in atomic units and are used in QMD and PSPW calculations.

The Cartesian coordinate input line also contains the optional keywords charge, mass and nucleus, which allow the user to specify the charge of the atom (or center) and its mass (in atomic mass units), and the nuclear model. The default charge for an atom is its atomic number, adjusted for the presence of ECPs. In order to specify a different value for the charge on a particular atom, the user must enter the keyword charge, followed by the desired value for the variable <charge>.

The default mass for an atom is taken to be the mass of its most abundant naturally occurring isotope or of the isotope with the longest half-life. To model some other isotope of the element, its mass must be defined explicitly by specifying the keyword mass, followed by the value (in atomic mass units) for the variable <mass>.

The default nuclear model is a point nucleus. The keyword nucleus (or nucl or nuc) followed by the model name <nucmodel> overrides this default. Allowed values of <nucmodel> are point or pt and finite or fi. The finite option is a nuclear model with a Gaussian shape. The RMS radius of the Gaussian is determined by the atomic mass number via the formula $r_{\rm RMS} = 0.836 * A^{1/3} + 0.57$ fm. The mass number A is derived from the variable <mass>.

The geometry of the system can be specified entirely in Cartesian coordinates by supplying a <tag> line of the type described above for each atom or center. The user has the option, however, of supplying the geometry of some or all of the atoms or centers using a Z-matrix description. In such a case, the user supplies the input tag line described above for any centers to be described by Cartesian coordinates, and then specifies the remainder of the system using the optional ZMATRIX directive described below in Z-matrix input.

ZMATRIX --Z-matrix input

The ZMATRIX directive is an optional directive that can be used within the compound GEOMETRY directive to specify the structure of the system with a Z-matrix, which can include both internal and Cartesian coordinates. The ZMATRIX directive is itself a compound directive that can include the VARIABLES and CONSTANTS directives, depending on the options selected. The general form of the compound ZMATRIX directive is as follows:

The input module recognizes three possible spellings of this directive name. It can be invoked with ZMATRIX, ZMT, or ZMAT. The user can specify the molecular structure using either Cartesian coordinates or internal coordinates (bond lengths, bond angles and dihedral angles. The Z-matrix input for a center defines connectivity, bond length, and bond or torsion angles. Cartesian coordinate input for a center consists of three real numbers defining the x,y,z coordinates of the atom.

Within the Z-matrix input, bond lengths and Cartesian coordinates must be input in the user-specified units, as defined by the value specified for the variable <units> on the first line of the GEOMETRY directive. All angles are specified in degrees.

The individual centers (denoted as i, j, and k below) used to specify Z-matrix connectivity may be designated either as integers (identifying each center by number) or as tags (If tags are used, the tag must be unique for each center.) The use of dummy atoms is possible, by using X or BQ at the start of the tag.

Bond lengths, bond angles and dihedral angles (denoted below as R, alpha, and beta, respectively) may be specified either as numerical values or as symbolic strings that must be subsequently defined using the VARIABLES or CONSTANTS directives. The numerical values of the symbolic strings labeled VARIABLES may be subject to changes during a geometry optimization say, while the numerical values of the symbolic strings labeled CONSTANTS will stay frozen to the value given in the input. The same symbolic string can be used more than once, and any mixture of numeric data and symbols is acceptable. Bond angles (α) must be in the range 0 < α < 180.

The Z-matrix input is specified sequentially as follows:

```
tag1
tag2 i R
tag3 i R j alpha
tag4 i R j alpha k beta [orient]
...
```

The structure of this input is described in more detail below. In the following discussion, the tag or number of the center being currently defined is labeled as C (C for current). The values entered for these tags for centers defined in the Z-matrix input are interpreted in the same way as the <tag> entries for Cartesian coordinates described above (see Cartesian coordinate input). Figures 1, 2 and 3 display the relationships between the input data and the definitions of centers and angles.



Figure 1: Relationships between the centers, bond angle and dihedral angle in Z-matrix input.



Figure 2: Relationships between the centers and two bond angles in Z-matrix input with optional parameter specified as +1.



Figure 3: Relationships between the centers and two bond angles in Z-matrix input with optional parameter specified as -1.

The Z-matrix input shown above is interpreted as follows:

1. tag1

Only a tag is required for the first center.

2. tag2 i R

The second center requires specification of its tag and the bond length (R_{Ci}) distance to a previous atom, which is identified by i.

3. tag3 i R j alpha

The third center requires specification of its tag, its bond length distance (R_{Ci}) to one of the two previous centers (identified by the value of i), and the bond angle $\alpha = \widehat{Cij}$.

4. tag i R j alpha k beta [<integer orient default 0>] The fourth, and all subsequent centers, require the tag, a bond length (R_{Ci}) relative to center i, the bond angle with centers i and j ($\alpha = \widehat{Cij}$, and either the dihedral angle (β) between the current center and centers i, j, and k (Figure 1), or a second bond angle $\beta = \widehat{Cik}$ and an orientation to the plane containing the other three centers (Figure 2 and 3).

By default, β is interpreted as a dihedral angle (see Figure 1), but if the optional final parameter (<orient>) is specified with the value ±1, then β is interpreted as the angle \widehat{Cik} . The sign of <orient> specifies the direction of the bond angle relative to the plane containing the three reference atoms. If <orient> is +1, then the new center (C) is above the plane (Figure 2); and if <orient> is -1, then C is below the plane (Figure 3).

Following the Z-matrix center definitions described above, the user can specify initial values for any symbolic variables used to define the Z-matrix tags. This is done using the optional VARIABLES directive, which has the general form:

VARIABLES <real value>

• • •

Each line contains the name of a variable followed by its value. Optionally, an equals sign (=) can be included between the symbol and its value, for clarity in reading the input file.

Following the VARIABLES directive, the CONSTANTS directive may be used to define any Z-matrix symbolic variables that remain unchanged during geometry optimizations. To freeze the Cartesian coordinates of an atom, refer to Applying constraints in geometry optimizations. The general form of this directive is as follows:

```
CONSTANTS
<string symbol> <real value>
...
```

Each line contains the name of a variable followed by its value. As with the VARIABLES directive, an equals sign (=) can be included between the symbol and its value.

The end of the Z-matrix input using the compound ZMATRIX directive is signaled by a line containing either END or ZEND, following all input for the directive itself and its associated optional directives.

A simple example is presented for water. All Z-matrix parameters are specified numerically, and symbolic tags are used to specify connectivity information. This requires that all tags be unique, and therefore different tags are used for the two hydrogen atoms, which may or may not be identical.

```
geometry
zmatrix
0
H1 0 0.95
H2 0 0.95 H1 108.0
end
end
```

The following example illustrates the Z-matrix input for the molecule CH_3CF_3 . This input uses the numbers of centers to specify the connectivity information (i, j, and k), and uses symbolic variables for the Z-matrix parameters R, alpha, and beta, which are defined in the inputs for the VARIABLES and CONSTANTS directives.

geometry

```
zmatrix
 С
C 1 CC
H 1 CH1 2 HCH1
H 1 CH2 2 HCH2 3 TOR1
H 1 CH3 2 HCH3 3 - TOR2
 F 2 CF1 1 CCF1 3 TOR3
 F 2 CF2 1 CCF2 6 FCH1
 F 2 CF3 1 CCF3 6 -FCH1
 variables
   CC
         1.4888
         1.0790
   CH1
         1.0789
   CH2
```

CH3	1.0789
CF1	1.3667
CF2	1.3669
CF3	1.3669
constan	ts
HCH1	104.28
HCH2	104.74
HCH3	104.7
CCF1	112.0713
CCF2	112.0341
CCF3	112.0340
T0R1	109.3996
T0R2	109.3997
T0R3	180.0000
FCH1	106.7846
end	
end	

The input for any centers specified with Cartesian coordinates must be specified using the format of the <tag> lines described in Cartesian coordinate input above. However, in order to correctly specify these Cartesian coordinates within the Z-matrix, the user must understand the orientation of centers specified using internal coordinates. These are arranged as follows:

- The first center is placed at the origin.
- The third center is placed in the z-x plane.

ZCOORD --Forcing internal coordinates

By default redundant internal coordinates are generated for use in geometry optimizations. Connectivity is inferred by comparing inter-atomic distances with the sum of the van der Waals radii of the two atoms involved in a possible bond, times a scaling factor. The scaling factor is an input parameter of ZCOORD which maybe changed from its default value of 1.3. Under some circumstances (unusual bonding, bond dissociation, ...) it will be necessary to augment the automatically generated list of internal coordinates to force some specific internal coordinates to be included in among the internal coordinates. This is accomplished by including the optional directive ZCOORD within the geometry directive. The general form of the ZCOORD directive is as follows:

```
ZCOORD

CVR_SCALING <real value>

BOND <integer i> <integer j> \

[<real value>] [<string name>] [constant]

ANGLE <integer i> <integer j> <integer k> \

[<real value>] [<string name>] [constant]

TORSION <integer i> <integer j> <integer k>

<integer l> \

[<real value>] [<string name>] [constant]

END
```

The centers i, j, k and l must be specified using the numbers of the centers, as supplied in the input for the Cartesian coordinates. The ZCOORD input parameters are defined as follows:

- cvr_scaling -- scaling factor applied to van der Waals radii.
- bond -- a bond between the two centers.
- angle -- a bond angle \widehat{ijk} .
- torsion -- a torsion (or dihedral) angle. The angle between the planes i-j-k and j-k-l.

A value may be specified for a user-defined internal coordinate, in which case it is forced upon the input Cartesian coordinates while attempting to make only small changes in the other internal coordinates. If no value is provided the value implicit in the input coordinates is kept. If the keyword constant is specified, then that internal variable is not modified during a geometry optimization with DRIVER. Each internal coordinate may also be named either for easy identification in the output, or for the application of constraints (Applying constraints in geometry optimizations).

If the keyword adjust is specified on the main GEOMETRY directive, only ZCOORD data may be specified and it can be used to change the user-defined internal coordinates, including adding/removing constraints and changing their values.

Applying constraints in geometry optimizations

Internal coordinates specified as constant in a ZCOORD directive or in the constants section of a ZMATRIX directive, will be frozen at their initial values if a geometry optimization is performed with DRIVER (Section 20).

If internal coordinates have the same name (give or take an optional sign for torsions) then they are forced to have the same value. This may be used to force bonds or angles to be equal even if they are not related by symmetry.

When atoms have been specified by their Cartesian coordinates, and internal coordinates are not being used, it is possible to freeze the cartesian position of selected atoms. This is useful for such purposes as optimizing a molecule absorbed on the surface of a cluster with fixed geometry. Only the gradients associated with the active atoms are computed. This can result in a big computational saving, since gradients associated with frozen atoms are forced to zero (Note, however, that this destroys the translational and rotational invariance of the gradient. This is not yet fully accommodated by the STEPPER geometry optimization software, and can sometimes result in slower convergence of the optimization. The DRIVER optimization package does not suffer from this problem).

The SET directive is used to freeze atoms, by specifying a directive of the form:

set geometry:actlist <integer list_of_center_numbers>

This defines only the centers in the list as active. All other centers will have zero force assigned to them, and will remain frozen at their starting coordinates during a geometry optimization.

For example, the following directive specifies that atoms numbered 1, 5, 6, 7, 8, and 15 are active and all other atoms are frozen:

set geometry:actlist 1 5:8 15

or equivalently,

set geometry:actlist 1 5 6 7 8 15

If this option is not specified by entering a SET directive, the default behavior in the code is to treat all atoms as active. To revert to this default behavior after the option to define frozen atoms has been invoked, the UNSET directive must be used. The form of the UNSET directive is as follows:

```
unset geometry:actlist
```

SYSTEM --Lattice parameters for periodic systems

This keyword is needed only for for 1-, 2-, and 3-dimensional periodic systems.

The system keyword can assume the following values

- polymer -- system with 1-d translational symmetry (not currently available with NWPW module).
- surface -- system with 2-d translational symmetry (not currently available with NWPW module).
- crystal -- system with 3-d translational symmetry.
- molecule -- no translational symmetry (this is the default)

When the system possess translational symmetry, fractional coordinates are used in the directions where translational symmetry exists. This means that for crystals x, y and z are fractional, for surfaces x and y are fractional, whereas for polymers only z is fractional. For example, in the following H_2O layer input (a 2-d periodic system), x and y coordinates are fractional, whereas z is expressed in Angstroms.

geometry units angstrom

0	0.353553	0.353553	2.100000000
Н	0.263094	0.353553	2.663590000
Н	0.444007	0.353553	2.663590000

Since no space group symmetry is available yet other than P1, input of cell parameters is relative to the primitive cell. For example, this is the input required for the cubic face-centered type structure of bulk MgO.

system crystal
lat_a 2.97692
lat_b 2.97692
lat_c 2.97692
alpha 60.00
beta 60.00
gamma 60.00

end

References

- [1] http://img.chem.ucl.ac.uk/sgp/mainmenu.htm
- [2] http://cst-www.nrl.navy.mil/lattice/spcgrp/index.html
- [3] http://www.uwgb.edu/dutchs/SYMMETRY/3dSpaceGrps/3dspgrp.htm
- [4] http://www.cryst.ehu.es/cgi-bin/cryst/programs/nph-repres?&change=new&ita=1

Release65:Basis

__NOTITLE__

Basis sets

NWChem currently supports basis sets consisting of generally contracted Cartesian Gaussian functions up to a maximum angular momentum of six (h functions), and also sp (or L) functions. The BASIS directive is used to define these, and also to specify use of an Effective Core Potential (ECP) that is associated with a basis set.

The basis functions to be used for a given calculation can be drawn from a standard set in the EMSL basis set library $^{[1]}$ that is included in the release of NWChem. Alternatively, the user can specify particular functions explicitly in the input, to define a particular basis set.

The general form of the BASIS directive is as follows:

Examining the keywords on the first line of the BASIS directive:

• name :

By default, the basis set is stored in the database with the name "ao basis". Another name may be specified in the BASIS directive, thus, multiple basis sets may be stored simultaneously in the database. Also, the DFT and RI-MP2 modules and the Dyall-modified-Dirac relativistic method require multiple basis sets with specific names. The user can associate the "ao basis" with another named basis using the SET directive (see SET).

• SPHERICAL or CARTESIAN :

The keywords spherical and cartesian offer the option of using either spherical-harmonic (5 d, 7 f, 9 g, ...) or Cartesian (6 d, 10 f, 15 g, ...) angular functions. The default is Cartesian. Note that the correlation-consistent basis sets were designed using spherical harmonics and to use these, the spherical keyword should be present in the BASIS

directive. The use of spherical functions also helps eliminate problems with linear dependence.

	Cartesian	Spherical
1	S	S
1	p _x	p _x
2	p _y	p _y
3	p _z	p _z
1	d _{xx}	d _{xy}
2	d _{xy}	d _{yz}
3	d _{xz}	$d_{z}^{2} - x^{2} - y^{2}$
4	d _{yy}	d _{xz}
5	d _{yz}	d _x 2 _{-y} 2
6	d _{zz}	
1	f _{xxx}	f _{xxy-yyy}
2	f _{xxy}	f _{xyz}
3	f _{xxz}	f _{yzz-xxy-yyy}
4	f _{xyy}	f _{zzz-xxz-yyz}
5	f _{xyz}	f _{-xzz+xxx+xyy}
6	f _{xzz}	f _{xxz-yyz}
7	f _{yyy}	f _{xyy-xxx}
8	f _{yyz}	
9	f	
10	f	

Order of functions.

• PRINT or NOPRINT :

The default is for the input module to print all basis sets encountered. Specifying the keyword noprint allows the user to suppress this output.

• REL :

This keyword marks the entire basis as a relativistic basis for the purposes of the Dyall-modified-Dirac relativistic integral code. The marking of the basis set is necessary for the code to make the proper association between the relativistic shells in the ao basis and the shells in the large and/or small component basis. This is only necessary for basis sets which are to be used as the ao basis. The user is referred to the section on Dyall's modified Dirac-Hamiltonian approximation for more details.

Basis sets are associated with centers by using the tag of a center in a geometry that has either been input by the user or is available elsewhere. Each atom or center with the same tag will have the same basis set. All atoms must have basis functions assigned to them -only dummy centers (X or Bq) may have no basis functions. To facilitate the specification of the geometry and the basis set for any chemical system, the matching process of a basis set tag to a geometry tag first looks for an exact match. If no match is found, NWChem will attempt to match, ignoring case, the name or symbol of the element. E.g., all hydrogen atoms in a system could be labeled "H1", "H2", ..., in the geometry but only one basis set specification for "H" or "hydrogen" is necessary. If desired, a special basis may be added to one or more centers (e.g., "H1") by providing a basis for that tag. If the matching mechanism fails then NWChem stops with an appropriate error message.

A special set of tags, "*" and tags ending with a "*" (E.g. "H*") can be used in combination with the keyword library. These tags facilitate the definition of a certain type of basis set of all atoms, or a group of atoms, in a geometry using only a single or very few basis set entries. The "*" tag will not place basis sets on dummy atoms, Bq* can be used for that if necessary.

Examined next is how to reference standard basis sets in the basis set library, and finally, how to define a basis set using exponents and coefficients.

Basis set library

The keyword library associated with each specific tag entry specifies that the calculation will use the standard basis set in NWChem for that center. The variable <standard_set> is the name that identifies the functions in the library. The names of standard basis sets are not case sensitive. For a complete list of basis sets and associated ECPs in the NWChem library see the available basis sets or the EMSL Basis Set Exchange ^[2] for naming conventions and their specifications.

The general form of the input line requesting basis sets from the NWChem basis set library is:

For example, the NWChem basis set library contains the Dunning cc-pvdz basis set. These may be used as follows

```
basis
   oxygen library cc-pvdz
   hydrogen library cc-pvdz
end
```

A default path of the NWChem basis set libraries is provided on installation of the code, but a different path can be defined by specifying the keyword file, and one can explicitly name the file to be accessed for the basis functions. For example,

```
basis
    o library 3-21g file /usr/d3g681/nwchem/library
    si library 6-31g file /usr/d3g681/nwchem/libraries/
end
```

directive tells the This code to use the basis set 3-21g in the file /usr/d3q681/nwchem/library for atom o and to use the basis set 6-31g in the directory /usr/d3g681/nwchem/libraries/ for atom si, rather than look for them in the default libraries. When a directory is defined the code will search for the basis set in a file with the

name 6-31g.

The "*" tag can be used to efficiently define basis set input directives for large numbers of atoms. An example is:

```
basis
    * library 3-21g
end
```

This directive tells the code to assign the basis sets 3-21g to all the atom tags defined in the geometry. If one wants to place a different basis set on one of the atoms defined in the geometry, the following directive can be used:

```
basis
  * library 3-21g except H
end
```

This directive tells the code to assign the basis sets 3-21g to all the atoms in the geometry, except the hydrogen atoms. Remember that the user will have to explicitly define the hydrogen basis set in this directive! One may also define tags that end with a "*":

```
basis
    oxy* library 3-21g
end
```

This directive tells the code to assign the basis sets 3-21g to all atom tags in the geometry that start with "oxy".

If standard basis sets are to be placed upon a dummy center, the variable <tag_in_lib> must also be entered on this line, to identify the correct atom type to use from the basis function library (see the ghost atom example in SET and below). For example: To specify the cc-pvdz basis for a calculation on the water monomer in the dimer basis, where the dummy oxygen and dummy hydrogen centers have been identified as bqo and bqh respectively, the BASIS directive is as follows:

```
basis
    o library cc-pvdz
    h library cc-pvdz
    bqo library o cc-pvdz
    bqh library h cc-pvdz
end
```

A special dummy center tag is bq*, which will assign the same basis set to all bq centers in the geometry. Just as with the "*" tag, the except list can be used to assign basis sets to unique dummy centers.

The library basis sets can also be marked as relativistic by adding the rel keyword to the tag line. See the section on relativistic all-electron approximations for more details. The correlation consistent basis sets have been contracted for relativistic effects and are included in the standard library.

There are also contractions in the standard library for both a point nucleus and a finite nucleus of Gaussian shape. These are usually distinguished by the suffix _pt and _fi. It is the user's responsibility to ensure that the contraction matches the nuclear type specified in

the geometry object. The specification of a finite nucleus basis set does NOT automatically set the nuclear type for that atom to be finite. See Geometries for information.

Explicit basis set definition

If the basis sets in the library or available in other external files are not suitable for a given calculation, the basis set may be explicitly defined. A generally contracted Gaussian basis function is associated with a center using an input line of the following form:

```
<string tag> <string shell_type> [rel]
  <real exponent> <real list_of_coefficients>
   ...
```

The variable <shell_type> identifies the angular momentum of the shell, *s*, *p*, *d*, NWChem is configured to handle up to h shells. The keyword rel marks the shell as relativistic -- see Section 9.3 for more details. Subsequent lines define the primitive function exponents and contraction coefficients. General contractions are specified by including multiple columns of coefficients.

The following example defines basis sets for the water molecule:

```
basis spherical
  oxygen s
    11720.0000
                   0.000710
                              -0.000160
     1759.0000
                   0.005470
                              -0.001263
      400.8000
                   0.027837
                              -0.006267
      113.7000
                   0.104800
                              -0.025716
       37.0300
                   0.283062
                              -0.070924
       13.2700
                   0.448719
                              -0.165411
                              -0.116955
        5.0250
                   0.270952
        1.0130
                   0.015458
                               0.557368
        0.3023
                  -0.002585
                               0.572759
  oxygen s
        0.3023
                   1.000000
  oxygen p
       17.7000
                   0.043018
                   0.228913
        3.8540
                   0.508728
        1.0460
        0.2753
                   0.460531
  oxygen p
        0.2753
                   1.000000
  oxygen d
        1.1850
                   1.000000
  hydrogen s
       13.0100
                   0.019685
        1.9620
                   0.137977
        0.4446
                   0.478148
        0.1220
                   0.501240
  hydrogen s
        0.1220
                   1.000000
```

```
hydrogen p
0.7270 1.000000
oxygen s
0.01 1.0
hydrogen s
0.02974 1.0
hydrogen p
0.141 1.0
end
```

Explicit basis set specifications are available from the basis set exchange ^[3]. We strive to provide all the basis sets from the exchange as an integral part of the internal basis set library.

Combinations of library and explicit basis set input

The user can use a mixture of library basis and explicit basis set input to define the basis sets used on the various atoms.

For example, the following BASIS directive augments the Dunning cc-pvdz basis set for the water molecule with a diffuse s-shell on oxygen and adds the aug-cc-pVDZ diffuse functions onto the hydrogen.

```
basis spherical
  oxygen library cc-pvdz
  hydrogen library cc-pvdz
  oxygen s
    0.01 1.0
  hydrogen library "aug-cc-pVDZ Diffuse"
end
```

The resulting basis set defined is identical to the one defined above in the explicit basis set input.

References

- [1] https://bse.pnl.gov/bse/portal
- [2] https://bse.pnl.gov/bse/portal
- [3] https://bse.pnl.gov/bse/portal

Release65:ECP

__NOTITLE__

Effective Core Potentials

Effective core potentials (ECPs) are a useful means of replacing the core electrons in a calculation with an effective potential, thereby eliminating the need for the core basis functions, which usually require a large set of Gaussians to describe them. In addition to replacing the core, they may be used to represent relativistic effects, which are largely confined to the core. In this context, both the scalar (spin-free) relativistic effects and spin-orbit (spin-dependent) relativistic effects may be included in effective potentials. NWChem has the facility to use both, and these are described in the next two sections.

A brief recapitulation of the development of RECPs is given here, following Pacios and Christiansen. The process can be viewed as starting from an atomic Dirac-Hartree-Fock calculation, done in jj coupling, and producing relativistic effective potentials (REPs) for each l and j value, U_{lj}^{REP} . From these, a local potential is extracted, which for example contains the Coulomb potential of the core electrons balanced by the part of the nuclear attraction which cancels the core electron charge. The residue is expressed in a semi-local

form,
$$U^{REP} = U_{LJ}^{REP}(r) + \sum_{l=0}^{L-1} \sum_{j=l-1/2}^{l+1/2} \left[U_{ij}^{REP}(r) - U_{LJ}^{REP}(r) \right] \sum_{m} |ljm\rangle \langle ljm|$$

where L is one larger than the maximum angular momentum in the atom. The scalar potential is obtained by averaging the REPs for each j for a given l to give an averaged relativistic effective potential, or AREP, $U_l^{AREP}(r) = \frac{1}{2l+1} \left[l U_{l-1/2}^{REP}(r) + (l+1) U_{l+1/2}^{REP}(r) \right].$

These are summed into the full potential.

The spin-orbit potential is obtained from the difference between the REPs for the two j values for a given l, and may be represented in terms of an effective spin-orbit operator, $H^{SO} = \mathbf{s} \cdot \sum_{l=1}^{L-1} \frac{2}{2l+1} \Delta U_l^{REP} \sum_{mm'} \langle lm | \hat{l} | lm' \rangle \langle lm' |.$

where

 $\Delta U_l^{REP} = U_{l+1/2}^{REP}(r) - U_{l-1/2}^{REP}(r).$

The spin-orbit integrals generated by NWChem are the integrals over the sum, including the factor of 2/(2l+1), so that they may be treated as an effective spin-orbit operator without further factors introduced.

The effective potentials, both scalar and spin-orbit, are fitted to Gaussians with the form

$$r^{2}U_{l}(r) = \sum_{k} A_{lk} r^{n_{lk}} e^{-B_{lk}r^{2}}$$

where A_{lk} is the contraction coefficient, n_{lk} is the exponent of the *r* term (r-exponent), and B_{lk} is the Gaussian exponent. The n_{lk} is shifted by 2, in accordance with most of the ECP literature and implementations, i.e., an $n_{lk} = 0$ implies r^{-2} . The current implementation allows n_{lk} values of only 0, 1, or 2.
Scalar ECPs

The optional directive ECP allows the user to describe an effective core potential (ECP) in terms of contracted Gaussian functions as given above. Potentials using these functions must be specified explicitly by user input in the ECP directive. This directive has essentially the same form and properties as the standard BASIS directive, except for essential differences required for ECPs. Because of this, the ECP is treated internally as a basis set. The form of the input for the ECP directive is as follows:

ECPs are automatically segmented, even if general contractions are input. The projection operators defined in an ECP are spherical by default, so there is no need to include the CARTESIAN or SPHERICAL keyword as there is for a standard basis set. ECPs are associated with centers in geometries through tags or names of centers. These tags must match in the same manner as for basis sets the tags in a GEOMETRY and ECP directives, and are limited to sixteen (16) characters. Each center with the same tag will have the same ECP. By default, the input module prints each ECP that it encounters. The NOPRINT option can be used to disable printing. There can be only one active ECP, even though several may exist in the input deck. The ECP modules load "ecp basis" inputs along with any "ao basis" inputs present. ECPs may be used in both energy and gradient calculations.

ECPs are named in the same fashion as geometries or regular basis sets, with the default name being "ecp basis". It should be clear from the above discussion on geometries and database entries how indirection is supported. All directives that are in common with the standard Gaussian basis set input have the same function and syntax.

As for regular basis sets, ECPs may be obtained from the standard library. For a complete list of basis sets and associated ECPs in the NWChem library see the available basis sets or the EMSL Basis Set Exchange ^[1] for naming conventions and their specifications.

The keyword nelec allows the user to specify the number of core electrons replaced by the ECP. Additional input lines define the specific coefficients and exponents. The variable <shell_type> is used to specify the components of the ECP. The keyword ul entered for <shell_type> denotes the local part of the ECP. This is equivalent to the highest angular momentum functions specified in the literature for most ECPs. The standard entries (s, p, d, etc.) for shell_type specify the angular momentum projector onto the local function. The shell type label of s indicates the ul-s projector input, p indicates the ul-p, etc.

For example, the Christiansen, Ross and Ermler ARECPs are available in the standard basis set libary named "crenbl_ecp". To perform a calculation on uranyl (UO_2^{2+}) with all-electron oxygen (aug-cc-pvdz basis), and uranium with an ARECP and using the corresponding basis the following input can be used

```
geometry
U 0 0 0
0 0 0 1.65
0 0 0 -1.65
end
basis
U library crenbl_ecp
0 library aug-cc-pvdz
end
ecp
U library crenbl_ecp
end
```

The following is an example of explicit input of an ECP for H_2CO . It defines an ECP for the carbon and oxygen atoms in the molecule.

```
ecp
  C nelec 2 # ecp replaces 2 electrons on C
  C ul
            # d
          1
                   80.000000
                                     -1.60000000
          1
                   30.000000
                                     -0.4000000
                    0.5498205
                                     -0.03990210
          2
 C s
            # s - d
          0
                    0.7374760
                                      0.63810832
          0
                  135.2354832
                                     11.00916230
          2
                    8.5605569
                                     20.13797020
  Ср
            # p - d
          2
                   10.6863587
                                     -3.24684280
          2
                   23.4979897
                                      0.78505765
  0 nelec 2 # ecp replaces 2 electrons on 0
  0 ul
            # d
          1
                   80.000000
                                     -1.60000000
          1
                   30.000000
                                     -0.4000000
                    1.0953760
                                     -0.06623814
          2
  0 s
            # s - d
          0
                    0.9212952
                                      0.39552179
                                      2.51654843
          0
                   28.6481971
          2
                    9.3033500
                                     17.04478500
            # p - s
  0 p
                   52.3427019
                                     27.97790770
          2
          2
                   30.7220233
                                    -16.49630500
end
```

Various ECPs without a local function are available, including those of the Stuttgart group. For those, no "ul" part needs to be defined. To define the absence of the local potential, simply specify one contraction with a zero coefficient:

<string tag> ul 2 1.00000 0.00000

Spin-orbit ECPs

The Spin-orbit ECPs can be used with the Density Functional Approach, but one has to run the calculations without symmetry. Note: when a Hartree-Fock method is specified the spin-orbit input will be ignored.

Spin-orbit ECPs are fitted in precisely the same functional form as the scalar RECPs and have the same properties, with the exception that there is no local potential ul, no *s* potential and no effective charge has to be defined. Spin-orbit potentials are specified in the same way as ECPs except that the directive SO is used instead of ECP. Note that there currently are no spin-orbit ECPs defined in the standard NWChem library. The SO directive is as follows:

```
S0 [<string name default "so basis">] \
      [print || noprint default print]
      <string tag> library [<string tag_in_lib>] \
            <string standard_set> [file <filename>]
            [except <string tag list>]
            ...
      <string tag> <string shell_type>
      <real r-exponent> <real Gaussian-exponent> <real
list_of_coefficients>
            ...
END
```

Note: in the literature the coefficients of the spin-orbit potentials are NOT always defined in the same manner. The NWChem code assumes that the spin-orbit potential defined in the input is of the form: $\Delta U_l^{NWChem} = \frac{2}{2l+1} \Delta U_l$

For example, in the literature (most of) the Stuttgart potentials are defined as ΔU_l and, hence, have to be multiplied by 2/(2l+1) (Note: On the Stuttgart and Kohln web pages the spin-orbit potentials have already been corrected by the appropriate scaling factor and can be used as is). On the other hand, the CRENBL potentials in the published papers are defined as $\frac{l}{2l+1}\Delta U_l$ and, hence, have to be multiplied by 2/l (Note: On the CRENBL website the spin-orbit potentials already have been corrected with the 2/l factor, so make sure the appropriate scaling is applied).

References

[1] https://bse.pnl.gov/bse/portal

Release65:Relativistic All-electron Approximations

NOTITLE

Relativistic all-electron approximations

All methods which include treatment of relativistic effects are ultimately based on the Dirac equation, which has a four component wave function. The solutions to the Dirac equation describe both positrons (the "negative energy' states) and electrons (the "positive energy" states), as well as both spin orientations, hence the four components. The wave function may be broken down into two-component functions traditionally known as the large and small components; these may further be broken down into the spin components.

The implementation of approximate all-electron relativistic methods in quantum chemical codes requires the removal of the negative energy states and the factoring out of the spin-free terms. Both of these may be achieved using a transformation of the Dirac Hamiltonian known in general as a Foldy-Wouthuysen transformation. Unfortunately this transformation cannot be represented in closed form for a general potential, and must be approximated. One popular approach is that originally formulated by Douglas and Kroll^[1] and developed by Hess^{[2] [3]}. This approach decouples the positive and negative energy parts to second order in the external potential (and also fourth order in the fine structure constant, α). Other approaches include the Zeroth Order Regular Approximation (ZORA)^[4] ^{[5] [6] [7]} and modification of the Dirac equation by Dyall^[8], and involves an exact FW transformation on the atomic basis set level^{[9] [10]}.

Since these approximations only modify the integrals, they can in principle be used at all levels of theory. At present the Douglas-Kroll and ZORA implementations can be used at all levels of theory whereas Dyall's approach is currently available at the Hartree-Fock level. The derivatives have been implemented, allowing both methods to be used in geometry optimizations and frequency calculations.

The RELATIVISTIC directive provides input for the implemented relativistic approximations and is a compound directive that encloses additional directives specific to the approximations:

Only one of the methods may be chosen at a time. If both methods are found to be on in the input block, NWChem will stop and print an error message. There is one general option for both methods, the definition of the speed of light in atomic units:

CLIGHT <real clight default 137.0359895>

The following sections describe the optional sub-directives that can be specified within the RELATIVISTIC block.

Douglas-Kroll approximation

The spin-free and spin-orbit one-electron Douglas-Kroll approximation have been implemented. The use of relativistic effects from this Douglas-Kroll approximation can be invoked by specifying:

DKH>]

The ON|OFF string is used to turn on or off the Douglas-Kroll approximation. By default, if the DOUGLAS-KROLL keyword is found, the approximation will be used in the calculation. If the user wishes to calculate a non-relativistic quantity after turning on Douglas-Kroll, the user will need to define a new RELATIVISTIC block and turn the approximation OFF. The user could also simply put a blank RELATIVISTIC block in the input file and all options will be turned off.

The FPP is the approximation based on free-particle projection operators^[11] whereas the DKH and DKFULL approximations are based on external-field projection operators^[12]. The latter two are considerably better approximations than the former. DKH is the Douglas-Kroll-Hess approach and is the approach that is generally implemented in quantum chemistry codes. DKFULL includes certain cross-product integral terms ignored in the DKH approach (see for example Häberlen and Rösch^[13]). The third-order Douglas-Kroll approximation has been implemented by T. Nakajima and K. Hirao^[14] ^[15]. This approximation can be called using DK3 (DK3 without cross-product integral terms) or DK3FULL (DK3 with cross-product integral terms).

The contracted basis sets used in the calculations should reflect the relativistic effects, i.e. one should use contracted basis sets which were generated using the Douglas-Kroll Hamiltonian. Basis sets that were contracted using the non-relativistic (Schödinger) Hamiltonian WILL PRODUCE ERRONEOUS RESULTS for elements beyond the first row. See appendix A for available basis sets and their naming convention.

NOTE: we suggest that spherical basis sets are used in the calculation. The use of high quality cartesian basis sets can lead to numerical inaccuracies.

In order to compute the integrals needed for the Douglas-Kroll approximation the implementation makes use of a fitting basis set (see literature given above for details). The current code will create this fitting basis set based on the given "ao basis" by simply uncontracting that basis. This again is what is commonly implemented in quantum chemistry codes that include the Douglas-Kroll method. Additional flexibility is available to the user by explicitly specifying a Douglas-Kroll fitting basis set. This basis set must be named "D-K basis" (see Basis Sets).

Zeroth Order regular approximation (ZORA)

The spin-free and spin-orbit one-electron zeroth-order regular approximation (ZORA) have been implemented. The use of relativistic effects with ZORA can be invoked by specifying:

ZORA [<string (ON||OFF) default ON>

The ON|OFF string is used to turn on or off ZORA. By default, if the ZORA keyword is found, the approximation will be used in the calculation. If the user wishes to calculate a non-relativistic quantity after turning on ZORA, the user will need to define a new RELATIVISTIC block and turn the approximation OFF. The user can also simply put a blank RELATIVISTIC block in the input file and all options will be turned off.

Dyall's Modified Dirac Hamitonian approximation

The approximate methods described in this section are all based on Dyall's modified Dirac Hamiltonian. This Hamiltonian is entirely equivalent to the original Dirac Hamiltonian, and its solutions have the same properties. The modification is achieved by a transformation on the small component, extracting out $\sigma \cdot \mathbf{p}/2mc$. This gives the modified small component the same symmetry as the large component, and in fact it differs from the large component only at order α^2 . The advantage of the modification is that the operators now resemble the operators of the Breit-Pauli Hamiltonian, and can be classified in a similar fashion into spin-free, spin-orbit and spin-spin terms. It is the spin-free terms which have been implemented in NWChem, with a number of further approximations.

The first is that the negative energy states are removed by a normalized elimination of the small component (NESC), which is equivalent to an exact Foldy-Wouthuysen (EFW) transformation. The number of components in the wave function is thereby effectively reduced from 4 to 2. NESC on its own does not provide any advantages, and in fact complicates things because the transformation is energy-dependent. The second approximation therefore performs the elimination on an atom-by-atom basis, which is equivalent to neglecting blocks which couple different atoms in the EFW transformation. The advantage of this approximation is that all the energy dependence can be included in the contraction coefficients of the basis set. The tests which have been done show that this approximation gives results well within chemical accuracy. The third approximation neglects the commutator of the EFW transformation with the two-electron Coulomb interaction, so that the only corrections that need to be made are in the one-electron integrals. This is the equivalent of the Douglas-Kroll(-Hess) approximation as it is usually applied.

The use of these approximations can be invoked with the use of the DYALL-MOD-DIRAC directive in the RELATIVISTIC directive block. The syntax is as follows.

DYALL-MOD-DIRAC [(ON || OFF) default ON] [(NESC1E || NESC2E) default NESC1E]

The ON|OFF string is used to turn on or off the Dyall's modified Dirac approximation. By default, if the DYALL-MOD-DIRAC keyword is found, the approximation will be used in the calculation. If the user wishes to calculate a non-relativistic quantity after turning on Dyall's modified Dirac, the user will need to define a new RELATIVISTIC block and turn the approximation OFF. The user could also simply put a blank RELATIVISTIC block in the input file and all options will be turned off.

Both one- and two-electron approximations are available NESC1E || NESC2E, and both have analytic gradients. The one-electron approximation is the default. The two-electron approximation specified by NESC2E has some sub options which are placed on the same logical line as the DYALL-MOD-DIRAC directive, with the following syntax:

NESC2E [(SS1CENT [(ON || OFF) default ON] || SSALL) default SSALL]
[(SSSS [(ON || OFF) default ON] || NOSSSS) default SSSS]

The first sub-option gives the capability to limit the two-electron corrections to those in which the small components in any density must be on the same center. This reduces the (LL|SS) contributions to at most three-center integrals and the (SS|SS) contributions to two centers. For a case with only one relativistic atom this option is redundant. The second controls the inclusion of the (SS|SS) integrals which are of order α^4 . For light atoms they may safely be neglected, but for heavy atoms they should be included.

In addition to the selection of this keyword in the RELATIVISTIC directive block, it is necessary to supply basis sets in addition to the ao basis. For the one-electron approximation, three basis sets are needed: the atomic FW basis set, the large component basis set and the small component basis set. The atomic FW basis set should be included in the ao basis. The large and small components should similarly be incorporated in basis sets named large component and small component, respectively. For the two-electron approximation, only two basis sets are needed. These are the large component and the small component. The large component should be included in the ao basis and the small component is specified separately as small component, as for the one-electron approximation. This means that the two approximations can not be run correctly without changing the ao basis, and it is up to the user to ensure that the basis sets are correctly specified.

There is one further requirement in the specification of the basis sets. In the ao basis, it is necessary to add the rel keyword either to the basis directive or the library tag line (See below for examples). The former marks the basis functions specified by the tag as relativistic, the latter marks the whole basis as relativistic. The marking is actually done at the unique shell level, so that it is possible not only to have relativistic and nonrelativistic atoms, it is also possible to have relativistic and nonrelativistic shells on a given atom. This would be useful, for example, for diffuse functions or for high angular momentum correlating functions, where the influence of relativity was small. The marking of shells as relativistic is necessary to set up a mapping between the ao basis and the large and/or small component basis sets. For the one-electron approximation the large and small component basis sets MUST be of the same size and construction, i.e. differing only in the contraction coefficients.

It should also be noted that the relativistic code will NOT work with basis sets that contain sp shells, nor will it work with ECPs. Both of these are tested and flagged as an error.

Some examples follow. The first example sets up the data for relativistic calculations on water with the one-electron approximation and the two-electron approximation, using the library basis sets.

```
start h2o-dmd
geometry units bohr
symmetry c2v
0 0.00000000 0.00000000 -0.009000000
```

```
Н
          1.515260000
                         0.000000000
                                        -1.058900000
  Н
         -1.515260000
                         0.000000000
                                        -1.058900000
end
basis "fw" rel
  oxygen library cc-pvdz pt sf fw
  hydrogen library cc-pvdz pt sf fw
end
basis "large"
  oxygen library cc-pvdz pt sf lc
  hydrogen library cc-pvdz_pt_sf_lc
end
basis "large2" rel
  oxygen library cc-pvdz pt sf lc
  hydrogen library cc-pvdz_pt_sf_lc
end
basis "small"
  oxygen library cc-pvdz_pt_sf_sc
  hydrogen library cc-pvdz_pt_sf_sc
end
set "ao basis" fw
set "large component" large
set "small component" small
relativistic
  dyall-mod-dirac
end
task scf
set "ao basis" large2
unset "large component"
set "small component" small
relativistic
  dyall-mod-dirac nesc2e
end
task scf
```

The second example has oxygen as a relativistic atom and hydrogen nonrelativistic.

```
start h2o-dmd2
geometry units bohr
symmetry c2v
                         0.00000000
  0
          0.000000000
                                       -0.009000000
  Н
         1.515260000
                         0.000000000
                                       -1.058900000
  Н
         -1.515260000
                         0.000000000
                                       -1.058900000
end
basis "ao basis"
  oxygen library cc-pvdz pt sf fw rel
  hydrogen library cc-pvdz
end
basis "large component"
```

```
oxygen library cc-pvdz_pt_sf_lc
end
basis "small component"
   oxygen library cc-pvdz_pt_sf_sc
end
relativistic
   dyall-mod-dirac
end
task scf
[1] <refbase>20</refbase>
[2] <refbase>18</refbase>
[3] <refbase>19</refbase>
```

[4] <refbase>21</refbase>
[5] <refbase>22</refbase>
[6] <refbase>23</refbase>
[7] <refbase>30</refbase>
[8] <refbase>24</refbase>
[9] <refbase>25</refbase>
[10] <refbase>18</refbase>
[11] <refbase>18</refbase>
[12] <refbase>19</refbase>
[13] <refbase>27</refbase>

[14] <refbase>28</refbase>
[15] <refbase>29</refbase>

Quantum Mechanical Methods

Release65:Hartree-Fock Theory for Molecules

__NOTITLE__

Hartree-Fock

The NWChem self-consistent field (SCF) module computes closed-shell restricted Hartree-Fock (RHF) wavefunctions, restricted high-spin open-shell Hartree-Fock (ROHF) wavefunctions, and spin-unrestricted Hartree-Fock (UHF) wavefunctions. The Hartree-Fock equations are solved using a conjugate-gradient method with an orbital Hessian based preconditioner^[1]. The module supports both replicated data and distributed data Fock builders^[2].

The SCF directive provides input to the SCF module and is a compound directive that encloses additional directives specific to the SCF module:

SCF

Wavefunction type

A spin-restricted, closed shell RHF calculation is performed by default. An error results if the number of electrons is inconsistent with this assumption. The number of electrons is inferred from the total charge on the system and the sum of the effective nuclear charges of all centers (atoms and dummy atoms, see GEOMETRY). The total charge on the system is zero by default, unless specified at some value by input on the CHARGE directive Total system charge.

The options available to define the SCF wavefunction and multiplicity are as follows:

SINGLET DOUBLET TRIPLET QUARTET QUINTET SEXTET SEPTET OCTET NOPEN <integer nopen default 0> RHF ROHF UHF The optional keywords SINGLET, DOUBLET, ..., OCTET and NOPEN allow the user to specify the number of singly occupied orbitals for a particular calculation. SINGLET is the default, and specifies a closed shell; DOUBLET specifies one singly occupied orbital; TRIPLET specifies two singly occupied orbitals; and so forth. If there are more than seven singly occupied orbitals, the keyword NOPEN must be used, with the integer nopen defining the number of singly occupied orbitals (sometimes referred to as open shells).

If the multiplicity is any value other than SINGLET, the default calculation will be a spin-restricted, high-spin, open-shell SCF calculation (keyword ROHF). The open-shell orbitals must be the highest occupied orbitals. If necessary, any starting vectors may be rearranged through the use of the SWAP keyword on the VECTORS directive to accomplish this.

A spin-unrestricted solution can also be performed by specifying the keyword UHF. In UHF calculations, it is assumed that the number of singly occupied orbitals corresponds to the difference between the number of alpha-spin and beta-spin orbitals. For example, a UHF calculation with 2 more alpha-spin orbitals than beta-spin orbitals can be obtained by specifying

```
scf
   triplet ; uhf # (Note: two logical lines of input)
   ...
end
```

The user should be aware that, by default, molecular orbitals are symmetry adapted in NWChem. This may not be desirable for fully unrestricted wavefunctions. In such cases, the user has the option of defeating the defaults by specifying the keywords ADAPT OFF and SYM OFF .

The keywords RHF and ROHF are provided in the code for completeness. It may be necessary to specify these in order to modify the behavior of a previous calculation (see NWChem Architecture for restart behavior).

SYM --use of symmetry

```
SYM <string (ON||OFF) default ON>
```

This directive enables/disables the use of symmetry to speed up Fock matrix construction (via the petite-list or skeleton algorithm) in the SCF, if symmetry was used in the specification of the geometry. Symmetry adaptation of the molecular orbitals is not affected by this option. The default is to use symmetry if it is specified in the geometry directive.

For example, to disable use of symmetry in Fock matrix construction:

sym off

ADAPT -symmetry adaptation of MOs

ADAPT <string (ON||OFF) default ON>

The default in the SCF module calculation is to force symmetry adaption of the molecular orbitals. This does not affect the speed of the calculation, but without explicit adaption the resulting orbitals may be symmetry contaminated for some problems. This is especially likely if the calculation is started using orbitals from a distorted geometry.

The underlying assumption in the use of symmetry in Fock matrix construction is that the density is totally symmetric. If the orbitals are symmetry contaminated, this assumption may not be valid -- which could result in incorrect energies and poor convergence of the calculation. It is thus advisable when specifying ADAPT OFF to also specify SYM OFF (Use of Symmetry).

TOL2E --integral screening threshold

```
TOL2E <real tol2e default min(10e-7 , 0.01*thresh)>
```

The variable tol2e is used in determining the integral screening threshold for the evaluation of the energy and related Fock-like matrices. The Schwarz inequality is used to screen the product of integrals and density matrices in a manner that results in an accuracy in the energy and Fock matrices that approximates the value specified for tol2e.

It is generally not necessary to set this parameter directly. Specify instead the required precision in the wavefunction, using the THRESH directive (Convergence threshold). The default threshold is the minimum of 10^{-7} and 0.01 times the requested convergence threshold for the SCF calculation (Convergence threshold).

The input to specify the threshold explicitly within the SCF directive is, for example:

tol2e 1e-9

For very diffuse basis sets, or for high-accuracy calculations it might be necessary to set this parameter. A value of 10^{-12} is sufficient for nearly all such purposes.

VECTORS --input/output of MO vectors

The VECTORS directive allows the user to specify the source and destination of the molecular orbital vectors. In a startup calculation (see START), the default source for guess vectors is a diagonalized Fock matrix constructed from a superposition of the atomic

density matrices for the particular problem. This is usually a very good guess. For a restarted calculation, the default is to use the previous MO vectors.

The optional keyword INPUT allows the user to specify the source of the input molecular orbital vectors as any of the following:

- ATOMIC -- eigenvectors of a Fock-like matrix formed from a superposition of the atomic densities (the default guess). See Atomic guess and Accuracy of initial guess.
- HCORE -- eigenvectors of the bare-nucleus Hamiltonian or the one-electron Hamiltonian.
- filename -- the name of a file containing the MO vectors from a previous calculation. Note that unless the path is fully qualified, or begins with a dot ("."), then it is assumed to reside in the directory for permanent files (see File directories).
- PROJECT basisname filename -- projects the existing MO vectors in the file filename from the smaller basis with name basisname into the current basis. The definition of the basis basisname must be available in the current database, and the basis must be smaller than the current basis. In addition, the geometry used for the previous calculations must have the atoms in the same order and in the same orientation as the current geometry.
- FRAGMENT file1 ... -- assembles starting MO vectors from previously performed calculations on fragments of the system and is described in more detail in Superposition of fragment molecular orbitals. Even though there are some significant restrictions in the use of the initial implementation of this method (see Superposition of fragment molecular orbitals), this is the most powerful initial guess option within the code. It is particularly indispensable for open shell metallic systems.
- ROTATE input_geometry input_movecs -- rotates MO vectors generated at a previous geometry to the current active geometry.

The molecular orbitals are saved every iteration if more than 600 seconds have elapsed, and also at the end of the calculation. At completion (converged or not), the SCF module always canonically transforms the molecular orbitals by separately diagonalizing the closed-closed, open-open, and virtual-virtual blocks of the Fock matrix.

The name of the file used to store the MO vectors is determined as follows:

- if the OUTPUT keyword was specified on the VECTORS directive, then the filename that follows this keyword is used, or
- if the input vectors were read from a file, this file is reused for the output vectors (overwriting the input vectors); else,
- a default file name is generated in the directory for permanent files (File directories) by prepending ".movecs" with the file prefix, i.e., "<file_prefix>.movecs".

The name of this file is stored in the database so that a subsequent SCF calculation will automatically restart from these MO vectors.

Applications of this directive are illustrated in the following examples.

Example 1:

vectors output h2o.movecs

Assuming a start-up calculation, this directive will result in use of the default atomic density guess, and will output the vectors to the file h2o.movecs.

Example 2:

vectors input initial.movecs output final.movecs

This directive will result in the initial vectors being read from the file "initial.movecs". The results will be written to the file final.movecs. The contents of "initial.movecs" will not be changed.

Example 3:

vectors input project "small basis" small.movecs

This directive will cause the calculation to start from vectors in the file "small.movecs" which are in a basis named "small basis". The output vectors will be written to the default file "<file_prefix.movecs>".

Once starting vectors have been obtained using any of the possible options, they may be reordered through use of the SWAP keyword. This optional keyword requires a list of orbital pairs that will be swapped. For UHF calculations, separate SWAP keywords may be provided for the alpha and beta orbitals, as necessary.

An example of use of the SWAP directive:

vectors input try1.movecs swap 173 175 174 176 output try2.movecs

This directive will cause the initial orbitals to be read from the file "try1.movecs". The vectors for the orbitals within the pairs 173-175 will be swapped with those within 174-176, so the resulting order is 175, 176, 173, 174. The final orbitals obtained in the calculation will be written to the file "try2.movecs".

The swapping of orbitals occurs as a sequential process in the order (left to right) input by the user. Thus, regarding each pair as an elementary transposition it is possible to construct arbitrary permutations of the orbitals. For instance, to apply the permutation (6789) we note that this permutation is equal to (67)(78)(89), and thus may be specified as

vectors swap 8 9 7 8 6 7

Another example, now illustrating this feature for a UHF calculation, is the directive

vectors swap beta 4 5 swap alpha 5 6

This input will result in the swapping of the 5-6 alpha orbital pair and the 4-5 beta orbital pair. (All other items in the input use the default values.)

The LOCK keyword allows the user to specify that the ordering of orbitals will be locked to that of the initial vectors, insofar as possible. The default is to order by ascending orbital energies within each orbital space. One application where locking might be desirable is a calculation where it is necessary to preserve the ordering of a previous geometry, despite flipping of the orbital energies. For such a case, the LOCK directive can be used to prevent the SCF calculation from changing the ordering, even if the orbital energies change.

The mapping of the MO's to the nuclei can be changed using the REORDER keyword. Once starting vectors have been obtained using any of the possible options, the REORDER keyword moves the MO coefficients between atoms listed in the integer list. This keyword is particularly useful for calculating localized electron and hole states.

This optional keyword requires a list containing the new atom ordering. It is not necessary to provide separate lists for alpha and beta orbitals.

An example of use of the REORDER keyword:

vectors input try1.movecs reorder 2 1 output try2.movecs

This directive will cause the initial orbitals to be read from the file "try1.movecs". The MO coefficients for the basis functions on atom 2 will be swapped with those on atom 1. The final orbitals obtained in the calculation will be written to the file "try2.movecs".

The following example shows how the ROTATE keyword can be used to rotate MO vectors calculated at geometry geom1 to geometry geom2, which has a different rotational orientation:

```
set geometry geom1
dft
vectors input atomic output geom1.mo
end
task dft
set geometry geom2
dft
vectors input rotate geom1 geom1.mo output geom2.mo
end
task dft
```

Superposition of fragment molecular orbitals

The fragment initial guess is particularly useful in the following instances:

- The system naturally decomposes into molecules that can be treated individually, e.g., a cluster.
- One or more fragments are particularly hard to converge and therefore much time can be saved by converging them independently.
- A fragment (e.g., a metal atom) must be prepared with a specific occupation. This can often be readily accomplished with a calculation on the fragment using dummy charges to model a ligand field.
- The molecular occupation predicted by the atomic initial guess is often wrong for systems with heavy metals which may have partially occupied orbitals with lower energy than some doubly occupied orbitals. The fragment initial guess avoids this problem.

```
VECTORS [input] fragment <string file1> [<string file2>
...]
```

The molecular orbitals are formed by superimposing the previously generated orbitals of fragments of the molecule being studied. These fragment molecular orbitals must be in the same basis as the current calculation. The input specifies the files containing the fragment molecular orbitals. For instance, in a calculation on the water dimer, one might specify

```
vectors fragment h2o1.movecs h2o2.movecs
```

where h2o1.movecs contains the orbitals for the first fragment, and h2o2.movecs contains the orbitals for the second fragment.

A complete example of the input for a calculation on the water dimer using the fragment guess is as follows:

```
start dimer
title "Water dimer SCF using fragment initial guess"
geometry dimer
0 -0.595 1.165 -0.048
```

```
Н
       0.110
               1.812
                      -0.170
  Н
      -1.452
               1.598
                      -0.154
  0
       0.724 -1.284
                       0.034
  Н
       0.175
              -2.013
                       0.348
       0.177 -0.480
  Н
                       0.010
end
geometry h2o1
  0
      -0.595
               1.165
                      -0.048
  Н
       0.110
               1.812
                      -0.170
  Н
      -1.452
               1.598
                      -0.154
end
geometry h2o2
  0
       0.724 -1.284
                       0.034
  н
       0.175 -2.013
                       0.348
  Н
       0.177 -0.480
                       0.010
end
basis
  o library 3-21g
  h library 3-21g
end
set geometry h2o1
scf; vectors input atomic output h2o1.movecs; end
task scf
set geometry h2o2
scf; vectors input atomic output h2o2.movecs; end
task scf
set geometry dimer
scf
vectors input fragment h2o1.movecs h2o2.movecs \
        output dimer.movecs
end
task scf
```

First, the geometry of the dimer and the two monomers are specified and given names. Then, after the basis specification, calculations are performed on the fragments by setting the geometry to the appropriate fragment (SET) and redirecting the output molecular orbitals to an appropriately named file. Note also that use of the atomic initial guess is forced, since the default initial guess is to use any existing MOs which would not be appropriate for the second fragment calculation. Finally, the dimer calculation is performed by specifying the dimer geometry, indicating use of the fragment guess, and redirecting the output MOs.

The following points are important in using the fragment initial guess:

- 1. The fragment calculations must be in the same basis set as the full calculation.
- 2. The order of atoms in the fragments and the order in which the fragment files are specified must be such that when the fragment basis sets are concatenated all the basis functions are in the same order as in the full system. This is readily accomplished by first generating the full geometry with atoms for each fragment contiguous, splitting this into

numbered fragments and specifying the fragment MO files in the correct order on the VECTORS directive.

- 3. The occupation of orbitals is preserved when they are merged from the fragments to the full molecule and the resulting occupation must match the requested occupation for the full molecule. E.g., a triplet ROHF calculation must be comprised of fragments that have a total of exactly two open-shell orbitals.
- 4. Because of these restrictions, it is not possible to introduce additional atoms (or basis functions) into fragments for the purpose of cleanly breaking real bonds. However, it is possible, and highly recommended, to introduce additional point charges to simulate the presence of other fragments.
- 5. MO vectors of partially occupied or strongly polarized systems are very sensitive to orientation. While it is possible to specify the same fragment MO vector file multiple times in the VECTORS directive, it is usually much better to do a separate calculation for each fragment.
- 6. Linear dependencies which were present in a fragment calculation may be magnified in the full calculation. When this occurs, some of the fragment's highest virtual orbitals will not be copied to the full system, and a warning will be printed.

A more involved example is now presented. We wish to model the sextet state of Fe(III) complexed with water, imidazole and a heme with a net unit positive charge. The default atomic guess does not give the correct d^5 occupation for the metal and also gives an incorrect state for the double anion of the heme. The following performs calculations on all of the fragments. Things to note are:

- 1. The use of a dummy +2 charge in the initial guess on the heme which in part simulates the presence of the metal ion, and also automatically forces an additional two electrons to be added to the system (the default net charge being zero).
- 2. The iron fragment calculation (charge +3, d^5 , sextet) will yield the correct open-shell occupation for the full system. If, instead, the d-orbitals were partially occupied (e.g., the doublet state) it would be useful to introduce dummy charges around the iron to model the ligand field and thereby lift the degeneracy to obtain the correct occupation.
- 3. C_s symmetry is used for all of the calculations. It is not necessary that the same symmetry be used in all of the calculations, provided that the order and orientation of the atoms is preserved.
- 4. The unset scf:* directive is used immediately before the calculation on the full system so that the default name for the output MO vector file can be used, rather than having to specify it explicitly.

```
start heme6al
title "heme-H20 (6A1) from M.Dupuis"
# Define the geometry of the full system and the fragments #
geometry full-system
 symmetry cs
 Н
     0.438
          -0.002
                 4.549
 С
     0.443
          -0.001
                 3.457
 С
     0.451
          -1.251
                 2.828
 С
     0.452
           1.250
                 2.828
```

Н	0.455	2.652	4.586
Н	0.461	-2.649	4.586
N1	0.455	-1.461	1.441
N1	0.458	1.458	1.443
С	0.460	2.530	3.505
С	0.462	-2.530	3.506
С	0.478	2.844	1.249
С	0.478	3.510	2.534
С	0.478	-2.848	1.248
С	0.480	-3.513	2.536
С	0.484	3.480	0.000
С	0.485	-3.484	0.000
Н	0.489	4.590	2.664
Н	0.496	-4.592	2.669
Н	0.498	4.573	0.000
Н	0.503	-4.577	0.000
Н	-4.925	1.235	0.000
Н	-4.729	-1.338	0.000
С	-3.987	0.685	0.000
Ν	-3.930	-0.703	0.000
С	-2.678	1.111	0.000
С	-2.622	-1.076	0.000
Н	-2.284	2.126	0.000
Н	-2.277	-2.108	0.000
Ν	-1.838	0.007	0.000
Fe	0.307	0.000	0.000
0	2.673	-0.009	0.000
Н	3.238	-0.804	0.000
Н	3.254	0.777	0.000
end			
geomet	ry ring-o	only	
symm	etry cs		
Н	0.438	-0.002	4.549
С	0.443	-0.001	3.457
С	0.451	-1.251	2.828
С	0.452	1.250	2.828
Н	0.455	2.652	4.586
Н	0.461	-2.649	4.586
N1	0.455	-1.461	1.441
N1	0.458	1.458	1.443
С	0.460	2.530	3.505
С	0.462	-2.530	3.506
С	0.478	2.844	1.249
С	0.478	3.510	2.534
С	0.478	-2.848	1.248
С	0.480	-3.513	2.536
С	0.484	3.480	0.000

```
С
      0.485
             -3.484
                     0.000
 Н
      0.489
           4.590
                     2.664
 Н
      0.496
             -4.592
                     2.669
 Bq
      0.307
              0.0
                     0.0
                           charge 2 # simulate the iron
end
geometry imid-only
 symmetry cs
 Н
      0.498
            4.573
                     0.000
 Н
      0.503
           -4.577
                     0.000
 Н
     -4.925
                     0.000
             1.235
     -4.729 -1.338
 Н
                     0.000
 С
     -3.987
            0.685
                     0.000
 Ν
     -3.930
           -0.703
                     0.000
 С
     -2.678
             1.111
                     0.000
 С
     -2.622 -1.076
                     0.000
 Н
     -2.284
             2.126
                     0.000
 Н
     -2.277 -2.108
                     0.000
 Ν
     -1.838
              0.007
                     0.000
end
geometry fe-only
 symmetry cs
 Fe
      .307
             0.000
                    0.000
end
geometry water-only
 symmetry cs
 0
      2.673
             -0.009
                     0.000
 Н
      3.238 -0.804
                     0.000
 Н
      3.254
              0.777
                     0.000
end
# Basis set for everything #
basis nosegment
0 library 6-31g*
N library 6-31g*
C library 6-31g*
H library 6-31g*
Fe library "Ahlrichs pVDZ"
end
# SCF on the fragments for initial guess for full system #
scf; thresh 1e-2; end
set geometry ring-only
scf; vectors atomic swap 80 81 output ring.mo; end
task scf
set geometry water-only
```

```
scf; vectors atomic output water.mo; end
task scf
set geometry imid-only
scf; vectors atomic output imid.mo; end
task scf
charge 3
set geometry fe-only
scf; sextet; vectors atomic output fe.mo; end
task scf
# SCF on the full system #
unset scf:*
             # This restores the defaults
charge 1
set geometry full-system
scf
sextet
vectors fragment ring.mo imid.mo fe.mo water.mo
maxiter 50
end
task scf
```

Example of projecting smaller basis into larger basis

Key ingredient needed: definition of both the smaller and the larger basis set, plus mention of the small basis set in the "input project" line.

```
start he
geometry
he 0 0 0
 symmetry oh
end
basis small
* library sto-3g
end
basis large
* library 3-21g
end
set "ao basis" small
scf
 vectors input atomic output small.mos
end
task scf
set "ao basis" large
scf
```

```
vectors input project small small.mos output large.mos
end
task scf
```

Atomic guess orbitals with charged atoms

As noted above, the default guess vectors are based on superimposing the density matrices of the neutral atoms. If some atoms are significantly charged, this default guess may be improved upon by modifying the atomic densities. This is done by setting parameters that add fractional charges to the occupation of the valence atomic orbitals. Since the atomic SCF program does not have its own input block, the SET directive (SET) must be used to set these parameters.

The input specifies a list of tags (i.e., names of atoms in a geometry, see GEOMETRY) and the charges to be added to those centers. Two parameters must be set as follows:

```
set atomscf:tags_z <string list_of_tags>
set atomscf:z <real list of charges>
```

The array of strings atomscf:tags_z should be set to the list of tags, and the array atomscf:z should be set to the list of charges which must be real numbers (not integers). All atoms that have a tag specified in the list of tags will be assigned the corresponding charge from the list of charges.

For example, the following specifies that all oxygen atoms with tag O be assigned a charge of -1 and all iron atoms with tag Fe be assigned a charge of +2

set atomscf:z -1 2.0
set atomscf:tags_z 0 Fe

There are some limitations to this feature. It is not possible to add electrons to closed shell atoms, nor is it possible to remove all electrons from a given atom. Attempts to do so will cause the code to report an error, and it will not report further errors in the input for modifying the charge even when they are detected.

Finally, recall that the database is persistent (Data persistence) and that the modified settings will be used in subsequent atomic guess calculations unless the data is deleted from the database with the UNSET directive (UNSET).

Accuracy of initial guess

For SCF, the initial Fock-matrix construction from the atomic guess is performed to a default precision of 1e-7. However, other wavefunctions, notably DFT, use a lower precision. In charged, or diffuse basis sets, this precision may not be sufficient and could result in incorrect ordering of the initial orbitals. The accuracy may be increased with the following directive which should be inserted in the top-level of input (i.e., outside of the SCF input block) and before the TASK directive.

```
set tolguess 1e-7
```

THRESH --convergence threshold

THRESH <real thresh default 1.0e-4>

This directive specifies the convergence threshold for the calculation. The convergence threshold is the norm of the orbital gradient, and has a default value in the code of 10^{-4} .

The norm of the orbital gradient corresponds roughly to the precision available in the wavefunction, and the energy should be converged to approximately the square of this number. It should be noted, however, that the precision in the energy will not exceed that of the integral screening tolerance. This tolerance (Integral screening threshold) is automatically set from the convergence threshold, so that sufficient precision is usually available by default.

The default convergence threshold suffices for most SCF energy and geometry optimization calculations, providing about 6-8 decimal places in the energy, and about four significant figures in the density and energy derivative with respect to nuclear coordinates. However, greater precision may be required for calculations involving weakly interacting systems, floppy molecules, finite-difference of gradients to compute the Hessian, and for post-Hartree-Fock calculations. A threshold of 10^{-6} is adequate for most such purposes, and a threshold of 10^{-8} might be necessary for very high accuracy or very weak interactions. A threshold of 10^{-10} should be regarded as the best that can be attained in most circumstances.

MAXITER --iteration limit

MAXITER <integer maxiter default 8>

The maximum number of iterations for the SCF calculation defaults to 20 for both ROHF/RHF and UHF calculations. For most molecules, this number of iterations is more than sufficient for the quadratically convergent SCF algorithm to obtain a solution converged to the default threshold (see Convergence threshold above). If the SCF program detects that the quadratically convergent algorithm is not efficient, then it will resort to a linearly convergent algorithm and increase the maximum number of iterations by 10.

Convergence may not be reached in the maximum number of iterations for many reasons, including input error (e.g., an incorrect geometry or a linearly dependent basis), a very low convergence threshold, a poor initial guess, or the fact that the system is intrinsically hard to converge due to the presence of many states with similar energies.

The following sets the maximum number of SCF iterations to 50:

maxiter 50

PROFILE --performance profile

This directive allows the user to obtain timing and parallel execution information about the SCF module. It is specified by the simple keyword

PROFILE

This option can be helpful in understanding the computational performance of an SCF calculation. However, it can introduce a significant overhead on machines that have expensive timing routines, such as the SUN.

DIIS --DIIS convergence

This directive allows the user to specify DIIS convergence rather than second-order convergence for the SCF calculation. The form of the directive is as follows:

DIIS

The implementation of this option is currently fairly rudimentary. It does not have level-shifting and damping, and does not support open shells or UHF. It is provided on an "as is" basis, and should be used with caution.

When the DIIS directive is specified in the input, the user has the additional option of specifying the size of the subspace for the DIIS extrapolation. This is accomplished with the DIISBAS directive, which is of the form:

DIISBAS <integer diisbas default 5>

The default of 5 should be adequate for most applications, but may be increased if convergence is poor. On large systems, it may be necessary to specify a lower value for diisbas, to conserve memory.

DIRECT and SEMIDIRECT --recomputation of integrals

In the context of SCF calculations direct means that all integrals are recomputed as required and none are stored. The other extreme are disk- or memory-resident (sometimes termed conventional) calculations in which all integrals are computed once and stored. Semi-direct calculations are between these two extremes with some integrals being precomputed and stored, and all other integrals being recomputed as necessary.

The default behavior of the SCF module is

- If enough memory is available, the integrals are computed once and are cached in memory.
- If there is not enough memory to store all the integrals at once, then 95% of the available disk space in the scratch directory (see File directories) is assumed to be available for this purpose, and as many integrals as possible are cached on disk (with no memory being used for caching). Some attempt is made to store the most expensive integrals in the cache.
- If there is not enough room in memory or on disk for all the integrals, then the ones that are not cached are recomputed in a semidirect fashion.

The integral file is deleted at the end of a calculation, so it is not possible to restart a semidirect calculation when the integrals are cached in memory or on disk. Many modern computer systems clear the fast scratch space at the end of each job, adding a further

complication to the problem of restarting a parallel semidirect calculation.

A fully direct calculation (with recomputation of the integrals at each iteration) is forced by specifying the directive

DIRECT

Alternatively, the SEMIDIRECT directive can be used to control the default semidirect calculation by defining the amount of disk space and the cache memory size. The form of this directive is as follows:

```
SEMIDIRECT [filesize <integer filesize default disksize>]
    [memsize <integer memsize default available>]
    [filename <string filename default
$file_prefix.aoints$>]
```

The keyword FILESIZE allows the user to specify the amount of disk space to be used per process for storing the integrals in 64-bit words. Similarly, the keyword MEMSIZE allows the user to specify the number of 64-bit words to be used per process for caching integrals in memory. (Note: If the amount of storage space specified by the entry for memsize is not available, the code cuts the value in half and checks again for available space. This process is repeated until the request is satisfied.)

By default, the integral files are placed into the scratch directory (see File directories). Specifying the keyword FILENAME overrides this default. The user-specified name entered in the string filename has the process number appended to it, so that each process has a distinct file but with a common base-name and directory. Therefore, it is not possible to use this keyword to specify different disks for different processes. The SCRATCH_DIR directive (see File directories) can be used for this purpose.

For example, to force full recomputation of all integrals:

direct

Exactly the same result could be obtained by entering the directive:

```
semidirect filesize 0 memsize 0
```

To disable the use of memory for caching integrals and limit disk usage by each process to 100 megawords (MW):

semidirect memsize 0 filesize 10000000

The integral records are typically 32769 words long and any non-zero value for filesize or memsize should be enough to hold at least one record.

Integral File Size and Format for the SCF Module

The file format is rather complex, since it accommodates a variety of packing and compression options and the distribution of data. This section presents some information that may help the user understand the output, and illustrates how to use the output information to estimate file sizes.

If integrals are stored with a threshold of greater than 10^{-10} , then the integrals are stored in a 32-bit fixed-point format (with appropriate treatment for large values to retain precision). If integrals are stored with a threshold less than 10^{-10} , however, the values are stored in 64-bit floating-point format. If a replicated-data calculation is being run, then 8 bits are used for each basis function label, unless there are more than 256 functions, in which case 16 bits are used. If distributed data is being used, then the labels are always packed to 8 bits (the distributed blocks always being less than 256; labels are relative to the start of the block).

Thus, the number (W) of 64-bit words required to store N integrals, may be computed as

(N, 8-bit labels and 32-bit values

$$\int \frac{3}{2}N$$
, 16-bit labels and 32-bit values

- $W = \begin{cases} \frac{2}{3}N, & \text{8-bit labels and 64-bit values} \end{cases}$
 - 2N, 16-bit labels and 64-bit values

The actual number of words required can exceed this computed value by up to one percent, due to bookkeeping overhead, and because the file itself is organized into fixed-size records.

With at least the default print level, all semidirect (not direct) calculations will print out information about the integral file and the number of integrals computed. The form of this output is as follows:

```
Integral file
                       = ./c6h6.aoints.0
Record size in doubles = 32769
                                       No. of integs per rec
                                                                 32768
                                                              =
Max. records in memory =
                              3
                                       Max. records in file
                                                              =
                                                                     5
No. of bits per label =
                              8
                                       No. of bits per value =
                                                                    32
#quartets = 2.0D+04 #integrals = 7.9D+05 direct = 63.6% cached =
36.4%
```

The file information above relates only to process 0. The line of information about the number of quartets, integrals, etc., is a sum over all processes.

When the integral file is closed, additional information of the following form is printed:

EAF file 0:	"./c6h6.a	oints.0" s	ize=262152	bytes	
	write	read	awrite	aread	wait
calls:	6	12	0	0	0
<pre>data(b):</pre>	1.57e+06	3.15e+06	0.00e+00	0.00e+00	
<pre>time(s):</pre>	1.09e-01	3.12e-02			0.00e+00
<pre>rate(mb/s):</pre>	1.44e+01	1.01e+02			
Parallel i	ntegral fi	le used	4 reco	rds with	0 large values

Again, the detailed file information relates just to process 0, but the final line indicates the total number of integral records stored by all processes.

This information may be used to optimize subsequent calculations, for instance by assigning more memory or disk space.

SCF Convergence Control Options

Note to users: It is desired that the SCF program converge reliably with the default options for a wide variety of molecules. In addition, it should be guaranteed to converge for any system, with sufficient iterations.

The SCF program uses a preconditioned conjugate gradient (PCG) method that is unconditionally convergent. Basically, a search direction is generated by multiplying the orbital gradient (the derivative of the energy with respect to the orbital rotations) by an approximation to the inverse of the level-shifted orbital Hessian. In the initial iterations (see Controlling the Newton-Raphson), an inexpensive one-electron approximation to the inverse orbital Hessian is used. Closer to convergence, the full orbital Hessian is used, which should provide quadratic convergence. For both the full or one-electron orbital Hessians, the inverse-Hessian matrix-vector product is formed iteratively. Subsequently, an approximate line search is performed along the new search direction. If the exact Hessian is being employed, then the line search should require a single step (of unity). Preconditioning with approximate Hessians may require additional steps, especially in the initial iterations. It is the (approximate) line search that provides the convergence guarantee. The iterations required to solve the linear equations are referred to as micro-iterations. A macro-iteration comprises both the iterative solution and a line search.

Level-shifting plays the same role in this algorithm as it does in the conventional iterative solution of the SCF equations. The approximate Hessian used for preconditioning should be positive definite. If this is not the case, then level-shifting by a positive constant (Δ) serves to make the preconditioning matrix positive definite, by adding Δ to all of its eigenvalues. The level-shifts employed for the RHF orbital Hessian should be approximately four times (only twice for UHF) the value that one would employ in a conventional SCF. Level-shifting is automatically enabled in the early iterations, and the default options suffice for most test cases.

So why do things go wrong and what can be done to fix convergence problems? Most problems encountered so far arise either poor initial guesses or from small or negative eigenvalues of the orbital Hessian. The atomic orbital guess is usually very good. However, in calculations on charged systems, especially with open shells, incorrect initial occupations may result. The SCF might then converge very slowly since very large orbital rotations might be required to achieve the correct occupation or move charge large distances in the molecule. Possible actions are

- Modify the atomic guess by assigning charges to the atoms known to carry substantial charges (Atomic guess)
- Examining an analysis of the initial orbitals (Printing) and then swapping them to attain the desired occupation (VECTORS).
- Converging the calculation in a minimal basis set, which is usually easier, and then projecting into a larger basis set (VECTORS).
- Using the fragment orbital initial guess (Fragment molecular orbitals).

Small or negative Hessian eigenvalues can occur even though the calculation seem to be close to convergence (as measured by the gradient norm, or the off-diagonal Fock matrix elements). Small eigenvalues will cause the iterative linear equation solver to converge slowly, resulting in an excessive number of micro-iterations. This makes the SCF expensive in terms of computation time, and it is possible to exceed the maximum number of iterations without achieving the accuracy required for quadratic convergence -- which causes more macro-iterations to be performed.

Two main options are available when a problem will not converge: Newton-Raphson can be disabled temporarily or permanently (see Controlling the Newton-Raphson), and level-shifting can be applied to the matrix (see Level-shifting). In some cases, both options may be necessary to achieve final convergence.

If there is reason to suspect a negative eigenvalue, the first course is to disable the Newton-Raphson iteration until the solution is closer to convergence. It may be necessary to disable it completely. At some point close to convergence, the Hessian will be positive definite, so disabling Newton-Raphson should yield a solution with approximately the same convergence rate as DIIS.

If temporarily disabling Newton-Raphson is not sufficient to achieve convergence, it may be necessary to disable it entirely and apply a small level-shift to the approximate Hessian. This should improve the convergence rate of the micro-iterations and stabilize the macro-iterations. The level-shifting will destroy exact quadratic convergence, but the optimization process is automatically adjusted to reflect this by enforcing conjugacy and reducing the accuracy to which the linear equations are solved. The net result of this is that the solution will do more macro-iterations, but each one should take less time than it would with the unshifted Hessian.

The following sections describe the directives needed to disable the Newton-Raphson iteration and specify level-shifting.

NR --controlling the Newton-Raphson

NR <real nr_switch default 0.1>

The exact orbital Hessian is adopted as the preconditioner when the maximum element of the orbital gradient is below the value specified for nr_switch. The default value is 0.1, which means that Newton-Raphson will be disabled until the maximum value of the orbital gradient (twice the largest off-diagonal Fock matrix element) is less than 0.1. To disable the Newton-Raphson entirely, the value of nr_switch must be set to zero. The directive to accomplish this is as follows:

nr 0

LEVEL --level-shifting the orbital Hessian

This directive allows the user to specify level-shifting to obtain a positive-definite preconditioning matrix for the SCF solution procedure. Separate level shifts can be set for the first-order convergent one-electron approximation to the Hessian used with the preconditioned conjugate gradient (PCG) method, and for the full Hessian used with the Newton-Raphson (NR) approach. It is also possible to change the level-shift automatically as the solution attains some specified accuracy. The form of the directive is as follows:

```
LEVEL [pcg <real initial default 20.0> \
        [<real tol default 0.5> <real final default
0.0>]] \
        [nr <real initial default 0.0> \
        [<real tol default 0.0> <real final default
0.0>]]
```

This directive contains only two keywords: one for the PCG method and the other for the exact Hessian (Newton Raphson, or NR). Use of PCG or NR is determined by the input specified for nr_switch on the NR directive, Controlling the Newton-Raphson above.

Specifying the keyword pcg on the LEVEL directive allows the user to define the level shifting for the approximate (i.e., PCG) method. Specifying the keyword nr allows the user to define the level shifting for the exact Hessians. In both options, the initial level shift is defined by the value specified for the variable initial. Optionally, tol can be specified independently with each keyword to define the level of accuracy that must be attained in the solution before the level shifting is changed to the value specified by input in the real variable final. Level shifts and gradient thresholds are specified in atomic units.

For the PCG method (as specified using the keyword pcg), the defaults for this input are 20.0 for initial, 0.5 for tol, and 0.0 for final. This means that the approximate Hessian will be shifted by 20.0 until the maximum element of the gradient falls below 0.5, at which point the shift will be set to zero.

For the exact Hessian (as specified using the keyword nr), the defaults are all zero. The exact Hessian is usually not shifted since this destroys quadratic convergence. An example of an input directive that applies a shift of 0.2 to the exact Hessian is as follows:

level nr 0.2

To apply this shift to the exact Hessian only until the maximum element of the gradient falls below 0.005, the required input directive is as follows:

level nr 0.2 0.005 0

Note that in both of these examples, the parameters for the PCG method are at the default values. To obtain values different from the defaults, the keyword pcg must also be specified. For example, to specify the level shifting in the above example for the exact Hessian and non-default shifting for the PCG method, the directive would be something like the following:

level pcg 20 0.3 0.0 nr 0.2 0.005 0.0

This input will cause the PCG method to be level-shifted by 20.0 until the maximum element of the gradient falls below 0.3, then the shift will be zero. For the exact Hessian, the level shifting is initially 0.2, until the maximum element falls below 0.005, after which the shift is zero.

The default options correspond to

level pcg 20 0.5 0 nr 0 0 0

Orbital Localization

The SCF module includes an experimental implementation of orbital localization, including Foster-Boys and Pipek-Mezey which only works for closed-shell (RHF) wavefunctions. There is currently no input in the SCF block to control this so the SET directive (SET) must be used.

The directive

set scf:localize t

will separately localize the core, valence, and virtual orbital spaces using the Pipek-Mezey algorithm. If the additional directive

set scf:loctype FB

is included, then the Foster-boys algorithm is used. The partitioning of core-orbitals is performed using the atomic information described in Section 16.1.

In the next release, this functionality will be extended to included all wavefunctions using molecular orbitals.

Printing Information from the SCF Module

All output from the SCF module is controlled using the PRINT directive described in Print control. The following list describes the items from SCF that are currently under direct print control, along with the print level for each one.

[htbp]

Name	Print Level	Description
"atomic guess density"	debug	guess density matrix
"atomic scf"	debug	details of atomic SCF
"mo guess"	default	brief info from mo guess
"information"	low	results
"initial vectors"	debug	
"intermediate vectors"	debug	
"final vectors"	debug	
"final vectors analysis"	default	
"initial vectors analysis"	never	
"intermediate evals"	debug	
"final evals"	default	
"schwarz"	high	integral screening info stats at completion
"screening statistics"	debug	display stats after every Fock build
"geometry"	high	
"symmetry"	debug	detailed symmetry info
"basis"	high	
"geombas"	debug	detailed basis map info

Table 1: SCF Print Control Specifications

"vectors i/o"	default	report vectors I/O
"parameters"	default	convergence parameters
"convergence"	default	info each iteration
"mulliken ao"	never	Mulliken population of basis functions

Hartree-Fock or SCF, MCSCF and MP2 Gradients

The input for this directive allows the user to adjust the print control for the SCF, UHF, ROHF, MCSCF and MP2 gradients. The form of the directive is as follows:

GRADIENTS
 [print || noprint] ...
END

The complementary keyword pair print and noprint allows the user some additional control on the information that can be included in the print output from the SCF calculation. Currently, only a few items can be explicitly invoked via print control. These are as follows:

Table 2: Gradient Print Control Specifications

Name	Print Level	Description
"information"	low	calculation info
"geometry"	high	geometry information
"basis"	high	basis set(s) used
"forces"	low	details of force components
"timing"	default	timing for each phase

References

- Wong, A. T. and Harrison, R. J. (1995) "Approaches to large-scale parallel self-consistent field calculation", J. Comp. Chem. 16, 1291-1300, doi: 10.1002/jcc.540161010 (http://dx.doi.org/10.1002/jcc.540161010)
- [2] Foster, I. T.; Tilson, J. L.; Wagner, A. F.; Shepard, R. L.; Harrison, R. J.; Kendall, R. A. and Littlefield, R. J. (1996) "Toward high-performance computational chemistry: I. Scalable Fock matrix construction algorithms", *J. Comp. Chem.* 17, 109-123, doi: 10.1002/(SICI)1096-987X(19960115)17:1<109::AID-JCC9>3.0.CO;2-V (http:// dx.doi.org/10.1002/(SICI)1096-987X(19960115)17:1<109::AID-JCC9>3.0.CO;2-V)

Release65:Density Functional Theory for Molecules

__NOTITLE___

Density Functional Theory

The NWChem density functional theory (DFT) module uses the Gaussian basis set approach to compute closed shell and open shell densities and Kohn-Sham orbitals in the:

- local density approximation (LDA),
- non-local density approximation (NLDA),
- local spin-density approximation (LSD),
- non-local spin-density approximation (NLSD),
- non-local meta-GGA approximation (metaGGA),
- any empirical mixture of local and non-local approximations (including exact exchange), and
- asymptotically corrected exchange-correlation potentials.

The formal scaling of the DFT computation can be reduced by choosing to use auxiliary Gaussian basis sets to fit the charge density (CD) and/or fit the exchange-correlation (XC) potential.

DFT input is provided using the compound DFT directive

DFT ... END

The actual DFT calculation will be performed when the input module encounters the TASK directive.

TASK DFT

Once a user has specified a geometry and a Kohn-Sham orbital basis set the DFT module can be invoked with no input directives (defaults invoked throughout). There are sub-directives which allow for customized application; those currently provided as options for the DFT module are:

```
[mpw91] [mpw1k] [xft97] [cft97] [ft97] [op] [bop] [pbeop]
  [xpkzb99] [cpkzb99] [xtpss03] [ctpss03] [xctpssh]
  [b1b95] [bb1k] [mpw1b95] [mpwb1k] [pw6b95] [pwb6k] [m05] [m05-2x]
[vs98]\
  [m06] [m06-hf] [m06-L] [m06-2x] \
  [HFexch <real prefactor default 1.0>] \
  [becke88 [nonlocal] <real prefactor default 1.0>] \
  [xperdew91 [nonlocal] <real prefactor default 1.0>] \
  [xpbe96 [nonlocal] <real prefactor default 1.0>] \
  [gill96 [nonlocal] <real prefactor default 1.0>] \
  [lyp <real prefactor default 1.0>] \
  [perdew81 < real prefactor default 1.0>] \
  [perdew86 [nonlocal] <real prefactor default 1.0>] \
  [perdew91 [nonlocal] <real prefactor default 1.0>] \
  [cpbe96 [nonlocal] <real prefactor default 1.0>] \
  [pw91lda <real prefactor default 1.0>] \
  [slater <real prefactor default 1.0>] \
  [vwn 1 <real prefactor default 1.0>] \
  [vwn 2 <real prefactor default 1.0>] \
  [vwn 3 < real prefactor default 1.0>] \
  [vwn 4 < real prefactor default 1.0 >] \
  [vwn 5 < real prefactor default 1.0>] \
  [vwn 1 rpa <real prefactor default 1.0>] \
  [xtpss03 [nonlocal] < real prefactor default 1.0>] \
  [ctpss03 [nonlocal] <real prefactor default 1.0>] \
  [bc95 [nonlocal] <real prefactor default 1.0>] \
  [xpw6b95 [nonlocal] < real prefactor default 1.0>] \
  [xpwb6k [nonlocal] <real prefactor default 1.0>] \
  [xm05 [nonlocal] <real prefactor default 1.0>] \
  [xm05-2x [nonlocal] <real prefactor default 1.0>] \
  [cpw6b95 [nonlocal] <real prefactor default 1.0>] \
  [cpwb6k [nonlocal] <real prefactor default 1.0>] \
  [cm05 [nonlocal] <real prefactor default 1.0>] \
  [cm05-2x [nonlocal] <real prefactor default 1.0> \
      [xvs98 [nonlocal] <real prefactor default 1.0> \
     [cvs98 [nonlocal] <real prefactor default 1.0>]] \
     [xm06-L [nonlocal] <real prefactor default 1.0>]] \
     [xm06-hf [nonlocal] <real prefactor default 1.0>]] \
     [xm06 [nonlocal] <real prefactor default 1.0>]] \
     [xm06-2x [nonlocal] <real prefactor default 1.0>]] \
     [cm06-L [nonlocal] <real prefactor default 1.0>]] \
     [cm06-hf [nonlocal] <real prefactor default 1.0>]] \
     [cm06 [nonlocal] <real prefactor default 1.0>]] \
     [cm06-2x [nonlocal] <real prefactor default 1.0>]]
CONVERGENCE energy <real energy default 1e-7>] \
        [density <real density default 1e-5>] \
        [gradient <real gradient default 5e-4>] \
```

```
[dampon <real dampon default 0.0>] \
        [dampoff <real dampoff default 0.0>] \
        [diison <real diison default 0.0>]
        [diisoff <real diisoff default 0.0>] \
        [levlon <real levlon default 0.0>] \
        [levloff <real levloff default 0.0>] \
        [ncydp <integer ncydp default 2>] \
        [ncyds <integer ncyds default 30>] \
        [ncysh <integer ncysh default 30>] \
        [damp <integer ndamp default 0>] [nodamping] \
        [diis [nfock <integer nfock default 10> \
               [nodiis] [lshift <real lshift default 0.5>] \
               [nolevelshifting] \
               [hl tol <real hl tol default 0.1>] \
               [rabuck [n rabuck <integer n rabuck default 25>]]
GRID [(xcoarse||coarse||medium||fine||xfine) default medium] \
      [(gausleg||lebedev ) default lebedev ] \
      [(becke||erf1||erf2||ssf) default erf1] \
      [(euler||mura||treutler) default mura] \
      [rm <real rm default 2.0>] \
      [nodisk]
TOLERANCES tight] [tol rho <real tol rho default 1e-10>]
١
       [accCoul <integer accCoul default 8>] \
       [radius <real radius default 25.0>
 [(LB94||CS00 <real shift default none>)]
DECOMP
ODFT
DIRECT
SEMIDIRECT [filesize <integer filesize default disksize>]
            [memsize <integer memsize default available>]
            [filename <string filename default
$file prefix.aoints$>]
INCORE
ITERATIONS <integer iterations default 30>
MAX OVL
CGMIN
RODFT
MULLIKEN
DISP
XDM [ a1 <real a1> ] [ a2 <real a2> ]
MULT <integer mult default 1>
NOIO
PRINT | | NOPRINT
```

The following sections describe these keywords and optional sub-directives that can be specified for a DFT calculation in NWChem.

Specification of Basis Sets for the DFT Module

The DFT module requires at a minimum the basis set for the Kohn-Sham molecular orbitals. This basis set must be in the default basis set named "ao basis", or it must be assigned to this default name using the SET directive.

In addition to the basis set for the Kohn-Sham orbitals, the charge density fitting basis set can also be specified in the input directives for the DFT module. This basis set is used for the evaluation of the Coulomb potential in the Dunlap scheme. The charge density fitting basis set must have the name "cd basis". This can be the actual name of a basis set, or a basis set can be assigned this name using the SET directive. If this basis set is not defined by input, the $O(N^4)$ exact Coulomb contribution is computed.

The user also has the option of specifying a third basis set for the evaluation of the exchange-correlation potential. This basis set must have the name "xc basis". If this basis set is not specified by input, the exchange contribution (XC) is evaluated by numerical quadrature. In most applications, this approach is efficient enough, so the "xc basis" basis set is not generally required.

For the DFT module, the input options for defining the basis sets in a given calculation can be summarized as follows;

- "ao basis" Kohn-Sham molecular orbitals; required for all calculations
- "cd basis" charge density fitting basis set; optional, but recommended for evaluation of the Coulomb potential
- "xc basis" exchange-correlation (XC) fitting basis set; optional, and usually not recommended

VECTORS and MAX_OVL --KS-MO Vectors

The VECTORS directive is the same as that in the SCF module (Section 10.5). Currently, the LOCK keyword is not supported by the DFT module, however the directive

MAX_OVL

has the same effect.

XC and DECOMP --Exchange-Correlation Potentials

```
XC acm] [b3lyp] [beckehandh] [pbe0] [bhlyp]\
[becke97] [becke97-1] [becke97-2] [becke97-3] [becke98] [hcth]
[hcth120] [hcth147] \
[hcth407] [becke97gga1] [hcth407p] \
[optx] [hcthp14] [mpw91] [mpw1k] [xft97] [cft97] [ft97] [op]
[bop] [pbeop]\
[HFexch <real prefactor default 1.0>] \
[becke88 [nonlocal] <real prefactor default 1.0>] \
[xpbe96 [nonlocal] <real prefactor default 1.0>] \
[gill96 [nonlocal] <real prefactor default 1.0>] \
[lyp <real prefactor default 1.0>] \
[perdew81 <real prefactor default 1.0>] \
[perdew86 [nonlocal] <real prefactor default 1.0>] \
```

[perdew91 [nonlocal] <real 1.0="" default="" prefactor="">]</real>
[cpbe96 [nonlocal] <real 1.0="" default="" prefactor="">] \</real>
[pw91lda <real 1.0="" default="" prefactor="">] \</real>
[slater <real 1.0="" default="" prefactor="">] \</real>
$[vwn_1 < real prefactor default 1.0>] \$
$[vwn_2 < real prefactor default 1.0>] \$
$[vwn_3 < real prefactor default 1.0>] \$
$[vwn_4 < real prefactor default 1.0>] \$
$[vwn_5 < real prefactor default 1.0>] \$
[vwn_1_rpa <real 1.0="" default="" prefactor=""></real>

The user has the option of specifying the exchange-correlation treatment in the DFT Module (see table below for full list of functionals). The default exchange-correlation functional is defined as the local density approximation (LDA) for closed shell systems and its counterpart the local spin-density (LSD) approximation for open shell systems. Within this approximation the exchange functional is the Slater $\rho^{1/3}$ functional (from J.C. Slater, Quantum Theory of Molecules and Solids, Vol. 4: The Self-Consistent Field for Molecules and Solids (McGraw-Hill, New York, 1974)), and the correlation functional is the Vosko-Wilk-Nusair (VWN) functional (functional V) (S.J. Vosko, L. Wilk and M. Nusair, Can. J. Phys. 58, 1200 (1980)). The parameters used in this formula are obtained by fitting to the Ceperley and Alder Quantum Monte-Carlo solution of the homogeneous electron gas.

These defaults can be invoked explicitly by specifying the following keywords within the DFT module input directive, XC slater vwn_5.

That is, this statement in the input file

```
dft
XC slater vwn_5
end
task dft
```

is equivalent to the simple line

task dft

The DECOMP directive causes the components of the energy corresponding to each functional to be printed, rather than just the total exchange-correlation energy which is the default. You can see an example of this directive in the sample input.

Many alternative exchange and correlation functionals are available to the user as listed in the table below. The following sections describe how to use these options.

Exchange-Correlation Functionals

There are several Exchange and Correlation functionals in addition to the default slater and vwn_5 functionals. These are either local or gradient-corrected functionals (GCA); a full list can be found in the table below.

The Hartree-Fock exact exchange functional, (which has ${\cal O}(N^4)$ computation expense), is invoked by specifying

XC HFexch

Note that the user also has the ability to include only the local or nonlocal contributions of a given functional. In addition the user can specify a multiplicative prefactor (the variable <prefactor> in the input) for the local/nonlocal component or total. An example of this might be,

XC becke88 nonlocal 0.72

The user should be aware that the Becke88 local component is simply the Slater exchange and should be input as such.

Any combination of the supported exchange functional options can be used. For example the popular Gaussian B3 exchange could be specified as:

XC slater 0.8 becke88 nonlocal 0.72 HFexch 0.2

Any combination of the supported correlation functional options can be used. For example B3LYP could be specified as:

XC vwn_1_rpa 0.19 lyp 0.81 HFexch 0.20 slater 0.80 becke88 nonlocal
0.72

and X3LYP as:

xc vwn_1_rpa 0.129 lyp 0.871 hfexch 0.218 slater 0.782 \
becke88 nonlocal 0.542 xperdew91 nonlocal 0.167

Setting up common exchange-correlation functionals

- B3LYP: xc b3lyp
- PBE0: xc pbe0
- PBE96: xc xpbe96 cpbe96
- PW91: xc xperdew91 perdew91
- BHLYP: xc bhlyp
- Becke Half and Half: xc beckehandh
- BP86: xc becke88 perdew86
- BP91: xc becke88 perdew91
- BLYP: xc becke88 lyp

Minnesota Functionals

- xc m05
- xc m05-2x
- xc m06
- xc m06-l
- xc m06-2x
- xc m06-hf
- xc m08-hx
- xc m08-so
- xc m11
- xc m11-l

Analytic second derivatives are not supported with the Minnesota functionals yet.
Combined Exchange and Correlation Functionals

In addition to the options listed above for the exchange and correlation functionals, the user has the alternative of specifying combined exchange and correlation functionals.

The available hybrid functionals (where a Hartree-Fock Exchange component is present) consist of the Becke "half and half" (see A.D. Becke, J. Chem. Phys. 98, 1372 (1992)), the adiabatic connection method (see A.D. Becke, J. Chem. Phys. 98, 5648 (1993)), B3LYP (popularized by Gaussian9X), Becke 1997 ("Becke V" paper: A.D.Becke, J. Chem. Phys., 107, 8554 (1997)).

The keyword beckehandh specifies that the exchange-correlation energy will be computed as

$$E_{XC} \approx \frac{1}{2} E_X^{\rm HF} + \frac{1}{2} E_X^{\rm Slater} + \frac{1}{2} E_C^{\rm PW91LDA}$$

We know this is NOT the correct Becke prescribed implementation which requires the XC potential in the energy expression. But this is what is currently implemented as an approximation to it.

The keyword acm specifies that the exchange-correlation energy is computed as

$$E_{XC} = a_0 E_X^{\text{HF}} + (1 - a_0) E_X^{\text{Slater}} + a_X \delta E_X^{Becke88} + E_C^{VWN} + a_C \delta E_C^{Perdew91}$$

where
$$a_0 = 0.20, a_X = 0.72, a_C = 0.81$$

 $a_0 = 0.20, a_X = 0.72, a_C = 0.81$ and Δ stands for a non-local component.

The keyword b3lyp specifies that the exchange-correlation energy is computed as

$$E_{XC} = a_0 E_X^{\text{HF}} + (1 - a_0) E_X^{\text{Slater}} + a_X \delta E_X^{Becke88} + (1 - a_C) E_C^{VWN \perp LRPA} + a_C \delta E_C^{LYP}$$

where
$$a_0 = 0.20, a_X = 0.72, a_C = 0.81$$

Table of available Exchange (X) and Correlation (C) functionals. GGA is the Generalized Gradient Approximation, and Meta refers to Meta-GGAs. The column 2nd refers to second derivatives of the energy with respect to nuclear position.

Keyword	X	C	GGA	Meta	Hybr.	2nd	Ref.
slater	*					Y	[1]
vwn_1		*				Y	[2]
vwn_2		*				Y	[2]
vwn_3		*				Y	[2]
vwn_4		*				Y	[2]
vwn_5		*				Y	[2]
vwn_1_rpa		*				Y	[2]
perdew81		*				Y	[3]
pw91lda		*				Y	[4]
xbecke86b	*		*			Ν	[54]
becke88	*		*			Y	[5]
xperdew86	*		*			Ν	[53]
xperdew91	*		*			Y	[6]

xpbe96	*		*			Y	[7]
gill96	*		*			Y	[8]
optx	*		*			Ν	[20]
mpw91	*		*			Y	[23]
xft97	*		*			Ν	[24]
rpbe	*		*			Y	[33]
revpbe	*		*			Y	[34]
xpw6b95	*		*			Ν	[36]
xpwb6k	*		*			Ν	[36]
perdew86		*	*			Y	[9]
lyp		*	*			Y	[10]
perdew91		*	*			Y	[6]
cpbe96		*	*			Y	[7]
cft97		*	*			Ν	[24]
ор		*	*			Ν	[31]
hcth	*	*	*			Ν	[11]
hcth120	*	*	*			Ν	[12]
hcth147	*	*	*			Ν	[12]
hcth407	*	*	*			Ν	[19]
becke97gga1	*	*	*			Ν	[18]
hcthp14	*	*	*			Ν	[21]
ft97	*	*	*			Ν	[24]
htch407p	*	*	*			Ν	[27]
bop	*	*	*			Ν	[31]
pbeop	*	*	*			Ν	[32]
xpkzb99	*			*		Ν	[26]
cpkzb99		*		*		Ν	[26]
xtpss03	*			*		Ν	[28]
ctpss03		*		*		Ν	[28]
bc95		*		*		Ν	[33]
cpw6b95		*		*		Ν	[36]
cpwb6k		*		*		Ν	[36]
xm05	*			*	*	Ν	[37]
cm05		*		*		Ν	[37]
m05-2x	*	*		*	*	Ν	[38]
xm05-2x	*			*	*	Ν	[38]
cm05-2x		*		*		Ν	[38]
xctpssh				*	*	Ν	[29]
bb1k				*	*	Ν	[34]

mpw1b95				*	*	Ν	[35]
mpwb1k				*	*	N	[35]
pw6b95				*	*	N	[36]
pwb6k				*	*	N	[36]
m05				*	*	Ν	[37]
VSXC				*	*	N	[39]
xvsxc	*			*		N	[39]
CVSXC		*		*		Ν	[39]
m06-L	*	*		*		Ν	[40]
xm06-L	*			*		Ν	[40]
cm06-L		*		*		Ν	[40]
m06-hf				*	*	Ν	[41]
xm06-hf	*			*	*	Ν	[41]
cm06-hf		*		*		Ν	[41]
m06				*	*	N	[42]
xm06	*			*	*	Ν	[42]
cm06		*		*		N	[42]
m06-2x				*	*	N	[42]
xm06-2x	*			*	*	Ν	[42]
cm06-2x		*		*		N	[42]
cm08-hx		*		*		N	[46]
xm08-hx	*			*		N	[46]
m08-hx	*	*		*	*	Ν	[46]
cm08-so		*		*		N	[46]
xm08-so	*			*		Ν	[46]
m08-so	*	*		*	*	Ν	[46]
cm11		*		*		Ν	[47]
xm11	*			*		Ν	[47]
m11	*	*		*	*	Ν	[47]
cm11-l		*		*		Ν	[48]
xm11-l	*			*		N	[48]
m11-l	*	*		*		N	[48]
csogga		*	*			N	[49]
xsogga	*		*			N	[49]
sogga	*	*	*			N	[49]
csogga11		*	*			Ν	[50]
xsogga11	*		*			Ν	[50]
sogga11	*	*	*			N	[50]
csogga11-x		*				Ν	[51]

xsogga11-x	*		*			Ν	[51]
sogga11-x	*	*	*		*	Ν	[51]
dldf	*	*		*	*	Ν	[52]
beckehandh	*	*			*	Y	[13]
b3lyp	*	*	*		*	Y	[14]
acm	*	*	*		*	Y	[14]
becke97	*	*	*		*	Ν	[15]
becke97-1	*	*	*		*	Ν	[11]
becke97-2	*	*	*		*	Ν	[22]
becke97-3	*	*	*		*	Ν	[30]
becke97-d	*	*	*		*	Ν	[45]
becke98	*	*	*		*	Ν	[16]
pbe0	*	*	*		*	Y	[17]
mpw1k	*	*	*		*	Y	[25]

- 1. J.C. Slater and K. H. Johnson, Phys. Rev. B 5, 844 (1972)
- 2. S.J. Vosko, L. Wilk and M. Nusair, Can. J. Phys. 58, 1200 (1980)
- 3. J. P. Perdew and A. Zunger, Phys. Rev. B 23, 5048 (1981).
- 4. J.P. Perdew and Y. Wang, Phys. Rev. B 45, 13244 (1992)
- 5. A.D. Becke, Phys. Rev. A 88, 3098 (1988)
- J.P. Perdew, J.A. Chevary, S.H. Vosko, K.A. Jackson, M.R. Pederson, D.J. Singh and C. Fiolhais, Phys. Rev. B 46, 6671 (1992)
- J.P. Perdew, K. Burke and M. Ernzerhof, Phys. Rev. Lett. 77, 3865 (1996); 78, 1396 (1997)
- 8. P.W.Gill, Mol. Phys. 89, 433 (1996)
- 9. J. P. Perdew, Phys. Rev. B 33, 8822 (1986)
- 10. C. Lee, W. Yang and R. G. Parr, Phys. Rev. B 37, 785 (1988)
- 11. F.A.Hamprecht, A.J.Cohen, D.J.Tozer and N.C. Handy, J. Chem. Phys. 109, 6264 (1998)
- 12. A.D.Boese, N.L.Doltsinis, N.C.Handy and M.Sprik. J. Chem. Phys. 112, 1670 (2000)
- 13. A.D. Becke, J. Chem. Phys. 98, 1372 (1992)
- 14. A.D. Becke, J. Chem. Phys. 98, 5648 (1993)
- 15. A.D.Becke, J. Chem. Phys. 107, 8554 (1997)
- 16. H.L.Schmider and A.D. Becke, J. Chem. Phys. 108, 9624 (1998)
- 17. C.Adamo and V.Barone, J. Chem. Phys. 110, 6158 (1999)
- 18. A.J.Cohen and N.C. Handy, Chem. Phys. Lett. 316, 160 (2000)
- 19. A.D.Boese, N.C.Handy, J. Chem. Phys. 114, 5497 (2001)
- 20. N.C.Handy, A.J. Cohen, Mol. Phys. 99, 403 (2001)
- 21. G. Menconi, P.J. Wilson, D.J. Tozer, J. Chem. Phys 114, 3958 (2001)
- 22. P.J. Wilson, T.J. Bradley, D.J. Tozer, J. Chem. Phys 115, 9233 (2001)
- 23. C. Adamo and V. Barone, J. Chem. Phys. 108, 664 (1998); Y. Zhao and D.G. Truhlar, J. Phys. Chem. A 109, 5656 (2005)
- 24. M.Filatov and W.Thiel, Mol.Phys. 91, 847 (1997). M.Filatov and W.Thiel, Int.J.Quantum Chem. 62, 603 (1997)
- 25. B.J. Lynch, P.L. Fast, M. Harris and D.G. Truhlar, J. Phys. Chem. A 104, 4811(2000)
- 26. J.P. Perdew, S. Kurth, A. Zupan and P. Blaha, Phys. Rev. Lett. 82, 2544 (1999)

- 27. A. D. Boese, A. Chandra, J. M. L. Martin and D. Marx, J. Chem. Phys. 119, 5965 (2003)
- 28. J. Tao, J.Perdew, V. Staroverov and G. Scuseria, Phys. Rev. Let. 91, 146401-1 (2003)
- 29. V. Staroverov, G. Scuseria, J. Tao and J.Perdew, J. Chem. Phys. 119, 12129 (2003)
- 30. T.W. Keal, D.J. Tozer, J. Chem. Phys 123, 121103 (2005)
- 31. T. Tsuneda, T. Suzumura and K. Hirao, J. Chem Phys. 110, 10664 (1999)
- 32. T. Tsuneda, T. Suzumura and K. Hirao, J. Chem Phys. 111, 5656 (1999)
- 33. B. Hammer, L. B. Hansen and J. Nørskov , Phys. Rev. B 58, 7413 (1999)
- 34. Y. Zhang and W. Yang, Phys. Rev. Letters 80, 890 (1998)
- 35. A. D. Becke, J. Chem. Phys. 104, 1040 (1996)
- 36. Y. Zhao and D. G. Truhlar, J. Phys. Chem. A 108, 2715 (2004)
- 37. Y. Zhao and D. G. Truhlar, J. Phys. Chem. A 108, 6908 (2004)
- 38. Y. Zhao and D. G. Truhlar, J. Phys. Chem. A 109, 5656 (2005)
- 39. Y. Zhao, N. E. Schultz and D. G. Truhlar, J. Chem. Phys. 123, 161103 (2005)
- 40. Y. Zhao, N. E. Schultz and D. G. Truhlar, J. Chem. Theory Comput. 2, 364 (2006)
- 41. T. Van Voorhis, G. E. Scuseria, J. Chem. Phys. 109, 400 (1998)
- 42. Y. Zhao, D. G. Truhlar, J. Chem. Phys. 125, 194101 (2006)
- 43. Y. Zhao, D. G. Truhlar, J. Phys. Chem. A. 110, 13126 (2006)
- 44. Y. Zhao, D. G. Truhlar, Theor. Chem. Acc. (2006)
- 45. S. Grimme, J. Comp. Chem. 27, 1787 (2006).
- 46. Y. Zhao and D. G. Truhlar, J. Chem. Theory Comput. 4, 1849 (2008)
- 47. R. Peverati and D. G. Truhlar, J. Phys. Chem. Letters 2, 2810 (2011)
- 48. R. Peverati and D. G. Truhlar, J. Phys. Chem. Letters 3, 117 (2012)
- 49. Y. Zhao and D. G. Truhlar, J. Chem. Phys. 128, 184109 (2008)
- 50. R. Peverati, Y. Zhao and D. G. Truhlar, J. Phys. Chem. Lett. 2, 1911 (2011)
- 51. R. Peverati and D.G. Truhlar, J. Chem. Phys. , 135, 191102 (2011)
- 52. K. Pernal, R. Podeszwa, K. Patkowski and K. Szalewicz, Phys. Rev. Lett. 103, 263201 (2009)
- 53. J. P. Perdew and W. Yue, Phys. Rev. B 33, 8800 (1986)
- 54. A. D. Becke, J. Chem. Phys. 85, 7184 (1986)

Meta-GGA Functionals

One way to calculate meta-GGA energies is to use orbitals and densities from fully self-consistent GGA or LDA calculations and run them in one iteration in the meta-GGA functional. It is expected that meta-GGA energies obtained this way will be close to fully self consistent meta-GGA calculations.

It is possible to calculate metaGGA energies both ways in NWChem, that is, self-consistently or with GGA/LDA orbitals and densities. However, since second derivatives are not available for metaGGAs, in order to calculate frequencies, one must use task dft freq numerical. A sample file with this is shown below, in Sample input file. In this instance, the energy is calculated self-consistently and geometry is optimized using the analytical gradients.

(For more information on metaGGAs, see S. Kurth, J. Perdew, P. Blaha, Int. J. Quant. Chem 75, 889 (1999) for a brief description of meta-GGAs, and citations 14-27 therein for thorough background) $\,$

Note: both TPSS and PKZB correlation require the PBE GGA CORRELATION (which is itself dependent on an LDA). The decision has been made to use these functionals with the

accompanying local PW91LDA. The user does not have the ability to set the local part of these metaGGA functionals.

Range-Separated Functionals

Range separated functionals (or long-range corrected or LC) can be specified as follows: CAM-B3LYP:

xc xcamb88 1.00 lyp 0.81 vwn_5 0.19 hfexch 1.00 cam 0.33 cam alpha 0.19 cam beta 0.46

LC-BLYP:

xc xcamb88 1.00 lyp 1.0 hfexch 1.00 cam 0.33 cam_alpha 0.0 cam_beta 1.0

LC-PBE:

xc xcampbe96 1.0 cpbe96 1.0 HFexch 1.0
cam 0.30 cam_alpha 0.0 cam_beta 1.0

LC-PBE0 or CAM-PBE0:

xc xcampbe96 1.0 cpbe96 1.0 HFexch 1.0 cam 0.30 cam_alpha 0.25 cam_beta 0.75

BNL (Baer, Neuhauser, Lifshifts):

xc xbnl07 0.90 lyp 1.00 hfexch 1.00 cam 0.33 cam_alpha 0.0 cam_beta 1.0

LC-wPBE:

xc xwpbe 1.00 cpbe96 1.0 hfexch 1.00 cam 0.3 cam_alpha 0.00 cam_beta 1.00

LC-wPBEh:

xc xwpbe 0.80 cpbe96 1.0 hfexch 1.00 cam 0.2 cam_alpha 0.20 cam_beta 0.80

HSE03 functional: 0.25*Ex(HF-SR) - 0.25*Ex(PBE-SR) + Ex(PBE) + Ec(PBE), where gamma(HF-SR) = gamma(PBE-SR)

xc hse03

or it can be explicitly set as

xc xpbe96 1.0 xcampbe96 -0.25 cpbe96 1.0 srhfexch 0.25 cam 0.33 cam_alpha 0.0 cam_beta 1.0

HSE06 functional:

xc xpbe96 1.0 xcampbe96 -0.25 cpbe96 1.0 srhfexch 0.25 cam 0.11 cam_alpha 0.0 cam_beta 1.0

cam represents the attenuation parameter, cam_alpha and cam_beta are parameters that control the amount of short-range DFT and long-range HF, respectively. In the HSE

functional, the HF part is short-ranged and DFT is long-ranged. Calculations with range-separated functionals can only be performed in direct mode with standard basis sets. However, the disk option can be utilized if a charge density fitting basis is utilized for the Coulomb part.

Example illustrating the CAM-B3LYP functional:

```
start h2o-camb3lyp
geometry units angstrom
   0
          0.00000000
                         0.0000000
                                         0.11726921
   Н
          0.75698224
                         0.00000000
                                        -0.46907685
   н
         -0.75698224
                         0.00000000
                                        -0.46907685
end
basis spherical
* library aug-cc-pvdz
end
dft
 xc xcamb88 1.00 lyp 0.81 vwn 5 0.19 hfexch 1.00
 cam 0.33 cam alpha 0.19 cam beta 0.46
 direct
 iterations 100
end
task dft energy
Example illustrating the HSE03 functional:
echo
start h2o-hse
geometry units angstrom
0
       0.00000000
                      0.00000000
                                      0.11726921
н
       0.75698224
                      0.00000000
                                     -0.46907685
н
      -0.75698224
                                     -0.46907685
                      0.0000000
end
basis spherical
 * library aug-cc-pvdz
end
dft
 xc hse03
 iterations 100
 direct
 end
task dft energy
#or alternatively
dft
 xc xpbe96 1.0 xcampbe96 -0.25 cpbe96 1.0 srhfexch 0.25
 cam 0.33 cam alpha 0.0 cam beta 1.0
 iterations 100
 direct
end
task dft energy
```

SSB-D functional

The recently developed SSB-D is a small correction to the non-empirical PBE functional and includes a portion of Grimme's dispersion correction (s6=0.847455). It is designed to reproduce the good results of OPBE for spin-state splittings and reaction barriers, and the good results of PBE for weak interactions. The SSB-D functional works excellent for these systems, including for difficult systems for DFT (dimerization of anthracene, branching of octane, water-hexamer isomers, C12H12 isomers, stacked adenine dimers), and for NMR chemical shieldings.

1. M. Swart, M. Solà, F.M. Bickelhaupt, J. Chem. Phys. 131, 094103 (2009)

2. M. Swart, M. Solà, F.M. Bickelhaupt, J. Comp. Meth. Sci. Engin. 9, 69 (2009)

It can be specified as

xc ssb-d

Semi-empirical hybrid DFT combined with perturbative MP2

This theory combines hybrid density functional theory with MP2 semi-empirically. The B2PLYP functional, which is an example of this approximation, can be specified as:

```
dft
xc HFexch 0.53 becke88 0.47 lyp 0.73 mp2 0.27
dftmp2 direct
direct
convergence energy 1e-8
iterations 100
end
```

This can also be performed in semidirect mode as

```
dft
xc HFexch 0.53 becke88 0.47 lyp 0.73 mp2 0.27
dftmp2 semidirect
direct
convergence energy 1e-8
iterations 100
end
```

For details of the theory, please see the following reference:

1. S. Grimme, "Semiempirical hybrid density functional with perturbative second-order correlation" Journal of Chemical Physics 124, 034108 (2006)

LB94 and CS00 --Asymptotic correction

The keyword LB94 will correct the asymptotic region of the XC definition of exchange-correlation potential by the van-Leeuwen-Baerends exchange-correlation potential that has the correct -1/r asymptotic behavior. The total energy will be computed by the XC definition of exchange-correlation functional. This scheme is known to tend to overcorrect the deficiency of most uncorrected exchange-correlation potentials.

The keyword CS00, when supplied with a real value of shift (in atomic units), will perform Casida-Salahub '00 asymptotic correction. This is primarily intended for use in conjunction

with TDDFT. The shift is normally positive (which means that the original uncorrected exchange-correlation potential must be shifted down).

When the keyword CS00 is specified without the value of shift, the program will automatically supply it according to the semi-empirical formula of Zhan, Nichols, and Dixon (again, see TDDFT for more details and references). As the Zhan's formula is calibrated against B3LYP results, it is most meaningful to use this in conjunction with the B3LYP functional, although the program does not prohibit (or even warn) the use of any other functional.

Sample input files of asymptotically corrected TDDFT calculations can be found in the corresponding section.

Sample input file

A simple example calculates the geometry of water, using the metaGGA functionals xtpss03 and ctpss03. This also highlights some of the print features in the DFT module. Note that you must use the line task dft freq numerical because analytic hessians are not available for the metaGGAs:

```
title "WATER 6-311G* meta-GGA XC geometry"
echo
geometry units angstroms
0
         0.0 0.0
                   0.0
Н
         0.0 0.0
                  1.0
Н
         0.0 1.0 0.0
end
basis
H library 6-311G*
0 library 6-311G*
end
dft
iterations 50
print kinetic energy
xc xtpss03 ctpss03
decomp
end
task dft optimize
task dft freq numerical
```

ITERATIONS or MAXITER --Number of SCF iterations

ITERATIONS or MAXITER <integer iterations default 30>

The default optimization in the DFT module is to iterate on the Kohn-Sham (SCF) equations for a specified number of iterations (default 30). The keyword that controls this optimization is ITERATIONS, and has the following general form,

```
iterations <integer iterations default 30>
```

or

```
maxiter <integer iterations default 30>
```

The optimization procedure will stop when the specified number of iterations is reached or convergence is met. See an example that uses this directive in Sample input file.

CONVERGENCE --SCF Convergence Control

```
CONVERGENCE [energy <real energy default 1e-6>] \
             [density <real density default 1e-5>] \
             [gradient <real gradient default 5e-4>] \
             [hl tol <real hl tol default 0.1>]
             [dampon <real dampon default 0.0>] \
             [dampoff <real dampoff default 0.0>] \
             [ncydp <integer ncydp default 2>] \
             [ncyds <integer ncyds default 30>] \
             [ncysh <integer ncysh default 30>] \
             [damp <integer ndamp default 0>] [nodamping] \
             [diison <real diison default 0.0>] \
             [diisoff <real diisoff default 0.0>] \
             [(diis [nfock <integer nfock default 10>]) ||
nodiis] \
             [levlon <real levlon default 0.0>] \
             [levloff <real levloff default 0.0>] \
             [(lshift <real lshift default 0.5>) ||
nolevelshifting] \
             [rabuck [n_rabuck <integer n_rabuck default 25>]]
```

Convergence is satisfied by meeting any or all of three criteria;

 convergence of the total energy; this is defined to be when the total DFT energy at iteration N and at iteration N-1 differ by a value less than some value (the default is 1e-6). This value can be modified using the key word,

```
CONVERGENCE energy <real energy default 1e-6>
```

• convergence of the total density; this is defined to be when the total DFT density matrix at iteration N and at iteration N-1 have a RMS difference less than some value (the default is 1e-5). This value can be modified using the key word,

CONVERGENCE density <real density default 1e-5>

• convergence of the orbital gradient; this is defined to be when the DIIS error vector becomes less than some value (the default is 5e-4). This value can be modified using the key word,

CONVERGENCE gradient <real gradient default 5e-4>

The default optimization strategy is to immediately begin direct inversion of the iterative subspace. Damping is also initiated (using 70% of the previous density) for the first 2 iteration. In addition, if the HOMO - LUMO gap is small and the Fock matrix somewhat diagonally dominant, then level-shifting is automatically initiated. There are a variety of ways to customize this procedure to whatever is desired.

An alternative optimization strategy is to specify, by using the change in total energy (from iterations when N and N-1), when to turn damping, level-shifting, and/or DIIS on/off. Start and stop keywords for each of these is available as,

```
CONVERGENCE [dampon <real dampon default 0.0>] \
[dampoff <real dampoff default 0.0>] \
[diison <real diison default 0.0>] \
[diisoff <real diisoff default 0.0>] \
[levlon <real levlon default 0.0>] \
[levloff <real levloff default 0.0>]
```

So, for example, damping, DIIS, and/or level-shifting can be turned on/off as desired.

Another strategy can be to simply specify how many iterations (cycles) you wish each type of procedure to be used. The necessary keywords to control the number of damping cycles (ncydp), the number of DIIS cycles (ncyds), and the number of level-shifting cycles (ncysh) are input as,

```
CONVERGENCE [ncydp <integer ncydp default 2>] \
[ncyds <integer ncyds default 30>] \
[ncysh <integer ncysh default 0>]
```

The amount of damping, level-shifting, time at which level-shifting is automatically imposed, and Fock matrices used in the DIIS extrapolation can be modified by the following keywords

CONVERGENCE [damp <integer ndamp default 0>] \
 [diis [nfock <integer nfock default 10>]] \
 [lshift <real lshift default 0.5>] \
 [hl_tol <real hl_tol default 0.1>]]

Damping is defined to be the percentage of the previous iterations density mixed with the current iterations density. So, for example

```
CONVERGENCE damp 70
```

would mix 30% of the current iteration density with 70% of the previous iteration density.

Level-Shifting is defined as the amount of shift applied to the diagonal elements of the unoccupied block of the Fock matrix. The shift is specified by the keyword lshift. For example the directive,

CONVERGENCE lshift 0.5

causes the diagonal elements of the Fock matrix corresponding to the virtual orbitals to be shifted by 0.5 a.u. By default, this level-shifting procedure is switched on whenever the HOMO-LUMO gap is small. Small is defined by default to be 0.05 au but can be modified by the directive hl_tol. An example of changing the HOMO-LUMO gap tolerance to 0.01 would be,

CONVERGENCE hl_tol 0.01

Direct inversion of the iterative subspace with extrapolation of up to 10 Fock matrices is a default optimization procedure. For large molecular systems the amount of available memory may preclude the ability to store this number of N^2 arrays in global memory. The user may then specify the number of Fock matrices to be used in the extrapolation (must be greater than three (3) to be effective). To set the number of Fock matrices stored and used in the extrapolation procedure to 3 would take the form,

CONVERGENCE diis 3

The user has the ability to simply turn off any optimization procedures deemed undesirable with the obvious keywords,

CONVERGENCE [nodamping] [nodiis] [nolevelshifting]

For systems where the initial guess is very poor, the user can try using fractional occupation of the orbital levels during the initial cycles of the SCF convergence (A. D. Rabuck and G. E. Scuseria, J. Chem. Phys 110,695 (1999)). The input has the following form

CONVERGENCE rabuck [n_rabuck <integer n_rabuck default 25>]]

where the optional value n_rabuck determines the number of SCF cycles during which the method will be active. For example, to set equal to 30 the number of cycles where the Rabuck method is active, you need to use the following line

CONVERGENCE rabuck 30

CDFT --Constrained DFT

This option enables the constrained DFT formalism by Wu and Van Voorhis described in the paper: Q. Wu, T. Van Voorhis, Phys. Rev. A 72, 024502 (2005).

```
CDFT <integer fatom1 latom1> [<integer fatom2 latom2>]
(charge||spin <real constaint_value>) \
      [pop (becke||mulliken||lowdin) default lowdin]
```

Variables fatom1 and latom1 define the first and last atom of the group of atoms to which the constaint will be applied. Therefore the atoms in the same group should be placed continuously in the geometry input. If fatom2 and latom2 are specified, the difference between group 1 and 2 (i.e. 1-2) is constrained.

The constraint can be either on the charge or the spin density (# of alpha - beta electrons) with a user specified constaint_value. Note: No gradients have been implemented for the spin constaints case. Geometry optimizations can only be performed using the charge constaint.

To calculate the charge or spin density, the Becke, Mulliken, and Lowdin population schemes can be used. The Lowdin scheme is default while the Mulliken scheme is not recommended. If basis sets with many diffuse functions are used, the Becke population scheme is recommended.

Multiple constaints can be defined simultaniously by defining multiple cdft lines in the input. The same population scheme will be used for all constaints and only needs to be specified once. If multiple population options are defined, the last one will be used. When there are convergence problems with multiple constaints, the user is advised to do one constraint first and to use the resulting orbitals for the next step of the constained calculations.

It is best to put "convergence nolevelshifting" in the dft directive to avoid issues with gradient calculations and convergence in CDFT. Use orbital swap to get a broken-symmetry solution.

An input example is given below.

```
geometry
symmetry
C 0.0 0.0
              0.0
0 1.2
        0.0
             0.0
C 0.0 0.0
            2.0
0
  1.2 0.0 2.0
end
basis
* library 6-31G*
end
dft
xc b3lyp
convergence nolevelshifting
odft
mult 1
vectors swap beta 14 15
cdft 1 2 charge 1.0
end
task dft
```

SMEAR --Fractional Occupation of the Molecular Orbitals

The SMEAR keyword is useful in cases with many degenerate states near the HOMO (eg metallic clusters)

SMEAR <real smear default 0.001>

This option allows fractional occupation of the molecular orbitals. A Gaussian broadening function of exponent smear is used as described in the paper: R.W. Warren and B.I. Dunlap, Chem. Phys. Letters 262, 384 (1996). The user must be aware that an additional energy term is added to the total energy in order to have energies and gradients consistent.

FON --Calculations with fractional numbers of electrons

• Restricted

fon partial 3 electrons 1.8 filled 2

Here 1.8 electrons will be equally divided over 3 valence orbitals and 2 orbitals are fully filled. The total number of electrons here is 5.8

Example input:

```
echo
title "carbon atom"
start carbon fon
geometry units angstrom nocenter
symmetry c1
    0.0 0.0 0.0
  С
end
basis
* library 6-31G
end
dft
 direct
 grid xfine
 convergence energy 1d-8
 xc pbe0
 fon partial 3 electrons 1.8 filled 2
end
task dft energy
```

```
• Unrestricted
```

fon alpha partial 3 electrons 0.9 filled 2 fon beta partial 3 electrons 0.9 filled 2

Here 0.9 electrons will be equally divided over 3 alpha valence orbitals and 2 alpha orbitals are fully filled. Similarly for beta. The total number of electrons here is 5.8

Example input:

```
echo
title "carbon atom"
start carbon fon
geometry units angstrom nocenter
symmetry c1
С
     0.0 0.0 0.0
end
basis
 * library 6-31G
end
dft
 odft
 fon alpha partial 3 electrons 0.9 filled 2
 fon beta partial 3 electrons 0.9 filled 2
end
```

task dft energy

To set fractional numbers in the core orbitals, add the following directive in the input file:

• set dft:core_fon .true.

Example input:

```
dft
print "final vectors analysis"
odft
direct
fon alpha partial 2 electrons 1.0 filled 2
fon beta partial 2 electrons 1.0 filled 2
xc pbe0
convergence energy 1d-8
end
task dft
```

OCCUP --Controlling the occupations of molecular orbitals

Example: echo start h2o_core_hole memory 1000 mb geometry units au 00 0 0 Η Θ 1.430 -1.107 Η 0 -1.430 -1.107 end basis 0 library 6-31g* H library 6-31g* end occup # core-hole in beta 6 6 1.0 0.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 0.0 0.0 end dft odft mult 1 xc beckehandh end task dft

GRID --Numerical Integration of the XC Potential

```
GRID [(xcoarse||coarse||medium||fine||xfine) default medium] \
    [(gausleg||lebedev ) default lebedev ] \
    [(becke||erf1||erf2||ssf) default erf1] \
    [(euler||mura||treutler) default mura] \
    [rm <real rm default 2.0>] \
    [nodisk]
```

A numerical integration is necessary for the evaluation of the exchange-correlation contribution to the density functional. The default quadrature used for the numerical integration is an Euler-MacLaurin scheme for the radial components (with a modified Mura-Knowles transformation) and a Lebedev scheme for the angular components. Within this numerical integration procedure various levels of accuracy have been defined and are available to the user. The user can specify the level of accuracy with the keywords; xcoarse, coarse, medium, fine, and xfine. The default is medium.

```
GRID [xcoarse||coarse||medium||fine||xfine]
```

Our intent is to have a numerical integration scheme which would give us approximately the accuracy defined below regardless of molecular composition.

Keyword	Total Energy Target Accuracy
xcoarse	$1x10^{-4}$
coarse	$1x10^{-5}$
medium	$1x10^{-6}$
fine	$1x10^{-7}$
xfine	$1x10^{-8}$

In order to determine the level of radial and angular quadrature needed to give us the target accuracy we computed total DFT energies at the LDA level of theory for many homonuclear atomic, diatomic and triatomic systems in rows 1-4 of the periodic table. In each case all bond lengths were set to twice the Bragg-Slater radius. The total DFT energy of the system was computed using the converged SCF density with atoms having radial shells ranging from 35-235 (at fixed 48/96 angular quadratures) and angular quadratures of 12/24-48/96 (at fixed 235 radial shells). The error of the numerical integration was determined by comparison to a "best" or most accurate calculation in which a grid of 235 radial points 48 theta and 96 phi angular points on each atom was used. This corresponds to approximately 1 million points per atom. The following tables were empirically determined to give the desired target accuracy for DFT total energies. These tables below show the number of radial and angular shells which the DFT module will use for for a given atom depending on the row it is in (in the periodic table) and the desired accuracy. Note, differing atom types in a given molecular system will most likely have differing associated numerical grids. The intent is to generate the desired energy accuracy (with utter disregard for speed).

Program default number of radial and angular shells empirically
determined for Row 1 atoms (Li

Keyword	Radial	Angular
xcoarse	21	194
coarse	35	302
medium	49	434
fine	70	590
xfine	100	1202

Program default number of radial and angular shells empirically determined for Row 2 atoms (Na

Radial	Angular	
xcoarse	42	194
coarse	70	302
medium	88	434
fine	123	770
xfine	125	1454

Program default number of radial and angular shells empirically determined for Row 3 atoms (K

Radial	Angular	
xcoarse	75	194
coarse	95	302
medium	112	590
fine	130	974
xfine	160	1454

Program default number of radial and angular shells empirically determined for Row 4 atoms (Rb

Radial	Angular	
xcoarse	84	194
coarse	104	302
medium	123	590
fine	141	974
xfine	205	1454

Angular grids

In addition to the simple keyword specifying the desired accuracy as described above, the user has the option of specifying a custom quadrature of this type in which ALL atoms have the same grid specification. This is accomplished by using the gausleg keyword.

Gauss-Legendre angular grid

GRID gausleg <integer nradpts default 50> <integer nagrid
default 10>

In this type of grid, the number of phi points is twice the number of theta points. So, for example, a specification of,

GRID gausleg 80 20

would be interpreted as 80 radial points, 20 theta points, and 40 phi points per center (or 64000 points per center before pruning).

Lebedev angular grid

A second quadrature is the Lebedev scheme for the angular components11.6. Within this numerical integration procedure various levels of accuracy have also been defined and are available to the user. The input for this type of grid takes the form,

GRID lebedev <integer radpts > <integer iangquad >

In this context the variable iangquad specifies a certain number of angular points as indicated by the table below:

IANGQUAD	Nangular	l
1	38	9
2	50	11
3	74	13
4	86	15
5	110	17
6	146	19
7	170	21
8	194	23
9	230	25
10	266	27
11	302	29
12	350	31
13	434	35
14	590	41
15	770	47
16	974	53

List of Lebedev quadratures

17	1202	59
18	1454	65
19	1730	71
20	2030	77
21	2354	83
22	2702	89
23	3074	95
24	3470	101
25	3890	107
26	4334	113
27	4802	119
28	5294	125
29	5810	131

Therefore the user can specify any number of radial points along with the level of angular quadrature (1-29).

The user can also specify grid parameters specific for a given atom type: parameters that must be supplied are: atom tag and number of radial points. As an example, here is a grid input line for the water molecule

grid lebedev 80 11 H 70 8 0 90 11

Partitioning functions

GRID [(becke||erf1||erf2||ssf) default erf1]

- becke : A. D. Becke, J. Chem. Phys. 88, 1053 (1988).
- ssf : R.E.Stratmann, G.Scuseria and M.J.Frisch, Chem. Phys. Lett. 257, 213 (1996).
- erf1 : modified ssf
- erf2 : modified ssf

 $\operatorname{Erf} n$ partioning functions

$$\begin{aligned} w_A(r) &= \prod_{B \neq A} \frac{1}{2} [1 - erf(\mu'_{AB})] \\ \mu'_{AB} &= \frac{1}{\alpha} \frac{\mu_{AB}}{(1 - \mu^2_{AB})^n} \\ \mu_{AB} &= \frac{\mathbf{r}_{A} - \mathbf{r}_{B}}{|\mathbf{r}_{A} - \mathbf{r}_{B}|} \end{aligned}$$

Radial grids

GRID [[euler||mura||treutler] default mura]

- euler : Euler-McLaurin quadrature wih the transformation devised by C.W. Murray, N.C. Handy, and G.L. Laming, Mol. Phys.78, 997 (1993).
- mura : Modification of the Murray-Handy-Laming scheme by M.E.Mura and P.J.Knowles, J Chem Phys 104, 9848 (1996) (we are not using the scaling factors proposed in this paper).
- treutler : Gauss-Chebyshev using the transformation suggested by O.Treutler and R.Alrhichs, J.Chem.Phys 102, 346 (1995).

Disk usage for Grid

NODISK

This keyword turns off storage of grid points and weights on disk.

TOLERANCES --Screening tolerances

TOLERANCES tight] [tol_rho <real tol_rho default 1e-10>]
\
[accCoul <integer accCoul default 8>] \
[...]

[radius <real radius default 25.0>

The user has the option of controlling screening for the tolerances in the integral evaluations for the DFT module. In most applications, the default values will be adequate for the calculation, but different values can be specified in the input for the DFT module using the keywords described below.

The input parameter accCoul is used to define the tolerance in Schwarz screening for the Coulomb integrals. Only integrals with estimated values greater than $10^{(-accCoul)}$ are evaluated.

TOLERANCES accCoul <integer accCoul default 8>

Screening away needless computation of the XC functional (on the grid) due to negligible density is also possible with the use of,

TOLERANCES tol_rho <real tol_rho default 1e-10>

XC functional computation is bypassed if the corresponding density elements are less than tol_rho.

A screening parameter, radius, used in the screening of the Becke or Delley spatial weights is also available as,

TOLERANCES radius <real radius default 25.0>

where radius is the cutoff value in bohr.

The tolerances as discussed previously are insured at convergence. More sleazy tolerances are invoked early in the iterative process which can speed things up a bit. This can also be problematic at times because it introduces a discontinuity in the convergence process. To avoid use of initial sleazy tolerances the user can invoke the tight option:

TOLERANCES tight

This option sets all tolerances to their default/user specified values at the very first iteration.

DIRECT, SEMIDIRECT and NOIO --Hardware Resource Control

```
DIRECT||INCORE

SEMIDIRECT [filesize <integer filesize default disksize>]

[memsize <integer memsize default available>]

[filename <string filename default

$file_prefix.aoints$>]

NOIO
```

The inverted charge-density and exchange-correlation matrices for a DFT calculation are normally written to disk storage. The user can prevent this by specifying the keyword noio within the input for the DFT directive. The input to exercise this option is as follows,

noio

If this keyword is encountered, then the two matrices (inverted charge-density and exchange-correlation) are computed ``on-the-fly *whenever needed*.

The INCORE option is always assumed to be true but can be overridden with the option DIRECT in which case all integrals are computed ``on-the-fly.

The SEMIDIRECT option controls caching of integrals. A full description of this option is described in User Manual 10.8. Some functionality which is only compatible with the DIRECT option will not, at present, work when using SEMIDIRECT.

ODFT and MULT -- Open shell systems

ODFT MULT <integer mult default 1>

Both closed-shell and open-shell systems can be studied using the DFT module. Specifying the keyword MULT within the DFT directive allows the user to define the spin multiplicity of the system. The form of the input line is as follows;

MULT <integer mult default 1>

When the keyword MULT is specified, the user can define the integer variable mult, where mult is equal to the number of alpha electrons minus beta electrons, plus 1.

When MULT is set to a negative number. For example, if MULT = -3, a triplet calculation will be performed with the beta electrons preferentially occupied. For MULT = 3, the alpha electrons will be preferentially occupied.

The keyword ODFT is unnecessary except in the context of forcing a singlet system to be computed as an open shell system (i.e., using a spin-unrestricted wavefunction).

CGMIN --Quadratic convergence algorithm

The cgmin keyword will use the quadratic convergence algorithm. It is possible to turn the use of the quadratic convergence algorithm off with the nocgmin keyword.

RODFT --Restricted open-shell DFT

The rodft keyword will perform restricted open-shell calculations. This keyword can only be used with the CGMIN keyword.

SIC --Self-Interaction Correction

sic [perturbative || oep || oep-loc <default perturbative>]

The Perdew and Zunger (see J. P. Perdew and A. Zunger, Phys. Rev. B 23, 5048 (1981)) method to remove the self-interaction contained in many exchange-correlation functionals has been implemented with the Optimized Effective Potential method (see R. T. Sharp and G. K. Horton, Phys. Rev. 90, 317 (1953), J. D. Talman and W. F. Shadwick, Phys. Rev. A 14, 36 (1976)) within the Krieger-Li-Iafrate approximation (J. B. Krieger, Y. Li, and G. J. Iafrate, Phys. Rev. A 45, 101 (1992); 46, 5453 (1992); 47, 165 (1993)) Three variants of these methods are included in NWChem:

- sic perturbative This is the default option for the sic directive. After a self-consistent calculation, the Kohn-Sham orbitals are localized with the Foster-Boys algorithm (see section 10.15) and the self-interaction energy is added to the total energy. All exchange-correlation functionals implemented in the NWChem can be used with this option.
- sic oep With this option the optimized effective potential is built in each step of the self-consistent process. Because the electrostatic potential generated for each orbital involves a numerical integration, this method can be expensive.
- sic oep-loc This option is similar to the oep option with the addition of localization of the Kohn-Sham orbitals in each step of the self-consistent process.

With oep and oep-loc options a xfine grid (see section 11.10) must be used in order to avoid numerical noise, furthermore the hybrid functionals can not be used with these options. More details of the implementation of this method can be found in J. Garza, J. A. Nichols and D. A. Dixon, J. Chem. Phys. 112, 7880 (2000). The components of the sic energy can be printed out using:

print "SIC information"

MULLIKEN -- Mulliken analysis

Mulliken analysis of the charge distribution is invoked by the keyword:

MULLIKEN

When this keyword is encountered, Mulliken analysis of both the input density as well as the output density will occur. For example, to perform a mulliken analysis and print the explicit population analysis of the basis functions, use the following

dft mulliken

```
print "mulliken ao"
end
task dft
```

FUKUI --Fukui Indices

Fukui inidces analysis is invked by the keyword:

FUKUI

When this keyword is encounters, the condensed Fukui indices will be calculated and printed in the output. Detailed information about the analysis can be obtained using the following

```
dft
fukui
print "Fukui information"
end
task dft
```

BSSE --Basis Set Superposition Error

Particular care is required to compute BSSE by the counter-poise method for the DFT module. In order to include terms deriving from the numerical grid used in the XC integration, the user must label the ghost atoms not just bq, but bq followed by the given atomic symbol. For example, the first component needed to compute the BSSE for the water dimer, should be written as follows

```
geometry h2o autosym units au
0
          0.0000000
                         0.0000000
                                         0.22143139
Н
          1.43042868
                         0.0000000
                                        -0.88572555
Н
         -1.43042868
                         0.00000000
                                        -0.88572555
          0.71521434
                         0.00000000
                                        -0.33214708
bqH
         -0.71521434
                         0.0000000
                                        -0.33214708
bqH
          0.0000000
bq0
                         0.0000000
                                        -0.88572555
end
basis
H library aug-cc-pvdz
0 library aug-cc-pvdz
bqH library H aug-cc-pvdz
bq0 library 0 aug-cc-pvdz
end
```

Please note that the ``ghost oxygen atom has been labeled bqO, and not just bq.

DISP -- Empirical Long-range Contribution (vdW)

DISP

[vdw <real vdw integer default 2]]
[[s6 <real s6 default depends on XC functional>] \
[alpha <real s6 default 20.0d0] \
[off] \</pre>

When systems with high dependence on van der Waals interactions are computed, the dispersion term may be added empirically through long-range contribution DFT-D, i.e. $E_{DFT-D} = E_{DFT-KS} + E_{disp}$, where:

$$E_{disp} = -s_6 \sum_{i=1}^{N_{atom}-1} \sum_{j=i+1}^{N_{atom}} \frac{C_6^{ij}}{R_{ij}^6} \left(1 + e^{-\alpha(R_{ij}/R_{vdw}-1)}\right)^{-1}$$

In this equation, the s_6 term depends in the functional and basis set used, C_6^{ij} is the dispersion coefficient between pairs of atoms. R_{vdw} and R_{ij} are related with van der Waals atom radii and the nucleus distance respectively. The α value contributes to control the corrections at intermediate distances.

There are available three ways to compute C_6^{ij} :

1.
$$C_6^{ij} = \frac{2(C_6^i C_6^j)^{2/3} (N_{effi} N_{effj})^{1/3}}{C_6^i (N_{effi}^2)^{1/3} + (C_6^i N_{effj}^2)^{1/3}}$$
 where N_{eff} and C_6 are obtained from Q. Wu and W.

Yang, J. Chem. Phys. 116 515 (2002) and U. Zimmerli, M Parrinello and P. Koumoutsakos J. Chem. Phys. 120 2693 (2004). (Use vdw 0)

2. $C_6^{ij} = 2 \frac{C_6^i C_6^j}{C_6^i + C_6^j}$. See details in S. Grimme J. Comp. Chem. 25 1463 (2004). (Use vdw 1)

3. $C_6^{ij} = \sqrt{C_6^i C_6^j}$ See details in S. Grimme J. Comp. Chem. 271787 (2006). (Use vdw 2)

Note that in each option there is a certain set of C_6 and R_{vdw} . ALso note that Grimme only defined parameters for elements up to Z=54 for the dispersion correction above. C_6 values for elements above Z=54 have been set to zero.

For options vdw 1 and vdw 2 , there are S_6 values by default for some functionals and triple-zeta plus double polarization basis set (TZV2P):

- vdw 1. BLYP 1.40, PBE 0.70 and BP86 1.30.
- vdw 2. BLYP 1.20, PBE 0.75, BP86 1.05, B3LYP 1.05, Becke97-D 1.25 and TPSS 1.00.

Grimme's DFT-D3 is also available. Here the dispersion term has the following form:

$$E_{disp} = \sum_{ij} \sum_{n=6,8} s_n \frac{C_n^{ij}}{R_{ij}^n} \left(1 + 6(R_{ij}/(s_{r,n}R_0^{ij}))^- \alpha_n \right)^{-1}$$

This new dispersion correction covers elements through Z=94. $C_n^{ij}(n=6,8)$ are coordination and geometry dependent. Details about the functional form can be found in S. Grimme, J. Antony, S. Ehrlich, H. Krieg, J. Chem. Phys. 132, 154104 (2010). To use the Grimme DFT-D3 dispersion correction, use the option

 vdw 3 (s6 and alpha cannot be set manually). Functionals for which DFT-D3 is available in NWChem are BLYP, B3LYP, BP86, Becke97-D, PBE96, TPSS, PBE0, B2PLYP, BHLYP, TPSSH, PWB6K, B1B95, SSB-D, MPW1B95, MPWB1K, M05, M05-2X, M06L, M06, M06-2X, and M06HF

This capability is also supported for energy gradients and Hessian. Is possible to be deactivated with OFF.

NOSCF -- Non Self-Consistent Calculations

The noscf keyword allows one to calculate the non self-consistent energy for a set of input vectors. For example, the following input shows how a non self-consistent B3LYP energy can be calculated using a self-consistent set of vectors calculated at the Hartree-Fock level.

```
start h2o-noscf
```

geometry	units angstrom		
0	0.00000000	0.00000000	0.11726921
Н	0.75698224	0.00000000	-0.46907685
Н	-0.75698224	0.0000000	-0.46907685

end

```
basis spherical
 * library aug-cc-pvdz
end
dft
 xc hfexch
 vectors output hf.movecs
end
task dft energy
dft
 xc b3lyp
 vectors input hf.movecs
 noscf
end
task dft energy
```

XDM --Exchange-hole dipole moment dispersion model

```
XDM
[ a1 <real a1> ] [ a2 <real a2> ]
```

See details (including list of a1 and a2 parameters) in A. Otero-de-la-Roza and E. R. Johnson, J. Chem. Phys. 138, 204109 (2013) and the website http://gatsby.ucmerced.edu/ wiki/XDM ^[1]

```
geometry
```

0	-0.190010095135	-1.168397415155	0.925531922479
Н	-0.124425719598	-0.832776238160	1.818190662986
Н	-0.063897685990	-0.392575837594	0.364048725248
0	0.174717244879	1.084630474836	-0.860510672419
Н	-0.566281023931	1.301941006866	-1.427261487135
Н	0.935093179777	1.047335209207	-1.441842151158
end			
basis s	pherical		
* lib	rary aug-cc-pvdz		
end			

```
dft
direct
xc b3lyp
xdm al 0.6224 a2 1.7068
end
```

task dft optimize

Print Control

PRINT | | NOPRINT

The PRINT||NOPRINT options control the level of output in the DFT. Please see some examples using this directive in Sample input file. Known controllable print options are:

Name	Print Level	Description
"all vector symmetries"	high	symmetries of all molecular orbitals
"alpha partner info"	high	unpaired alpha orbital analysis
"common"	debug	dump of common blocks
"convergence"	default	convergence of SCF procedure
"coulomb fit"	high	fitting electronic charge density
"dft timings"	high	
"final vectors"	high	
"final vectors analysis"	high	print all orbital energies and orbitals
"final vector symmetries"	default	symmetries of final molecular orbitals
"information"	low	general information
"initial vectors"	high	
"intermediate energy info"	high	
"intermediate evals"	high	intermediate orbital energies
"intermediate fock matrix"	high	
"intermediate overlap"	high	overlaps between the alpha and beta sets
"intermediate S2"	high	values of S2
"intermediate vectors"	high	intermediate molecular orbitals
"interm vector symm"	high	symmetries of intermediate orbitals
"io info"	debug	reading from and writing to disk
"kinetic_energy"	high	kinetic energy
"mulliken ao"	high	mulliken atomic orbital population
"multipole"	default	moments of alpha, beta, and nuclear charge densities
"parameters"	default	input parameters
"quadrature"	high	numerical quadrature
"schwarz"	high	integral screening info & stats at completion

DFT Print Control Specifications

"screening parameters"	high
"semi-direct info"	default

integral accuracies semi direct algorithm

Spin-Orbit Density Functional Theory (SODFT)

The spin-orbit DFT module (SODFT) in the NWChem code allows for the variational treatment of the one-electron spin-orbit operator within the DFT framework. The implementation requires the definition of an effective core potential (ECP) and a matching spin-orbit potential (SO). The current implementation does NOT use symmetry.

The actual SODFT calculation will be performed when the input module encounters the TASK directive (TASK).

TASK SODFT

Input parameters are the same as for the DFT. Some of the DFT options are not available in the SODFT. These are max_ovl and sic.

Besides using the standard ECP and basis sets, see Effective Core Potentials for details, one also has to specify a spin-orbit (SO) potential. The input specification for the SO potential can be found in Effective Core Potentials. At this time we have not included any spin-orbit potentials in the basis set library.

Note: One should use a combination of ECP and SO potentials that were designed for the same size core, i.e. don't use a small core ECP potential with a large core SO potential (it will produce erroneous results).

Also, note that charge fitting basis sets will not work with spin-orbit calculations.

The following is an example of a calculation of UO_{2} :

```
start uo2 sodft
echo
Memory 32 mw
charge 2
geometry noautoz noautosym units angstrom
 U
       0.00000
                     0.00000
                                  0.00000
 0
       0.00000
                     0.00000
                                  1.68000
                     0.00000
 0
       0.00000
                                 -1.68000
end
basis "ao basis" cartesian print
U
     S
       12.12525300
                             0.02192100
        7.16154500
                            -0.22516000
        4.77483600
                             0.56029900
        2.01169300
                           -1.07120900
U
     S
        0.58685200
                             1.00000000
U
     S
        0.27911500
                             1.00000000
U
     S
                             1.00000000
        0.06337200
```

U	S		
		0.02561100	1.00000000
U	Р		
		17.25477000	0.00139800
		7.73535600	-0.03334600
		5.15587800	0.11057800
		2.24167000	-0.31726800
U	Р		
		0.58185800	1.00000000
U	Р		
		0.26790800	1.00000000
U	Р		
		0.08344200	1.00000000
U	Р		
		0.03213000	1.00000000
U	D		
-		4.84107000	0.00573100
		2.16016200	-0.05723600
		0.57563000	0.23882800
п	Л	0.37303000	0.23002000
0	U	0 27813600	1 0000000
п	Л	0.27013000	1.0000000
U	U	0 12/87000	1 0000000
	Л	0.12407900	1.0000000
U	U	0 05154900	1 0000000
	E	0.03134800	1.00000000
U	Г	2 42644100	0 25501100
		2.43044100	0.35501100
		1.14400200	0.40004000
	г	0.52909500	0.3040/900
U	Г	0 24050600	1 0000000
	-	0.24059000	1.0000000
U	F	0 10106700	1 0000000
•	~	0.10186/00	1.0000000
0	5	47 10551000	0.01440000
		47.10551800	-0.01440800
		5.91134600	0.12956800
	_	0.97648300	-0.56311800
0	S		
		0.29607000	1.00000000
0	Р		
		16.69221900	0.04485600
		3.90070200	0.22261300
		1.07825300	0.50018800
0	Р		
		0.28418900	1.00000000
0	Р		
		0.07020000	1.0000000

ECP U nelec 78 U s 2 4.06365300 112.92010300 2 0.88656700 3.68997100 2 0.88656700 3.68997100 U p 2 3.98618100 118.75801600 2 2.00016000 15.07722800 2 0.96084100 0.55672000 U d 2 4.14797200 60.85589200 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 0.99564100 1.38948000 U f 2 3.99893800 49.92403500 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 0 s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.98838 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	END)			
U nelec 78 U s 2 4.06365300 112.92010300 2 1.88399500 15.64750000 2 0.88656700 -3.68997100 U p 2 3.98618100 118.75801600 2 2.00016000 15.07722800 2 0.96084100 0.55672000 U d 2 4.14797200 60.85589200 2 2.23456300 29.28004700 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	ECF	C			
U s 2 4.06365300 112.92010300 2 1.88399500 15.64750000 2 0.88656700 -3.68997100 U p 2 3.98618100 118.75801600 2 2.00016000 15.07722800 2 0.96084100 0.55672000 U d 2 4.14797200 60.85589200 2 2.23456300 29.28004700 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	U	nel	ec 78		
2 4.06365300 112.92010300 2 1.88399500 15.64750000 2 0.88656700 -3.68997100 U p 2 3.98618100 118.75801600 2 2.00016000 15.07722800 2 0.96084100 0.55672000 U d 2 4.14797200 60.85589200 2 2.23456300 29.28004700 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	U	S			
2 1.88399500 15.64750000 2 0.88656700 -3.68997100 U p 2 3.98618100 118.75801600 2 0.96084100 0.55672000 U d 2 4.14797200 60.85589200 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	4	.06365300	112.92010300
2 0.88656700 -3.68997100 U p 2 3.98618100 118.75801600 2 0.96084100 0.55672000 U d 2 4.14797200 60.85589200 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 0.99564100 1.38948000 U f 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	1	.88399500	15.64750000
U p 2 3.98618100 118.75801600 2 2.00016000 15.07722800 2 0.96084100 0.55672000 U d 2 4.14797200 60.85589200 2 2.23456300 29.28004700 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	0	.88656700	-3.68997100
2 3.98618100 118.75801600 2 2.00016000 15.07722800 2 0.96084100 0.55672000 U d 2 4.14797200 60.85589200 2 2.23456300 29.28004700 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	U	р			
2 2.00016000 15.07722800 2 0.96084100 0.55672000 U d 2 4.14797200 60.85589200 2 2.23456300 29.28004700 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	3	.98618100	118.75801600
2 0.96084100 0.55672000 U d 2 4.14797200 60.85589200 2 2.23456300 29.28004700 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	2	.00016000	15.07722800
U d 2 4.14797200 60.85589200 2 2.23456300 29.28004700 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	0	.96084100	0.55672000
2 4.14797200 60.85589200 2 2.23456300 29.28004700 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	U	d			
2 2.23456300 29.28004700 2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	4	.14797200	60.85589200
2 0.91369500 4.99802900 U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	2	.23456300	29.28004700
U f 2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	0	.91369500	4.99802900
2 3.99893800 49.92403500 2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	U	f			
2 1.99884000 -24.67404200 2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	3	.99893800	49.92403500
2 0.99564100 1.38948000 U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 O nelec 2 O s 2 10.44567000 50.77106900 O p 2 18.04517400 -4.90355100 O d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	1	.99884000	-24.67404200
U g 2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 0 nelec 2 0 s 2 10.44567000 50.77106900 0 p 2 18.04517400 -4.90355100 0 d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	0	.99564100	1.38948000
2 3.81742200 -36.04097700 2 0.26250100 -0.09051100 0 nelec 2 0 s 2 10.44567000 50.77106900 0 p 2 18.04517400 -4.90355100 0 d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	U	g			
2 0.26250100 -0.09051100 0 nelec 2 0 s 2 10.44567000 50.77106900 0 p 2 18.04517400 -4.90355100 0 d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	3	.81742200	-36.04097700
0 nelec 2 0 s 2 10.44567000 50.77106900 0 p 2 18.04517400 -4.90355100 0 d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	0	.26250100	-0.09051100
0 s 2 10.44567000 50.77106900 0 p 2 18.04517400 -4.90355100 0 d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	0	nel	ec 2		
2 10.44567000 50.77106900 0 p 2 18.04517400 -4.90355100 0 d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	0	S			
0 p 2 18.04517400 -4.90355100 0 d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	10	.44567000	50.77106900
2 18.04517400 -4.90355100 0 d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	0	р			
0 d 2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	18	.04517400	-4.90355100
2 8.16479800 -3.31212400 END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	0	d			
END SO U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch		2	8	.16479800	-3.31212400
S0 U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	END)			
U p 2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	S0				
2 3.986181 1.816350 2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	U	р			
2 2.000160 11.543940 2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	2		3.986181	1.816350	
2 0.960841 0.794644 U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	2		2.000160	11.543940	
U d 2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	2	(0.960841	0.794644	
2 4.147972 0.353683 2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	U	d			
2 2.234563 3.499282 2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	2		4.147972	0.353683	
2 0.913695 0.514635 U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	2		2.234563	3.499282	
U f 2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	2	(0.913695	0.514635	
2 3.998938 4.744214 2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	U	f			
2 1.998840 -5.211731 2 0.995641 1.867860 END dft mult 1 xc hfexch	2		3.998938	4.744214	
2 0.995641 1.867860 END dft mult 1 xc hfexch	2		1.998840	-5.211731	
END dft mult 1 xc hfexch	2		0.995641	1.867860	
dft mult 1 xc hfexch	END)			
mult 1 xc hfexch	dft	t			
xc hfexch	mu	ult	1		
	X	c hf	exch		

```
odft
grid fine
convergence energy 1.000000E-06
convergence density 1.000000E-05
convergence gradient 1E-05
iterations 100
mulliken
end
```

 $task \ sodft$

References

[1] http://gatsby.ucmerced.edu/wiki/XDM

Release65:Excited-State Calculations

_NOTITLE__

CIS, TDHF, TDDFT

Overview

NWChem supports a spectrum of single excitation theories for vertical excitation energy calculations, namely, configuration interaction singles (CIS), time-dependent Hartree-Fock (TDHF or also known as random-phase approximation RPA), time-dependent density functional theory (TDDFT),[ref] and Tamm-Dancoff approximation to TDDFT. These methods are implemented in a single framework that invokes Davidson's trial vector algorithm (or its modification for a non-Hermitian eigenvalue problem). The capabilities of the module are summarized as follows:

- Vertical excitation energies,
- Spin-restricted singlet and triplet excited states for closed-shell systems,
- Spin-unrestricted doublet, etc., excited states for open-shell systems,
- Tamm-Dancoff and full time-dependent linear response theories,
- Davidson's trial vector algorithm,
- Symmetry (irreducible representation) characterization and specification,
- Spin multiplicity characterization and specification,
- Transition moments and oscillator strengths,
- Analytical first derivatives of vertical excitation energies with a selected set of exchange-correlation functionals (see TDDFT gradients documentation for further information),
- Numerical second derivatives of vertical excitation energies,
- Disk-based and fully incore algorithms,
- Multiple and single trial-vector processing algorithms,
- Frozen core and virtual approximation,
- Asymptotically correct exchange-correlation potential by van Leeuwen and Baerends (R. van Leeuwen and E. J. Baerends, Phys. Rev. A 49, 2421 (1994)),

- Asymptotic correction by Casida and Salahub (M. E. Casida, C. Jamorski, K. C. Casida, and D. R. Salahub, J. Chem. Phys. 108, 4439 (1998)),
- Asymptotic correction by Hirata, Zhan, Aprà, Windus, and Dixon (S. Hirata, C.-G. Zhan, E. Aprà, T. L. Windus, and D. A. Dixon, J. Phys. Chem. A 107, 10154 (2003)).

These are very effective way to rectify the shortcomings of TDDFT when applied to Rydberg excited states (see below).

Performance of CIS, TDHF, and TDDFT methods

The accuracy of CIS and TDHF for excitation energies of closed-shell systems are comparable to each other, and are normally considered a zeroth-order description of the excitation process. These methods are particularly well balanced in describing Rydberg excited states, in contrast to TDDFT. However, for open-shell systems, the errors in the CIS and TDHF excitation energies are often excessive, primarily due to the multi-determinantal character of the ground and excited state wave functions of open-shell systems in a HF reference.[ref] The scaling of the computational cost of a CIS or TDHF calculation per state with respect to the system size is the same as that for a HF calculation for the ground state, since the critical step of the both methods are the Fock build, namely, the contraction of two-electron integrals with density matrices. It is usually necessary to include two sets of diffuse exponents in the basis set to properly account for the diffuse Rydberg excited states of neutral species.

The accuracy of TDDFT may vary depending on the exchange-correlation functional. In general, the exchange-correlation functionals that are widely used today and are implemented in NWChem work well for low-lying valence excited states. However, for high-lying diffuse excited states and Rydberg excited states in particular, TDDFT employing these conventional functionals breaks down and the excitation energies are substantially underestimated. This is because of the fact that the exchange-correlation potentials generated from these functionals decay too rapidly (exponentially) as opposed to the slow -1/r asymptotic decay of the true potential. A rough but useful index is the negative of the highest occupied KS orbital energy; when the calculated excitation energies become close to this threshold, these numbers are most likely underestimated relative to experimental results. It appears that TDDFT provides a better-balanced description of radical excited states. This may be traced to the fact that, in DFT, the ground state wave function is represented well as a single KS determinant, with less multi-determinantal character and less spin contamination, and hence the excitation thereof is described well as a simple one electron transition. The computational cost per state of TDDFT calculations scales as the same as the ground state DFT calculations, although the prefactor of the scaling may be much greater in the former.

A very simple and effective way to rectify the TDDFT's failure for Rydberg excited states has been proposed by Tozer and Handy (D. J. Tozer and N. C. Handy, J. Chem. Phys. 109, 10180 (1998)) and by Casida and Salahub (see previous reference). They proposed to splice a -1/r asymptotic tail to an exchange-correlation potential that does not have the correct asymptotic behavior. Because the approximate exchange-correlation potentials are too shallow everywhere, a negative constant must be added to them before they can be spliced to the -1/r tail seamlessly in a region that is not sensitive to chemical effects or to the long-range behavior. The negative constant or the shift is usually taken to be the difference of the HOMO energy from the true ionization potential, which can be obtained either from

experiment or from a Δ SCF calculation. Recently, we proposed a new, expedient, and self-contained asymptotic correction that does not require an ionization potential (or shift) as an external parameter from a separate calculation. In this scheme, the shift is computed by a semi-empirical formula proposed by Zhan, Nichols, and Dixon (C.-G. Zhan, J. A. Nichols, and D. A. Dixon, J. Phys. Chem. A 107, 4184 (2003)). Both Casida-Salahub scheme and this new asymptotic correction scheme give considerably improved (Koopmans type) ionization potentials and Rydberg excitation energies. The latter, however, supply the shift by itself unlike to former.

Input syntax

The module is called TDDFT as TDDFT employing a hybrid HF-DFT functional encompasses all of the above-mentioned methods implemented. To use this module, one needs to specify TDDFT on the task directive, e.g.,

TASK TDDFT ENERGY

for a single-point excitation energy calculation, and

TASK TDDFT OPTIMIZE

for an excited-state geometry optimization (and perhaps an adiabatic excitation energy calculation), and

TASK TDDFT FREQUENCIES

for an excited-state vibrational frequency calculation. The TDDFT module first invokes DFT module for a ground-state calculation (regardless of whether the calculations uses a HF reference as in CIS or TDHF or a DFT functional), and hence there is no need to perform a separate ground-state DFT calculation prior to calling a TDDFT task. When no second argument of the task directive is given, a single-point excitation energy calculation will be assumed. For geometry optimizations, it is usually necessary to specify the target excited state and its irreducible representation it belongs to. See the subsections TARGET and TARGETSYM for more detail.

Individual parameters and keywords may be supplied in the TDDFT input block. The syntax is:

```
TDDFT
```

```
[(CIS||RPA) default RPA]
[NR00TS <integer nroots default 1>]
[MAXVECS <integer maxvecs default 1000>]
[(SINGLET||NOSINGLET) default SINGLET]
[(TRIPLET||NOTRIPLET) default TRIPLET]
[THRESH <double thresh default 1e-4>]
[MAXITER <integer maxiter default 100>]
[TARGET <integer target default 1>]
[TARGETSYM <character targetsym default 'none'>]
[SYMMETRY]
[ECUT] <-cutoff energy>
[EWIN] <-lower cutoff energy> <-higher cutoff energy>
[alpha] <integer lower orbital> <integer upper orbital>
```

```
[beta] <integer lower orbital> <integer upper orbital>
[CIVECS]
[GRAD, END]
[CDSPECTRUM]
[VELOCITY]
[ALGORITHM <integer algorithm default 0>]
[FREEZE |
<integer nfzc default 0>)] \
        [virtual <integer nfzv default 0>
[PRINT (none||low||medium||high||debug)
        <string list_of_names ...>]
END
```

The user can also specify the reference wave function in the DFT input block (even when CIS and TDHF calculations are requested). See the section of Sample input and output for more details.

Since each keyword has a default value, a minimal input file will be

```
GEOMETRY
Be 0.0 0.0 0.0
END
BASIS
Be library 6-31G**
END
TASK TDDFT ENERGY
```

Note that the keyword for the asymptotic correction must be given in the DFT input block, since all the effects of the correction (and also changes in the computer program) occur in the SCF calculation stage. See DFT (keyword CS00 and LB94) for details.

Keywords of TDDFT input block

CIS and RPA --the Tamm-Dancoff approximation

These keywords toggle the Tamm-Dancoff approximation. CIS means that the Tamm-Dancoff approximation is used and the CIS or Tamm-Dancoff TDDFT calculation is requested. RPA, which is the default, requests TDHF (RPA) or TDDFT calculation.

The performance of CIS (Tamm-Dancoff TDDFT) and RPA (TDDFT) are comparable in accuracy. However, the computational cost is slightly greater in the latter due to the fact that the latter involves a non-Hermitian eigenvalue problem and requires left and right eigenvectors while the former needs just one set of eigenvectors of a Hermitian eigenvalue problem. The latter has much greater chance of aborting the calculation due to triplet near instability or other instability problems.

NROOTS -- the number of excited states

One can specify the number of excited state roots to be determined. The default value is 1. It is advised that the users request several more roots than actually needed, since owing to the nature of the trial vector algorithm, some low-lying roots can be missed when they do not have sufficient overlap with the initial guess vectors.

MAXVECS --the subspace size

This keyword limits the subspace size of Davidson's algorithm; in other words, it is the maximum number of trial vectors that the calculation is allowed to hold. Typically, 10 to 20 trial vectors are needed for each excited state root to be converged. However, it need not exceed the product of the number of occupied orbitals and the number of virtual orbitals. The default value is 1000.

SINGLET and NOSINGLET --singlet excited states

SINGLET (NOSINGLET) requests (suppresses) the calculation of singlet excited states when the reference wave function is closed shell. The default is SINGLET.

TRIPLET and NOTRIPLET --triplet excited states

TRIPLET (NOTRIPLET) requests (suppresses) the calculation of triplet excited states when the reference wave function is closed shell. The default is TRIPLET.

THRESH --the convergence threshold of Davidson iteration

This keyword specifies the convergence threshold of Davidson's iterative algorithm to solve a matrix eigenvalue problem. The threshold refers to the norm of residual, namely, the difference between the left-hand side and right-hand side of the matrix eigenvalue equation with the current solution vector. With the default value of 1e-4, the excitation energies are usually converged to 1e-5 hartree.

MAXITER -- the maximum number of Davidson iteration

It typically takes 10-30 iterations for the Davidson algorithm to get converged results. The default value is 100.

TARGET and TARGETSYM--the target root and its symmetry

At the moment, excited-state first geometry derivatives can be calculated analytically for a set of functionals, while excited-state second geometry derivatives are obtained by numerical differentiation. These keywords may be used to specify which excited state root is being used for the geometrical derivative calculation. For instance, when TARGET 3 and TARGETSYM a1g are included in the input block, the total energy (ground state energy plus excitation energy) of the third lowest excited state root (excluding the ground state) transforming as the irreducible representation a1g will be passed to the module which performs the derivative calculations. The default values of these keywords are 1 and none, respectively.

The keyword TARGETSYM is essential in excited state geometry optimization, since it is very common that the order of excited states changes due to the geometry changes in the course of optimization. Without specifying the TARGETSYM, the optimizer could (and would

likely) be optimizing the geometry of an excited state that is different from the one the user had intended to optimize at the starting geometry. On the other hand, in the frequency calculations, TARGETSYM must be none, since the finite displacements given in the course of frequency calculations will lift the spatial symmetry of the equilibrium geometry. When these finite displacements can alter the order of excited states including the target state, the frequency calculation is not be feasible.

SYMMETRY -- restricting the excited state symmetry

By adding this keyword to the input block, the user can request the module to generate the initial guess vectors transforming as the same irreducible representation as TARGETSYM. This causes the final excited state roots be (exclusively) dominated by those with the specified irreducible representation. This may be useful, when the user is interested in just the optically allowed transitions, or in the geometry optimization of an excited state root with a particular irreducible representation. By default, this option is not set. TARGETSYM must be specified when SYMMETRY is invoked.

ECUT --energy cutoff

This keyword enables restricted excitation window TDDFT (REW-TDDFT). This is an approach best suited for core excitations. By specifying this keyword only excitations from occupied states below the energy cutoff will be considered.

EWIN --energy window

This keyword enables a restricted energy window between a lower energy cutoff and a higher energy cutoff. For example, ewin -20.0 - 10.0 will only consider excitations within the specfied energy window

Alpha, Beta --alpha, beta orbital windows

Orbital windows can be specified using the following keywords:

- alpha 1 4
- beta 2 5

Here alpha excitations will be considered from orbitals 1 through 4 depending on the number of roots requested and beta excitations will be considered from orbitals 2 through 5 depending on the number of roots requested.

CIVECS --CI vectors

This keyword will result in the CI vectors being written out. By default this is off. Please note this can be a very large file, so avoid turning on this keyword if you are calculating a very large number of roots. CI vectors are needed for excited-state gradient and transition density calculations.

GRAD --TDDFT gradients

Analytical TDDFT gradients can be calculated by specifying a grad block within the main TDDFT block

For example, the following will perform a TDDFT optimization on the first singlet excited state (S1). Note that the civecs keyword must be specified. To perform a single TDDFT

gradient, replace the optimize keyword with gradient in the task line. A complete TDDFT optimization input example is given the Sample Inputs section. A TDDFT gradients calculation allows one to calculate the excited state density of a specific excited state. This is written to a file with the dmat suffix.

```
tddft
nroots 2
algorithm 1
notriplet
target 1
targetsym a
civecs
grad
root 1
end
end
task tddft optimize
```

At the moment the following exchange-correlation functionals are supported with TDDFT gradients

```
LDA, BP86, PBE, BLYP, B3LYP, PBE0, BHLYP, CAM-B3LYP, LC-PBE, LC-PBE0, BNL, LC-wPBE, LC-wPBEh, LC-BLYP
```

CDSpectrum --optical rotation calculations

Perform optical rotation calculations.

VELOCITY --velocity gauge

Perform CD spectrum calculations with the velocity gauge.

ALGORITHM --algorithms for tensor contractions

There are four distinct algorithms to choose from, and the default value of 0 (optimal) means that the program makes an optimal choice from the four algorithms on the basis of available memory. In the order of decreasing memory requirement, the four algorithms are:

- ALGORITHM 1 : Incore, multiple tensor contraction,
- ALGORITHM 2 : Incore, single tensor contraction,
- ALGORITHM 3 : Disk-based, multiple tensor contraction,
- ALGORITHM 4 : Disk-based, single tensor contraction.

The incore algorithm stores all the trial and product vectors in memory across different nodes with the GA, and often decreases the MAXITER value to accommodate them. The disk-based algorithm stores the vectors on disks across different nodes with the DRA, and retrieves each vector one at a time when it is needed. The multiple and single tensor contraction refers to whether just one or more than one trial vectors are contracted with integrals. The multiple tensor contraction algorithm is particularly effective (in terms of speed) for CIS and TDHF, since the number of the direct evaluations of two-electron integrals is diminished substantially.
FREEZE --the frozen core/virtual approximation

Some of the lowest-lying core orbitals and/or some of the highest-lying virtual orbitals may be excluded in the CIS, TDHF, and TDDFT calculations by this keyword (this does not affect the ground state HF or DFT calculation). No orbitals are frozen by default. To exclude the atom-like core regions altogether, one may request

FREEZE atomic

To specify the number of lowest-lying occupied orbitals be excluded, one may use

```
FREEZE 10
```

which causes 10 lowest-lying occupied orbitals excluded. This is equivalent to writing

FREEZE core 10

To freeze the highest virtual orbitals, use the virtual keyword. For instance, to freeze the top 5 virtuals

FREEZE virtual 5

PRINT -- the verbosity

This keyword changes the level of output verbosity. One may also request some particular items in the table below.

Printable items in the TDDFT modules and their default print levels.

Item	Print Level	Description
"timings"	high	CPU and wall times spent in each step
"trial vectors"	high	Trial CI vectors
"initial guess"	debug	Initial guess CI vectors
"general information"	default	General information
"xc information"	default	HF/DFT information
"memory information"	default	Memory information
"convergence"	debug	Convergence
"subspace"	debug	Subspace representation of CI matrices
"transform"	debug	MO to AO and AO to MO transformation of CI vectors
"diagonalization"	debug	Diagonalization of CI matrices
"iteration"	default	Davidson iteration update
"contract"	debug	Integral transition density contraction
"ground state"	default	Final result for ground state
"excited state"	low	Final result for target excited state

Sample input

The following is a sample input for a spin-restricted TDDFT calculation of singlet excitation energies for the water molecule at the $B3LYP/6-31G^*$.

```
START h2o
TITLE "B3LYP/6-31G* H20"
GEOMETRY
 0
       0.00000000
                       0.00000000
                                      0.12982363
 Н
       0.75933475
                       0.00000000
                                     -0.46621158
 н
      -0.75933475
                       0.0000000
                                     -0.46621158
END
BASIS
* library 6-31G*
END
DFT
XC B3LYP
END
TDDFT
 RPA
 NROOTS 20
END
TASK TDDFT ENERGY
```

To perform a spin-unrestricted TDHF/aug-cc-pVDZ calculation for the CO+ radical,

```
START co
TITLE "TDHF/aug-cc-pVDZ CO+"
CHARGE 1
GEOMETRY
 C 0.0 0.0 0.0
 0 1.5
        0.0 0.0
END
BASIS
 * library aug-cc-pVDZ
END
DFT
XC HFexch
MULT 2
END
TDDFT
 RPA
 NROOTS 5
END
TASK TDDFT ENERGY
```

A geometry optimization followed by a frequency calculation for an excited state is carried out for BF at the CIS/ $6-31G^*$ level in the following sample input.

```
START bf
TITLE "CIS/6-31G* BF optimization frequencies"
GEOMETRY
 B 0.0 0.0 0.0
 F 0.0 0.0 1.2
END
BASIS
* library 6-31G*
END
DFT
XC HFexch
END
TDDFT
 CIS
 NROOTS 3
 NOTRIPLET
 TARGET 1
END
TASK TDDFT OPTIMIZE
TASK TDDFT FREQUENCIES
```

TDDFT with an asymptotically corrected SVWN exchange-correlation potential. Casida-Salahub scheme has been used with the shift value of 0.1837 a.u. supplied as an input parameter.

START tddft_ac_co GEOMETRY 0 0.0 0.0 0.0000 C 0.0 0.0 1.1283 END BASIS SPHERICAL C library aug-cc-pVDZ 0 library aug-cc-pVDZ END DFT XC Slater VWN_5 CS00 0.1837 END TDDFT NROOTS 12 END TASK TDDFT ENERGY

TDDFT with an asymptotically corrected B3LYP exchange-correlation potential. Hirata-Zhan-Apra-Windus-Dixon scheme has been used (this is only meaningful with B3LYP functional).

START tddft_ac_co
GEOMETRY

```
0 0.0 0.0 0.0000
C 0.0 0.0 1.1283
END
BASIS SPHERICAL
C library aug-cc-pVDZ
0 library aug-cc-pVDZ
END
DFT
XC B3LYP
CS00
END
TDDFT
NR00TS 12
END
TASK TDDFT ENERGY
```

TDDFT for core states. The following example illustrates the usage of an energy cutoff and energy and orbital windows.

```
echo
start h2o_core
memory 1000 mb
geometry units au noautosym noautoz
 0 0.00000000
                  0.00000000
                                0.22170860
 H 0.0000000
                 1.43758081 -0.88575430
 H 0.00000000 -1.43758081
                                -0.88575430
end
basis
0 library 6-31g*
H library 6-31g*
end
dft
xc beckehandh
print "final vector analysis"
end
task dft
tddft
ecut -10
nroots 5
notriplet
thresh 1d-03
end
task tddft
tddft
ewin -20.0 -10.0
cis
nroots 5
notriplet
```

```
thresh 1d-03
end
task tddft
dft
odft
mult 1
xc beckehandh
print "final vector analysis"
end
task dft
tddft
alpha 1 1
beta 1 1
cis
nroots 10
notriplet
thresh 1d-03
end
task tddft
```

TDDFT optimization with LDA of Pyridine with the 6-31G basis

```
echo
start tddftgrad_pyridine_opt
title "TDDFT/LDA geometry optimization of Pyridine with 6-31G"
geometry nocenter
 Ν
      0.00000000
                     0.0000000
                                   1.41599295
 С
       0.0000000
                  -1.15372936
                                   0.72067272
 С
       0.00000000
                    1.15372936
                                   0.72067272
 С
       0.00000000
                  -1.20168790
                                  -0.67391011
 С
       0.00000000
                    1.20168790
                                  -0.67391011
 С
       0.00000000
                     0.00000000
                                  -1.38406147
 Н
       0.0000000
                  -2.07614628
                                   1.31521089
 Н
       0.0000000
                     2.07614628
                                   1.31521089
 н
       0.0000000
                     2.16719803 -1.19243296
       0.00000000
 н
                  -2.16719803
                                  -1.19243296
 Н
       0.00000000
                     0.00000000
                                  -2.48042299
 symmetry cl
end
basis spherical
* library "6-31G"
end
driver
  clear
  maxiter 100
end
dft
  iterations 500
```

```
xc slater 1.0 vwn_5 1.0
 grid xfine
 grid euler
 direct
end
tddft
  nroots 2
 algorithm 1
 notriplet
 target 1
 targetsym a
 civecs
 grad
    root 1
 end
end
task tddft optimize
```

TDDFT calculation followed by a calculation of the transition density for a specific excited state using the DPLOT block

```
echo
start h2o-td
title h2o-td
memory total 800 stack 400 heap 50 global 350 mb
charge 0
geometry units au noautoz nocenter
symmetry group c1
0
     0.0000000000000
                           0.00000000000000
                                                 0.00000000000000
Н
     0.47043554760291
                          1.35028113274600
                                                 1.06035416576826
                      -0.23369304784300
Н
    -1.74335410533480
                                                 0.27360785442967
end
basis "ao basis" print
Н
     S
   13.0107010
                           0.19682158E-01
    1.9622572
                           0.13796524
    0.44453796
                           0.47831935
Н
     S
    0.12194962
                           1.0000000
    Р
Н
    0.8000000
                           1.0000000
0
     S
 2266.1767785
                          -0.53431809926E-02
  340.87010191
                          -0.39890039230E-01
   77.363135167
                          -0.17853911985
   21.479644940
                          -0.46427684959
                          -0.44309745172
    6.6589433124
     S
0
```

```
0.80975975668
                           1.0000000
0
    S
                           1.0000000
    0.25530772234
    Р
0
   17.721504317
                           0.43394573193E-01
    3.8635505440
                           0.23094120765
    1.0480920883
                           0.51375311064
0
    Р
    0.27641544411
                    1.0000000
0
    D
    1.2000000
                       1.0000000
end
dft
xc bhlyp
grid fine
direct
convergence energy 1d-5
end
tddft
rpa
nroots 5
thresh 1d-5
singlet
notriplet
civecs
end
task tddft energy
dplot
civecs h2o-td.civecs_singlet
root 2
LimitXYZ
 -3.74335 2.47044 50
 -2.23369 3.35028 50
 -2 3.06035 50
  gaussian
  output root-2.cube
end
```

task dplot

Release65:RT-TDDFT

__NOTITLE__

Real-time TDDFT

Overview

Real-time time-dependent density functional theory (RT-TDDFT) is a DFT-based approach to electronic excited states based on integrating the time-dependent Kohn-Sham (TDKS) equations in time. The theoretical underpinnings, strengths, and limitations are similar to traditional linear-response (LR) TDDFT methods, but instead of a frequency domain solution to the TDKS equations, RT-TDDFT yields a full time-resolved, potentially non-linear solution. Real-time simulations can be used to compute not only spectroscopic properties (e.g., absorption spectra, polarizabilites, etc), but also the time and space-resolved electronic response to arbitrary external stimuli (e.g., electron charge dynamics after laser excitation). For theoretical and computational details, please refer to the following paper:

 K. Lopata, N. Govind, "Modeling Fast Electron Dynamics with Real-Time Time-Dependent Density Functional Theory: Application to Small Molecules and Chromophores", J. Chem. Theory Comput., 7, 1344 (2011)

This functionality is built on the Gaussian basis set DFT module, and will work for closed-shell (spin-restricted) and open-shell (spin unrestricted) calculations with essentially any combination of basis set and exchange-correlation functional in NWChem. The current implementation assumes frozen nuclei (Born-Oppenheimer approximation).

In a nutshell, running a RT-TDDFT calculation takes the following form:

- 1. Compute ground state density matrix with DFT module
- 2. Propagate density matrix using RT-TDDFT
- 3. Post-process resulting time-dependent observables (e.g., dipole moment)

Units

Unless specified otherwise, all inputs and outputs are in **atomic units**. Some useful conversions are:

Quantity	Conversion
Time	1 au = 0.02419 fs
Length	1 au = 0.5292 A
Energy	1 au = 27.2114 eV
Electric field	1 au = 514.2 V/nm
Dipole moment	1 au = 2.542 D

Syntax

The charge, geometry, basis set, and DFT options are all specified as normal, using their respective syntax. Real-time TDDFT parameters are supplied in the RT_TDDFT block (note, nothing is case-sensitive), with all possible options summarized below, and each discussed in detail afterwards.

```
RT TDDFT
  [TMAX <double default 1000>]
  [DT <double default 0.1>]
  [TAG <string default "<rt tddft>: "]
  [LOAD (scf || vectors <string>)]
  [NCHECKS <integer default 10>]
  [NPRINTS (* || <integer>)]
  [NRESTARTS (* || <integer>)]
  [TOLERANCES (zero <double default 1e-8> || series <double
default le-10> || interpol <double default le-7>)]
  [PROPAGATOR (euler || rk4 || magnus) default magnus]
  [EXP (diag || pseries)]
  [PROF]
  [NOPROP]
  [STATIC]
  [PRINT (*, dipole, quadrupole, field, moocc, field, energy, cputime,
charge, convergence, s2)]
  [EXCITE <string geomname> with <string fieldname>]
  [FIELD]
    . . .
  [END]
  [VISUALIZATION]
    . . .
  [END]
END
```

TMAX --Simulation time

This option specifies the maximum time (in au) to run the simulation before stopping, which must be a positive real number. In practice, you can just stop the simulation early, so in most cases it is simplest to just set this to a large value to ensure you capture all the important dynamics (see Hints and Tricks). For most valence excitations, for example, 1000 au is overkill so you might want to automatically stop at 500 au:

```
rt_tddft
...
tmax 500.0
...
end
```

DT --Time step

This specifies the electronic time step for time integration. A larger time step results in a faster simulation, but there are two issues which limit the size of the time step. First, the integration algorithm can become unstable and/or inaccurate for larger time steps, which depends on the integrator used. Very roughly speaking, the second order Magnus integrator should be reliable for time steps up to 0.2 au. Second, you must choose a time step small enough to capture the oscillations of interest, i.e., to resolve an excitation of energy ω , your time step needs to be smaller than π/ω , and typically a tenth of that for accuracy. For example, to capture high energy oscillations such as core-level excitations (e.g., $\omega = 50$ au) you might want a relative small time step:

rt_tddft ... dt 0.01 ... end

It is always good practice to check that your results are independent of time step.

TAG --Output label

This option sets a label for the output for convenient parsing (e.g., with "grep"). Every output line with time-dependent data will begin with this string (set to "<rt_tddft>: " by default). For example setting:

rt_tddft ... tag "nameofrun" ... end

will result in outputs that look like:

```
...
nameofrun 2.20000 -7.589146713114E+001 # Etot
...
```

NCHECKS --Number of run-time check points

This option takes an integer number (default 10), or "*" which means every step, which sets the total of number of run-time checkpoints, where various sanity checks are made such as symmetries, idempotency, traces, etc. These checks are not terribly efficient (e.g., involve re-building the TD Fock matrix) so excessive checking will slow down execution.

```
rt_tddft
...
nchecks 10
...
end
```

NPRINTS --Number of print points

This sets the number of print points, i.e., the total number of time-dependent observables (e.g., dipole, charge, energy) that are computed and printed. It either takes an integer number or "*" which means every time step (this is the default). Since there is no appreciable cost to computing and printing these quantities, there is usually no need to change this from "*".

```
rt_tddft
    ...
    nprints *
    ...
end
```

NRESTARTS --Number of restart checkpoints

This sets the number of run-time check points where the time-dependent complex density matrix is saved to file, allowing the simulation to be restarted) from that point. By default this is set to 0. There is no significant computational cost to restart checkpointing, but of course there is some disk I/O cost (which may become somewhat significant for larger systems). For example, in the following example there will be 100 restart points, which corresponds to 1 backup every 100 time steps.

```
rt_tddft
...
tmax 1000.0
dt 0.1
nrestarts 100
...
end
```

TOLERANCES --Controlling numerical tolerances

This option controls various numerical tolerances:

- zero: threshold for checks that quantities are zero, e.g., in symmetry checks (default 1e-8)
- series: numerical convergence for series, e.g., matrix exponentiation (default 1e-10)
- interpol: numerical convergence for interpolation, e.g., in Magnus propagator (default 1e-7)

Occasionally it is useful to loosen the interpolation tolerances if the Magnus interpolator requires an excessive amount of steps; usually this will not impact accuracy. For example, this sets the tolerances to their defaults with a looser interpolation tolerance:

```
rt_tddft
...
tolerances zero 1d-8 series 1d-10 interpol 1e-5
end
```

PROPAGATOR --Selecting the integrator method

This selects the propagtor (i.e., time integrator) method. Possible choices include "euler" for Euler integration (terrible, you should never use this), "rk4" for 4th order Runge-Kutta, and "magnus" for 2nd order Magnus with self-consistent interpolation. In virtually all cases Magnus is superior in terms of stability. Euler or rk4 are perhaps only useful for debugging or simplicity (e.g., for code development).

```
rt_tddft
    ...
    propagator magnus
    ...
end
```

EXP --Selecting the matrix exponentiation method

This selects the method for exponentiation matrices. For now this can either be "pseries" for a contractive power series or "diag" for diagonalization. In general the power series (default) is faster.

```
rt_tddft
    ...
    exp diag
    ...
end
```

PROF -- Run-time profiling

This turns on run-time profiling, which will display time spent in each component of the code (e.g., building components of the TD Fock matrix, properites, etc). This slows code down slightly and results in very verbose output.

rt_tddft ... prof ... end

NOPROP --Skipping propagation

This options causes the RT-TDDFT module skip propagation, i.e., to initialize and finalize. For now this is largely useful for skipping to visualization post-processing without having to re-run a simulation.

```
rt_tddft
...
noprop
...
end
```

STATIC --Force static Fock matrix

This option sets the static Fock matrix flag, meaning the time-dependent Fock matrix will not be recalculated at each time, but instead use the t=0 value. This will drastically increase the simulation speed since the bulk of the work is spent rebuilding the TD Fock matrix, but will give non-physical results. For example, using "static" to compute an absorption spectrum will result in excitations corresponding to the raw eigenvalue differences without electron-hole relaxation. This option has few uses besides dry-runs and debugging.

```
rt_tddft
...
static
...
end
```

PRINT --Selecting time-dependent quantities to be printed

This sets the various time-dependent properties that are to be computed and printed at each print point. Note that for many of these options, the values are computed and printed for each geometry specified in the input deck, not only the active one (i.e., the one set using "set geometry ..." in the input deck). Possible choices are:

- dipole: Dipole moment
- quadrupole: Quadrupole moment
- field: External (applied) electric field
- moocc: Molecular orbital occupations
- energy: Components of system energy (e.g., core, XC, total, etc)
- cputime: CPU time taken in simulation so far (useful for checking scaling)
- charge: Electronic charge (computed from density matrix, not from the XC grid)
- convergence: Convergence information (e.g., from Magnus)
- s2: <S2> value (openshell only)
- *: Print all quantities

The defaults correspond to:

```
rt_tddft
...
print dipole field energy convergence
...
end
```

FIELD --Sub-block for specifying external electric fields

This sub-block is used to specify external electric fields, each of which must be given a unique name. Numerous fields can be specified, but each will applied to the system only if an appropriate excitation rule is set. There are a few preset field types; others would have to be manually coded. Note the names are arbitrary, but chosen here to be descriptive:

```
field "kick"
  type delta
                  \# E(t=0) = max; E(t>0) = 0
  polarization x \# = x, y, z
                  # maximum value of electric field
  max 0.0001
  spin total
                  # = alpha, beta, total (only valid for open-shell)
end
field "gpulse"
  type gaussian
                 # Gaussian enveloped quasi-monochromatic pulse: E(t)
= \exp(-(t-t0)^2 / 2s^2)
  polarization x \# = x, y, z
  frequency 0.12 # frequency of laser pulse in au (e.g., 0.12 au =
3.27 eV)
  center 200.0
                  # center of Gaussian envelope (in au time)
  width 50.0
                  # width of Gaussian pulse (in au time)
  max 0.0001
                  # maximum value of electric field
                  # = alpha, beta, total (only valid for open-shell)
  spin total
end
field "hpulse"
  type hann
                  # sin^2 (Hann) enveloped quasi-monochromatic pulse
  polarization x \# = x, y, z
  frequency 0.12 # frequency of laser pulse in au (e.g., 0.12 au =
3.27 eV)
  center 200.0
                  # center of Hann envelope (in au time)
  width 50.0
                  # width of Hann pulse (in au time)
  max 0.0001
                  # maximum value of electric field
  spin total
                  # = alpha, beta, total (only valid for open-shell)
end
field "resonant"
  type cw
                  # monochromatic continuous wave
  frequency 0.12 # frequency of laser pulse in au (e.g., 0.12 au =
3.27 eV)
  polarization x \# = x, y, z
  max 0.0001
                  # maximum value of electric field
  spin total
                  # = alpha, beta, total (only valid for open-shell)
end
```

EXCITE --Excitation rules

This sets the rules for applying external fields to the system. It takes the form "excite <geom> with <field>", where <geom> is the name of a geometry fragment (defaults to "geometry" which is the default geometry name), and <field> is the name of a field structure. Assuming, for example, you have defined a field name "kick" this option takes the form (note that quotes are optional and shown for clarity):

```
rt_tddft
...
excite "geometry" with "kick"
...
end
```

VISUALIZATION -- Sub-block for controlling 3D visualization

This block is used to control visualization of the electronic charge density, which is typically used during a resonant excitation. This is a two stage process. During the propagation, a series of density matrices will be dumped to file (see options below). After propagation, if the "dplot" option is set, the code will read in options from a separate DPLOT block and convert the density matrix snapshots to a corresponding series of real-space charge density "cube" files.

```
visualization
tstart 0.0  # start visualization at this time
tend 100.0  # stop visualization at this time
treference 0.0  # subtract density matrix at this time (useful for
difference densities)
dplot  # post-process density matrices into cube files
after propagation
end
```

Worked Examples

Absorption spectrum of water

Here, we compute the 6-31G/TD-PBE0 absorption spectrum of gas-phase water using RT-TDDFT. In the weak-field limit, these results are essentially identical to those obtained via traditional linear-response TDDFT. Although it involves significantly more work do use RT-TDDFT in this case, for very large systems with many roots a real-time approach becomes advantageous computationally and also does not suffer from algorithm stability issues.

To compute the absorption, we find the ground state of the system and then subject it to three delta-function excitations (x,y,z), which simultaneously excites all electronic modes of that polarization. The three resulting dipole moments are then Fourier transformed to give the frequency-dependent linear polarizability, and thus the absorption spectrum. The full input deck is media:RT_TDDFT_h2o_abs.nw and the corresponding output is media:RT_TDDFT_h2o_abs.nwo.gz.

```
title "Water TD-PBE0 absorption spectrum"
echo
```

```
scratch_dir ./scratch
permanent dir ./perm
start water
##
## aug-cc-pvtz / pbe0 optimized
##
## Note: you are required to explicitly name the geometry
##
geometry "system" units angstroms nocenter noautoz noautosym
 0
       0.0000000
                    -0.00001441
                                   -0.34824012
 Н
      -0.00000000
                      0.76001092 -0.93285191
      0.00000000
 Н
                    -0.75999650 -0.93290797
end
## Note: We need to explicitly set the "active" geometry even though
there is only one geom.
set geometry "system"
## All DFT and basis parameters are inherited by the RT-TDDFT code
basis
* library 6-31G
end
dft
 xc pbe0
end
## Compute ground state of the system
task dft energy
##
## Now, we compute an x, y, and z kick simulation, which we give
separate "tags" for post-processing.
##
unset rt_tddft:*
rt tddft
 tmax 200.0
```

```
dt 0.2
 tag "kick_x"
 field "kick"
    type delta
    polarization x
    max 0.0001
 end
 excite "system" with "kick"
end
task dft rt_tddft
unset rt_tddft:*
rt tddft
 tmax 200.0
 dt 0.2
 tag "kick_y"
 field "kick"
    type delta
    polarization y
    max 0.0001
 end
 excite "system" with "kick"
end
task dft rt_tddft
unset rt_tddft:*
rt tddft
 tmax 200.0
 dt 0.2
 tag "kick z"
 field "kick"
   type delta
    polarization z
    max 0.0001
 end
 excite "system" with "kick"
end
task dft rt_tddft
```

After running the simulation, we extract the x-dipole moment for the x-kick and similarly for the y and z-kicks (see "contrib/parsers" directory for this script or download here: $media:RT_TDDFT_scripts.tgz$).

```
nw_rtparse.py -xdipole -px -tkick_x h2o_abs.nwo > x.dat
nw_rtparse.py -xdipole -py -tkick_y h2o_abs.nwo > y.dat
nw_rtparse.py -xdipole -pz -tkick_z h2o_abs.nwo > z.dat
```

Note, the syntax for extracting the x polarization for the x-kick, etc. Alternatively, we could grep and cut, or whatnot. This will give use the resulting time-dependent dipole moments:



Now, we need to take the Fourier transforms of these dipole moments to yield the the x,x element of the 3x3 linear polarizability tensor, and similarly for the y,y and z,z elements. Here I am using an FFT utility, although any discrete Fourier transform will do. To accelerate convergence of the FFT, I have damped the time signals by $\exp(-t/\tau)$ which results in Lorentzians with FWHM of $2/\tau$ and have also "zero padded" the data with 50000 points. This is not critical for extracting frequencies, but creates "cleaner" spectra, although care must be taken to damp sufficiently if padding to avoid artifacts (see small ripples around 23 eV in plot below). After Fourier transform, I "paste" the three files together to easily plot the absorption, which is constructed from the trace of the polarizability matrix, i.e., the sum of the imaginary parts of the FFTs of the dipole moments.

$$S(\omega) = \frac{4\pi\omega}{3c\kappa} \operatorname{Tr}[\operatorname{Im}\alpha(\omega)]$$

where c is the speed of light (137 in atomic units), κ is the kick electric field strength, and $\alpha(\omega)$ is the linear polarizability tensor computed from the Fourier transforms of the time-dependent dipole moments. For example,

```
fft1d -d50 -z -p50000 < x.dat | rotate_fft > xw.dat
fft1d -d50 -z -p50000 < y.dat | rotate_fft > yw.dat
fft1d -d50 -z -p50000 < z.dat | rotate_fft > zw.dat
paste xw.dat yw.dat zw.day > s.dat
```

Here, you can just use your favorite Fourier transform utility or analysis software, but for convenience there is also a simple GNU Octave fft1d.m utility in the "contrib/parsers" directory of the trunk or download here: media:RT_TDDFT_scripts.tgz Note, options are hardcoded at the moment, so the switches above are not correct instead edit the file and run (also it reads file rather than redirect from stdin). Assuming the FFT output takes the form (w, Re, Im, Abs), to plot using gnuplot we would do:

```
gnuplot> plot "s.dat" u ($1*27.2114):($1*($3+$7+$11))
```

where we have scaled by 27.2114 to output in eV instead of atomic units, and we have not properly scaled to get the absolute oscillator strengths (thus our magnitudes are in "arbitrary units"). The real-time spectrum is shown below, along with the corresponding

linear-response TDDFT excitations are shown in orange for comparison. Since we are in the weak field regime, the two are identical. Note the oscillator strengths are arbitrary and scaled, if not scaled the area under each RT-TDDFT curve should integrate to the linear response oscillator strength.



Resonant ultraviolet excitation of water

In this example we compute the time-dependent electron response to а quasi-monochromatic laser pulse tuned to a particular transition. We will use the results of the previous example (6-31G/PBE0 gas-phase water). First, we consider the absorption spectrum (computed previously) but plotted for the three polarizations (x,y,z) rather then as a sum. Say we are interested in the excitation near 10 eV. We can clearly see this is a z-polarized transition (green on curve). To selectively excite this we could use a continuous wave E-field, which has a delta-function, i.e., single frequency, bandwidth but since we are doing finite simulations we need a suitable envelope. The broader the envelope in time the narrower the excitation in frequency domain, but of course long simulations become costly so we need to put some thought into the choice of our envelope. In this case the peak of interest is spectrally isolated from other z-polarized peaks, so this is quite straightforward. The procedure is outlined below, and the corresponding frequency extent of the pulse is shown on the absorption figure in orange. Note that it only covers one excitation, i.e., the field selectively excites one mode. The full input deck is media:RT TDDFT h2o resonant.nw and the output is media:RT TDDFT h2o resonant.nwo.gz.



```
dft
xc pbe0
end
## Compute ground state of the system
task dft energy
##
## We excite the system with a quasi-monochromatic
## (Gaussian-enveloped) z-polarized E-field tuned to a transition at
## 10.25 eV. The envelope takes the form:
##
\#\# G(t) = \exp(-(t-t0)^{2})^{2s^{2}}
##
## The target excitation has an energy (frequency) of w = 0.3768 au
## and thus an oscillation period of T = 2 pi / w = 16.68 au
##
## Since we are doing a Gaussian envelope in time, we will get a
## Gaussian envelope in frequency (Gaussians are eigenfunctions of a
## Fourier transform), with width equal to the inverse of the width in
## time. Say, we want a Gaussian in frequency with FWHM = 1 eV
## (recall FWHM = 2 sqrt (2ln2) s freq) we want an s freq = 0.42 \text{ eV} =
## 0.0154 au, thus in time we need s_time = 1 / s_time = 64.8 au.
##
## Now we want the envelope to be effectively zero at t=0, say 1e-8
## (otherwise we get "windowing" effects). Reordering G(t):
##
## t0 = t - sqrt(-2 s^2 ln G(t))
##
## That means our Gaussian needs to be centered at t0 = 393.3 au.
##
## The total simulation time will be 1000 au to leave lots of time to
## see oscillations after the field has passed.
##
rt tddft
  tmax 1000.0
  dt 0.2
  field "driver"
    type gaussian
    polarization z
    frequency 0.3768 # = 10.25 eV
    center 393.3
    width 64.8
    max 0.0001
  end
  excite "system" with "driver"
 end
```

task dft rt_tddft



From the time-dependent dipole moment you can see the field driving the system into a superposition of the ground state and the one excited state, which manifests as monochromatic oscillations. After the field has passed the dipole oscillations continue forever as there is no damping in the system.

Charge transfer between a TCNE dimer

Here we compute the time-dependent charge oscillations between a TCNE (tetracyanoethylene) dimer separated by 3 Angstroms, where the top molecule starts neutral and the bottom one starts with a -1 charge. This somewhat non-physical starting point will lead to far-from-equilibrium dynamics as the charge violently sloshes between the two molecules, with the oscillation period a function of the molecular separation. The trick here is to use fragments by have multiple geometries in the input deck, where each fragment is converged separately, then assembled together without SCF to use as a starting point. We use a small but diffuse basis and a range-separated functional (CAM-B3LYP). The input deck is media:RT_TDDFT_tcne_dimer.nw and the full output is media:RT_TDDFT_tcne_dimer.nw and the full output is

title "Tetracyanoethylene dimer charge transfer"

```
echo
scratch_dir ./scratch
permanent_dir ./perm
start tcne
echo
```

##	Fach fragment	ntimized with a		
## ##	Each Tragment (optimized with Co	C-DV02/B3LTP	
##				
geo	Dimetry Dottom	units angstroms	noautosym nocenter noautoz	
C	-1.//5/6486	0.66496556	0.00004199	
N	-2.946/6621	0./13/9/9/	0.00004388	
C	-0.36046718	0.62491168	0.00003506	
C	0.36049301	-0.62492429	-0.00004895	
C	1.77579907	-0.66504145	-0.00006082	
Ν	2.94680364	-0.71382258	-0.00006592	
С	-0.31262746	-1.87038951	-0.00011201	
Ν	-0.85519492	-2.90926164	-0.00016331	
С	0.31276207	1.87031662	0.00010870	
Ν	0.85498782	2.90938919	0.00016857	
end	t			
geo	ometry "top" uni	its angstroms no	autosym nocenter noautoz	
C	-1.77576486	0.66496556	3.00004199	
Ν	-2.94676621	0.71379797	3.00004388	
С	-0.36046718	0.62491168	3.00003506	
С	0.36049301	-0.62492429	2.99995105	
С	1.77579907	-0.66504145	2.99993918	
Ν	2.94680364	-0.71382258	2.99993408	
С	-0.31262746	-1.87038951	2.99988799	
Ν	-0.85519492	-2.90926164	2.99983669	
С	0.31276207	1.87031662	3.00010870	
Ν	0.85498782	2.90938919	3.00016857	
end	t			
##	dimer geometry	is the union of	bottom and top geometry	
geo	ometry "dimer" ι	units angstroms i	noautosym nocenter noautoz	
С	-1.77576486	0.66496556	0.00004199	
Ν	-2.94676621	0.71379797	0.00004388	
С	-0.36046718	0.62491168	0.00003506	
С	0.36049301	-0.62492429	-0.00004895	
С	1.77579907	-0.66504145	-0.00006082	
Ν	2.94680364	-0.71382258	-0.00006592	
С	-0.31262746	-1.87038951	-0.00011201	
Ν	-0.85519492	-2.90926164	-0.00016331	
С	0.31276207	1.87031662	0.00010870	
Ν	0.85498782	2,90938919	0.00016857	
#				
, C	-1.77576486	0.66496556	3,00004199	
N	-2 94676621	0.71370707	3 00004388	
C	-0 360/6719	0 62401162	3 00003506	
C	0.36040710	-0.62491100	2 00005105	
C		0.6650/1/5	5.9999703	
	1.//5/990/		5.9993910	
N	2.94080364	-0./1382258	2.99995408	

```
С
      -0.31262746
                     -1.87038951
                                      2.99988799
 Ν
      -0.85519492
                     -2.90926164
                                      2.99983669
 С
       0.31276207
                      1.87031662
                                      3.00010870
 Ν
       0.85498782
                      2.90938919
                                      3.00016857
end
##
## C, N: 3-21++G
##
basis spherical
С
    S
    172.2560000
                              0.0617669
     25.9109000
                              0.3587940
     5.5333500
                             0.7007130
С
     SP
      3.6649800
                             -0.3958970
                                                     0.2364600
     0.7705450
                                                     0.8606190
                             1.2158400
С
     SP
     0.1958570
                             1.0000000
                                                     1.0000000
С
    SP
      0.0438000
                             1.0000000
                                                     1.0000000
     S
Ν
    242,7660000
                              0.0598657
     36.4851000
                              0.3529550
      7.8144900
                             0.7065130
     SP
Ν
      5.4252200
                            -0.4133010
                                                     0.2379720
      1.1491500
                             1.2244200
                                                     0.8589530
     SP
Ν
      0.2832050
                                                     1.0000000
                             1.0000000
     SP
Ν
      0.0639000
                              1.0000000
                                                     1.0000000
end
##
## Charge density fitting basis.
##
basis "cd basis"
С
     S
      5.91553927E+02
                              0.31582020
      1.72117940E+02
                              0.87503863
      5.47992590E+01
                             2.30760524
С
     S
     1.89590940E+01
                             1.0000000
С
     S
      7.05993000E+00
                              1.0000000
С
     S
      2.79484900E+00
                              1.0000000
```

С	S	
-	1.15863400E+00	1.0000000
С	S	
C	4.94324000E-01 S	1.0000000
C	2.12969000E-01	1.0000000
С	Р	
C	3.27847358E-01 P	1.0000000
C	7.86833659E-01	1.0000000
С	Р	
C	1.97101832E+00 D	1.0000000
C	4.01330100E+00	1.0000000
С	D	
C	1.24/50500E+00 D	1.0000000
C	4.08148000E-01	1.0000000
С	F	1 0000000
N	9.0000000E-01 S	1.0000000
	7.91076935E+02	0.41567506
	2.29450184E+02	1.14750694
N	7.28869600E+01 S	3.01935/6/
	2.51815960E+01	1.0000000
Ν	S	1 0000000
N	S	1.0000000
	3.71065500E+00	1.0000000
Ν	S	1 0000000
N	S	1.0000000
	6.57553000E-01	1.0000000
Ν	S 2 83654000F-01	1 0000000
N	P	1.0000000
	4.70739194E-01	1.0000000
N	P 1.12977407F+00	1.0000000
Ν	P	110000000
	2.83008403E+00	1.0000000
N	5.83298650E+00	1.0000000
Ν	D	
N	1.73268650E+00	1.0000000
N	U	

```
5.45242500E-01
                             1.0000000
     F
Ν
      1.82648000E+00
                             1.0000000
end
##
## Universal DFT parameters. Note, we are doing open-shell even for
## the neutral fragment so the movecs have the correct size.
##
## We are using the CAM-B3LYP functional (no need to use "direct"
## since we are doing CD fitting).
##
dft
  xc xcamb88 1.00 lyp 0.81 vwn_5 0.19 hfexch 1.00
  cam 0.33 cam alpha 0.19 cam beta 0.46
  odft
 convergence density 1d-9
 grid fine
  maxiter 1000
end
##
## Converge bottom fragment with extra electron and top fragment as
## neutral.
##
charge -1
set geometry "bottom"
dft
  mult 2
  vectors input atomic output "bottom.movecs"
end
task dft energy
charge 0
set geometry "top"
dft
  mult 1
  vectors input atomic output "top.movecs"
end
task dft energy
##
## Assemble the two fragments but don't do SCF--this keeps the system
## in a far-from-equilibrium state from which we will watch the
## dynamics.
##
charge -1
set geometry "dimer"
dft
```

```
mult 2
  vectors input fragment "bottom.movecs" "top.movecs" output
"dimer.movecs"
  noscf
end
task dft energy
##
## Now do RT-TDDFT from this crazy state without any electric fields.
##
rt tddft
  tmax 500.0
  dt 0.2
  load vectors "dimer.movecs"
  print dipole field energy s2 charge
end
task dft rt_tddft
```



The time-dependent charge shows that the excess electron starts on the "bottom" molecule (i.e., a total electronic charge of -65), then swings to completely occupy the "top" molecule then oscillates back and forth. The frequency of this oscillation is dependent on the separation, with larger separations leading to lower frequencies. It is important to note, however, this starting point is highly non-physical, specifically converging the two fragments together and "gluing" them together introduces an indeterminate amount of energy to the system, but this simulation shows how charge dynamics simulations can be done.

Release65:Plane-Wave Density Functional Theory

__NOTITLE___

Pseudopotential plane-wave density functional theory (NWPW)

The NWChem plane-wave (NWPW) module uses pseudopotentials and plane-wave basis sets to perform Density Functional Theory calculations (simple introduction Media:Pw-lecture.pdf). This module complements the capabilities of the more traditional Gaussian function based approaches by having an accuracy at least as good for many applications, yet is still fast enough to treat systems containing hundreds of atoms. Another significant advantage is its ability to simulate dynamics on a ground state potential surface directly at run-time using the Car-Parrinello algorithm. This method's efficiency and accuracy make it a desirable first principles method of simulation in the study of complex molecular, liquid, and solid state systems. Applications for this first principles method include the calculation of free energies, search for global minima, explicit simulation of solvated molecules, and simulations of complex vibrational modes that cannot be described within the harmonic approximation.

The NWPW module is a collection of three modules.

- PSPW (PSeudopotential Plane-Wave) A gamma point code for calculating molecules, liquids, crystals, and surfaces.
- Band A band structure code for calculating crystals and surfaces with small band gaps (e.g. semi-conductors and metals).
- PAW a (gamma point) projector augmented plane-wave code for calculating molecules, crystals, and surfaces

The PSPW, Band, and PAW modules can be used to compute the energy and optimize the geometry. Both the PSPW and Band modules can also be used to find saddle points, and compute numerical second derivatives. In addition the PSPW module can also be used to perform Car-Parrinello molecular dynamics. Section PSPW Tasks describes the tasks contained within the PSPW module, section Band Tasks describes the tasks contained within the Band module, section PAW Tasks describes the tasks contained within the PAW module, and section Pseudopotential and PAW basis Libraries describes the pseudopotential library included with NWChem. The datafiles used by the PSPW module are described in section NWPW RTDB Entries and DataFiles. Car-Parrinello output data files are described in section Car-Parrinello Output Datafiles, and the minimization and Car-Parrinello algorithms are described in section Car-Parrinello Scheme for Ab Initio Molecular Dynamics. Examples of how to setup and run a PSPW geometry optimization, a Car-Parrinello simulation, a band structure minimization, and a PAW geometry optimization are presented at the end. Finally in section NWPW Capabilities and Limitations the capabilities and limitations of the NWPW module are discussed.

If you are a first time user of this module it is recommended that you skip the next five sections and proceed directly to the tutorials.

PSPW Tasks

All input to the PSPW Tasks is contained within the compound PSPW block,

PSPW

... END

To perform an actual calculation a TASK PSPW directive is used (Section Task).

TASK PSPW

In addition to the directives listed in Task, i.e. TASK pspw energy TASK pspw gradient TASK pspw optimize TASK pspw saddle TASK pspw freqencies TASK pspw vib there are additional directives that are specific to the PSPW module, which are:

TASK	PSPW	[Car-Parrinello		
		pspw_dplot		
		wannier		
		psp_generator		
		<pre>steepest_descent</pre>		
		psp_formatter		
		wavefunction_initializer		
		<pre>v_wavefunction_initializer</pre>		
		wavefunction_expander]	

Once a user has specified a geometry, the PSPW module can be invoked with no input directives (defaults invoked throughout). However, the user will probably always specify the simulation cell used in the computation, since the default simulation cell is not well suited for most systems. There are sub-directives which allow for customized application; those currently provided as options for the PSPW module are:

NWPW

```
SIMULATION CELL
                            ... (see section #Simulation Cell) END
CELL_NAME <string cell_name default 'cell_default'>
VECTORS |
           [output(<string output_wavefunctions default</pre>
file_prefix.movecs>)
XC (Vosko
                                || PBE96
                || LDA
                                                  || revPBE
                                                                  11
PBEsol
                || LDA-SIC/4
     LDA-SIC
               || LDA-SIC/2
                                || LDA-0.4SIC
                                                                  11
LDA-0.2SIC
            - 11
     PBE96-SIC || PBE96-SIC/2 || PBE96-0.4SIC || PBE96-SIC/4
                                                                  PBE96-0.2SIC ||
     revPBE-SIC || revPBE-SIC/2 || revPBE-0.4SIC || revPBE-SIC/4 ||
revPBE-0.2SIC ||
     PBE0
                || revPBE0
                                || HSE || HF || default Vosko)
DFT||ODFT||RESTRICTED||UNRESTRICTED
MULT <integer mult default 1>
CG
LMBFGS
```

```
SCF [Anderson|| simple || Broyden]
    [CG || RMM-DIIS]
    [density || potential]
    [ALPHA real alpha default 0.25]
    [Kerker real ekerk nodefault]
    [ITERATIONS integer inner iterations default 5]
    [OUTER ITERATIONS integer outer iterations default 0]
LOOP <integer inner iteration outer iteration default 10 100>
TOLERANCES <real tole tolc default 1.0e-7 1.0e-7>
FAKE MASS <real fake mass default 400000.0>
TIME STEP <real time step default 5.8>
EWALD NCUT <integer ncut default 1>
EWALD RCUT <real rcut default (see input description)>
CUTOFF <real cutoff>
ENERGY CUTOFF <real ecut default (see input description)>
WAVEFUNCTION CUTOFF <real wcut default (see input description)>
ALLOW TRANSLATION
TRANSLATION (ON || OFF)
ROTATION (ON || OFF)
MULLIKEN [OFF]
EFIELD
```

```
MAPPING <integer mapping default 1>
NP DIMENSIONS <integer npi npj default -1 -1>
                           ... (see section Car-Parrinello) END
CAR-PARRINELLO
STEEPEST DESCENT
                           ... (see section Steepest Descent) END
DPLOT
                           ... (see section DPLOT) END
                           ... (see section Wannier) END
WANNIER
                            ... (see section PSP Generator)) END
PSP GENERATOR
WAVEFUNCTION INITIALIZER ... (see section Wavefunction
Initializer - retired) END
V WAVEFUNCTION INITIATIZER ... (see section Wavefunction
Velocity Initializer - retired) END
WAVEFUNCTION EXPANDER
                            ... (see section Wavefunction
Expander - retired) END
INPUT_WAVEFUNCTION_FILENAME <string input_wavefunctions default
file prefix.movecs>
OUTPUT WAVEFUNCTION FILENAME <string output wavefunctions default
file prefix.movecs>
END
```

The following list describes the keywords contained in the PSPW input block.

- <cell_name> name of the simulation_cell named <cell_name>. See section Simulation Cell.
- <input_wavefunctions> name of the file containing one-electron orbitals
- <output_wavefunctions> name of the file that will contain the one-electron orbitals at the end of the run.

- <fake_mass> value for the electronic fake mass ($0\,M$). This parameter is not presently used in a conjugate gradient simulation.
- <time_step> value for the time step (Δt). This parameter is not presently used in a conjugate gradient simulation.
- <inner_iteration> number of iterations between the printing out of energies and tolerances
- <outer_iteration> number of outer iterations
- <tole> value for the energy tolerance.
- <tolc> value for the one-electron orbital tolerance.
- <cutoff> value for the cutoff energy used to define the wavefunction. In addition using the CUTOFF keyword automatically sets the cutoff energy for the density to be twice the wavefunction cutoff.
- <ecut> value for the cutoff energy used to define the density. Default is set to be the maximum value that will fit within the simulation_cell <cell_name>.
- <wcut> value for the cutoff energy used to define the one-electron orbitals. Default is set to be the maximum value that will fit within the simulation_cell <cell_name>.
- <ncut> value for the number of unit cells to sum over (in each direction) for the real space part of the Ewald summation. Note Ewald summation is only used if the simulation_cell is periodic.
- <rcut> value for the cutoff radius used in the Ewald summation. Note Ewald summation is only used if the simulation_cell is periodic.

Default set to be
$$rac{MIN(ert ec a_iert ec))}{\pi}, i=1,2,3.$$

- (Vosko || PBE96 || revPBE || ...) Choose between Vosko et al's LDA parameterization or the orginal and revised Perdew, Burke, and Ernzerhof GGA functional. In addition, several hybrid options.
- MULT optional keyword which if specified allows the user to define the spin multiplicity of the system
- MULLIKEN optional keyword which if specified causes a Mulliken analysis to be performed at the end of the simulation.
- EFIELD optional keyword which if specified causes an atomic electric field analysis to be performed at the end of the simulation.
- ALLOW_TRANSLATION By default the the center of mass forces are projected out of the computed forces. This optional keyword if specified allows the center of mass forces to not be zero.
- TRANSLATION By default the the center of mass forces are projected out of the computed forces. TRANSLATION ON allows the center of mass forces to not be zero.
- ROTATION By default the overall rotation is not projected out of the computed forces. ROTATION OFF projects out the overal rotation of the molecule.
- CG optional keyword which sets the minimizer to $1 \label{eq:cg}$
- LMBFGS optional keyword which sets the minimizer to 2
- SCF optional keyword which sets the minimizer to be a band by band minimizer. Several options are available for setting the density or potential mixing, and the type of Kohn-Sham minimizer.
- <mapping> for a value of 1 slab FFT is used, for a value of 2 a 2d-hilbert FFT is used.

A variety of prototype minimizers can be used to minimize the energy. To use these new optimizers the following SET directive needs to be specified:

```
set nwpw:mimimizer 1 # Default - Grassman conjugate gradient minimizer
is used to minimize the energy.
set nwpw:mimimizer 2 # Grassman LMBFGS minimimzer is used to minimize
the energy.
set nwpw:minimizer 4 # Stiefel conjugate gradient minimizer is used to
minimize the energy.
set nwpw:minimizer 5 # Band-by-band (potential) minimizer is used to
minimize the energy.
set nwpw:minimizer 6 # Projected Grassman LMBFGS minimizer is used to
minimize the energy.
set nwpw:minimizer 7 # Stiefel LMBFGS minimizer is used to minimize the
energy.
set nwpw:minimizer 8 # Band-by-band (density) minimizer is used to
minimize the energy.
```

Limited testing suggests that the Grassman LMBFGS minimizer is about twice as fast as the conjugate gradient minimizer. However, there are several known cases where this optimizer fails, so it is currently not a default option, and should be used with caution.

In addition the following SET directives can be specified:

```
set nwpw:lcao_skip .false. # Initial wavefunctions generated using an
LCAO guess.
set nwpw:lcao_skip .true. # Default - Initial wavefunctions generated
using a random plane-wave guess.
set nwpw:lcao_print .false. # Default - Output not produced during the
generation of the LCAO guess.
set nwpw:lcao_print .true. # Output produced during the generation of
the LCAO guess.
set nwpw:lcao_iterations 2 #specifies the number of LCAO iterations.
```

Wannier

The pspw wannier task is generate maximally localized (Wannier) molecular orbitals. The algorithm proposed by Silvestrelli et al is use to generate the Wannier orbitals.

Input to the Wannier task is contained within the Wannier sub-block.

```
NWPW
...
Wannier
...
END
...
END
```

To run a Wannier calculation the following directive is used:

TASK PSPW Wannier

Listed below is the format of a Wannier sub-block.

```
NWPW
...
Wannier
OLD_WAVEFUNCTION_FILENAME <string input_wavefunctions default
input_movecs>
    NEW_WAVEFUNCTION_FILENAME <string output_wavefunctions default
input_movecs>
    END
...
END
```

The following list describes the input for the Wannier sub-block.

- <input wavefunctions> name of pspw wavefunction file.
- <output_wavefunctions> name of pspw wavefunction file that will contain the Wannier orbitals.

Self-Interaction Corrections

The SET directive is used to specify the molecular orbitals contribute to the self-interaction-correction (SIC) term.

set pspw:SIC_orbitals <integer list_of_molecular_orbital_numbers>

This defines only the molecular orbitals in the list as SIC active. All other molecular orbitals will not contribute to the SIC term. For example the following directive specifies that the molecular orbitals numbered 1,5,6,7,8, and 15 are SIC active.

```
set pspw:SIC_orbitals 1 5:8 15
```

or equivalently

```
set pspw:SIC_orbitals 1 5 6 7 8 15
```

The following directive turns on self-consistent SIC.

```
set pspw:SIC_relax .false. # Default - Perturbative SIC calculation
set pspw:SIC_relax .true. # Self-consistent SIC calculation
```

Two types of solvers can be used and they are specified using the following SET directive

```
set pspw:SIC_solver_type 1 # Default - cutoff coulomb kernel
set pspw:SIC_solver_type 2 # Free-space boundary condition kernel
```

The parameters for the cutoff coulomb kernel are defined by the following SET directives:

set pspw:SIC_screening_radius <real rcut>
set pspw:SIC_screening_power <real rpower>

Point Charge Analysis

The MULLIKEN option can be used to generate derived atomic point charges from a plane-wave density. This analysis is based on a strategy suggested in the work of P.E. Blochl, J. Chem. Phys. vol. 103, page 7422 (1995). In this strategy the low-frequency components a plane-wave density are fit to a linear combination of atom centered Gaussian functions.

The following SET directives are used to define the fitting.

```
set pspw_APC:Gc <real Gc_cutoff> # specifies the maximum
frequency component of the density to be used in the fitting in units
of au.
set pspw_APC:nga <integer number_gauss> # specifies the the
number of Gaussian functions per atom.
set pspw_APC:gamma <real gamma_list> # specifies the decay
lengths of each atom centered Gaussian.
```

We suggest using the following parameters.

set pspw_APC:Gc 2.5
set pspw_APC:nga 3
set pspw_APC:gamma 0.6 0.9 1.35

PSPW_DPLOT

The pspw dplot task is used to generate plots of various types of electron densities (or orbitals) of a molecule. The electron density is calculated on the specified set of grid points from a PSPW calculation. The output file generated is in the Gaussian Cube format. Input to the DPLOT task is contained within the DPLOT sub-block.

```
NWPW
...
DPLOT
...
END
...
END
```

To run a DPLOT calculation the following directive is used:

TASK PSPW PSPW_DPLOT

Listed below is the format of a DPLOT sub-block.

```
orbital_name no default>
  [LIMITXYZ [units <string Units default angstroms>]
  <real X_From> <real X_To> <integer
No_Of_Spacings_X>
    <real Y_From> <real Y_To> <integer
No_Of_Spacings_Y>
    <real Z_From> <real Z_To> <integer
No_Of_Spacings_Z>]
  END
...
END
```

The following list describes the input for the DPLOT sub-block.

VECTORS <string input_wavefunctions default input_movecs>

This sub-directive specifies the name of the molecular orbital file. If the second file is optionally given the density is computed as the difference between the corresponding electron densities. The vector files have to match.

```
DENSITY [total||difference||alpha||beta||laplacian||potential default
total] <string density_name no default>
```

This sub-directive specifies, what kind of density is to be plotted. The known names for total, difference, alpha, beta, laplacian, and potential.

```
ELF [restricted|alpha|beta] <string elf_name no default>
```

This sub-directive specifies that an electron localization function (ELF) is to be plotted.

```
ORBITAL <integer orbital_number no default> <string
orbital_name no default>
```

This sub-directive specifies the molecular orbital number that is to be plotted.

```
LIMITXYZ [units <string Units default angstroms>]
<real X_From> <real X_To> <integer No_Of_Spacings_X>
<real Y_From> <real Y_To> <integer No_Of_Spacings_Y>
<real Z_From> <real Z_To> <integer No_Of_Spacings_Z>
```

By default the grid spacing and the limits of the cell to be plotted are defined by the input wavefunctions. Alternatively the user can use the LIMITXYZ sub-directive to specify other limits. The grid is generated using No_Of_Spacings + 1 points along each direction. The known names for Units are angstroms, au and bohr.

Band Tasks

All input to the Band Tasks is contained within the compound NWPW block,

NWPW

... END

To perform an actual calculation a Task Band directive is used (Section Task).

Task Band

Once a user has specified a geometry, the Band module can be invoked with no input directives (defaults invoked throughout). There are sub-directives which allow for customized application; those currently provided as options for the Band module are:

```
NWPW
CELL_NAME <string cell_name default 'cell_default'>
ZONE NAME <string zone name default 'zone default'>
INPUT WAVEFUNCTION FILENAME <string input wavefunctions default
input movecs>
OUTPUT WAVEFUNCTION FILENAME <string output wavefunctions default
input movecs>
 FAKE_MASS <real fake_mass default 400000.0>
TIME STEP <real time step default 5.8>
LOOP <integer inner iteration outer iteration default 10 100>
TOLERANCES <real tole tolc default 1.0e-7 1.0e-7>
CUTOFF <real cutoff>
ENERGY CUTOFF <real ecut default (see input description)>
WAVEFUNCTION CUTOFF <real wcut default (see input description)>
EWALD NCUT <integer ncut default 1>]
EWALD_RCUT <real rcut default (see input description)>
XC (Vosko
                || LDA
                                || PBE96
                                                  || revPBE
                                                                  11
PBEsol
                || HSE || default Vosko)
 #Note that HSE is the only hybrid functional implemented in BAND
DFT||ODFT||RESTRICTED||UNRESTRICTED
MULT <integer mult default 1>
CG
LMBFGS
SCF [Anderson|| simple || Broyden]
 [CG || RMM-DIIS] [density || potential]
 [ALPHA real alpha default 0.25]
 [ITERATIONS integer inner iterations default 5]
 [OUTER_ITERATIONS integer outer_iterations default 0]
SIMULATION_CELL
   ... (see input description)
END
```
```
BRILLOUIN_ZONE
   ... (see input description)
END
MONKHORST-PACK <real n1 n2 n3 default 1 1 1>
BAND_DPLOT
   ... (see input description)
END
MAPPING <integer mapping default 1>
SMEAR <sigma default 0.001>
[TEMPERATURE <temperature>]
[FERMI || GAUSSIAN default FERMI]
[ORBITALS <integer orbitals default 4>]
END
```

The following list describes these keywords.

- <cell_name> name of the simulation_cell named <cell_name>. See #Simulation Cell.
- <input_wavefunctions> name of the file containing one-electron orbitals
- <output_wavefunctions> name that will point to file containing the one-electron orbitals at the end of the run.
- <fake_mass> value for the electronic fake mass (μ). This parameter is not presently used in a conjugate gradient simulation
- <time_step> value for the time step (Δt). This parameter is not presently used in a conjugate gradient simulation.
- <inner_iteration> number of iterations between the printing out of energies and tolerances
- <outer_iteration> number of outer iterations
- <tole> value for the energy tolerance.
- <tolc> value for the one-electron orbital tolerance.
- <cutoff> value for the cutoff energy used to define the wavefunction. In addition using the CUTOFF keyword automatically sets the cutoff energy for the density to be twice the wavefunction cutoff.
- <ecut> value for the cutoff energy used to define the density. Default is set to be the maximum value that will fit within the simulation_cell <cell_name>.
- <wcut> value for the cutoff energy used to define the one-electron orbitals. Default is set to be the maximum value that will fix within the simulation_cell <cell_name>.
- <ncut> value for the number of unit cells to sum over (in each direction) for the real space part of the Ewald summation. Note Ewald summation is only used if the simulation cell is periodic.
- <rcut> value for the cutoff radius used in the Ewald summation. Note Ewald summation is only used if the simulation_cell is periodic.

Default set to be
$$rac{MIN(ert ec a_i ert))}{\pi}, i=1,2,3.$$

- (Vosko || PBE96 || revPBE) Choose between Vosko et al's LDA parameterization or the orginal and revised Perdew, Burke, and Ernzerhof GGA functional.
- SIMULATION_CELL (see section -sec:pspw_cell-)
- BRILLOUIN_ZONE (see section -sec:band_brillouin_zone-)

- MONKHORST-PACK Alternatively, the MONKHORST-PACK keyword can be used to enter a MONKHORST-PACK sampling of the Brillouin zone.
- <smear> value for smearing broadending
- <temperature> same as smear but in units of K.
- CG optional keyword which sets the minimizer to $1 \label{eq:cg}$
- LMBFGS optional keyword which sets the minimizer to 2
- SCF optional keyword which sets the minimizer to be a band by band minimizer. Several options are available for setting the density or potential mixing, and the type of Kohn-Sham minimizer.

Brillouin Zone

To supply the special points of the Brillouin zone, the user defines a brillouin_zone sub-block within the NWPW block. Listed below is the format of a brillouin_zone sub-block.

NWPW

```
...
BRILLOUIN_ZONE
ZONE_NAME <string name default 'zone_default'>
(KVECTOR <real k1 k2 k3 no default> <real weight default
(see input description)>
...)
END
...
END
```

The user enters the special points and weights of the Brillouin zone. The following list describes the input in detail.

- <name> user-supplied name for the simulation block.
- <k1 k2 k3> user-supplied values for a special point in the Brillouin zone.
- <weight<> user-supplied weight. Default is to set the weight so that the sum of all the weights for the entered special points adds up to unity.

Band Structure Paths

SC: gamma, m, r, x FCC: gamma, k, l, u, w, x BCC: gamma, h, n, p Rhombohedral: not currently implemented Hexagonal: gamma, a, h, k, l, m Simple Tetragonal: gamma, a, m, r, x, z Simple Orthorhomic: gamma, r, s, t, u, x, y, z Body-Centered Tetragonal: gamma, m, n, p, x

Special Points of Different Space Groups (Conventional Cells)

(1) P1

(2) P-1

(3)

BAND_DPLOT

The BAND BAND_DPLOT task is used to generate plots of various types of electron densities (or orbitals) of a crystal. The electron density is calculated on the specified set of grid points from a Band calculation. The output file generated is in the Gaussian Cube format. Input to the BAND_DPLOT task is contained within the BAND_DPLOT sub-block.

NWPW

```
BAND_DPLOT
...
END
...
END
```

To run a BAND_DPLOT calculation the following directive is used:

```
TASK BAND BAND_DPLOT
```

Listed below is the format of a BAND_DPLOT sub-block.

```
NWPW
. . .
 BAND DPLOT
   VECTORS <string input_wavefunctions default input_movecs>
   DENSITY [total||difference||alpha||beta||laplacian||potential
default total]
           <string density_name no default>
   ELF [restricted|alpha|beta] <string elf name no default>
   ORBITAL (density || real || complex default density)
           <integer orbital_number no default>
           <integer brillion number default 1>
           <string orbital_name no default>
   [LIMITXYZ [units <string Units default angstroms>]
   <real X_From> <real X_To> <integer
No_Of_Spacings_X>
   <real Y From> <real Y To> <integer
No Of Spacings Y>
   <real Z_From> <real Z_To> <integer
No_Of_Spacings_Z>]
 END
. . .
END
```

The following list describes the input for the BAND_DPLOT sub-block.

VECTORS <string input_wavefunctions default input_movecs>

This sub-directive specifies the name of the molecular orbital file. If the second file is optionally given the density is computed as the difference between the corresponding electron densities. The vector files have to match.

```
DENSITY [total||difference||alpha||beta||laplacian||potential default
total] <string density_name no default>
```

This sub-directive specifies, what kind of density is to be plotted. The known names for total, difference, alpha, beta, laplacian, and potential.

ELF [restricted|alpha|beta] <string elf_name no default>

This sub-directive specifies that an electron localization function (ELF) is to be plotted.

```
ORBITAL (density || real || complex default density) <integer
orbital_number no default> <integer brillion_number default
1> <string orbital name no default>
```

This sub-directive specifies the molecular orbital number that is to be plotted.

```
LIMITXYZ [units <string Units default angstroms>]
<real X_From> <real X_To> <integer No_Of_Spacings_X>
<real Y_From> <real Y_To> <integer No_Of_Spacings_Y>
<real Z_From> <real Z_To> <integer No_Of_Spacings_Z>
```

By default the grid spacing and the limits of the cell to be plotted are defined by the input wavefunctions. Alternatively the user can use the LIMITXYZ sub-directive to specify other limits. The grid is generated using No_Of_Spacings + 1 points along each direction. The known names for Units are angstroms, au and bohr.

Car-Parrinello

The Car-Parrinello task is used to perform ab initio molecular dynamics using the scheme developed by Car and Parrinello. In this unified ab initio molecular dynamics scheme the motion of the ion cores is coupled to a fictitious motion for the Kohn-Sham orbitals of density functional theory. Constant energy or constant temperature simulations can be performed. A detailed description of this method is described in section Car-Parrinello Scheme for Ab Initio Molecular Dynamics.

Input to the Car-Parrinello simulation is contained within the Car-Parrinello sub-block.

```
NWPW

...

Car-Parrinello

...

END

...

END
```

To run a Car-Parrinello calculation the following directives are used:

```
TASK PSPW Car-Parrinello
TASK BAND Car-Parrinello
```

```
TASK PAW Car-Parrinello
```

The Car-Parrinello sub-block contains a great deal of input, including pointers to data, as well as parameter input. Listed below is the format of a Car-Parrinello sub-block.

```
NWPW
. . .
Car-Parrinello
  CELL NAME <string cell name default 'cell default'>
   INPUT WAVEFUNCTION FILENAME <string input wavefunctions default
file prefix.movecs>
   OUTPUT WAVEFUNCTION FILENAME <string output wavefunctions default
file prefix.movecs>
   INPUT V WAVEFUNCTION FILENAME <string input v wavefunctions
default file prefix.vmovecs>
   OUTPUT_V_WAVEFUNCTION_FILENAME <string output_v_wavefunctions
default file prefix.vmovecs>
   FAKE MASS <real fake mass default default 1000.0>
  TIME STEP <real time step default 5.0>
   LOOP <integer inner iteration outer iteration default 10 1>
  SCALING <real scale c scale r default 1.0 1.0>
   ENERGY CUTOFF <real ecut default (see input description)>
  WAVEFUNCTION_CUTOFF <real wcut default (see input
description)>
   EWALD NCUT <integer ncut default 1>
   EWALD_RCUT <real rcut default (see input description)>
  XC (Vosko
                  || LDA
                            || PBE96
                                                  || revPBE
                                                                   HF
              LDA-SIC
                || LDA-SIC/2 || LDA-0.4SIC || LDA-SIC/4
                                                                   LDA-0.2SIC ||
       PBE96-SIC || PBE96-SIC/2 || PBE96-0.4SIC || PBE96-SIC/4
                                                                   PBE96-0.2SIC ||
       revPBE-SIC || revPBE-SIC/2 || revPBE-0.4SIC || revPBE-SIC/4 ||
revPBE-0.2SIC ||
       PBE0
                  || revPBE0
                                  || default Vosko)
   [Nose-Hoover <real Period electron Temperature electron
                       Period ion
                                      Temperature ion default 100.0
298.15 100.0 298.15>]
   [SA decay <real sa scale c sa scale r default 1.0 1.0>]
  XYZ_FILENAME <string xyz_filename default file_prefix.xyz>
   ION MOTION FILENAME <string ion motion filename default
file prefix.ion motion
   EMOTION_FILENAME <string emotion_filename default</pre>
file prefix.emotion>
  HMOTION FILENAME <string hmotion filename nodefault>
   OMOTION_FILENAME <string omotion_filename nodefault>
   EIGMOTION FILENAME <string eigmotion filename nodefault>
END
```

... END

The following list describes the input for the Car-Parrinello sub-block.

- <cell_name> name of the simulation_cell named <cell_name>. See section Simulation Cell.
- <input_wavefunctions> name of the file containing one-electron orbitals
- <output_wavefunctions> name of the file that will contain the one-electron orbitals at the end of the run.
- <input_v_wavefunctions> name of the file containing one-electron orbital velocities.
- <output_v_wavefunctions> name of the file that will contain the one-electron orbital velocities at the end of the run.
- <fake_mass> value for the electronic fake mass (μ).
- <time_step> value for the Verlet integration time step (Δt).
- <inner_iteration> number of iterations between the printing out of energies.
- <outer_iteration> number of outer iterations
- <scale_c> value for the initial velocity scaling of the one-electron orbital velocities.
- < scale_r> value for the initial velocity scaling of the ion velocities.
- <ecut> value for the cutoff energy used to define the density. Default is set to be the maximum value that will fit within the simulation_cell <cell_name>.
- <wcut> value for the cutoff energy used to define the one-electron orbitals. Default is set to be the maximum value that will fit within the simulation_cell <cell_name>.
- <ncut> value for the number of unit cells to sum over (in each direction) for the real space part of the Ewald summation. Note Ewald summation is only used if the simulation cell is periodic.
- <rcut> value for the cutoff radius used in the Ewald summation. Note Ewald summation is only used if the simulation_cell is periodic.

Default set to be
$$rac{MIN(ert ec a_i ert)}{\pi}, i=1,2,3.$$

- (Vosko || PBE96 || revPBE || ...) Choose between Vosko et al's LDA parameterization or the orginal and revised Perdew, Burke, and Ernzerhof GGA functional. In addition, several hybrid options.
- Nose-Hoover optional subblock which if specified causes the simulation to perform Nose-Hoover dynamics. If this subblock is not specified the simulation performs constant energy dynamics. See section -sec:pspw_nose- for a description of the parameters.
 - <Period_electron> $\equiv P_{electron}$ estimated period for fictitious electron thermostat.
 - <Temperature_electron> $\equiv T_{electron}$ temperature for fictitious electron motion
 - <Period_ion> $\equiv P_{ion}$ estimated period for ionic thermostat
 - <Temperature_ion> $\equiv T_{ion}$ temperature for ion motion
- SA_decay optional subblock which if specified causes the simulation to run a simulated annealing simulation. For simulated annealing to work the Nose-Hoover subblock needs to be specified. The initial temperature are taken from the Nose-Hoover subblock. See section -sec:pspw_nose- for a description of the parameters.
 - <sa_scale_c $> \equiv \tau_{electron}$ decay rate in atomic units for electronic temperature.
 - <sa_scale_r $> \equiv \tau_{ionic}$ decay rate in atomic units for the ionic temperature.
- <xyz_filename> name of the XYZ motion file generated

- <emotion_filename> name of the emotion motion file. See section EMOTION motion file for a description of the datafile.
- <hmotion_filenameh> name of the hmotion motion file. See section HMOTION motion file for a description of the datafile.
- <eigmotion_filename> name of the eigmotion motion file. See section EIGMOTION motion file for a description of the datafile.
- <ion_motion_filename> name of the ion_motion motion file. See section ION_MOTION motion file- for a description of the datafile.
- MULLIKEN optional keyword which if specified causes an omotion motion file to be created.
- <omotion_filename> name of the omotion motion file. See section [[#OMOTION motion file]OMOTION motion file] for a description of the datafile.

When a DPLOT sub-block is specified the following SET directive can be used to output dplot data during a PSPW Car-Parrinello simulation:

set pspw_dplot:iteration_list <integer list_of_iteration_numbers>

The Gaussian cube files specified in the DPLOT sub-block are appended with the specified iteration number.

For example, the following directive specifies that at the 3,10,11,12,13,14,15, and 50 iterations Gaussian cube files are to be produced.

set pspw_dplot:iteration_list 3,10:15,50

Adding Geometry Constraints to a Car-Parrinello Simulation

The Car-Parrinello module allows users to freeze the cartesian coordinates in a simulation (Note - the Car-Parrinello code recognizes Cartesian constraints, but it does not recognize internal coordinate constraints). The +SET+ directive (Section Applying constraints in geometry optimizations) is used to freeze atoms, by specifying a directive of the form:

set geometry:actlist <integer list_of_center_numbers>

This defines only the centers in the list as active. All other centers will have zero force assigned to them, and will remain frozen at their starting coordinates during a Car-Parrinello simulation.

For example, the following directive specifies that atoms numbered 1, 5, 6, 7, 8, and 15 are active and all other atoms are frozen:

set geometry:actlist 1 5:8 15

or equivalently,

set geometry:actlist 1 5 6 7 8 15

If this option is not specified by entering a +SET+ directive, the default behavior in the code is to treat all atoms as active. To revert to this default behavior after the option to define frozen atoms has been invoked, the +UNSET+ directive must be used (since the database is persistent, see Section NWChem Architecture). The form of the +UNSET+ directive is as follows:

```
unset geometry:actlist
```

In addition, the Car-Parrinello module allows users to freeze bond lengths via a Shake algorithm. The following +SET+ directive shows how to do this.

set nwpw:shake_constraint "2 6 L 6.9334"

This input fixes the bond length between atoms 2 and 6 to be 6.9334 bohrs. Note that this input only recognizes bohrs.

When using constraints it is usually necessary to turn off center of mass shifting. This can be done by the following +SET+ directive.

set nwpw:com_shift .false.

MetaDynamics

Metadynamics[1][2][3] is a powerful, non-equilibrium molecular dynamics method which accelerates the sampling of the multidimensional free energy surfaces of chemical reactions. This is achieved by adding an external time-dependent bias potential that is a function of user defined collective variables, \mathbf{s} . The bias potential discourages the system from sampling previously visited values of \mathbf{s} (i.e., encourages the system to explore new values of \mathbf{s}). During the simulation the bias potential accumulates in low energy wells which then allows the system to cross energy barriers much more quickly than would occur in standard dynamics. The collective variable \mathbf{s} is a generic function of the system coordinates, \mathbf{R} (e.g. bond distance, bond angle, coordination numbers, etc.) that is capable of describing the chemical reaction of interest. $\mathbf{s}(\mathbf{R})$ can be regarded as a reaction coordinate if it can distinguish between the reactant, transition, and products states, and also capture the kinetics of the reaction.

The biasing is achieved by "flooding" the energy landscape with repulsive Gaussian "hills" centered on the current location of $\mathbf{s}(\mathbf{R})$ at a constant time interval Δt . If the height of the Gaussians is constant in time then we have standard metadynamics; if the heights vary (slowly decreased) over time then we have well-tempered metadynamics. In between the addition of Gaussians, the system is propagated by normal (but out of equilibrium) dynamics. Suppose that the dimension of the collective space is d, i.e. $\mathbf{s}(\mathbf{R}) = \{s_1(\mathbf{R}), s_2(\mathbf{R}), \dots, s_d(\mathbf{R})\}$ and that prior to any time t during the simulation, N + 1 Gaussians centered on \mathbf{S}^{t_g} are deposited along the trajectory of $\mathbf{s}(\mathbf{R})$ at times $t_g = 0, \Delta t, 2\Delta t, \dots, N\Delta t$. Then, the value of the bias potential, V, at an arbitrary point, $\mathbf{s}(\mathbf{R}) = \{s_1(\mathbf{R}), s_2(\mathbf{R}), \dots, s_d(\mathbf{R})\}$, along the trajectory of $\mathbf{s}(\mathbf{R})$ at time t is given by

$$\begin{split} V_{meta}\left(\mathbf{s},t\right) &= \sum_{t_g=0}^{t_g < t} W(t) \exp\left(-\sum_{i=1}^d \frac{(s_i - s_i^{t_g})^2}{2\sigma_i^2}\right) \\ \text{where } W(t) &= W_0 \exp\left(-\frac{V_{meta}\left(\mathbf{s},t-\Delta t\right)}{k_B T_{tempered}}\right) \text{ is the time-dependent Gaussian height.} \\ \sigma_i\left(i=1,2,\ldots,d\right) \text{ and } W_0 \text{ are width and initial height respectively of Gaussians, and} \\ T_{tempered} \text{ is the tempered metadynamics temperature. } T_{tempered} = 0 \text{ corresponds to standard} \\ \text{molecular dynamics because } W(t) = 0 \text{ and therfore there is no bias. } T_{tempered} = \infty \\ \text{corresponds to standard metadynamics since in this case } W(t) = W_0 = \text{constant. A positive,} \\ \text{finite value of } T_{tempered} \text{ (eg. } T_{tempered} = 1500 \text{ K) corresponds to } well-tempered \text{ metadynamics} \\ \text{in which } 0 < W(t) \leq W_0. \end{split}$$

For sufficiently large t, the history potential $V_{meta}(\mathbf{s},t)$ will nearly flatten the free energy surface, $F(\mathbf{s})$, along \mathbf{S} and an unbiased estimator of $F(\mathbf{s})$ is given by

$$F(\mathbf{s}) = -\left(1 + \frac{T}{T_{tempered}}\right) \lim_{t \to \infty} V_{meta}(\mathbf{s}, t)$$

Bond Distance Collective Variable

This describes the bond distance between any pair of atoms i and j: $s(r_{ij}) = |\mathbf{r}_i - \mathbf{r}_j| = r_{ij}$

Angle Collective Variable

This describes the bond angle formed at *i* by the triplet $\langle jik \rangle$:

$$s(r_{ij}, r_{ik}) = rac{\mathbf{r}_{ij} \cdot \mathbf{r}_{ik}}{r_{ij}r_{ik}}$$

Coordination Collective Variable

The coordination number collective variable is defined as

$$s\left(r_{ij},r_{0}
ight)=\sum_{i,j}\xi_{ij}$$

where the summation over i and j runs over two types of atoms, ξ_{ij} is the weighting function, and r_0 is the cut-off distance. In the standard procedure for computing the coordination number, $\xi_{ij}=1$ if $r_{ij} < r_0$, otherwise $\xi_{ij}=0$, implying that ξ_{ij} is not continuous when $r_{ij} = r_0$. To ensure a smooth and continuous definition of the coordination number, we adopt two variants of the weighting function. The first variant is

$$\xi_{ij} = \frac{1 - (r_{ij}/r_0)^n}{1 - (r_{ij}/r_0)^m}$$

where n and m are integers (m >> n) chosen such that $\xi_{ij} \approx 1$ when $r_{ij} < r_0$ and $\xi_{ij} \rightarrow 0$ when r_{ij} is much larger than r_0 . For example, the parameters of the O-H coordination in water is well described by $r_0=1.6$ Å, n=6 and m=18. In practice, n and m must tuned for a given r_0 to ensure that ξ_{ij} is smooth and satisfies the above mentioned properties, particularly the large r_{ij} behavior.

The second form of the weighting function, which is due to Sprik, is

$$\xi_{ij} = rac{1}{1 + \exp\left[n\left(r_{ij} - r_0\right)
ight]}$$

In this definition ξ_{ij} is analogous to the Fermi function and its width is controlled by the parameter $\frac{1}{n}$. Large and small values of n respectively correspond to sharp and soft transitions at $r_{ij} = r_0$. Furthermore ξ_{ij} should approach 1 and 0 when $r_{ij} < r_0$ and $r_{ij} >> r_0$ respectively. In practice n=6-10 Å -1. For example, a good set of parameters of the O-H coordination in water is $r_0=1.4$ Å and n=10 Å -1.

N-Plane Collective Variable

The N-Plane collective variable is useful for probing the adsorption of adatom/admolecules to a surface. It is defined as the *average distance* of the adatom/admolecule from a given layer in the slab along the surface normal:

$$s = Z_{ads} - \frac{1}{N_{plane}} \sum_{i=1}^{N_{plane}} Z_i$$

where Z_{ads} denotes the position of the adatom/admolecule/impurity along the surface normal (here, we assume the surface normal to be the z-axis) and the summation over iruns over N_{plane} atoms at Z_i which form the layer. The layer could be on the face or in the interior of the slab.

Input

Input to a metadynamics simulation is contained within the METADYNAMICS sub-block. Listed below is the the format of a METADYNAMICS sub-block,

NWPW

```
METADYNAMICS
    Γ
   BOND <integer atom1 index no default> <integer atom2 index
no default>
         [W <real w default 0.00005>]
         [SIGMA <real sigma default 0.1>]
         [RANGE <real a b default (see input description)>]
         [NRANGE <integer nrange default 501>]
    ...]
    [
    ANGLE <integer atom1 index no default> <integer
atom2 index no default> <integer atom3 index no default>
         [W <real w default 0.00005>]
         [SIGMA <real sigma default 0.1>]
         [RANGE <real a b default 0
[UNIQ-math-103-de8df65943921cf5-QINU[>]
         [NRANGE <integer nrange default 501>]
    ...]
    [
    COORD_NUMBER [INDEX1 <integer_list atom1_indexes no
default>][INDEX2 <integer_list atom2_indexes no default>]
         [SPRIK]
         [N <real n default 6.0>]
         [M <real m default 12.0>]
         [R0 <real r0 default 3.0>]
         [W <real w default 0.00005>]
         [SIGMA <real sigma default 0.1>]
         [RANGE <real a b no default>]
         [NRANGE <integer nrange default 501>]
    ...]
    [
```

```
N-PLANE <integer atom1_index no default> <integer_list
atom_indexes no default>
        [W <real w default 0.00005>]
        [SIGMA <real sigma default 0.1>]
        [RANGE <real a b no default>]
        [NRANGE <integer nrange default 501>]
        [NVECTOR <real(3) nx ny nz>]
        ...]
     [UPDATE <integer meta_update default 1>]
     [PRINT_SHIFT <integer print_shift default 0>]
     [TEMPERED <real tempered_temperature no default>]
    END
END
```

Multiple collective variables can be defined at the same time, e.g.

```
NWPW
METADYNAMICS
BOND 1 8 W 0.0005 SIGMA 0.1
BOND 1 15 W 0.0005 SIGMA 0.1
END
END
```

will produce a two-dimensional potential energy surface.

Car-Parrinello Output Datafiles

XYZ motion file

Data file that stores ion positions and velocities as a function of time in XYZ format.

```
[line 1: ] n_ion
[line 2: ] do ii=1,n_ion
[line 2+ii: ] atom_name(ii), x(ii),y(ii),z(ii),vx(ii),vy(ii),vz(ii)
end do
[line n_ion+3 ] n_nion
do ii=1,n_ion
[line n_ion+3+ii: ] atom_name(ii), x(ii),y(ii),z(ii),
vx(ii),vy(ii),vz(ii)
end do
[line 2*n_ion+4: ] ....
```

ION_MOTION motion file

Datafile that stores ion positions and velocities as a function of time

```
[line 1: ] it_out, n_ion, omega, al.x,al.y,al.z, a2.x,a2,y,a2.z,
a3.x,a3.y,a3.z
[line 2: ] time
do ii=1,n_ion
[line 2+ii: ] ii, atom_symbol(ii),atom_name(ii), x(ii),y(ii),z(ii),
```

```
vx(ii),vy(ii),vz(ii)
end do
[line n_ion+3 ] time
do do ii=1,n_ion
[line n_ion+3+ii: ] ii, atom_symbol(ii),atom_name(ii),
x(ii),y(ii),z(ii), vx(ii),vy(ii),vz(ii)
end do
[line 2*n_ion+4: ] ....
```

EMOTION motion file

Datafile that store energies as a function of time.

```
[line 1: ] time, E1,E2,E3,E4,E5,E6,E7,E8,(E9,E10, if
Nose-Hoover),eave,evar,have,hvar,ion_Temp
[line 2: ] ...
```

where

```
E1 = total energy
E2 = potential energy
E3 = ficticious kinetic energy
E4 = ionic kinetic energy
E5 = orbital energy
E6 = hartree energy
E7 = exchange-correlation energy
E8 = ionic energy
eave = average potential energy
evar = variance of potential energy
have = average total energy
hvar = variance of total energy
ion_Temp = temperature
```

HMOTION motion file

Datafile that stores the rotation matrix as a function of time.

```
[line 1: ] time
[line 2: ] ms,ne(ms),ne(ms)
do i=1,ne(ms)
[line 2+i: ] (hml(i,j), j=1,ne(ms)
end do
[line 3+ne(ms): ] time
[line 4+ne(ms): ] ....
```

EIGMOTION motion file

Datafile that stores the eigenvalues for the one-electron orbitals as a function of time.

[line 1:] time, (eig(i), i=1,number_orbitals)
[line 2:] ...

OMOTION motion file

Datafile that stores a reduced representation of the one-electron orbitals. To be used with a molecular orbital viewer that will be ported to NWChem in the near future.

Steepest Descent

The functionality of this task is now performed automatically by the PSPW and BAND. For backward compatibility, we provide a description of the input to this task.

The steepest_descent task is used to optimize the one-electron orbitals with respect to the total energy. In addition it can also be used to optimize geometries. This method is meant to be used for coarse optimization of the one-electron orbitals.

Input to the steepest_descent simulation is contained within the steepest_descent sub-block.

```
NWPW

...

STEEPEST_DESCENT

...

END

...

END
```

To run a steepest_descent calculation the following directive is used:

```
TASK PSPW steepest_descent
TASK BAND steepest_descent
```

The steepest_descent sub-block contains a great deal of input, including pointers to data, as well as parameter input. Listed below is the format of a STEEPEST_DESCENT sub-block.

```
NWPW
```

```
STEEPEST_DESCENT
CELL_NAME <string cell_name>
[GEOMETRY_OPTIMIZE]
INPUT_WAVEFUNCTION_FILENAME <string input_wavefunctions default
file_prefix.movecs>
OUTPUT_WAVEFUNCTION_FILENAME <string output_wavefunctions default
file_prefix.movecs>
FAKE_MASS <real fake_mass default 400000.0>
TIME_STEP <real time_step default 5.8>
LOOP <integer inner_iteration outer_iteration default 10 1>
TOLERANCES <real tole tolc tolr default 1.0d-9 1.0d-9 1.0d-4>
ENERGY CUTOFF <real ecut default (see input desciption)>
```

```
WAVEFUNCTION_CUTOFF <real wcut default (see input
description)>
   EWALD NCUT <integer ncut default 1>
   EWALD_RCUT <real rcut default (see input description)>
  XC (Vosko
                 || LDA
                                 || PBE96
                                                  || revPBE
                                                                  HF
              LDA-SIC
                 || LDA-SIC/2 || LDA-0.4SIC || LDA-SIC/4
                                                                  LDA-0.2SIC
             PBE96-SIC || PBE96-SIC/2 || PBE96-0.4SIC || PBE96-SIC/4
                                                                  PBE96-0.2SIC ||
       revPBE-SIC || revPBE-SIC/2 || revPBE-0.4SIC || revPBE-SIC/4 ||
revPBE-0.2SIC ||
       PBE0
                 || revPBE0
                                 || default Vosko)
   [MULLIKEN]
END
. . .
END
```

The following list describes the input for the STEEPEST_DESCENT sub-block.

- <cell_name> name of the simulation_cell named <cell_name>. See Simulation Cell.
- GEOMETRY_OPTIMIZE optional keyword which if specified turns on geometry optimization.
- <input_wavefunctions> name of the file containing one-electron orbitals
- <output_wavefunctions> name of the file tha will contain the one-electron orbitals at the end of the run.
- <fake_mass> value for the electronic fake mass (μ).
- <time_step> value for the time step (Δt).
- <inner_iteration> number of iterations between the printing out of energies and tolerances
- <outer_iteration> number of outer iterations
- <tole> value for the energy tolerance.
- <tolc> value for the one-electron orbital tolerance.
- <tolr> value for the ion position tolerance.
- <ecut> value for the cutoff energy used to define the density. Default is set to be the maximum value that will fit within the simulation_cell <cell_name>.
- <wcut> value for the cutoff energy used to define the one-electron orbitals. Default is set to be the maximum value that will fit within the simulation_cell <cell_name>.
- <ncut> value for the number of unit cells to sum over (in each direction) for the real space part of the Ewald summation. Note Ewald summation is only used if the simulation cell is periodic.
- <rcut> value for the cutoff radius used in the Ewald summation. Note Ewald summation is only used if the simulation_cell is periodic.

Default set to be
$$rac{MIN(ert ec{a_i}ert)}{\pi}, i=1,2,3.$$

 (Vosko || PBE96 || revPBE || ...) - Choose between Vosko et al's LDA parameterization or the orginal and revised Perdew, Burke, and Ernzerhof GGA functional. In addition, several hybrid options (hybrid options are not available in BAND). • MULLIKEN - optional keyword which if specified causes a Mulliken analysis to be performed at the end of the simulation.

Simulation Cell

The simulation cell parameters are entered by defining a simulation_cell sub-block within the PSPW block. Listed below is the format of a simulation_cell sub-block.

```
NWPW
...
SIMULATION_CELL CELL_NAME <string name default 'cell_default'>
BOUNDARY_CONDITIONS (periodic || aperiodic default periodic)
LATTICE_VECTORS
    <real a1.x a1.y a1.z default 20.0 0.0 0.0>
    <real a2.x a2.y a2.z default 0.0 20.0 0.0>
    <real a3.x a3.y a3.z default 0.0 20.0>
NGRID <integer nal na2 na3 default 32 32 32> END
...
```

END

Basically, the user needs to enter the dimensions, gridding and boundary conditions of the simulation cell. The following list describes the input in detail.

- <name> user-supplied name for the simulation block.
- periodic keyword specifying that the simulation cell has periodic boundary conditions.
- aperiodic keyword specifying that the simulation cell has free-space boundary conditions.
- <a1.x a1.y a1.z> user-supplied values for the first lattice vector
- <a2.x a2.y a2.z> user-supplied values for the second lattice vector
- <a3.x a3.y a3.zh> user-supplied values for the third lattice vector
- <na1 na2 na3> user-supplied values for discretization along lattice vector directions.

Alternatively, instead of explicitly entering lattice vectors, users can enter the unit cell using the standard cell parameters, a, b, c, α , β , and γ , by using the LATTICE block. The format for input is as follows:

NWPW

```
SIMULATION_CELL
...
LATTICE
[lat_a <real a default 20.0>]
[lat_b <real b default 20.0>]
[lat_c <real c default 20.0>]
[alpha <real alpha default 90.0>]
[beta <real beta default 90.0>]
[gamma <real gamma default 90.0>]
END
...
END
...
```

END

The user can also enter the lattice vectors of standard unit cells using the keywords SC, FCC, BCC, for simple cubic, face-centered cubic, and body-centered cubic respectively. Listed below is an example of the format of this type of input.

NWPW

```
SIMULATION_CELL SC 20.0
....
END
...
END
```

Finally, the lattice vectors from the unit cell can also be defined using the fractional coordinate input in the GEOMETRY input (see section Geometry Lattice Parameters). Listed below is an example of the format of this type of input for an 8 atom silicon carbide unit cell.

```
geometry units au
system crystal
  lat a 8.277d0
  lat b 8.277d0
  lat c 8.277d0
  alpha 90.0d0
   beta 90.0d0
  gamma 90.0d0
end
Si -0.50000d0 -0.50000d0 -0.50000d0
Si 0.00000d0 0.00000d0 -0.50000d0
Si 0.00000d0 -0.50000d0 0.00000d0
Si -0.50000d0 0.00000d0 0.00000d0
C -0.25000d0 -0.25000d0 -0.25000d0
C 0.25000d0 0.25000d0 -0.25000d0
C 0.25000d0 -0.25000d0 0.25000d0
C -0.25000d0 0.25000d0 0.25000d0
end
```

Warning - Currently only the "system crystal" option is recognized by NWPW. The "system slab" and "system polymer" options will be supported in the future.

Unit Cell Optimization

The PSPW module using the DRIVER geometry optimizer can optimize a crystal unit cell. Currently this type of optimization works only if the geometry is specified in fractional coordinates. The following SET directive is used to tell the DRIVER geometry optimizer to optimize the crystal unit cell in addition to the geometry.

```
set includestress .true.
```

SMEAR -Fractional Occupation of the Molecular Orbitals

The smear keyword to turn on fractional occupation of the molecular orbitals in PSPW and **BAND** calculations

```
SMEAR <sigma default 0.001> [TEMPERATURE <temperature>]
[FERMI || GAUSSIAN default FERMI]
                            [ORBITALS <integer orbitals default
```

4>]

Both Fermi-Dirac (FERMI) and Gaussian broadening functions are available. The ORBITALS keyword is used to change the number of virtual orbitals to be used in the calculation. Note to use this option the user must currently use the SCF minimizer. The following SCF options are recommended for running fractional occupation

SCF Anderson outer iterations 0 Kerker 2.0

Spin Penalty Functions

Spin-penalty functions makes it easier to define antiferromagnetic structures. These functions are implemented by adding a scaling factor to the non-local psp for up/down spins on atoms and angular momentum that you specify.

Basically, the pseudopotential energy

$$E_{psp} = \sum_{\sigma=\uparrow,\downarrow} \sum_{i=1}^{n_{elc}^{\sigma}} \sum_{I=1}^{n_{ions}} \left(<\psi_i^{\sigma} | V_{local}^{I} | \psi_i^{\sigma} > + \sum_{l=0}^{l_{max}} \sum_{m=-l}^{l} \sum_{n=1}^{n_{max}^{I}} \sum_{n'=1}^{n_{max}^{I}} <\psi_i^{\sigma} | P_{nlm}^{I} > h_{l,n,n'}^{I} < P_{n'lm}^{I} | \psi_i^{\sigma} > \right)$$
was modified to

was modified to

$$E_{psp} = \sum_{\sigma=\uparrow,\downarrow} \sum_{i=1}^{n_{elc}^{\sigma}} \sum_{I=1}^{n_{ions}} \left(<\psi_i^{\sigma} | V_{local}^I | \psi_i^{\sigma} > + \sum_{l=0}^{l_{max}} \sum_{m=-l}^{n_{max}} \sum_{n=1}^{n_{max}^I} \sum_{n'=1}^{n_{max}^I} (1 - \delta_{l,l^{\sigma}} \delta_{I,ionlist^{\sigma}} (\xi^{\sigma} - 1)) < \psi_i^{\sigma} | P_{nlm}^I > h_{l,n,n'}^I \right)$$

An example input is as follows:

```
title "hematite 10 atoms"
start hema10
memory 1900 mb
permanent dir ./perm
scratch dir
              ./perm
geometry center noautosym noautoz print
```

system crystal

```
lat_a 5.42
```

lat_b 5.42 lat_c 5.42 alpha 55.36 beta 55.36 gamma 55.36 end	5		
Fo	0 355000	0 355000	0 355000
Fe	0.555000	0.333000	0.333000
Fe	-0.355000	-0.355000	-0.355000
Fe	0.855000	0.855000	0.855000
0	0.550000	-0.050000	0.250000
0	0.250000	0.550000	-0.050000
0	-0.050000	0.250000	0.550000
0	-0.550000	0.050000	-0.250000
0	-0.250000	-0.550000	0.050000
0	0.050000	-0.250000	-0.550000
end			
odft ewald_rcut 3 ewald_ncut 8 xc pbe96 lmbfgs cutoff 10.0 mult 1 dplot density c end	3.0 3 diff diff1.cube		
#spin penalt pspspin up pspspin dowr end	ty functions d -1.0 1:2 n d -1.0 3:4		
task pspw ener task pspw pspv	rgy v_dplot		
nwpw pspspin off dplot density o end end task pspy epot	liff diff2.cube		
task pspw ener	yy v_dplot		

AIMD/MM (QM/MM)

A QM/MM capability is available that is integrated with PSPW module and can be used with Car-Parrinello simulations. Currently, the input is not very robust but it is straightforward. The first step to run a QM/MM simulations is to define the MM atoms in the geometry block. The MM atoms must be at the end of the geometry and a carat, " $^$ ", must be appended to the end of the atom name, e.g.

```
geometry units angstrom nocenter noautosym noautoz print xyz
C -0.000283 0.000106 0.000047
Cl -0.868403 1.549888 0.254229
Cl 0.834043 -0.474413 1.517103
Cl -1.175480 -1.275747 -0.460606
Cl 1.209940 0.200235 -1.310743
O^ 0.3226E+01 -0.4419E+01 -0.5952E+01
H^ 0.3193E+01 -0.4836E+01 -0.5043E+01
H^ 0.4167E+01 -0.4428E+01 -0.6289E+01
O^ 0.5318E+01 -0.3334E+01 -0.1220E+01
H^ 0.4978E+01 -0.3040E+01 -0.2113E+01
H^ 0.5654E+01 -0.2540E+01 -0.7127E+00
end
```

Another way to specify the MM atoms is to use the mm_tags option which appends the atoms with a " $^$ ".

```
geometry units angstrom nocenter noautosym noautoz print xyz
C -0.000283 0.000106 0.000047
Cl -0.868403 1.549888 0.254229
Cl 0.834043 -0.474413 1.517103
Cl -1.175480 -1.275747 -0.460606
Cl 1.209940 0.200235 -1.310743
0 0.3226E+01 -0.4419E+01 -0.5952E+01
H 0.3193E+01 -0.4836E+01 -0.5043E+01
H 0.4167E+01 -0.4428E+01 -0.6289E+01
0 0.5318E+01 -0.3334E+01 -0.1220E+01
H 0.4978E+01 -0.3040E+01 -0.2113E+01
H 0.5654E+01 -0.2540E+01 -0.7127E+00
end
NWPW
 OMMM
    mm_tags 6:11
 END
END
```

The option "mm_tags off" can be used to remove the " ^ " from the atoms, i.e.

```
NWPW
QMMM
mm_tags 6:11 off
END
```

END

Next the pseudopotentials have be defined for the every type of MM atom contained in the geometry blocks. The following local pseudopotential suggested by Laio, VandeVondele and Rothlisberger can be automatically generated.

 $V(\vec{r}) = -Z_{ion} \frac{r_c{}^{n\sigma} - r^{n\sigma}}{-sign(Z_{ion}) * r_c{}^{n\sigma+1} - r^{n\sigma+1}}$

The following input To define this pseudopo the O^ MM atom using the following input

```
NWPW

QMMM

mm_psp 0^ -0.8476 4 0.70

END

END
```

defines the local pseudopotential for the O^ MM atom , where $Z_{ion} = -0.8476$, $n_{\sigma} = 4$, and $r_c = 0.7$. The following input can be used to define the local pseudopotentials for all the MM atoms in the geometry block defined above

NWPW QMMM mm_psp 0^ -0.8476 4 0.70 mm_psp H^ 0.4238 4 0.40 END END

Next the Lenard-Jones potentials for the QM and MM atoms need to be defined. This is done as as follows

NWPW

```
QMMM
    lj_ion_parameters C 3.41000000d0 0.10d0
    lj_ion_parameters Cl 3.45000000d0 0.16d0
    lj_ion_parameters 0^ 3.16555789d0 0.15539425d0
    END
END
```

Note that the Lenard-Jones potential is not defined for the MM H atoms in this example. The final step is to define the MM fragments in the simulation. MM fragments are a set of atoms in which bonds and angle harmonic potentials are defined, or alternatively shake constraints are defined. The following input defines the fragments for the two water molecules in the above geometry,

```
angle_spring 2 1 3 0.07293966 1.910611932 #angle i j k Kspring
theta0
end
END
END
```

The fragments can be defined using shake constraints as

```
NWPW

QMMM

fragment spc

size 3 #size of fragment

index_start 6:9:3 #atom index list that defines the start of

# the fragments (start:final:stride)

shake units angstroms 1 2 3 cyclic 1.0 1.632993125 1.0

end

END

END
```

Alternatively, each water could be defined independently as follows.

```
NWPW
QMMM
   fragment spc1
     size 3
                             #size of fragment
                             #atom index list that defines the start of
     index start 6
                             #the fragments
     bond spring 1 2 0.467307856 1.889726878 #bond i j Kspring r0
     bond spring 1 3 0.467307856 1.889726878 #bond i j Kspring r0
     angle spring 2 1 3 0.07293966 1.910611932 #angle i j k Kspring
theta0
   end
  fragment spc2
     size 3
                             #size of fragment
                             #atom index list that defines the start of
     index start 9
                             #the fragments
     shake units angstroms 1 2 3 cyclic 1.0 1.632993125 1.0
  end
END
END
```

PSP_GENERATOR

A one-dimensional pseudopotential code has been integrated into NWChem. This code allows the user to modify and develop pseudopotentials. Currently, only the Hamann and Troullier-Martins norm-conserving pseudopotentials can be generated. In future releases, the pseudopotential library (section Pseudopotential and PAW basis Libraries) will be more complete, so that the user will not have explicitly generate pseudopotentials using this

module.

Input to the PSP_GENERATOR task is contained within the PSP_GENERATOR sub-block.

```
NWPW
```

```
PSP_GENERATOR
...
END
...
END
```

To run a PSP GENERATOR calculation the following directive is used:

```
TASK PSPW PSP_GENERATOR
```

Listed below is the format of a PSP_GENERATOR sub-block.

NWPW

```
...
PSP_GENERATOR
PSEUDOPOTENTIAL_FILENAME: <string psp_name>
ELEMENT: <string element>
CHARGE: <real charge>
MASS_NUMBER: <real mass_number>
ATOMIC_FILLING: <integer ncore nvalence> ( (1||2||...)
(s||p||d||f||...) <real filling> ...)
```

```
[CUTOFF: <integer lmax> ( (s||p||d||f||g) <real rcut>
```

```
...)]
```

```
PSEUDOPOTENTIAL_TYPE: (TROULLIER-MARTINS || HAMANN default HAMANN)
SOLVER_TYPE: (PAULI || SCHRODINGER default PAULI)
EXCHANGE_TYPE: (dirac || PBE96 default DIRAC)
CORRELATION_TYPE: (VOSKO || PBE96 default VOSKO)
[SEMICORE_RADIUS: <real rcore>]
```

END

```
...
END
```

The following list describes the input for the PSP_GENERATOR sub-block.

- <psp_name> name that points to a.
- <element> Atomic symbol.
- <charge> charge of the atom
- <mass> mass number for the atom
- <ncore> number of core states
- <nvalence> number of valence states.
- ATOMIC_FILLING:.....(see below)
- <filling> occupation of atomic state
- CUTOFF:....(see below)
- <rcore> value for the semicore radius (see below)

ATOMIC_FILLING Block

This required block is used to define the reference atom which is used to define the pseudopotential. After the ATOMIC_FILLING: <ncore> <nvalence> line, the core states are listed (one per line), and then the valence states are listed (one per line). Each state contains two integer and a value. The first integer specifies the radial quantum number, n, the second integer specifies the angular momentum quantum number, l, and the third value specifies the occupation of the state.

For example to define a pseudopotential for the Neon atom in the $1s^22s^22p^6$ state could have the block

```
ATOMIC_FILLING: 1 2

1 s 2.0 #core state - 1s^2

2 s 2.0 #valence state - 2s^2

2 p 6.0 #valence state - 2p^6
```

for a pseudopotential with a 2s and 2p valence electrons or the block

ATOMIC_FILLING: 3 0 1 s 2.0 #core state 2 s 2.0 #core state 2 p 6.0 #core state

could be used for a pseudopotential with no valence electrons.

CUTOFF

This optional block specifies the cutoff distances used to match the all-electron atom to the pseudopotential atom. For Hamann pseudopotentials $r_{cut}(l)$ defines the distance where the all-electron potential is matched to the pseudopotential, and for Troullier-Martins pseudopotentials $r_{cut}(l)$ defines the distance where the all-electron orbital is matched to the pseudowavefunctions. Thus the definition of the radii depends on the type of pseudopotential. The cutoff radii used in Hamann pseudopotentials will be smaller than the cutoff radii used in Troullier-Martins pseudopotentials.

For example to define a softened Hamann pseudopotential for Carbon would be

ATOMIC_FILLING: 1 2 1 s 2.0 2 s 2.0 2 p 2.0 CUTOFF: 2 s 0.8 p 0.85 d 0.85

while a similarly softened Troullier-Marting pseudopotential for Carbon would be

ATOMIC_FILLING: 1 2 1 s 2.0 2 s 2.0 2 p 2.0 CUTOFF: 2 p 1.275

d 1.275

SEMICORE_RADIUS

Specifying the SEMICORE_RADIUS option turns on the semicore correction approximation proposed by Louie et al (S.G. Louie, S. Froyen, and M.L. Cohen, Phys. Rev. B, **26**(, 1738, (1982)). This approximation is known to dramatically improve results for systems containing alkali and transition metal atoms.

The implementation in the PSPW module defines the semi-core density, $\rho_{semicore}$ in terms of the core density, ρ_{core} , by using the sixth-order polynomial

 $\rho_{semicore}(r) = \begin{cases} \rho_{core} & \text{if } r \ge r_{semicore} \\ c_0 + c_3 r^3 + c_4 r^4 + c_5 r^5 + c_6 r^6 & \text{if } r < r_{semicore} \end{cases}$

This expansion was suggested by Fuchs and Scheffler (M. Fuchs, and M. Scheffler, Comp. Phys. Comm., **119**,67 (1999)), and is better behaved for taking derivatives (i.e. calculating ionic forces) than the expansion suggested by Louie et al.

PAW Tasks

All input to the PAW Tasks is contained within the compound NWPW block,

NWPW

• • •

END

To perform an actual calculation a TASK PAW directive is used (Task).

TASK PAW

In addition to the directives listed in Task, i.e.

```
TASK paw energy
TASK paw gradient
TASK paw optimize
TASK paw saddle
TASK paw freqencies
TASK paw vib
```

there are additional directives that are specific to the PSPW module, which are:

```
TASK PAW [Car-Parrinello || steepest_descent ]
```

Once a user has specified a geometry, the PAW module can be invoked with no input directives (defaults invoked throughout). There are sub-directives which allow for customized application; those currently provided as options for the PAW module are:

```
NWPW
CELL_NAME <string cell_name default 'cell_default'>
[GEOMETRY_OPTIMIZE]
INPUT_WAVEFUNCTION_FILENAME <string input_wavefunctions default
input_movecs>
```

```
OUTPUT_WAVEFUNCTION_FILENAME <string output_wavefunctions default
input movecs>
FAKE_MASS <real fake_mass default 400000.0>
TIME STEP <real time step default 5.8>
LOOP <integer inner iteration outer iteration default 10 100>
TOLERANCES <real tole tolc default 1.0e-7 1.0e-7>
CUTOFF <real cutoff>
ENERGY CUTOFF <real ecut default (see input description)>
WAVEFUNCTION CUTOFF <real wcut default (see input description)>
EWALD NCUT <integer ncut default 1>]
EWALD RCUT <real rcut default (see input description)>
XC (Vosko || PBE96 || revPBE default Vosko)
DFT||ODFT||RESTRICTED||UNRESTRICTED
MULT <integer mult default 1>
INTEGRATE MULT L <integer imult default 1>
SIMULATION CELL
   ... (see input description)
END
CAR-PARRINELLO
   ... (see input description)
END
MAPPING <integer mapping default 1>
END
```

The following list describes these keywords.

- <cell_name> name of the the simulation_cell named <cell_name>. The current version of PAW only accepts periodic unit cells. See Simulation Cell.
- GEOMETRY_OPTIMIZE optional keyword which if specified turns on geometry optimization.
- <input_wavefunctions> name of the file containing one-electron orbitals
- <output_wavefunctions> name of the file that will contain the one-electron orbitals at the end of the run.
- <fake_mass> value for the electronic fake mass (μ). This parameter is not presently used in a conjugate gradient simulation
- <time_step> value for the time step (Δt). This parameter is not presently used in a conjugate gradient simulation.
- <inner_iteration> number of iterations between the printing out of energies and tolerances
- <outer_iteration> number of outer iterations
- <tole> value for the energy tolerance.
- <tolc> value for the one-electron orbital tolerance.
- <cutoff> value for the cutoff energy used to define the wavefunction. In addition using the CUTOFF keyword automatically sets the cutoff energy for the density to be twice the wavefunction cutoff.
- <ecut> value for the cutoff energy used to define the density. Default is set to be the maximum value that will fit within the simulation_cell <cell_name>.

- <wcut> value for the cutoff energy used to define the one-electron orbitals. Default is set to be the maximum value that will fix within the simulation_cell <cell_name>.
- <ncuth> value for the number of unit cells to sum over (in each direction) for the real space part of the smooth compensation summation.
- <rcut> value for the cutoff radius used in the smooth compensation summation.

Default set to be
$$rac{MIN(ert ec{a_i}ert)}{\pi}, i=1,2,3.$$

- (Vosko || PBE96 || revPBE) Choose between Vosko et al's LDA parametrization or the original and revised Perdew, Burke, and Ernzerhof GGA functional.
- MULT optional keyword which if specified allows the user to define the spin multiplicity of the system
- INTEGRATE_MULT_L optional keyword which if specified allows the user to define the angular XC integration of the augmented region
- SIMULATION_CELL (see [[#Simulation Cell|Simulation Cell])
- CAR-PARRINELLO(see [[#Car-Parrinello|Car-Parrinello])
- <mapping> for a value of 1 slab FFT is used, for a value of 2 a 2d-Hilbert FFT is used.

Pseudopotential and PAW basis Libraries

A library of pseudopotentials used by PSPW and BAND is currently available in the directory \$NWCHEM_TOP/src/nwpw/libraryp/pspw_default

The elements listed in the following table are present:

	H		_															Не
	Li	Ве	_										В	С	N	0	F	Ne
-	Na	Mg	_										Al	Si	Р	S	Cl	Ar
-	K	Ca	Sc	Τi	V	Cr	Mn	Fe	Со	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr
-	Rb	Sr	Y	Zr	Nb	Мо	Тс	Ru	Rh	Pd	Ag	Cd	In	Sn	Sb	Те	I	Xe
-	Cs	Ва	La	Hf	Та	W	Re	0s	Ir	Pt	Au	Hg	тι	Pb	Bi	Ро	At	Rn
	Fr	Ra	•															
				•	•	•	•	•	•	Gd	•	•	•	•	•	•	•	
				•	•	U	•	Pu	•	•	•	•			•	•	•	

The pseudopotential libraries are continually being tested and added. Also, the PSPW program can read in pseudopotentials in CPI and TETER format generated with pseudopotential generation programs such as the OPIUM package of Rappe et al. The user can request additional pseudopotentials from Eric J. Bylaska at (Eric.Bylaska@pnl.gov).

н Не - - - - - - -Li Be B C N O F Ne _ _ _ _ _ _ _ _ Al Si P S Cl Ar Na Mg K Ca Sc Ti V Cr Mn Fe Co Ni Cu Zn Ga Ge As Se Br Kr

Similarly, a library of PAW basis used by PAW is currently available in the directory \$NWCHEM_TOP/src/nwpw/libraryp/paw_default

Currently there are not very many elements available for PAW. However, the user can request additional basis sets from Eric J. Bylaska at (Eric.Bylaska@pnl.gov).

A preliminary implementation of the HGH pseudopotentials (Hartwigsen, Goedecker, and Hutter) has been implemented into the PSPW module. To access the pseudopotentials the pseudopotentials input block is used. For example, to redirect the code to use HGH pseudopotentials for carbon and hydrogen, the following input would be used.

```
nwpw
...
pseudopotentials
C library HGH_LDA
H library HGH_LDA
end
...
end
```

The implementation of HGH pseudopotentials is rather limited in this release. HGH pseudopotentials cannot be used to optimize unit cells, and they do not work with the MULLIKEN option. They also have not yet been implemented into the BAND structure code.

To read in pseudopotentials in CPI format the following input would be used.

```
nwpw
...
pseudopotentials
C CPI c.cpi
H CPI h.cpi
```

In order for the program to recognize the CPI format the CPI files, e.g. c.cpi have to be prepended with the "<CPI>" keyword.

To read in pseudopotentials in TETER format the following input would be used.

```
nwpw
...
pseudopotentials
C TETER c.teter
H TETER h.teter
end
...
end
```

In order for the program to recognize the TETER format the TETER files, e.g. c.teter have to be prepended with the "<TETER>" keyword.

If you wish to redirect the code to a different directory other than the default one, you need to set the environmental variable NWCHEM_NWPW_LIBRARY to the new location of the libraryps directory.

NWPW RTDB Entries and Miscellaneous DataFiles

Input to the PSPW and Band modules are contained in both the RTDB and datafiles. The RTDB is used to store input that the user will need to directly specify. Input of this kind includes ion positions, ion velocities, and simulation cell parameters. The datafiles are used to store input, such the one-electron orbitals, one-electron orbital velocities, formatted pseudopotentials, and one-dimensional pseudopotentials, that the user will in most cases run a program to generate.

Ion Positions

The positions of the ions are stored in the default geometry structure in the RTDB and must be specified using the GEOMETRY directive.

Ion Velocities

The velocities of the ions are stored in the default geometry structure in the RTDB, and must be specified using the GEOMETRY directive.

Wavefunction Datafile

The one-electron orbitals are stored in a wavefunction datafile. This is a binary file and cannot be directly edited. This datafile is used by steepest_descent and Car-Parrinello tasks and can be generated using the wavefunction_initializer or wavefunction_expander tasks.

Velocity Wavefunction Datafile

The one-electron orbital velocities are stored in a velocity wavefunction datafile. This is a binary file and cannot be directly edited. This datafile is automatically generated the first time a Car-Parrinello task is run.

Formatted Pseudopotential Datafile

The pseudopotentials in Kleinman-Bylander form expanded on a simulation cell (3d grid) are stored in a formatted pseudopotential datafile (PSPW-"atomname.vpp", BAND-"atomname.cpp", PAW-"atomname.jpp"). These are binary files and cannot be directly edited. These datafiles are automatically generated.

One-Dimensional Pseudopotential Datafile

The one-dimensional pseudopotentials are stored in a one-dimensional pseudopotential file ("atomname.psp"). This is an ASCII file and can be directly edited with a text editor or can be generated using the pspw_generator task. However, these datafiles are usually atomatically generated.

The data stored in the one-dimensional pseudopotential file is

```
character*2 element :: element name
integer charge :: valence charge of ion
real mass :: mass of ion
integer lmax :: maximum angular component
real rcut(lmax) :: cutoff radii used to define pseudopotentials
integer nr :: number of points in the radial grid
real dr :: linear spacing of the radial grid
real r(nr):: one-dimensional radial grid
real Vpsp(nr,lmax) :: one-dimensional pseudopotentials
real psi(nr,lmax) :: one-dimensional pseudowavefunctions
real r_semicore :: semicore radius
real rho_semicore(nr) :: semicore density
```

and the format of it is:

```
[line 1: ] element [line 2: ] charge mass lmax
[line 3: ] (rcut(l), l=1,lmax)
[line 4: ] nr dr
[line 5: ] r(1) (Vpsp(1,l), l=1,lmax)
[line 6: ] ....
[line nr+4: ] r(nr) (Vpsp(nr,l), l=1,lmax)
[line nr+5: ] r(1) (psi(1,l), l=1,lmax) [line nr+6: ] ....
[line 2*nr+4:] r(nr) (psi(nr,l), l=1,lmax)
[line 2*nr+5:] r_semicore
if (r_semicore read) then
[line 2*nr+6:] r(1) rho_semicore(1)
[line 2*nr+7:] ....
[line 3*nr+5:] r(nr) rho_semicore(nr)
end if
```

Car-Parrinello Scheme for Ab Initio Molecular Dynamics

Car and Parrinello developed a unified scheme for doing *ab initio* molecular dynamics by combining the motion of the ion cores and a fictitious motion for the Kohn-Sham orbitals of density-functional theory (R. Car and M. Parrinello, Phys. Rev. Lett. **55**, 2471, (1985) - simple introduction Media:Cpmd-lecture.pdf). At the heart of this method they introduced a fictitious kinetic energy functional for the Kohn-Sham orbitals.

$$KE\left(\left\{\psi_{i,\sigma}(\vec{r})\right\}\right) = \sum_{i,\sigma}^{occ} \int d\vec{r} \; \mu \left|\dot{\psi}_{i,\sigma}(\vec{r})\right|^2$$

Given this kinetic energy the constrained equations of motion are found by taking the first variation of the auxiliary Lagrangian.

$$\begin{split} L &= \sum_{i,\sigma}^{occ} \int d\vec{r} \; \mu \left| \dot{\psi}_{i,\sigma}(\vec{r}) \right|^2 + \frac{1}{2} \sum_I M_I \left| \dot{\vec{R}}_I \right|^2 - E \left[\left\{ \psi_{i,\sigma}(\vec{r}) \right\}, \left\{ \vec{R}_I \right\} \right] \\ &+ \sum_{ij,\sigma} \Lambda_{ij,\sigma} \left(\int d\vec{r} \; \psi^*_{i,\sigma}(\vec{r}) \psi_{j,\sigma}(\vec{r}) - \delta_{ij\sigma} \right) \end{split}$$

Which generates a dynamics for the wavefunctions $\psi_{i,\sigma}(\vec{r})$ and atoms positions \vec{R}_I through the constrained equations of motion:

$$egin{aligned} & \mu\ddot{\psi}_{i,\sigma}(ec{r},t) = -rac{\delta E}{\delta\psi^*_{i,\sigma}(ec{r},t)} + \sum_j \Lambda_{ij,\sigma}\psi_{j,\sigma}\left(ec{r},t
ight) \\ & M_I \ddot{ec{R}}_I = -rac{\partial E}{\partialec{R}_I} \end{aligned}$$

where μ is the fictitious mass for the electronic degrees of freedom and M_I are the ionic masses. The adjustable parameter μ is used to describe the relative rate at which the wavefunctions change with time. $\Lambda_{ij,\sigma}$ are the Lagrangian multipliers for the orthonormalization of the single-particle orbitals $\psi_{i,\sigma}(\vec{r})$. They are defined by the orthonormalization constraint conditions and can be rigorously found. However, the equations of motion for the Lagrange multipliers depend on the specific algorithm used to integrate the Eqns. above.

For this method to give ionic motions that are physically meaningful the kinetic energy of the Kohn-Sham orbitals must be relatively small when compared to the kinetic energy of the ions. There are two ways where this criterion can fail. First, the numerical integrations for the Car-Parrinello equations of motion can often lead to large relative values of the kinetic energy of the Kohn-Sham orbitals relative to the kinetic energy of the ions. This kind of failure is easily fixed by requiring a more accurate numerical integration, i.e. use a smaller time step for the numerical integration. Second, during the motion of the system a the ions can be in locations where there is an Kohn-Sham orbital level crossing, i.e. the density-functional energy can have two states that are nearly degenerate. This kind of failure often occurs in the study of chemical reactions. This kind of failure is not easily fixed and requires the use of a more sophisticated density-functional energy that accounts for low-lying excited electronic states.

Verlet Algorithm for Integration

Integrating the Eqns. above using the Verlet algorithm results in

$$\begin{split} \psi_{i,\sigma}^{t+\Delta t} &\leftarrow 2\psi_{i,\sigma}^t - \psi_{i,\sigma}^{t-\Delta t} + \frac{(\Delta t)^2}{\mu} \left[\frac{\delta E}{\delta \psi_{i,\sigma}^*} + \sum_j \psi_{j,\sigma} \Lambda_{ji,\sigma} \right]_t \\ \vec{R}_I^{t+\Delta t} &\leftarrow 2\vec{R}_I^t - \vec{R}_I^{t-\Delta t} + \frac{(\Delta t)^2}{M_I} \frac{\partial E}{\partial \vec{R}_I} \end{split}$$

In this molecular dynamic procedure we have to know variational derivative $\frac{\delta E}{\delta \psi_{i,\sigma}^*}$ and the

matrix $\Lambda_{ij,\sigma}$. The variational derivative $\frac{\delta E}{\delta \psi_{i,\sigma}^*}$ can be analytically found and is

$$\begin{split} \frac{\delta E}{\delta \psi_{i,\sigma}^*} &= -\frac{1}{2} \nabla^2 \psi_{i,\sigma}(\vec{r}) \\ &+ \int d\vec{r'} W_{ext}(\vec{r},\vec{r'}) \psi_{i,\sigma}(\vec{r'}) \\ &+ \int d\vec{r'} \frac{n(\vec{r'})}{|\vec{r}-\vec{r'}|} \psi_{i,\sigma}(\vec{r}) \\ &+ \mu_{xc}^{\sigma}(\vec{r}) \psi_{i,\sigma}(\vec{r}) \\ &\equiv \hat{H} \psi_{i,\sigma} \end{split}$$

To find the matrix $\Lambda_{ij,\sigma}$ we impose the orthonormality constraint on $\psi_{i,\sigma}^{t+\Delta t}$ to obtain a matrix Riccatti equation, and then Riccatti equation is solved by an iterative solution.

Constant Temperature Simulations: Nose-Hoover Thermostats

Nose-Hoover Thermostats for the electrons and ions can also be added to the Car-Parrinello simulation. In this type of simulation thermostats variables x_e and x_R are added to the simulation by adding the auxiliary energy functionals to the total energy.

$$ION_THERMOSTAT(x_R) = \frac{1}{2}Q_R \dot{x_R} + E_{R0} x_R$$
$$ELECTRON_THERMOSTAT(x_e) = \frac{1}{2}Q_e \dot{x_e} + E_{e0} x_e$$

In these equations, the average kinetic energy for the ions is

 $E_{R0} = \frac{1}{2} f k_B T$

where f is the number of atomic degrees of freedom, k_B is Boltzmann's constant, and T is the desired t emperature. Defining the average fictitious kinetic energy of the electrons is not as straightforward. Blöchl and Parrinello (P.E. Blöchl and M. Parrinello, Phys. Rev. B, **45**, 9413, (1992)) have suggested the following formula for determining the average fictitious kinetic energy

 $E_{e0} = 4k_B T \frac{\mu}{M} \sum_i \langle \psi_i | -\frac{1}{2} \nabla^2 | \psi_i \rangle$

where μ is the fictitious electronic mass, M is average mass of one atom, and $\sum_i < \psi_i | -\frac{1}{2} \nabla^2 | \psi_i >$ is the kinetic energy of the electrons.

Blöchl and Parrinello suggested that the choice of mass parameters, Q_e , and Q_R should be made such that the period of oscillating thermostats should be chosen larger than the typical time scale for the dynamical events of interest but shorter than the simulation time.

$$P_{ion} = 2\pi \sqrt{\frac{Q_R}{4E_{R0}}}$$
$$P_{electron} = 2\pi \sqrt{\frac{Q_e}{4E_{e0}}}$$

where P_{ion} and $P_{electron}$ are the periods of oscillation for the ionic and fictitious electronic thermostats.

In simulated annealing simulations the electronic and ionic Temperatures are scaled according to an exponential cooling schedule,

$$T_e(t) = T_e^0 \exp^{-\frac{t}{\tau_e}}$$

 $T_{ionic}(t) = T_{ionic}^0 \exp^{-\frac{t}{\tau_{ionic}}}$

where T_e^0 and T_{ionic}^0 are the initial temperatures, and τ_e and τ_{ionic} are the cooling rates in atomic units.

NWPW Tutorial 1: S ² dimer examples with PSPW

A description of all the examples in NWPW Tutorial 1 can be found in the attached pdf Media:nwpwexample1.pdf

Total energy of S ² dimer with LDA approximation

(input:Media:s2-example1.nw, output:Media:s2-example1.nwout)

In this example, the total energy of the S 2 dimer using LDA approximation for the exchange-correlation functional is calculated.

```
echo
title "total energy of s2-dimer LDA/30Ry with PSPW method"
scratch dir
              ./scratch
permanent_dir ./perm
start s2-pspw-energy
geometry
S 0.0 0.0 0.0
S 0.0 0.0 1.88
end
nwpw
  simulation cell
    SC 20.0
  end
  cutoff 15.0
  mult 3
  xc lda
  lmbfgs
end
task pspw energy
```

The energies from the simulation will be

---== Summary Of Results ==

```
number of electrons: spin up=
                                  7.00000 down=
                                                    5.00000 (real
space)
 total
           energy
                   : -0.2041363137E+02 (
                                              -0.10207E+02/ion)
 total orbital energy: -0.4944372503E+01 (
                                              -0.41203E+00/electron)
 hartree
           energy
                    : 0.1680529987E+02 (
                                               0.14004E+01/electron)
                                              -0.36005E+00/electron)
 exc-corr energy
                     : -0.4320620600E+01 (
 ion-ion
                    : 0.8455644190E-02 (
                                               0.42278E-02/ion)
           energy
 kinetic (planewave) : 0.7529965882E+01 (
                                               0.62750E+00/electron)
 V local (planewave) : -0.4506036741E+02 (
                                              -0.37550E+01/electron)
 V nl
         (planewave) : 0.4623635248E+01 (
                                               0.38530E+00/electron)
 V Coul
         (planewave) : 0.3361059973E+02 (
                                               0.28009E+01/electron)
 V xc.
         (planewave) : -0.5648205953E+01 (
                                              -0.47068E+00/electron)
 Virial Coefficient : -0.1656626150E+01
 orbital energies:
    -0.2001309E+00 ( -5.446eV)
    -0.2001309E+00 ( -5.446eV)
    -0.3294434E+00 ( -8.965eV)
                                   -0.2991148E+00 ( -8.139eV)
    -0.3294435E+00 ( -8.965eV)
                                   -0.2991151E+00 ( -8.139eV)
    -0.3582269E+00 ( -9.748eV)
                                   -0.3352434E+00 ( -9.123eV)
    -0.5632339E+00 ( -15.326eV)
                                   -0.5246249E+00 ( -14.276eV)
    -0.7642738E+00 ( -20.797eV)
                                   -0.7413909E+00 ( -20.174eV)
 Total PSPW energy : -0.2041363137E+02
. . .
```

Structural optimization of S ² dimer with LDA approximation

(input:Media:s2-example2.nw, output:Media:s2-example2.nwout)

In this example, the structure of the S 2 dimer using results generated from prior energy calculation is calculated. Since most of the parameters are already stored in the run-time database the input is very simple.

```
echo
title "optimization of s2-dimer LDA/30Ry with PSPW method"
scratch_dir ./scratch
permanent_dir ./perm
restart s2-pspw-energy
driver
maxiter 20
xyz s2
end
task pspw optimize
```

As the optimization process consists of series of total energy evaluations the contents of the output file are very much similar to that in Example I. At each step the total energy and force information will be outputed as follows

St Wallt	ep ime	Energy	Delta E	Gmax	Grms	Xrms	Xmax
 0	 1 7.8	-20.41364254	-7.1D-05	0.00004	0.00004	0.00605	0.01048

The best way to keep track of the optimization calculation is to run the following grep command on the output file.

```
grep @ outputfile
@ Step
                         Delta E
                                   Gmax
                                            Grms
                                                     Xrms
                                                             Xmax
             Energy
Walltime
@ -----
. . . . . . . .
     0
           -20.41357202 0.0D+00 0.00672 0.00672
                                                   0.00000
                                                            0.00000
(d
     1.5
           -20.41364254 -7.1D-05 0.00004 0.00004
                                                   0.00605 0.01048
     1
0
     7.8
     2
           -20.41364256 -2.3D-08 0.00020 0.00020
                                                   0.00003
                                                            0.00005
(d
     9.7
     2
(d
           -20.41364256 -2.3D-08 0.00020 0.00020
                                                    0.00003
                                                            0.00005
     9.7
```

The optimized energy and geometry will be

Optimization converged

. . .

St	ер	Energy	Delta E	Gmax	Grms	Xrms	Xmax	
Wallt	ime							
0	2	-20.41364256	-2.3D-08	0.00020	0.00020	0.00003	0.00005	
	9.7							
				ok	ok	ok	ok	

Z-matrix (autoz)

```
- - - - - - - - -
```

Units are Angstrom for bonds and degrees for angles

Type Gradient	Name	I	J	К	L	Μ	Value
1 Stretch 0.00020		1	2				1.89115

		Geometry "g	eometry" -> "	geometry" 	
Output co a.u.)	ordinates	in angstroms (sc	ale by 1.889	725989 to convert to	
No.	Tag Z	Charge	Χ	Υ	
1 S -0.94557591		16.0000	0.00000000	0.0000000	
2 S 0.94557591		16.0000	0.00000000	0.0000000	

Frequency calculation of S ² dimer with LDA approximation

(input:Media:s2-example3.nw, output:Media:s2-example3.nwout)

In this example, the vibrational frequency of the S 2 dimer using results generated from prior geometry optimization is calculated. Since most of the parameters are already stored in the run-time database the input is very simple.

```
echo
title "frequency calculation of s2-dimer LDA/30Ry with PSPW method"
scratch_dir ./scratch
permanent_dir ./perm
restart s2-pspw-energy
freq
    animate
end
task pspw freq
```

The frequency and thermodynamic analysis generated

• • •		
Temperature	=	298.15K
frequency scaling parameter	=	1.0000
Linear Molecule		
Zero-Point correction to Energy	=	1.034 kcal/mol (0.001647 au)
Thermal correction to Energy	=	2.579 kcal/mol (0.004110 au)
Thermal correction to Enthalpy	=	3.171 kcal/mol (0.005054 au)
Total Entropy	=	52.277 cal/mol-K
- Translational	=	38.368 cal/mol-K (mol. weight =
63.9441)		
- Rotational	=	13.630 cal/mol-K (symmetry # =
2)		
- Vibrational	=	0.279 cal/mol-K

```
Cv (constant volume heat capacity) =
                                 5.750 cal/mol-K
                                 2.979 cal/mol-K
   - Translational
                             =
   - Rotational
                                 1.986 cal/mol-K
                             =
                             =
   - Vibrational
                                 0.785 cal/mol-K
. . .
Normal Eigenvalue ||
                         Projected Infra Red Intensities
        [cm**-1] || [atomic units] [(debye/angs)**2] [(KM/mol)]
  Mode
[arbitrary]
 . . . . . . . . . . .
   1
           0.000 ||
                    0.000030
                                   0.001
                                               0.029
0.000
                               56.914
    2
           0.000 ||
                    2.466908
                                            2404.864
15.000
   3
           0.000 ||
                    2.466908
                                   56.914
                                            2404.864
15.000
   4
           0.000 ||
                    2,466908
                                   56.914
                                            2404.864
15.000
    5
           0.000 ||
                    2.466908
                                   56.914
                                            2404.864
15.000
   6
         723.419 ||
                    0.000000
                                   0.000
                                               0.000
0.000
```

Ab initio molecular dynamics simulation (Car-Parrinello) of S 2 dimer using the LDA approximation

(input:Media:s2-example4.nw, output:Media:s2-example4.nwout Media:s2-md.xyz Media:s2-md.emotion.dat)

In this example, a constant energy Car-Parrinello simulation of S² dimer using LDA approximation is calculated. A brief introduction to the Car-Parrinello method can be found in Media:cpmd-lecture.pdf

```
echo
title "AIMD simulation of s2-dimer"
scratch_dir ./scratch
permanent_dir ./perm
start s2-md
geometry
S 0.0 0.0 0.0
S 0.0 0.0 0.0
S 0.0 0.0 1.95
end
nwpw
simulation_cell
```
```
SC 20.0
end
cutoff 15.0
mult 3
xc lda
lmbfgs
car-parrinello
time_step 5.0
fake_mass 600.0
loop 1 1000
xyz_filename s2-md.xyz
end
end
task pspw energy
task pspw car-parrinello
```

A plotting program (e.g. gnuplot, xmgrace) can be used to look at the total, potential, kinetic energies, contained in the s2-md.emotion file (see section EMOTION motion file for datafile format) i.e.,

```
seattle-1604% gnuplot
```

```
GNUPLOT
     Version 4.0 patchlevel 0
     last modified Thu Apr 15 14:44:22 CEST 2004
      System: Linux 2.6.18-194.8.1.el5
      Copyright (C) 1986 - 1993, 1998, 2004
     Thomas Williams, Colin Kelley and many others
     This is gnuplot version 4.0. Please refer to the documentation
      for command syntax changes. The old syntax will be accepted
      throughout the 4.0 series, but all save files use the new syntax.
     Type `help` to access the on-line reference manual.
     The gnuplot FAQ is available from
              http://www.gnuplot.info/faq/
      Send comments and requests for help to
              <gnuplot-info@lists.sourceforge.net>
      Send bugs, suggestions and mods to
              <gnuplot-bugs@lists.sourceforge.net>
Terminal type set to 'x11'
gnuplot> plot "s2-md.emotion","s2-md.emotion" using 1:3
```

gnuplot>

The following plot shows the Car-Parrinello ${}^{3}\Sigma_{g}^{-}$ S ² energy surface generated from the simulation.



Ab initio molecular dynamics simulation (Born-Oppenheimer) of S $^{\rm 2}$ dimer using the LDA approximation

(input:Media:s2-example5.nw, output:Media:s2-example5.nwout Media:s2-bomd.xyz Media:s2-bomd.emotion.dat) In this example, a constant energy Born-Oppenheimer simulation of S2 dimer using LDA approximation is calculated.

```
title "AIMD simulation of s2-dimer"
echo
scratch dir
              ./scratch
permanent_dir ./perm
start s2-bomd
geometry
5 0.0 0.0 0.0
S 0.0 0.0 1.95
end
nwpw
  simulation cell
    SC 20.0
  end
  cutoff 15.0
  mult 3
  xc lda
```

```
lmbfgs
end
task pspw energy
nwpw
    bo_steps 1 500
    bo_time_step 10.0
end
task pspw born-oppenheimer
```

The following plot shows the ${}^{3}\Sigma_{g}^{-}$ S ² energy surface generated from the simulation.



NWPW Tutorial 2: Using PSPW Car-Parrinello Simulated Annealing Simulations to Optimize Structures

In principle quantum mechanical calculations can be used to determine the structure of any chemical system. One chooses a structure, calculates the total energy of the system, and repeats the calculation for all possible geometries. Of course the major limitation of this approach is that the number of local minima structures increases dramatically with system size and the cost of quantum mechanical calculations also increases dramatically with system size. Not surprisingly most quantum mechanical calculations limit the number of structures to be calculated by using experimental results or chemical intuition. One could speed up the calculations. However, inter-atomic forces fields have many simplifying assumptions that can severely limit their predictability. Another approach is to use ab initio molecular dynamics methods combined with simulated annealing. These methods are quite

robust and allow strongly interacting many body systems to be studied by direct dynamics simulation without the introduction of empirical interactions. In these methods, the atomic forces are calculated from ab initio calculations that are performed "on-the-fly" as the molecular dynamics trajectory is generated.

The following examples demonstrate how to use the ab initio molecular dynamics methods and simulated annealing strategies of NWChem to determine the lowest energy structures of the B 12 cluster. This example is based on a study performed by Kiran Boggavarapu et al.. One might expect from chemical intuition that lowest energy structure of B 12 will be an icosahedran, since B 12 icosahedra are a common structural unit found in many boron rich materials. Despite this prevalence, ab initio calculations performed by several researchers have suggested that B 12 , as well as B $^+_{12}$ and B $^-_{12}$, will have a more open geometry.



Simulated Annealing Using Constant Energy Simulation

(input:Media:b12-example2a.nw, output:Media:b12-example2a.nwout Media:b12.00.xyz Media:b12.00.emotion.dat Media:b12.01.xyz Media:b12.01.emotion.dat)

This example uses a series of constant energy Car-Parrinello simulations with velocity scaling to do simulated annealing. The initial four Car-Parrinello simulations are used to heat up the system to several thousand Kelvin. Then the system is cooled down thru a series of constant energy simulations in which the electronic and ionic velocities are scaled by 0.99 at the start of each Car-Parrinello simulation. Energy minimization calculations are used periodically in this simulation to bring the system back down to Born-Oppenheimer surface. This is necessary because of electronic heating.

The Car-Parrinello keyword "scaling" scales the wavefunction and ionic velocities at the start of the simulation. The following input is used to increase the ionic velocities by a factor of two at the start of the Car-Parrinello simulation.

Key Input

```
...
Car-Parrinello
fake_mass 500.0
time_step 5.0
loop 10 100
scaling 1.0 2.0
emotion filename b12.00.emotion
```

```
xyz_filename
                  b12.00.xyz
end
.....
Output
.....
     wavefnc cutoff= 10.000 fft= 42x 42x 42(
                                                   6027 waves
                                                                   1004
per task)
technical parameters:
     translation contrained
     time step=
                     5.00
                              ficticious mass=
                                                    500.0
     cooling/heatting rates: 0.10000E+01 (psi)
                                                   0.20000E+01 (ion)
     maximum iterations =
                             1000 (
                                      10 inner 100 outer )
     initial kinetic energy: 0.99360E-05 (psi)
                                                   0.27956E-03 (ion)
                                                   0.20205E-28 (c.o.m.)
     after scaling:
                              0.99360E-05 (psi)
                                                   0.11182E-02 (ion)
     increased energy:
                              0.00000E+00 (psi)
                                                   0.83868E-03 (ion)
```

Constant Energy Simulation

.....

The program checks to see if the initial input ionic velocities have a non-zero center of mass velocity. If there is a non-zero center of mass velocity in the system then by default the program removes it. To turn off this feature set the following

nwpw translation on end or

```
set nwpw:com shift .false.
```

Simulated Annealing Using Constant Temperature Simulation

(input:Media:b12-example2b.nw, output:Media:b12-example2b.nwout Media:b12.10.xyz Media:b12.10.emotion.dat Media:b12.11.xyz.gz Media:b12.11.emotion.dat)

(mpeg movie of simulation: Media:boron.mpg)

The simulated annealing calculation in this example uses a constant temperature Car-Parrinello simulation with an exponential cooling schedule,

 $T(t) = T_0 e^{-t/\tau}$

where T0 and τ are an initial temperature and a time scale of cooling, respectively. In the present calculations T0=3500K and τ =4.134e+4 au (1.0 ps) were used and the thermostat masses were kept fixed to the initial values determined by T=Te=3500K and ($2\pi/\omega$)=250 a.u. (6 fs). Annealing proceeded for 50000 steps, until a temperature of 10K was reached. After which, the metastable structure is optimized using the driver optimizer. The keyword SA_decay is used to enter the decay rates, τ electron and τ ion, used in the simulated annealing algorithm in the constant temperature car-parrinello simulation. The decay rates are in units of au (conversion 1 au = 2.41889e-17 seconds).

Key Input

```
....
Car-Parrinello
SA_decay 4.134d4 4.134d4 #decay rate in units of au
(lau=4.1889e-17seconds)
....
```

NWPW Tutorial 3: using isodesmic reaction energies to estimate gas-phase thermodynamics

(Media:isodesmic.pdf Media:isodesmic.tgz)

The development of a computational scheme that can accurately predict reaction energies requires some care. As shown in Table 1 energy errors associated with ab initio calculations can be quite high. Even though ab initio electronic structure methods are constantly being developed and improved upon, these methods are rarely able to give heat of formations of a broad class of molecules with error limits of less than a few kcal/mol. Only when very large basis sets such as the correlation-consistent basis sets, high level treatments of correlation energy such as coupled cluster methods (CCSD(T)), and small correction factors such as core-valence correlation energies and relativistic effects, are included will the heat of formation from ab initio electronic structure methods be accurate to within one kcal/mol. Although one can now accurately calculate the heats of formation of molecules with up to 6 first row atoms, such high-level calculations are extremely demanding and scale computationally as N^7 for N basis functions.

Examples of these types of large errors are shown in the following Table, where the enthalpies of formation of CCl ³SH are calculated by using atomization energies from different levels of ab initio theory.

	MP2/cc-pVDZ	LDA/DZVP2	BP91/DZVP2	B3LYP/DZVP2	G2 Theory
$\Delta H f^{o}$	+4.9	-80.0	-2.6	+26.5	-13.0

Table 1: Standard enthalpy of formation (▲H

Differences of up to 106.5 kcal/mol are found between different levels of theory. This example demonstrates that care must be taken in choosing the appropriate method for calculating the heats of formation from total atomization energies.

The difficulties associated with calculating absolute heats of formation from atomization energies can be avoided by using a set of isodesmic reactions[1]. The defining property of an isodesmic reaction - that there are an equal number of like bonds on the left-hand and right-hand sides of the reaction - helps to minimize the error in the reaction energy. These reactions are designed to separate out the interactions between molecular subsistents and non-bonding electrons from the direct bonding interactions by having the direct bonding interactions largely canceling one another. This separation is quite attractive. Most ab initio methods give substantial errors when estimating direct bonding interactions due to the computational difficulties associated with electron pair correlation, whereas ab initio methods are expected to be more accurate for estimating neighboring interactions and long-range through-bond effects. The following isodesmic reaction can be used determine the enthalpy of formation for CCl 3 SH that is significantly more accurate than the estimates based on atomization energies.

CCl
3
SH + CH $^{4} \rightarrow$ CH 3 SH + CCl 3 H, Δ H r (calc).

The first step is to calculate the reaction enthalpy of this reaction from electronic, thermal and vibrational energy differences at 298.15K at a consistent level of theory. The defining property of an isodesmic reaction that there are an equal number of like bonds on the left-hand and right-hand sides of the reaction helps to minimize the error in the calculation of the reaction energy. The enthalpy of formation of CCl ³SH can then be calculated by using Hess's law with the calculated enthalpy change and the experimentally known heats of formation of the other 3 species (see Table 3).

 $\Delta H f(CCl ^{3}SH) = \Delta H f(CH ^{3}SH)(exp) + \Delta H f(CCl ^{3}H)(exp) - \Delta H f(CH ^{4})(exp) - \Delta H r (calc).$

In this example, try to design and run NWPW simulations that can be used to estimate the enthalpy of formation for CCl ³SH using its atomization energy and using the reaction enthalpy of the isodesmic reaction and compare your results to Table 2. Be careful to make sure that you use the same cutoff energy for all the simulations (.e.g. cutoff 35.0). You might also try to estimate enthalpies of formation for CHCl ²SH and CH ²ClSH. Also try designing simulations that use the SCF, DFT, MP2, and TCE modules.

 $\mathrm{CCl}\;{}^3\mathrm{SH}+\mathrm{CH}\;{}^4\longrightarrow\mathrm{CH}\;{}^3\mathrm{SH}+\mathrm{CCl}\;{}^3\mathrm{H}$

Un-optimized geometries for CCl ³SH, CH ³SH, CCl ³H and CH ⁴ which are needed to design your simulations are contained in the file Media:thermodynamics.xyz. You will also need to calculate the energies for the H, C, S, and Cl atoms to calculate the atomization energies. The multiplicities for these atoms are 2, 3, 3 and 2 respectively. You will also need to calculate the enthalpy of a molecule. The enthalpy of a molecule at 298.15K is sum of the total energy and a thermal correction to the enthalpy. A good estimate for the thermal correction to the enthalpy can be obtained from a frequency calculation, i.e.

H = E + H correction

Thermodynamic output from a frequency calculation:

Temperature frequency scaling parameter	= =	298.15K 1.0000
Zero-Point correction to Energy Thermal correction to Energy	= =	27.528 kcal/mol (0.043869 au) 29.329 kcal/mol (0.046739 au)
The following line contains the value f	or H	correction
Thermal correction to Enthalpy	=	29.922 kcal/mol (0.047683 au)
Total Entropy - Translational 16 0313)	= =	44.401 cal/mol-K 34.246 cal/mol-K (mol. weight =
- Rotational 12)	=	10.060 cal/mol-K (symmetry # =
- Vibrational	=	0.095 cal/mol-K
Cv (constant volume heat capacity - Translational	y) = =	6.503 cal/mol-K 2.979 cal/mol-K

-	Rotational	=	2.979	cal/mol-K
-	Vibrational	=	0.544	cal/mol-K

Table 2: Gas-phase standard enthalpies of formation (**A**H

Compounds	MP2/cc-pVDZ	LDA/DZVP2	BP91/DZVP2	B3LYP/DZVP2	G2 G2	NWPW	NWPW	Experiment
	(isodesmic)	(isodesmic)	(isodesmic)	(isodesmic)	(atomization)	(isodesmic)	(atomization)	
CCl ³ SH	-13.40	-11.86	-8.68	-7.64	-12.95			
CHCl ² SH	-11.48	-11.07	-8.66	-7.92	-11.52			
CH ² ClSH	-7.01	-6.66	-5.44	-5.20	-6.98			
CH ³ SH					-4.76			-5.34

Table 3: Miscellaneous experimental gas-phase enthalpies of formation (kcal/mol) taken from [3].

Compounds	ΔH ^o _f (298K)
Н	52.095
С	171.291
S	66.636
Cl	29.082
CCl ⁴	-24.59
CCl ³ H	-24.65
CCl ² H ²	-22.10
CClH ³	-19.32
CH ⁴	-17.88
CH ³ SH	-5.34

- 1. Hehre, W. J., L. Radom, P.v.R. Schleyer, and J.A. Pople Ab Initio Molecular Orbital Theory; John Wiley & Sons: New York, 1986).
- E.J. Bylaska, D.A. Dixon, and A.R. Felmy(2000), "The Free Energies of Reactions of Chlorinated Methanes with Aqueous Monovalent Anions: Application of ab initio Electronic Structure Theory", J. Phys. Chem. A, 104(3), 610-617.
- 3. Chase, M. W., Jr. Phys. Chem. Ref. Data, Monograph No. 9 1998, 9, 1-1951.

NWPW Tutorial 4: AIMD/MM simulation of CCl 4 +64 H 2O

(input:Media:ccl4-64water.nw, output:Media:ccl4-64water.nwout)

In this section we show how use the PSPW module to perform a Car-Parrinello AIMD/MM simulation for a CCl ⁴ molecule in a box of 64 H ²O. Before running a PSPW Car-Parrinello simulation the system should be on the Born-Oppenheimer surface, i.e. the one-electron orbitals should be minimized with respect to the total energy (i.e. task pspw energy). In this example, default pseudopotentials from the pseudopotential library are used for C, Cl, O[^] and H[^], exchange correlation functional is PBE96, The boundary condition is periodic, and with a side length of 23.577 Bohrs and has a cutoff energy is 50 Ry). The time step and fake

mass for the Car-Parrinello run are specified to be 5.0 au and 600.0 au, respectively.

NWPW Tutorial 5: Optimizing the Unit Cell and Geometry of Diamond

The PSPW and BAND codes can be used to determine structures and energies for a wide range of crystalline systems. It can also be used to generate band structure and density of state plots.

Optimizing the Unit Cell and Geometry for an 8 Atom Supercell of Diamond with PSPW

(input:Media:diamond-pspw.nw, output:Media:diamond-pspw.nwout, Media:diamond.opt.cif)

(input:Media:catom-pspw.nw, output:Media:catom-pspw.nwout)



The following example uses the PSPW module to optimize the unit cell and geometry for a diamond crystal. The fractional coordinates and the unit cell are defined in the geometry block. The simulation_cell block is not needed since NWPW automatically uses the unit cell defined in the geometry block.

```
title "Diamond 8 atom cubic cell - geometry and unit cell optimization"
echo
permanent_dir ./perm
scratch dir
              ./scratch
start diamond
memory 950 mb
#**** Enter the geometry using fractional coordinates ****
geometry center noautosym noautoz print
  system crystal
    lat_a 3.56d0
    lat b 3.56d0
   lat_c 3.56d0
   alpha 90.0d0
    beta 90.0d0
   gamma 90.0d0
 end
  C -0.50000d0 -0.50000d0 -0.50000d0
  C 0.0000d0 0.0000d0 -0.5000d0
  C 0.0000d0 -0.5000d0 0.0000d0
 C -0.50000d0 0.00000d0 0.00000d0
 C -0.25000d0 -0.25000d0 -0.25000d0
  C 0.25000d0 0.25000d0 -0.25000d0
```

```
C 0.25000d0 -0.25000d0 0.25000d0
 C -0.25000d0 0.25000d0 0.25000d0
end
nwpw
 ewald rcut 3.0
 ewald ncut 8 #The default value of 1 needs to be increased for small
cells
 lmbfgs
 xc pbe96
end
driver
 clear
 maxiter 40
end
set nwpw:cif_filename diamond.opt # create a CIF file containing
optimization history
                      # this option tells driver to
set includestress .true.
optimize the unit cell
task pspw optimize ignore
The optimized energy and geometry will be
 . . .
    Optimization converged
    -----
 Step Energy Delta E Gmax Grms Xrms
                                                  Xmax
Walltime
 - - - - - - - -
       -45.07688304 -1.1D-07 0.00037 0.00021 0.00002 0.00003
6
  6
   174.5
                                    ok
                                                  ok
                             ok
                                           ok
                   Geometry "geometry" -> "geometry"
                   -----
Output coordinates in angstroms (scale by 1.889725989 to convert to
a.u.)
```

No.	Tag	Charge	Х	Y	Z
1 C		6.0000	1.82723789	1.82729813	
1.8270544 2 C	40	6.0000	0.00000857	-0.00006053	
1.8273002	27				

3 C 0.00002852	6.0000	-0.00000584	1.82706061
4 C	6.0000	1.82712018	0.00006354
5 C	6.0000	2.74074195	2.74072805
2.74088522 6 C	6.0000	0.91366407	0.91370055
2.74064976 7 C	6.0000	0.91351181	2.74080771
0.91352917 8 C	6.0000	2.74078843	0.91348115
0.91365446			
Lattice Parameter	- -		
lattice vectors i a.u.)	n angstroms.	(scale by 1.8897	25989 to convert to
al=< 3.654 0. a2=< 0.000 3.	000 0.000 654 0.000	>	
a3=< 0.000 0.	000 3.654	>	
alpha= 90.000 be	eta= 90.000	gamma= 90.000	
rociprocal lattic	o voctors in	2 11	
		a.u.	
b1=< 0.910 0. b2=< 0.000 0.	000 0.000 910 0.000	>	
b3=< 0.000 0.	000 0.910	>	
Atomic Mass			
C	12.000000		
	int	ernuclear distanc	es
center one	cente	r two atom	ic units
angstroms			
5 C	1 C	l	2.99027
1.58238 6 C	1 C	I	2.99027
1.58238 6 C	2 C	I	2.99027
1.58238	1 1 0		2,00026
		I	2.99020

1.58238					
7 C		3 C	1	2.99027	
1.58238					
8 C	I	1 C		2.99027	
1.58238		4.6			
8 L 1 58238	I	4 C	I	2.99027	
1.30230					
	1	number of inc [.]	luded inter	nuclear distance	S:
7					
	====:				
	:				
		inter	nuclear ang	les	
center 1		center 2	2	center 3	 I
degrees	•				·
5 C		1 C		6 C	I
109.46				7.0	
5 C	I	1 C	I	/ (I
109.40 5 C	1	1 (1	8 (I.
109.48	1	1.0	I	0 0	I
6 C		1 C	1	7 C	I
109.47					
6 C		1 C		8 C	I
109.46					
7 C	I	1 C		8 C	I
109.48		6.0	1	2 C	
109.48	I	0 C	I	2 (I
1 C	1	7 C	1	3 C	1
109.47					•
1 C		8 C		4 C	I
109.47					
Q		number of :	included in	iternuclear angle	5:
<i>5</i> ====================================					

The C-C bond distance after the geometry optimization is 1.58 Angs. and agrees very well with the experimental value of 1.54 Angs.. Another quantity that can be calculated from this simulation is the cohesive energy. The cohesive energy of a crystal is the energy needed to separate the atoms of the solid into isolated atoms, i.e.

$$E_{coh} = -\left(E_{solid} - \sum_{a} E^{a}_{atom}\right)$$

where E_{solid} is the energy of the solid and E^a_{atom} are the energies of the isolated atoms. In order to calculate the cohesive energy the energy of an isolated carbon atom at the same level of theory and cutoff energy will need to be calculated. The following input can be used to the energy of an isolated carbon atom.

```
)
(input:
                    , output:
title "triplet carbon atom at pbe96 level using a large unit cell"
start c1-pspw
memory 1400 mb
permanent dir ./perm
              ./scratch
scratch dir
geometry
C 0 0 0
end
nwpw
   simulation cell
      FCC 38.0
                   #large unit cell
      boundary conditions
                             periodic # periodic boundary conditions
are used by default.
      #boundary_conditions aperiodic # free-space (or aperiodic)
boundary conditions could also be used.
   end
   xc pbe96
   mult 3
  lmbfgs
end
task pspw energy
```

The total energy from the simulation will be

Total PSPW energy : -0.5421213534E+01

Using this energy and energy of diamond the cohesive energy per atom is calculated to be

 $E_{coh} = -(-45.07688304au/8 - (-5.421213534au)) = 0.2133968au = 5.8eV$

This value is substantially lower than the experimental value of 7.37eV! It turns out this error is a result of the unit cell being too small for the diamond calculation (or too small of a Brillioun zone sampling). In the next section, we show how increasing the Brillouin zone sampling reduces the error in the calculated cohesive energy.

Optimizing the Unit Cell for an 8 Atom Supercell of Diamond with BAND

(input:Media:diamond-band.nw, output:Media:diamond-band.nwout)

In this example the BAND module is used to optimize the unit cell and geometry for a diamond crystal at different Brillouin zone samplings.

```
title "Diamond 8 atom cubic cell - geometry and unit cell optimization"
echo
permanent dir ./perm
scratch dir
              ./scratch
start diamond-band
memory 1950 mb
#**** Enter the geometry using fractional coordinates ****
geometry center noautosym noautoz print
  system crystal
   lat a 3.58d0
   lat_b 3.58d0
   lat c 3.58d0
   alpha 90.0d0
   beta 90.0d0
   gamma 90.0d0
 end
 C -0.50000d0 -0.50000d0 -0.50000d0
 C 0.00000d0 0.0000d0 -0.50000d0
 C 0.00000d0 -0.50000d0 0.00000d0
 C -0.50000d0 0.00000d0 0.00000d0
 C -0.25000d0 -0.25000d0 -0.25000d0
 C 0.25000d0 0.25000d0 -0.25000d0
  C 0.25000d0 -0.25000d0 0.25000d0
  C -0.25000d0 0.25000d0 0.25000d0
end
set includestress
                             # option tells driver to optimize the
                     .true.
unit cell
set nwpw:zero_forces .true. # option zeros the forces on the
atoms--> only lattice parameters optimized
nwpw
 ewald_rcut 3.0
 ewald ncut 8 #The default value of 1 needs to be increased
 lmbfgs
 xc pbe96
end
#1x1x1 k-point mesh
nwpw
 monkhorst-pack 1 1 1
```

```
end
set nwpw:cif_filename diamond111.opt
driver; clear; maxiter 40; end; task band optimize ignore
#2x2x2 k-point mesh
nwpw
  monkhorst-pack 2 2 2
end
set nwpw:cif filename diamond222.opt
driver; clear; maxiter 40; end; task band optimize ignore
#3x3x3 k-point mesh
nwpw
  monkhorst-pack 3 3 3
end
set nwpw:cif filename diamond333.opt
driver; clear; maxiter 40; end; task band optimize ignore
#4x4x4 k-point mesh
nwpw
  monkhorst-pack 4 4 4
end
set nwpw:cif filename diamond444.opt
driver; clear; maxiter 40; end; task band optimize ignore
#5x5x5 k-point mesh
nwpw
  monkhorst-pack 5 5 5
end
set nwpw:cif filename diamond555.opt
driver; clear; maxiter 40; end; task band optimize ignore
```

The following figure shows a plot of the cohesive energy and C-C bond distance versus the Brillouin zone sampling. As can be seen in this figure the cohesive energy (w/o zero-point correction) and C-C bond distance agree very well with the experimental values of 7.37 eV (including zero-point correction) and 1.54 Angs.

Using BAND to Optimize the Unit Cell for a 2 Atom Primitive Cell of Diamond

(input:Media:diamond-fcc.nw, output:Media:diamond-fcc.nwout.gz)

In this example the BAND module is used to optimize a 2 atom unit cell for a diamond crystal at different Brillouin zone samplings. The optimized energy and geometry will be (Monkhorst-Pack sampling of 11x11x11)

```
Optimization converged

Step Energy Delta E Gmax Grms Xrms Xmax

Walltime
```

@ 1 -11.40586236 5.2D-07 0.00039 0.00018 0.00002 0.00003 662.0 ok ok ok ok Geometry "geometry" -> "geometry" -----Output coordinates in angstroms (scale by 1.889725989 to convert to a.u.) No. Tag Charge X Υ Ζ 1 C 6.0000 0.0000000 0.0000000 0.00000000 2 C 6.0000 0.72201500 1.25056532 0.51054180 Lattice Parameters lattice vectors in angstroms (scale by 1.889725989 to convert to a.u.) al=< 2.165 1.251 0.001 > a2=< 0.001 2.500 0.001 > a3=< 0.722 1.251 2.041 > 2.500 b= 2.500 c= a= 2.500 alpha= 59.966 beta= 59.966 gamma= 59.966 omega= 11.0 reciprocal lattice vectors in a.u. b1=< 1.536 -0.768 0.000 >b2=< 0.000 1.330 0.000 > b3=< -0.543 -0.543 1.629 > Atomic Mass С 12.000000 ______ internuclear distances center one | center two | atomic units | angstroms



The following figure shows a plot of the cohesive energy and C-C bond distance versus the Brillouin zone sampling for the 8 atom SC unit cell and the 2 atom FCC unit cell.

Using BAND to Calculate the Band Structures of Diamond

(input:Media:diamond-structure.nw, output:Media:diamond-structure.nwout,



The following example uses the BAND module to calculate the band structure for the FCC cell of the a diamond crystal. The fractional coordinates and the unit cell are defined in the geometry block. The simulation_cell block is not needed since NWPW automatically uses the unit cell defined in the geometry block.

```
title "Diamond 2 atom fcc cell Brillouin sampling=9x9x9 M-P - Band
structure plot"
echo
permanent dir ./perm
scratch dir
             ./scratch
start diamondfcc
memory 1950 mb
#**** Enter the geometry using fractional coordinates ****
geometry center noautosym noautoz print
  system crystal
   lat a 2.500d0
   lat b 2.500d0
   lat c 2.500d0
   alpha 60.0d0
    beta 60.0d0
   gamma 60.0d0
 end
C 0.0000d0 0.0000d0 0.0000d0
C 0.25000d0 0.25000d0 0.25000d0
end
```

```
nwpw
  ewald_rcut 3.0
               #The default value of 1 needs to be increased
  ewald ncut 8
  lmbfgs
  xc pbe96
  monkhorst-pack 9 9 9
end
#need to run "task band energy" before "task band structure" can be run
task band energy
nwpw
   virtual 16
   brillouin zone
     zone name fccpath
     path fcc l gamma x w k gamma
   end
   zone structure name fccpath
end
task band structure
```

This calculation outputs the) data file in the permanent_directory. A plotting (e.g. gnuplot or xmgrace) can be used to display the band structure.

Using BAND to Calculate the Density of States of Diamond

(2 atom cell - input:Media:diamond-dos.nw output:Media:diamond-dos.nwout, Media:diamond-dos.dos.dat) (8 atom cell - input:Media:diamond-dos8.nw output: Media:diamond-dos8.nwout.gz, Media:diamond-dos8.dos.dat)

The following example uses the BAND module to calculate the density of states the diamond crystal.

```
title "Diamond 2 atom fcc cell Brillouin sampling=9x9x9 M-P - Band
structure plot"
echo
permanent_dir ./perm
scratch_dir ./scratch
start diamond-dos
memory 1950 mb
#**** Enter the geometry using fractional coordinates ****
geometry center noautosym noautoz print
system crystal
lat_a 2.500d0
```

```
lat b 2.500d0
   lat c 2.500d0
   alpha 60.0d0
    beta 60.0d0
   gamma 60.0d0
 end
C 0.00000d0 0.0000d0 0.0000d0
C 0.25000d0 0.25000d0 0.25000d0
end
nwpw
 ewald rcut 3.0
 ewald ncut 8
               #The default value of 1 needs to be increased
 lmbfgs
 xc pbe96
 monkhorst-pack 9 9 9
end
#need to run "task band energy" before "task band dos" can be run
task band energy
nwpw
  virtual 26
                            #26 virtual orbitals included in the DOS
calculation
  dos-grid 11 11 11
end
task band dos
```

This calculation outputs the data file in the permanent_directory. A plotting (e.g. gnuplot or xmgrace) can be used to display the density of states.

NWPW Tutorial 6: optimizing the unit cell of nickel with fractional occupation

(input:Media:Ni-band.nw output:Media:Ni-band.nwout) The following example demonstrates how to uses the BAND module to optimize the unit cell and geometry for FCC cell of Nickel metal

```
title "Ni FCC metal, monkhorst-pack=3x3x3, 5x5x5, and 7x7x7, fermi
smearing, xc=pbe96"
echo
start Ni-band
memory 1900 mb
```

```
permanent_dir ./perm
scratch dir ./scratch
geometry units angstroms center noautosym noautoz print
 system crystal
    lat a 3.5451d0
    lat b 3.5451d0
   lat c 3.5454d0
    alpha 90.0d0
    beta 90.0d0
    gamma 90.0d0
  end
Ni 0.000000
              0.000000
                         0.000000
Ni 0.000000 0.500000
                         0.500000
Ni 0.500000
              0.000000
                         0.500000
Ni 0.500000
              0.500000
                         0.000000
end
set nwpw:cif filename Ni-band
set nwpw:zero_forces .true.
set includestress
                   .true.
#turn on pseudopotential filtering
set nwpw:kbpp_ray .true.
set nwpw:kbpp_filter .true.
nwpw
   #fractional occupation
   smear fermi
   #scf option used with smear
   scf anderson outer iterations 0 kerker 2.0
   ewald ncut 8
   ewald rcut 3.0
   xc pbe96
   monkhorst-pack 3 3 3
   np dimensions -1 -1 4
end
#generate initial wavefunctions w/ low cutoff energy
nwpw
   loop 10 10
   cutoff 10.0
end
task band energy
#increase cutoff energy and number of iterations
nwpw
   cutoff 50.0
```

```
loop 10 100
end
#3x3x3 k-point mesh
nwpw
  monkhorst-pack 3 3 3
end
set nwpw:cif filename nickel333.opt
driver; clear; maxiter 40; end; task band optimize ignore
#5x5x5 k-point mesh
nwpw
  monkhorst-pack 5 5 5
end
set nwpw:cif filename nickel555.opt
driver; clear; maxiter 40; end; task band optimize ignore
#7x7x7 k-point mesh
nwpw
  monkhorst-pack 7 7 7
end
set nwpw:cif filename nickel777.opt
driver; clear; maxiter 40; end; task band optimize ignore
```

The following figure shows a plot of the cohesive energy and Ni-Ni bond distance versus the Brillouin zone sampling. As can be seen in this figure the cohesive energy (w/o zero-point correction) and Ni-Ni bond distance agree very well with the experimental values of 4.44 eV (including zero-point correction) and 2.49 Angs.

NWPW Tutorial 7: Optimizing the unit cells with symmetry: Diamond with Fd-3m symmetry and Brucite with P-3m1 symmetry

(Diamondexample,input:Media:diamond-symmetry.nw,output:Media:diamond-symmetry.nwout)(Bruciteexample,input:Media:brucite-symmetry.nw,output:Media:brucite-symmetry.nwout)output:Media:brucite-symmetry.nwout)(Brucite(Brucite-symmetry.nw,

The following example uses the BAND module to optimize the unit cell and geometry for a Diamond crystal with Fd-3m symmetry. The fractional coordinates, unit cell, and symmetry are defined in the geometry block.

```
title "Diamond 8 atom cubic cell generated using Fd-3m symmetry -
geometry and unit cell optimization"
echo
memory 1500 mb
permanent_dir ./perm
scratch_dir ./scratch
start diamond-symmetry
```

```
geometry nocenter noautosym noautoz print
 system crystal
   lat a 3.58
   lat b 3.58
   lat c 3.58
   alpha 90.0
   beta 90.0
   gamma 90.0
 end
symmetry Fd-3m
C 0.0 0.0 0.0
end
set nwpw:cif filename diamond-symmetry
#turn on pseudopotential filtering
set nwpw:kbpp ray
                     .true.
set nwpw:kbpp filter .true.
#***** setup the nwpw Band code - 3x3x3 k-point mesh ****
nwpw
  ewald_rcut 3.0
  ewald ncut 8
 xc pbe96
 lmbfgs
  monkhorst-pack 3 3 3
  np dimensions -1 -1 4
end
set includestress .true. # tell driver to optimize unit cell
set includelattice .true. # tell driver to optimize with
a,b,c,alpha,beta,gamma
task band optimize ignore
```

The optimized geometry will also contain the information about the symmetry being used

```
. . . .
   Optimization converged
   Step
        Energy
                 Delta E
                         Gmax
                                Grms
                                      Xrms
                                             Xmax
Walltime
- - - -
_ _ _ _ _ _ _ _ _
  7
       -45.62102901 -4.1D-07 0.00010 0.00003 0.00019 0.00060
6
  287.1
                           ok
                                  ok
                                         ok
                                                ok
                 Geometry "geometry" -> "geometry"
```

a.u.))									
No.		Tag	Cha	arge		Х		Y		Z
1 0.000	C)000000		l	6.0000	0.0	000000	0	0.00000	00	
2 1.767	C 715074		(6.0000	0.0	0000000	00	1.767150	74	
3 0.000	C)00000		(6.0000	1.7	7671507	'4	1.767150	74	
4 1.767	C 15074		(6.0000	1.7	7671507	4	0.00000	00	
5	C			6.0000	2.6	6507261	.1	0.883575	37	
6 0 88	C 857537		(6.0000	0.8	3835753	57	0.883575	37	
7 2 650	C		(6.0000	0.8	3835753	37	2.650726	11	
8 0.883	C 857537		(6.0000	2.6	507261	.1	2.650726	11	
	Lattic	e Parame	ters							
a.u.)	lattic	e vectors	s in ang	gstroms	(scale	e by 1	. 88972	25989 to	convert t	0
	al=< a2=< a3=<	3.534 0.000 0.000	0.000 3.534 0.000	0.000 × 0.000 × 3.534 ×	> > >					
	a= alpha= omega=	3.534 90.000 44.1	b= beta=	3.534 (90.000 (c= gamma=	3.5 = 90.0	534 100			
	recipr	ocal lat	tice ve	ctors in	a.u.					
	b1=< b2=< b3=<	0.941 0.000 0.000	0.000 0.941 0.000	0.000 0.000 0.941	> > >					

Output coordinates in angstroms (scale by 1.889725989 to convert to a.u.)

Atomic Mass

С

12.000000

Symmetry information

239



1 C 109 47	I	6 C	I	3 C	I
1 C	I	6 C	I	4 C	I
2 C	I	6 C	I	3 C	Ι
2 C	I	6 C	I	4 C	I
109.47 3 C 109.47	T	6 C	I	4 C	I
		number of ir	 cluded in	 ternuclear	angles:
9					

The following example uses the BAND module to optimize the unit cell and geometry for a Brucite $^{[4]}$ crystal (Mg(OH) ²) with P-3m1 symmetry.



title "brucite testing - using P-3ml symmetry" echo memory 1500 mb

permanent_dir ./perm
scratch_dir ./scratch

geometry nocenter noautosym noautoz print
system crystal
 lat_a 3.14979
 lat_b 3.14979
 lat_c 4.7702
 alpha 90.0

```
beta 90.0
   gamma 120.0
 end
symmetry P-3m1
    0.00000
Mg
               0.00000
                        0.00000
0
    0.33333
              0.66667
                        0.22030
Н
    0.33333
              0.66667
                        0.41300
end
set nwpw:cif filename brucite
#turn on pseudopotential filtering
set nwpw:kbpp_ray .true.
set nwpw:kbpp_filter .true.
#***** setup the nwpw gamma point code ****
nwpw
  ewald rcut 3.0
  ewald ncut 8
  xc pbe96
  lmbfgs
  monkhorst-pack 3 3 2
  #np dimensions -1 -1 4
end
driver
  clear
  maxiter 31
end
set includestress .true.
                                   # tell driver to optimize unit cell
set includelattice .true.
task band optimize ignore
```

Optimizing Brucite, which is a soft layered material (2.5-3 Mohs scale), is more difficult to optimize than a hard material such as Diamond. For these types of materials using symmetry can often result in a faster optimization. For example, with symmetry the optimization converges within 20 to 30 geometry optimization steps,

```
@ Step
                        Delta E
                                  Gmax
                                           Grms
                                                    Xrms
             Energy
                                                             Xmax
Walltime
@ ---- --
----
   0
           -34.39207476 0.0D+00 0.24673 0.10223 0.00000
                                                            0.00000
(d
   172.7
           -34.39340208 -1.3D-03 0.00872 0.00302
(d
    1
                                                   0.00198
                                                            0.00485
   328.5
. . . .
           -34.39042736 -1.2D-05 0.00195 0.00083 0.00440
   20
                                                            0.01964
@
3019.2
```

@	21	-34.39043463	-7.3D-06	0.00028	0.00011	0.00493	0.02042
3150	0.6						
@	22	-34.39043484	-2.1D-07	0.00043	0.00014	0.00002	0.00008
3278	3.5						
@	22	-34.39043484	-2.1D-07	0.00043	0.00014	0.00002	0.00008
3278	3.5						

whereas, without symmetry the optimization may not be converged even at 100 geometry steps (input:Media:brucite-nosymmetry.nw, output:Media:brucite-nosymmetry.nwout).

Delta E @ Step Energy Gmax Grms Xrms Xmax Walltime @ ----- - - - - - - -0 -34.39207476 0.0D+00 0.24673 0.10250 0.00000 0.00000 (d 18.4 6 1 -34.39340765 -1.3D-03 0.02963 0.00715 0.00202 0.00500 30.7 . . . **(**d 49 -34.39027641 -2.1D-06 0.01870 0.00646 0.00074 0.00202 595.7 **(**d 50 -34.39027503 1.4D-06 0.01962 0.00669 0.00069 0.00197 608.4 . . . a 100 -34.39034236 -3.8D-07 0.00380 0.00150 0.00036 0.00132 1155.3 @ 101 -34.39034431 -1.9D-06 0.00305 0.00118 0.00012 0.00045 1166.8 @ 102 -34.39034449 -1.8D-07 0.00370 0.00144 0.00006 0.00020 1177.9 . . .

NWPW Tutorial 8: Free Energy Simulations

A description of using the WHAM method for generating free energy of the gas-phase dissociation reaction CH $^{3}Cl \rightarrow CH ^{3}+Cl$ can be found in the attached pdf (Media:nwchem-new-pmf.pdf)

PAW Tutorial

Optimizing a water molecule

The following input deck performs for a water molecule a PSPW energy calculation followed by a PAW energy calculation and a PAW geometry optimization calculation. The default unit cell parameters are used (SC=20.0, ngrid 32 32 32). In this simulation, the first PAW run optimizes the wavefunction and the second PAW run optimizes the wavefunction and geometry in tandem.

title "paw steepest descent test"
start paw_test

```
charge 0
geometry units au nocenter noautoz noautosym
0
       0.00000
                  0.00000
                             0.01390
н
      -1.49490
                  0.00000
                            -1.18710
н
       1.49490
                  0.00000 -1.18710
end
nwpw
  time step 15.8
  ewald rcut 1.50
  tolerances 1.0d-8 1.0d-8
end
set nwpw:lcao iterations 1
set nwpw:minimizer 2
task pspw energy
task paw energy
nwpw
  time step 5.8
  geometry optimize
  ewald rcut 1.50
  tolerances 1.0d-7 1.0d-7 1.0d-4
end
task paw steepest descent
task paw optimize
```

Optimizing a unit cell and geometry for Silicon-Carbide

The following example demonstrates how to uses the PAW module to optimize the unit cell and geometry for a silicon-carbide crystal.

```
title "SiC 8 atom cubic cell - geometry and unit cell optimization"
start SiC
#**** Enter the geometry using fractional coordinates ****
geometry units au center noautosym noautoz print
system crystal
  lat a 8.277d0
  lat b 8.277d0
  lat c 8.277d0
  alpha 90.0d0
   beta 90.0d0
  gamma 90.0d0
end
Si
      -0.50000d0
                 -0.50000d0 -0.50000d0
Si
      0.00000d0
                   0.0000d0 -0.5000d0
      0.0000d0 -0.5000d0
Si
                               0.00000d0
Si
      -0.5000d0
                   0.00000d0
                               0.00000d0
С
      -0.25000d0 -0.25000d0 -0.25000d0
С
      0.25000d0
                   0.25000d0 -0.25000d0
С
      0.25000d0 -0.25000d0
                               0.25000d0
С
      -0.25000d0
                   0.25000d0
                               0.25000d0
```

```
end
#***** setup the nwpw gamma point code ****
nwpw
  simulation cell
    ngrid 16 16 16
  end
  ewald ncut 8
end
set nwpw:minimizer 2
set nwpw:psi nolattice .true. # turns of unit cell checking for
wavefunctions
driver
  clear
  maxiter 40
end
set includestress .true.
                                # this option tells driver to optimize
 the unit cell
set nwpw:stress numerical .true. #currently only numerical stresses
implemented in paw
task paw optimize
```

Running a Car-Parrinello Simulation

In this section we show how use the PAW module to perform a Car-Parrinello molecular dynamic simulation for a C_2 molecule at the LDA level. Before running a PAW Car-Parrinello simulation the system should be on the Born-Oppenheimer surface, i.e. the one-electron orbitals should be minimized with respect to the total energy (i.e. task pspw energy). The input needed is basically the same as for optimizing the geometry of a C_2 molecule at the LDA level, except that and additional Car-Parrinello sub-block is added.

In the following example we show the input needed to run a Car-Parrinello simulation for a C_2 molecule at the LDA level. In this example, default pseudopotentials from the pseudopotential library are used for C, the boundary condition is free-space, the exchange correlation functional is LDA, The boundary condition is free-space, and the simulation cell cell is aperiodic and cubic with a side length of 10.0 Angstroms and has 40 grid points in each direction (cutoff energy is 44 Ry). The time step and fake mass for the Car-Parrinello run are specified to be 5.0 au and 600.0 au, respectively.

```
start c2_paw_lda_md
title "C2 restricted singlet dimer, LDA/44Ry - constant energy
Car-Parrinello simulation"
geometry
C    -0.62 0.0 0.0
C     0.62 0.0 0.0
end
pspw
    simulation_cell units angstroms
        boundary_conditions aperiodic
        lattice
```

```
lat_a 10.00d0
lat_b 10.00d0
lat_c 10.00d0
end
ngrid 40 40 40
end
Car-Parrinello
fake_mass 600.0
time_step 5.0
loop 10 10
end
end
set nwpw:minimizer 2
task paw energy
task paw Car-Parrinello
```

NWPW Capabilities and Limitations

- Hybrid Functionals (e.g. PBE0, LDA-SIC) only work in PSPW.
- Wannier orbital task only works in PSPW.
- AIMD/MM simulation only works with PSPW.

Development Blog

Notes on current plane-wave developments can be found at the this link.

Questions and Difficulties

Questions and encountered problems should be reported to the NWChem Community Forum, nwchem-users@emsl.pnl.gov or to Eric J. Bylaska, Eric.Bylaska@pnl.gov

References

- [1] http://en.wikipedia.org/wiki/Metadynamics
- [2] http://iopscience.iop.org/0034-4885/71/12/126601
- [3] http://people.sissa.it/~laio/Research/Res_metadynamics.php
- [4] http://en.wikipedia.org/wiki/Brucite

Release65:TCE

__NOTITLE___

Tensor Contraction Engine Module: CI, MBPT, and CC

Overview

The Tensor Contraction Engine (TCE) Module of NWChem implements a variety of approximations that converge at the exact solutions of Schrödinger equation. They include configuration interaction theory through singles, doubles, triples, and quadruples substitutions, coupled-cluster theory through connected singles, doubles, triples, and quadruples substitutions, and many-body perturbation theory through fourth order in its tensor formulation. Not only optimized parallel programs of some of these high-end correlation theories are new, but also the way in which they have been developed is unique. The working equations of all of these methods have been derived completely automatically by a symbolic manipulation program called a Tensor Contraction Engine (TCE), and the optimized parallel programs have also been computer-generated by the same program, which were interfaced to NWChem. The development of the TCE program and this portion of the NWChem program has been financially supported by the United States Department of Energy, Office of Science, Office of Basic Energy Science, through the SciDAC program.

The capabilities of the module include:

- Restricted Hartree-Fock, unrestricted Hartree-Fock, and restricted open-shell Hartree-Fock references,
- Restricted KS DFT and unrestricted KS DFT references,
- Unrestricted configuration interaction theory (CISD, CISDT, and CISDTQ),
- Unrestricted coupled-cluster theory (LCCD, CCD, LCCSD, CCSD, QCISD, CCSDT, CCSDTQ),
- Unrestricted iterative many-body perturbation theory [MBPT(2), MBPT(3), MBPT(4)] in its tensor formulation,
- Unrestricted coupled-cluster singles and doubles with perturbative connected triples {CCSD(T), CCSD[T]},
- Unrestricted equation-of-motion coupled-cluster theory (EOM-CCSD, EOM-CCSDT, EOM-CCSDTQ) for excitation energies, transition moments and oscillator strengths, and excited-state dipole moments,
- Unrestricted coupled-cluster theory (CCSD, CCSDT, CCSDTQ) for dipole moments.
- Several variants of active-space CCSDt and EOMCCSDt methods that employ limited set of triply excited cluster amplitudes defined by active orbitals.
- Ground-state non-iterative CC approaches that account for the effect of triply and/or quadruply excited connected clusters: the perturbative approaches based on the similarity transformed Hamiltonian: CCSD(2), $CCSD(2)_T$, $CCSDT(2)_Q$, the completely and locally renormalized methods: CR-CCSD(T), LR-CCSD(T), LR-CCSD(TQ)-1.
- Excited-state non-iterative corrections due to triples to the EOMCCSD excitation energies: the completely renormalized EOMCCSD(T) method (CR-EOMCCSD(T)).

- Dynamic dipole polarizabilities at the CCSD and CCSDT levels using the linear response formalism.
- Ground- and excited- states the iterative second-order model CC2.
- Dynamic dipole polarizabilities at the CCSDTQ level using the linear response formalism.
- State-specific Multireference Coupled Cluster methods (MRCC) (Brillouin-Wigner (BW-MRCC) and Mukherjee (Mk-MRCC) approaches).
- Electron affinity/Ionization potential EOMCCSD formulations (EA/IP-EOMCC; available for RHF reference only).

The distributed binary executables do not contain CCSDTQ and its derivative methods, owing to their large volume. The source code includes them, so a user can reinstate them by setenv CCSDTQ yes and recompile TCE module. The following optimizations have been used in the module:

- Spin symmetry (spin integration is performed wherever possible within the unrestricted framework, making the present unrestricted program optimal for an open-shell system. The spin adaption was not performed, although in a restricted calculation for a closed-shell system, certain spin blocks of integrals and amplitudes are further omitted by symmetry, and consequently, the present unrestricted CCSD requires only twice as many operations as a spin-adapted restricted CCSD for a closed-shell system),
- Point-group symmetry,
- Index permutation symmetry,
- Runtime orbital range tiling for memory management,
- Dynamic load balancing (local index sort and matrix multiplications) parallelism,
- Multiple parallel I/O schemes including fully in-core algorithm using Global Arrays,
- Frozen core and virtual approximation.
- DIIS extrapolation and Jacobi update of excitation amplitudes
- Additional algorithms for the 2-e integral transformation, including efficient and scalable spin-free out-of-core N^5 algorithms.
- Hybrid I/O schemes for both spin-orbital and spin-free calculations which eliminate the memory bottleneck of the 2-e integrals in favor of disk storage. Calculations with nearly 400 basis functions at the CCSD(T) can be performed on workstation using this method.
- Parallel check-pointing and restart for ground-state (including property) calculations at the CCSD, CCSDT and CCSDTQ levels of theory.

Performance of CI, MBPT, and CC methods

For reviews or tutorials of these highly-accurate correlation methods, the user is referred to:

- Trygve Helgaker, Poul Jorgensen and Jeppe Olsen, Molecular Electronic-Structure Theory.
- A. Szabo and N. S. Ostlund, Modern Quantum Chemistry: Introduction to Advanced Electronic Structure Theory.
- B. O. Roos (editor), Lecture Notes in Quantum Chemistry.

For background on development of the symbolic algebra tools which help create the code used in this model see:

- S. Hirata, J. Phys. Chem. A 107, 9887 (2003).
- S. Hirata, J. Chem. Phys. 121, 51 (2004).
- S. Hirata, Theor. Chem. Acc. 116, 2 (2006).

For details of particular CC implementations, see:

- S. Hirata, P.-D. Fan, A.A. Auer, M. Nooijen, P. Piecuch, J. Chem. Phys. 121, 12197 (2004).
- K. Kowalski, S. Hirata, M. Wloch, P. Piecuch, T.L. Windus, J. Chem. Phys. 123, 074319 (2005).
- K. Kowalski, P. Piecuch, J. Chem. Phys. 115, 643 (2001).
- K. Kowalski, P. Piecuch, Chem. Phys. Lett. 347, 237 (2001).
- P. Piecuch, S.A. Kucharski, and R.J. Bartlett, J. Chem. Phys. 110, 6103 (1999).
- P. Piecuch, N. Oliphant, and L. Adamowicz, J. Chem. Phys. 99, 1875 (1993).
- N. Oliphant and L. Adamowicz, Int. Rev. Phys. Chem. 12, 339 (1993).
- P. Piecuch, N. Oliphant, and L. Adamowicz, J. Chem. Phys. 99, 1875 (1993).
- K. Kowalski, P. Piecuch, J. Chem. Phys. 120, 1715 (2004).
- K. Kowalski, J. Chem. Phys. 123, 014102 (2005).
- P. Piecuch, K. Kowalski, I.S.O. Pimienta, M.J. McGuire, Int. Rev. Phys. Chem. 21, 527 (2002).
- K. Kowalski, P. Piecuch, J. Chem. Phys. 122, 074107 (2005)
- K. Kowalski, W. de Jong, J. Mol. Struct.: THEOCHEM, 768, 45 (2006).
- O. Christiansen, H. Koch, P. Jørgensen, Chem. Phys. Lett. 243, 409 (1995).
- K. Kowalski, J. Chem. Phys. 125, 124101 (2006).
- K. Kowalski, S. Krishnamoorthy, O. Villa, J.R. Hammond, N. Govind, J. Chem. Phys. 132, 154103 (2010).
- J.R. Hammond, K. Kowalski, W.A. de Jong, J. Chem. Phys. 127, 144105 (2007).
- J.R. Hammond, W.A. de Jong, K. Kowalski, J. Chem. Phys. 128, 224102 (2008).
- J.R. Hammond, K. Kowalski, J. Chem. Phys. 130, 194108 (2009).
- W. Ma. S. Krishnamoorthy, O. Villa, J. Chem. Theory Comput. 7, 1316 (2011).
- J.Brabec, J. Pittner, H.J.J. van Dam, E. Apra, K. Kowalski, J. Chem. Theory Comput. 8, 487 (2012).
- K. Bhaskaran-Nair, J. Brabec, E. Apra, H.J.J. van Dam. J. Pittner, K. Kowalski, J. Chem. Phys. 137, 094112 (2012).
- K. Bhaskaran-Nair, K. Kowalski, J. Moreno, M. Jarrell, W.A. Shelton, J. Chem. Phys. 141, 074304 (2014).

Algorithms of CI, MBPT, and CC methods

Spin, spatial, and index permutation symmetry

The TCE thoroughly analyzes the working equation of many-electron theory models and automatically generates a program that takes full advantage of these symmetries at the same time. To do so, the TCE first recognizes the index permutation symmetries among the working equations, and perform strength reduction and factorization by carefully monitoring the index permutation symmetries of intermediate tensors. Accordingly, every input and output tensor (such as integrals, excitation amplitudes, residuals) has just two independent but strictly ordered index strings, and each intermediate tensor has just four independent but strictly ordered index strings. The operation cost and storage size of tensor contraction is minimized by using the index range restriction arising from these index permutation symmetries and also spin and spatial symmetry integration.

Runtime orbital range tiling

To maintain the peak local memory usage at a manageable level, in the beginning of the calculation, the orbitals are rearranged into tiles (blocks) that contains orbitals with the same spin and spatial symmetries. So the tensor contractions in these methods are carried out at the tile level; the spin, spatial, and index permutation symmetry is employed to reduce the operation and storage cost at the tile level also. The so-called tile-structure of all tensors used in CC equations is also the key-factor determining the parallel structure of the TCE CC codes . The tiling scheme corresponds to partitioning of the spin-orbital domain into smaller subsets containing the spin-orbitals of the same spin and spatial symmetries (the so-called tiles). This partitioning of the spin-orbital domain entails the blocking of all tensors corresponding to one- and two-electron integrals, cluster amplitudes, and all recursive intermediates, into smaller blocks of the size defined by the size of the tile (or tilesize for short). Since the parallel scheme used in all TCE generated codes is deeply rooted in dynamic load balancing techniques, the tile-structure defines the granularity of the work to be distributed. The size of tiles (tilesize) defines also the local memory requirements in all TCE derived CC implementations. For CI/CC/EOMCC/LR-CC models based on the sinlges and doubles models (CISD,CCSD,EOMCCSD,LR-CCSD) the peak local memory requirement is proportional to the $(tilesize)^4$. In approaches accounting for triples, either in iterative or non-iterative fashion, the local memory usage is proportional to (tilesize)⁶. This means that in the CCSD(T), CCSDt, CCSDT, CR-EOMCCSD(T), EOMCCSDt, EOMCCSDT, LR-CCSDT caluclations the tilesize cannot be defined too large.

Dynamic load balancing parallelism

In a parallel execution, dynamic load balancing of tile-level local tensor index sorting and local tensor contraction (matrix multiplication) will be invoked.

Parallel I/O schemes

Each process is assigned a local tensor index sorting and tensor contraction dynamically. It must first retrieve the tiles of input tensors, and perform these local operations, and accumulate the output tensors to the storage. We have developed a uniform interface for these I/O operations to either (1) a global file on a global file system, (2) a global memory on a global or distributed memory system, and (3) semi-replicated files on a distributed file systems. Some of these operations depend on the ParSoft library.

CCSD(T) method with CUDA

NWChem 6.3 offers a possibility of using GPU accelerators to perform the most computationally intensive part of the CCSD(T) calculations (non-iterative triples corrections). To enable this option one has to enable compilation options described below and add the "cuda n" directive to the tce block of input, where "n" refers to number of CUDA devices per node.

geometry/basis set specifications

```
tce
io ga
freeze atomic
thresh 1.0d-6
tilesize 15
```

ccsd(t) cuda 1 end

In the example above the number of CUDA devises is set equal to 1, which means that user will use 1 GPU per node.

To enable the compilation of CUDA code one has to set the following variables before the compilation of NWChem.

```
export TCE_CUDA=Y
export CUDA_LIBS="-L<Your Path to cuda>/lib64 -L<Your Path to
cuda>/lib -lcudart"
export CUDA_FLAGS="-arch compute capability 2.x or higher"
export CUDA_INCLUDE="-I. -I<Your Path to cuda>/include"
```

For example:

```
export TCE_CUDA=Y
export CUDA_LIBS="-L/usr/local/cuda-5.0/lib64 -L/usr/local/cuda-5.0/lib
    -lcudart"
export CUDA_FLAGS="-arch sm_20 "
export CUDA_INCLUDE="-I. -I/usr/local/cuda-5.0/include"
```

In addition the code needs to be compiled with the following make command

make FC=<fortran compiler> CUDA=nvcc

NOTE: Current version of cuda implementation is NOT supported for ARMCI_NETWORK=MPI-TS.

Before running production style calculations we strongly suggest the users to perform QA test from the /nwchem/QA/tests/tce_cuda directory. A full example of a TCE CUDA input file is given below:

```
start tce cuda
echo
memory stack 1000 mb heap 100 mb global 500 mb verify
geometry units bohr
  0
        0.00000000
                       0.00000000
                                      0.22138519
  Н
        0.0000000
                      -1.43013023
                                     -0.88554075
  н
        0.00000000
                       1.43013023
                                     -0.88554075
end
basis spherical
  H library cc-pVDZ
  0 library cc-pVDZ
end
charge 0
scf
  thresh 1.0e-10
  tol2e 1.0e-10
  singlet
  rhf
```

```
end
tce
ccsd(t)
io ga
cuda 1
tilesize 18
end
task tce energy
```

Input syntax

The keyword to invoke the many-electron theories in the module is TCE. To perform a single-point energy calculation, include

TASK TCE ENERGY

in the input file, which may be preceeded by the TCE input block that details the calculations:

TCE

```
[(DFT||HF||SCF) default HF=SCF]
   [FREEZE |
<integer nfzc default 0>)] \
             [virtual <integer nfzv default 0>
   [(LCCD||CCD||CCSD||CC2||LR-CCSD||LCCSD||CCSDT||CCSDTA||CCSDTQ|| \
     CCSD(T)||CCSD[T]||CCSD(2)_T||CCSD(2)||CCSDT(2)_Q|| \
     CR-CCSD[T]||CR-CCSD(T)|| \
     LR-CCSD(T)||LR-CCSD(TQ)-1||CREOMSD(T)|| \setminus
     QCISD||CISD||CISDT||CISDTQ|| \
     MBPT2||MBPT3||MBPT4||MP2||MP3||MP4) default CCSD]
   [THRESH <double thresh default 1e-6>]
   [MAXITER <integer maxiter default 100>]
   [PRINT (none||low||medium||high||debug)
     <string list_of_names ...>]
   [IO (fortran||eaf||ga||sf||replicated||dra||ga_eaf) default ga]
   [DIIS <integer diis default 5>]
   [LSHIFT <double lshift default is 0.0d0>]
   [NROOTS <integer nroots default 0>]
   [TARGET <integer target default 1>]
   [TARGETSYM <character targetsym default 'none'>]
   [SYMMETRY]
   [2E0RB]
   [2EMET <integer fast2e default 1>]
   [T3A LVL]
   [ACTIVE OA]
   [ACTIVE OB]
   [ACTIVE VA]
   [ACTIVE VB]
   [DIPOLE]
```
```
[TILESIZE <no default (automatically adjusted)>]
[(NO)FOCK <logical recompf default .true.>]
[FRAGMENT <default -1 (off)>]
END
```

Also supported are energy gradient calculation, geometry optimization, and vibrational frequency (or hessian) calculation, on the basis of numerical differentiation. To perform these calculations, use

TASK TCE GRADIENT

or

TASK TCE OPTIMIZE

or

TASK TCE FREQUENCIES

The user may also specify the parameters of reference wave function calculation in a separate block for either HF (SCF) or DFT, depending on the first keyword in the above syntax.

Since every keyword except the model has a default value, a minimal input file will be

```
GEOMETRY
Be 0.0 0.0 0.0
END
BASIS
Be library cc-pVDZ
END
TCE
ccsd
END
TASK TCE ENERGY
```

which performs a CCSD/cc-pVDZ calculation of the Be atom in its singlet ground state with a spin-restricted HF reference.

New implementions of the iterative CCSD and EOMCCSD methods based on the improved task scheduling can be enable by the "set tce:nts T" command as in the following example:

```
geometry/basis set specifications
tce
freeze atomic
creomccsd(t)
tilesize 20
2eorb
2emet 13
eomsol 2
end
set tce:nts T
task tce energy
```

New task scheduling should reduce time to solutions and provide better parallel perfromance especially in large CCSD/EOMCCSD runs.

Keywords of TCE input block

HF, SCF, or DFT -- the reference wave function

This keyword tells the module which of the HF (SCF) or DFT module is going to be used for the calculation of a reference wave function. The keyword HF and SCF are one and the same keyword internally, and are default. When these are used, the details of the HF (SCF) calculation can be specified in the SCF input block, whereas if DFT is chosen, DFT input block may be provided.

For instance, RHF-RCCSDT calculation (R standing for spin-restricted) can be performed with the following input blocks:

SCF SINGLET RHF END TCE SCF CCSDT END TASK TCE ENERGY

This calculation (and any correlation calculation in the TCE module using a RHF or RDFT reference for a closed-shell system) skips the storage and computation of all β spin blocks of integrals and excitation amplitudes. ROHF-UCCSDT (U standing for spin-unrestricted) for an open-shell doublet system can be requested by

and likewise, UHF-UCCSDT for an open-shell doublet system can be specified with

SCF DOUBLET UHF END TCE SCF CCSDT END

TASK TCE ENERGY

The operation and storage costs of the last two calculations are identical. To use the KS DFT reference wave function for a UCCSD calculation of an open-shell doublet system,

DFT ODFT MULT 2 END TCE DFT CCSD END TASK TCE ENERGY

Note that the default model of the DFT module is LDA.

CCSD,CCSDT,CCSDTQ,CISD,CISDT,CISDTQ, MBPT2,MBPT3,MBPT4, etc.--the correlation models

These keywords stand for the following models:

- LCCD: linearized coupled-cluster doubles,
- CCD: coupled-cluster doubles,
- LCCSD: linearized coupled-cluster singles & doubles,
- CCSD: coupled-cluster singles & doubles (also EOM-CCSD),
- CCSD_ACT: coupled-cluster singles & active doubles (also active-space EOMCCSD),
- LR-CCSD: locally renormalized EOMCCSD method.
- EACCSD: Electron affinity EOMCCSD method.
- IPCCSD: Ionization potential EOMCCSD method.
- CC2: second-order approximate coupled cluster with singles and doubles model
- CCSDT: coupled-cluster singles, doubles, & triples (also EOM-CCSDT),
- CCSDTA: coupled-cluster singles, doubles, & active triples (also EOM-CCSDT). Three variants of the active-space CCSDt and EOMCCSDt approaches can be selected based on various definitions of triply excited clusters: (1) version I (keyword T3A_LVL 1) uses the largest set of triply excited amplitudes defined by at least one occupied and one unoccupied active spinorbital labels. (2) Version II (keyword T3A_LVL 2) uses triply excited amplitudes that carry at least two occupied and unoccupied active spinorbital labels. (3) Version III (keyword T3A_LVL 3) uses triply excited amplitudes that are defined by active indices only. Each version requires defining relevant set of occupied active and β spinorbitals (ACTIVE_OA and ACTIVE_OB) as well as active unoccupied α and β spinorbitals (ACTIVE_VA and ACTIVE_VB).
- CCSDTQ: coupled-cluster singles, doubles, triples, & quadruples (also EOM-CCSDTQ),
- CCSD(T): CCSD and perturbative connected triples,
- CCSD[T]: CCSD and perturbative connected triples,
- CR-CCSD[T]: completely renormalized CCSD[T] method,
- CR-CCSD(T): completely renormalized CCSD(T) method,
- CCSD(2) T: CCSD and perturbative $CCSD(T)_T$ correction,
- CCSD(2)_TQ: CCSD and perturbative CCSD(2) correction,
- CCSDT(2)_Q: CCSDT and perturbative CCSDT(2)\$_Q\$ correction.

- LR-CCSD(T): CCSD and perturbative locally renormalized CCSD(T) correction,
- LR-CCSD(TQ)-1: CCSD and perturbative locally renormalized CCSD(TQ) (LR-CCSD(TQ)-1) correction,
- CREOMSD(T): EOMCCSD energies and completely renormalized EOMCCSD(T)(IA) correction. In this option NWCHEM prints two components: (1) total energy of the K-th state $E_K = E_K^{\text{EOMCCSD}} + \delta_K^{\text{CR}-\text{EOMCCSD(T),IA}}(T)$ and (2) the so-called δ -corrected EOMCCSD excitation energy $\omega_K^{\text{CR}-\text{EOMCCSD(T),IA}} = \omega_K^{\text{EOMCCSD}} + \delta_K^{\text{CR}-\text{EOMCCSD(T),IA}}(T)$.
- CREOM(T)AC: active-space CR-EOMCCSD(T) approach,
- QCISD: quadratic configuration interaction singles & doubles,
- CISD: configuration interaction singles & doubles,
- CISDT: configuration interaction singles, doubles, & triples,
- CISDTQ: configuration interaction singles, doubles, triples, & quadruples,
- MBPT2=MP2: iterative tensor second-order many-body or Møller-Plesset perturbation theory,
- MBPT3=MP3: iterative tensor third-order many-body or Møller-Plesset perturbation theory,
- MBPT4=MP4: iterative tensor fourth-order many-body or Møller-Plesset perturbation theory,

All of these models are based on spin-orbital expressions of the amplitude and energy equations, and designed primarily for spin-unrestricted reference wave functions. However, for a restricted reference wave function of a closed-shell system, some further reduction of operation and storage cost will be made. Within the unrestricted framework, all these methods take full advantage of spin, spatial, and index permutation symmetries to save operation and storage costs at every stage of the calculation. Consequently, these computer-generated programs will perform significantly faster than, for instance, a hand-written spin-adapted CCSD program in NWChem, although the nominal operation cost for a spin-adapted CCSD there are three independent sets of excitation amplitudes, whereas in spin-adapted CCSD there is only one set, so the nominal operation cost for the latter is one third of that of the former. For a restricted reference wave function of a closed-shell system, all β spin block of the excitation amplitudes and integrals can be trivially mapped to the all α spin block, reducing the ratio to one half).

While the MBPT (MP) models implemented in the TCE module give identical correlation energies as conventional implementation for a canonical HF reference of a closed-shell system, the former are intrinsically more general and theoretically robust for other less standard reference wave functions and open-shell systems. This is because the zeroth order of Hamiltonian is chosen to be the full Fock operatior (not just the diagonal part), and no further approximation was invoked. So unlike the conventional implementation where the Fock matrix is assumed to be diagonal and a correlation energy is evaluated in a single analytical formula that involves orbital energies (or diagonal Fock matrix elements), the present tensor MBPT requires the iterative solution of amplitude equations and subsequent energy evaluation and is generally more expensive than the former. For example, the operation cost of many conventional implementation of MBPT(2) scales as the fourth power of the system size, but the cost of the present tensor MBPT(2) scales as the fifth power of the system size, as the latter permits non-canonical HF reference and the former does not (to reinstate the non-canonical HF reference in the former makes it also scale as the fifth power of the system size).

State-Specific Multireference Coupled Cluster methods (MRCC)

Several State-Specific MRCC methods have been implemented in 6.3 release of nwchem. These include:

- Iterative Brillouin-Wigner MRCC method employing single and double excitations (BW-MRCCSD)
- Iterative Mukherjee MRCC method employing single and double excitations (Mk-MRCCSD)
- Non-iterative methods accounting for triple excitations in MRCC formalisms: BW-MRCCSD(T) and Mk-MRCCSD(T)

The current implementation can be used in studies of systems composed of an even number of correlated electrons (this limitation will be removed in the next release). This includes typical examples of diradical, open-shell singlets, and bond-forming/breaking processes where the corresponding wavefunctions have strong quasidegenerate character.

To enable the compilation of the MRCC codes one has to set the following variable before the compilation of NWChem

export MRCC_METHODS=y

To run MRCC calculations the user has to define two groups in the input file. First, the TCE group and secondly the MRCCDATA group. In the TCE group the iterative level of theory is defined, e.g. BWCCSD or MKCCSD. This implementation was designed for complete model spaces (CMS) which means that the modelspace contains all Slater determinants of all possible (in the context of the spatial and spin symmetry, M_s) distributions of active electrons among active spin orbitals. The user can define the modelspace in two ways. As a first approach the model space can be defined by hand, as shown in the two examples below. The input of the model space starts with the "NREF" keyword followed by the number of reference configurations that will be used, which should equal the number of strings for references below. In the input "2" refers to doubly occupied orbitals, "a" to alpha electrons, "b" to beta electrons and "0" identifies an unoccupied orbital. When the model space is defined by hand the occupation strings have to include the frozen orbitals as well. In the second way the CMS can be generated using the keyword "CAS" followed by the number of active electrons and the number of active orbitals. When using the "CAS" keyword we strongly recommend that users check the references that are generated.

As the model space typically includes multiple configurations it is possible to use the MRCC method to calculate excited states instead of the ground state. For this reason it is required to specify the root of interest. The ROOT keyword followed by the root number specifies the state the code calculates. The lowest root, the ground state, is identified as root 1. If one wants to calculate the third root the keyword ROOT 3 should be used. An example is given below.

```
echo
start tce mrcc bwcc
memory stack 1000 mb heap 100 mb global 500 mb verify
geometry units au
  Н
                         0.0000000
                                        -2.27289450
                                                         -1.58834700
  0
                         0.0000000
                                         0.0000000
                                                         -0.01350000
  Н
                         0.0000000
                                         2.27289450
                                                         -1.58834700
end
```

```
basis spherical
  0 library cc-pvdz
  H library cc-pvdz
end
charge 0
scf
  rohf
  singlet
  thresh 1.0e-10
  tol2e 1.0e-10
end
tce
  bwccsd
  thresh 1.0e-7
 targetsym al
  io ga
  tilesize 18
end
mrccdata
  root 1
  nref 4
  222220
  222202
  2222ab
  2222ba
end
task tce energy
echo
start tce_mrcc_mkcc
memory stack 1000 mb heap 100 mb global 500 mb verify
geometry units au
  Н
                      0.00000000
                                      -2.27289450
                                                       -1.58834700
  0
                       0.00000000
                                       0.00000000
                                                       -0.01350000
  Н
                       0.00000000
                                       2.27289450
                                                       -1.58834700
end
basis spherical
  0 library cc-pvdz
  H library cc-pvdz
end
charge 0
scf
  rohf
  singlet
  thresh 1.0e-10
  tol2e 1.0e-10
end
tce
```

```
mkccsd
thresh 1.0e-5
targetsym al
maxiter 100
io ga
tilesize 18
end
mrccdata
root 1
cas 2 2 # Please make sure the references generated are correct.
end
task tce energy
```

This version of MRCC works only with GA as specified by the "IO GA" option. In addition this code works only with the spin-orbit 4-index transformation, however in all circumstances an RHF Hartree-Fock initial calculation has to be used. In this implementation the effective Hamiltonian operator contains only scalar, one- and two-body many body components. Finally, in our implementation the BWCCSD methods use the energy threshold for the convergence, whereas the MKCCSD method uses the norm of the residual.

In addition to the iterative single-double calculations the code can calculate non-iterative triples corrections. To request these triples corrections the keyword "SE4T" should be added to the MRCCDATA block. The implementation details and the from of the triples correction are given in equation 20 [[http://dx.doi.org/10.1063/1.4747698 J. Chem. Phys. 137, 094112 (2012)]].

```
echo
start tce mrcc bwcc
memory stack 1000 mb heap 100 mb global 500 mb verify
geometry units au
  Н
                         0.0000000
                                         -2.27289450
                                                         -1.58834700
  0
                         0.00000000
                                          0.00000000
                                                         -0.01350000
  Н
                         0.00000000
                                          2.27289450
                                                         -1.58834700
end
basis spherical
  0 library cc-pvdz
  H library cc-pvdz
end
charge 0
scf
  rohf
  singlet
  thresh 1.0e-10
  tol2e 1.0e-10
end
tce
  bwccsd
  thresh 1.0e-7
```

targetsym al io ga tilesize 18 end mrccdata se4t no_aposteriori root 1 nref 4 222220 222202 2222ab 2222ba end task tce energy echo start tce_mrcc_mkcc memory stack 1000 mb heap 100 mb global 500 mb verify geometry units au Н 0.00000000 -2.27289450 -1.58834700 0 0.00000000 0.00000000 -0.01350000 н 0.00000000 2,27289450 -1.58834700end basis spherical 0 library cc-pvdz H library cc-pvdz end charge 0 scf rohf singlet thresh 1.0e-10 tol2e 1.0e-10 end tce mkccsd thresh 1.0e-5 targetsym al io ga tilesize 18 maxiter 100 end mrccdata se4t root 1 nref 4 222220

222202 2222ab 2222ba end task tce energy

The current version of the MRCC codes contains also a pilot implementation of the reference-level-parallelism based on the use of processor groups for BWCCSD and BWCCSD(T) approaches. The main ideas of this approach have been described in

- J.Brabec, J. Pittner, H.J.J. van Dam, E. Apra, K. Kowalski, J. Chem. Theory Comput. 8, 487 (2012)^[1].
- K. Bhaskaran-Nair, J. Brabec, E. Apra, H.J.J. van Dam. J. Pittner, K. Kowalski, J. Chem. Phys. 137, 094112 (2012)^[2].

Two essential keywords have to be added to the "mrccdata" block of the input:

subgroupsize n improvetiling

and

diis 0

in tce block. The "subgroupsize n" defines the size of the subgroup and improvetiling refers to the data representation in the MRCC subgroup algorithm. For example, if user has 4 references and total 32 cores/CPU then n should be defined as 32/4=8. If user has 10 references and 1200 cores/CPU available then the size of the subgroupsize (n) is 120.

```
echo
start tce mrcc bwcc subgroups
memory stack 1000 mb heap 100 mb global 500 mb verify
geometry units au
  Н
                       0.00000000
                                      -2.27289450
                                                       -1.58834700
  0
                       0.0000000
                                       0.0000000
                                                       -0.01350000
                                       2.27289450
  н
                       0.0000000
                                                       -1.58834700
end
basis spherical
  0 library cc-pvdz
  H library cc-pvdz
end
charge 0
scf
  rohf
  singlet
  thresh 1e-12
  tol2e 1e-12
end
tce
  bwccsd
  targetsym al
  io ga
```

```
diis 0
thresh 1e-7
tilesize 18
end
mrccdata
subgroupsize 2 # Please read the documentation below.
improvetiling
root 1
cas 2 2
end
task tce energy
```

CAUTION: Before using the subgroup-based algorithm the users should perform the GA subgroup test in nwchem/src/tools/ga-5-2/global/testing/pgtest.x and pg2test.x in the same location. Additionally it is strongly encouraged to run the NWChem QA tests from the /nwchem/QA/tests/tce_mrcc_bwcc_subgroups directory with various combinations of subgroup size and total number of CPU.

Electron affinity, ionization potential EOMCCSD methods

The EA/IP-EOMCCSD methodologies are available in the 6.5 NWChem release. These implementation are available for the RHF type of the reference function. Two input examples for the EA/IP-EOMCCSD calculations are shown below.

• EA-EOMCCSD calculations for the ozone molecule

```
start tce_eaccsd_ozone
title "tce eaccsd ozone"
echo
memory stack 1000 mb heap 200 mb global 500 mb
geometry units bohr
symmetry cl
                         0.000000000
                                             0.000000000
0
   0.0000000000
0
    0.000000000
                        -2.0473224350
                                            -1.2595211660
0
    0.000000000
                         2.0473224350
                                            -1.2595211660
end
basis spherical
 * library cc-pvdz
end
scf
thresh 1.0e-10
tol2e 1.0e-10
singlet
rhf
end
tce
eaccsd
```

```
nroots 2
freeze atomic
tilesize 20
thresh 1.0d-6
end
task tce energy
• IP-EOMCCSD calculations for the F2 molecule
start tce_ipccsd_f2
title "tce_ipccsd_f2"
echo
memory stack 1000 mb heap 200 mb global 500 mb
geometry units angstroms
symmetry c1
 F
      0.000000000
                           0.000000000
                                          0.7059650
 F
      0.000000000
                           0.0000000000
                                        -0.7059650
end
basis spherical
* library cc-pvdz
end
scf
thresh 1.0e-10
tol2e 1.0e-10
singlet
rhf
end
tce
ipccsd
nroots 1
freeze atomic
thresh 1.0e-7
end
task tce energy
```

As in the EOMCCSD input we can request any number of roots.

In analogy to the EOMCC calculations we can customize the number of initial guesses by using "set tce:maxeorb" directive. For example for system with the C2V symmetry with the orbital energy structure shown below



one can use the energy window (in the sense of the absolute value of the HF orbital energies) to pinpoint the initial guesses. If one is interested in calculating one EA-EOMCCSD root of the a1 symmetry the

set tce:maxeorb 0.1

should be used. This means that the number of starting vectors will be equal to the number of the unoccupied a1 symmetry orbitals with the corresponding orbital energies less than 0.1 (in our example there will be only one such a vector corresponding to the unoccupied orbital energy 0.072). If one looks for two roots of b2 symmetry

set tce:maxeorb 0.16

option should be used(there are two b2 unoccupied orbitals with energies less than 0.16).

For the IP-EOMCCSD case the "set tce:maxeorb" option works in a similar way. For example if one is looks for 1 IP-EOMCCSD root of a 1 symmetry ,

```
set tce:maxeorb 0.24
```

directive should be used (there is only one occupied orbital of a1 symmetry with the absolute value of the corresponding orbital energy less than 0.24), etc.

THRESH --the convergence threshold of iterative solutions of amplitude equations

This keyword specifies the convergence threshold of iterative solutions of amplitude equations, and applies to all of the CI, CC, and MBPT models. The threshold refers to the norm of residual, namely, the deviation from the amplitude equations. The default value is 1e-6.

MAXITER --the maximum number of iterations

It sets the maximum allowed number iterations for the iterative solutions of amplitude equations. The default value is 100.

IO --parallel I/O scheme

There are five parallel I/O schemes implemented for all the models, which need to be wisely chosen for a particular problem and computer architecture.

- fortran : Fortran77 direct access,
- eaf : Exclusive Access File library,
- ga : Fully incore, Global Array virtual file,
- sf : Shared File library,
- replicated : Semi-replicated file on distributed file system with EAF library.
- dra : Distributed file on distributed file system with DRA library.
- ga_eaf : Semi-replicated file on distributed file system with EAF library. GA is used to speedup the file reconciliation.

The GA algorithm, which is default, stores all input (integrals and excitation amplitudes), output (residuals), and intermediate tensors in the shared memory area across all nodes by virtue of GA library. This fully incore algorithm replaces disk I/O by inter-process communications. This is a recommended algorithm whenever feasible. Note that the memory management through runtime orbital range tiling described above applies to local (unshared) memory of each node, which may be separately allocated from the shared memory space for GA. So when there is not enough shared memory space (either physically or due to software limitations, in particular, shmmax setting), the GA algorithm can crash due to an out-of-memory error. The replicated scheme is the currently the only disk-based algorithm for a genuinely distributed file system. This means that each node keeps an identical copy of input tensors and it holds non-identical overlapping segments of intermediate and output tensors in its local disk. Whenever data coherency is required, a file reconcilation process will take place to make the intermediate and output data identical throughout the nodes. This algorithm, while requiring redundant data space on local disk, performs reasonably efficiently in parallel. For sequential execution, this reduces to the EAF scheme. For a global file system, the SF scheme is recommended. This together with the Fortran77 direct access scheme does not usually exhibit scalability unless shared files on the global file system also share the same I/O buffer. For sequential executions, the SF, EAF, and replicated schemes are interchangeable, while the Fortran77 scheme is appreciably slower.

Two new I/O algorithms dra and ga_eaf combines GA and DRA or EAF based replicated algorithm. In the former, arrays that are not active (e.g., prior T amplitudes used in DIIS or EOM-CC trial vectors) in GA algorithm will be moved to DRA. In the latter, the intermediates that are formed by tensor contractions are initially stored in GA, thereby

266

avoiding the need to accumulate the fragments of the intermediate scattered in EAFs in the original EAF algorithm. Once the intermediate is formed completely, then it will be replicated as EAFs.

The spin-free 4-index transformation algorithms are exclusively compatible with the GA I/O scheme, although out-of-core algorithms for the 4-index transformation are accessible using the 2emet options. See Alternative storage of two-electron integrals for details.

DIIS --the convergence acceleration

It sets the number iterations in which a DIIS extrapolation is performed to accelerate the convergence of excitation amplitudes. The default value is 5, which means in every five iteration, one DIIS extrapolation is performed (and in the rest of the iterations, Jacobi rotation is used). When zero or negative value is specified, the DIIS is turned off. It is not recommended to perform DIIS every iteration, whereas setting a large value for this parameter necessitates a large memory (disk) space to keep the excitation amplitudes of previous iterations. In 5.0 version we significantly improved the DIIS solver by re-organizing the itrative process and by introducing the level shift option (lshift) that enable to increase small orbital energy differences used in calculating the up-dates for cluster amplitudes. Typical values for lshift oscillates between 0.3 and 0.5 for CC calculations for ground states of multi-configurational character. Otherwise, the value of lshift is by default set equal to 0.

FREEZE -- the frozen core/virtual approximation

Some of the lowest-lying core orbitals and/or some of the highest-lying virtual orbitals may be excluded in the calculations by this keyword (this does not affect the ground state HF or DFT calculation). No orbitals are frozen by default. To exclude the atom-like core regions altogether, one may request

FREEZE atomic

To specify the number of lowest-lying occupied orbitals be excluded, one may use

FREEZE 10

which causes 10 lowest-lying occupied orbitals excluded. This is equivalent to writing

FREEZE core 10

To freeze the highest virtual orbitals, use the virtual keyword. For instance, to freeze the top 5 virtuals

FREEZE virtual 5

NROOTS -- the number of excited states

One can specify the number of excited state roots to be determined. The default value is 1. It is advised that the users request several more roots than actually needed, since owing to the nature of the trial vector algorithm, some low-lying roots can be missed when they do not have sufficient overlap with the initial guess vectors.

TARGET and TARGETSYM --the target root and its symmetry

At the moment, the first and second geometrical derivatives of excitation energies that are needed in force, geometry, and frequency calculations are obtained by numerical differentiation. These keywords may be used to specify which excited state root is being used for the geometrical derivative calculation. For instance, when TARGET 3 and TARGETSYM a1g are included in the input block, the total energy (ground state energy plus excitation energy) of the third lowest excited state root (excluding the ground state) transforming as the irreducible representation a1g will be passed to the module which performs the derivative calculations. The default values of these keywords are 1 and none, respectively.

The keyword TARGETSYM is essential in excited state geometry optimization, since it is very common that the order of excited states changes due to the geometry changes in the course of optimization. Without specifying the TARGETSYM, the optimizer could (and would likely) be optimizing the geometry of an excited state that is different from the one the user had intended to optimize at the starting geometry. On the other hand, in the frequency calculations, TARGETSYM must be none, since the finite displacements given in the course of frequency calculations will lift the spatial symmetry of the equilibrium geometry. When these finite displacements can alter the order of excited states including the target state, the frequency calculation is not be feasible.

SYMMETRY --restricting the excited state symmetry

By adding this keyword to the input block, the user can request the module to seek just the roots of the specified irreducible representation as TARGETSYM. By default, this option is not set. TARGETSYM must be specified when SYMMETRY is invoked.

EOMSOL --alternative solver for the right EOMCCSD eigenvalue problem

The EOMSOL enables the user to switch between two algorithms for solving EOMCCSD eigenproblem. When EOMSOL is set equal to 1 ("eomsol 1" directive in the tce group) the old solver is invoked. The advantage of this solver is a possibility of finding states of complicated configurational structure, for example doubly excited states. However, the dimension of the iterative space increases with each iteration and in effect this algorithm requires large memory allocations especially for large systems. In order to address this bottleneck, new algorithm ("eomsol 2" directive in the tce group) was designed. In EOMSOL 2 algorithm all iterations are split into microcycles corresponding to diis microiterations (the use of "diis" parameter is discussed earlier). This algorithm enables the user to precisely estimate the memory usage in the EOMCCSD calculations, which is equal to diis*nroots*(size_x1+size_x2), where diis is the length of the DIIS cycle, nroots is the number of sought roots, size_x1 corresponds to the size of GA storing singly excited EOMCC amplitudes, and size_x2 is the size of GA with doubly excited EOMCC amplitudes.

Generally, larger values of diis parameter lead to a faster convergence, however, this happens at the expense of larger memory requirements. It is recommended not to use in the EOMCCSD calculations with "eomsol 2" diis parameter smaller than 5, which is its default value. The EOMSOL 2 algorithm uses the CIS vectors as initial guesses, and for this reason is suited mainly to track singly excited states. By default, the EOMSOL 1 option is called in the EOMCCSD calculations. It should be also stressed that all iterative EOMCC methods with higher than double excitations use EOMSOL 1 approach.

In some situations it is convenient to use separate convergence threshold for the CCSD and EOMCCSD solvers. This can be achieved by setting proper environmetal variables. In the following example

```
geometry/basis set specifications
tce
  thresh 1.0d-6
  ccsd
  nroots 2
end
set tce:thresheom 1.0d-4
task tce energy
```

the CCSD equations will be converged to the 1.0d-6 threshold while the EOMCCSD ones to 1.0d-4. This option shoul dbe used with the "eomsol 2" option. In some situations finding several (n) roots to the EOMCCSD equations can be quite challenging. To by-pass this problem one can use the "n+1" model, i.e., we request another root to be converged. Usually, the presence the "buffer" root can imporve the iterative process for n roots of interest. However, the buffer root does not have to be converged to the same accuracy as n roots of interest. The following example, shows how to handle this process (we chose n=2, n+1=3):

```
geometry/basis set specifications
tce
  freeze core
  ccsd
  nroots 3
  thresh 1.0d-6
end
set tce:thresheom 1.0d-4
set tce:threshl 1.0d-3
task tce energy
```

In this example the CCSD equations are solved with the 1.0d-6 threshold, the first n (2) EOMCCSD roots are determined with the 10d-4 accuracy, while the buffer root is determined with relax conv. criterion 1.0d-3.

2EORB --alternative storage of two-electron integrals

In the 5.0 version a new option has been added in order to provide more economical way of storing two-electron integrals used in CC calculations based on the RHF and ROHF references. The 2EORB keyword can be used for all CC methods except for those using an active-space (CCSDt). All two-electron integrals are transformed and subsequently stored in a way which is compatible with assumed tiling scheme. The transformation from orbital to spinorbital form of the two-electron integrals is performed on-the-fly during execution of the CC module. This option, although slower, allows to significantly reduce the memory requirements needed by the first half of 4-index transformation and final file with fully transformed two-electron integrals. Savings in the memory requirements on the order of magnitude (and more) have been observed for large-scale open-shell calculations.

2EMET --alternative storage of two-electron integrals

Several new computation-intensive algorithms has been added with the purpose of improving scalability and overcoming local memory bottleneck of the 5.0 2EORB 4-index transformation. In order to give the user a full control over this part of the TCE code several keywords were designed to define the most vital parameters that determine the perfromance of 4-index transformation. All new keywords must be used with the 2EORB keyword. The 2emet keyword (default value 1 or 2emet 1, refers to the older 4-index transformation), defines the algorithm to be used. By putting 2emet 2 the TCE code will execute the algoritm based on the two step procedure with two intermediate files. In some instances this algorithm is characterized by better timings compared to algorithms 3 and 4, although it is more memory demanding. In contrast to algorithms nr 1,3, and 4 this approach can make use of a disk to store intermediate files. For this purpose one should use the keyword idiskx (idiskx 0 causes that all intermediate files are stored on global arrays, while idiskx 1 tells the code to use a disk to store intermediates; default value of idiskx is equal 0). Algorithm nr 3 (2emet 3) uses only one intermediate file whereas algorithm nr 4 (2emet 4) is a version of algorithm 3 with the option of reducing the memory requirements. For example, by using new keyword split 4 we will reduce the size of only intermediate file by factor of 4 (the split keyword can be only used in the context of algorithm nr 4). All new algorithms (i.e. 2emet 2+) use the attilesize setting to define the size of the atomic tile. By default attilesize is set equal 30. For larger systems the use of larger values of attilesize is recommended (typically between 40-60).

Additional algorithms are numbered 5, 6 and 9. Other values of 2emet are not supported and refer to methods which do not function properly. Algorithms 5 and 6 were written as out-of-core N^5 methods (idiskx 1) and are the most efficient algorithms at the present time. The corresponding in-core variants (idiskx 0) are available but require excessive memory with respect to the methods discussed above, although they may be faster if sufficient memory is available (to get enough memory often requires excessive nodes, which decreases performance in the later stages of the calculation). The difference between 5 and 6 is that 5 writes to a single file (SF or GA) while 6 uses multiple files. For smaller calculations, particularly single-node jobs, 5 is faster than 6, but for more than a handful of processors, algorithm 6 should be used. The perforance discrepancy depends on the hardware used but in algorithm eliminates simulataneous disk access on parallel file systems or memory mutexes for the in-core case. For NFS filesystems attached to parallel clusters, no performance differences have been observed, but for Lustre and PVFS they are signficant. Using algorithm 5 for large parallel file systems will make the file system inaccessible to other users, invoking the wrath of system administrators.

Algorithm 9 is an out-of-core solution to the memory bottleneck of the 2-e integrals. In this approach, the intermediates of the 4-index transformation as well as the MO integrals are stored in an SF file. As before, this requires a shared file system. Because algorithm 9 is based upon algorithm 5, described above, it is not expected to scale. The primary purpose of algorithm 9 is to make the performance of the NWChem coupled-cluster codes competive with fast serial codes on workstations. It succeeds in this purpose when corresponding functionality is compared. A more scalable version of this algorithm is possible, but the utility is limited since large parallel computers do not permit the wall times necessary to use an out-of-core method, which is necessarily slower than the in-core variant. An extensible solution to these issues using complex heterogeneous I/O is in development. Restarting with algorithm 9 is not supported and attempting to use this feature with the present version may produce meaningless results.

New is the inclusion of multiple 2emet options for the spin-orbital transformations, which are the default when 2eorb is not set and are mandatory for UHF and KS references. The are currently three algorithms 1, 2 and 3 available. The numbering scheme does not correspond in any way to the numbering scheme for the 2eorb case, except that 2emet 1 corresponds to the default algorithm present in previous releases, which uses the user-defined I/O scheme. Algorithm 2 (2emet 2) writes an SF file for the half-transformed integrals, which is at least an order-of-magnitude larger than the fully-transformed integrals, but stores the fully-transformed integrals in core. Thus, once the 4-index transformation is complete, this algorithm will perform exactly as when algorithm 1 is used. Unfortuntely, the spin-orbital 2-e fully-transformed integrals are still quite large and an algorithm corresponding to 2eorb/2emet=9 is available with 2emet 3. Algorithm 3 is also limited in its scalability, but it permits relatively large UHF-based calculations using single workstations for patient users.

In cases where the user has access to both shared and local filesystems for parallel calculations, the permanent_dir setting refers to the location of SF files. The file system for scratch_dir will not be used for any of the 4-index transformation algorithms which are compatible with io=ga.

Algorithms 13 and 14 are the N^5 variants of algorithms 3 and 4. They are the most efficient in core GA-based algorithms for the RHF and ROHF reference functions. Again, two parameters are needed to define the perfromance of these algorithms: tilesize and attilesize. By default attilesize is set equal to 40. In all runs tilesize is required to be less than attilesize (tilesize < attilesize).

New 4-index transformation for RHF/ROHF references (2emet 15) is available in NWChem 6.5. In contrast to algorithms 13 and 14 inter-processor communication is significantly reduced resulting in much better performance.

In the later part of this manual several examples illustrate the use of the newly introduced keywords.

CCSD(T)/CR-EOMCCSD(T) calculations with large tiles

In 6.5 version of NWChem we have enabled versions of the CCSD(T) and CR-EOMCCSD(T) codes, which by-pass the local memory limitation of previous implementations. For this purpose a sliced versions of the CCSD(T)/CR-EOMCCSD(T) codes have been developed (see K. Kowalski, S. Krishnamoorthy, R. Olson, V. Tipparaju, E. Apra, Supercomputing 2011, Seattle). In order to enable these versions it is enough to add

set tce:xmem 100

which defines maximum memory size (in MB) for the slice of 6-dimensional tensors (in the current example 100 MB; for more details see QA tests tce_ccsd_t_xmem and tce_cr_eomccsd_t_xmem).

DIPOLE --the ground-and excited-state dipole moments

When this is set, the ground-state CC calculation will enter another round of iterative step for the so-called \$\Lambda\$ equation to obtain the one-particle density matrix and dipole moments. Likewise, for excited-states (EOM-CC), the transition moments and dipole moments will be computed when (and only when) this option is set. In the latter case, EOM-CC left hand side solutions will be sought incurring approximately three times the computational cost of excitation energies alone (note that the EOM-CC effective Hamiltonian is not Hermitian and has distinct left and right eigenvectors).

(NO)FOCK -- (not) recompute Fock matrix

The default is FOCK meaning that the Fock matrix will be reconstructed (as opposed to using the orbital energies as the diagonal part of Fock). This is essential in getting correct correlation energies with ROHF or DFT reference wave functions. However, currently, this module cannot reconstruct the Fock matrix when one-component relativistic effects are operative. So when a user wishes to run TCE's correlation methods with DK or other relativistic reference, NOFOCK must be set and orbital energies must be used for the Fock matrix.

PRINT -- the verbosity

This keyword changes the level of output verbosity. One may also request some particular items in the table below.

Item	Print Level	Description
"time"	vary	CPU and wall times
"tile"	vary	Orbital range tiling information
"t1"	debug	$T_{1 m excitation}$ amplitude dumping
"t2"	debug	T_2 excitation amplitude dumping
"t3"	debug	$T_{ m 3}{ m excitation}$ amplitude dumping
"t4"	debug	$T_4\mathrm{excitation}$ amplitude dumping
"general information"	default	General information
"correlation information"	default	TCE information

Printable items in the TCE modules and their default print levels

"mbpt2"	debug	Caonical HF MBPT2 test
"get_block"	debug	I/O information
"put_block"	debug	I/O information
"add_block"	debug	I/O information
"files"	debug	File information
"offset"	debug	File offset information
"ao1e"	debug	AO one-electron integral evaluation
"ao2e"	debug	AO two-electron integral evaluation
"mole"	debug	One-electron integral transformation
"mo2e"	debug	Two-electron integral transformation

Sample input

The following is a sample input for a ROHF-UCCSD energy calculation of a water radical cation.

START h2o TITLE "ROHF-UCCSD/cc-pVTZ H20" CHARGE 1 **GEOMETRY** 0 0.00000000 0.00000000 0.12982363 н 0.75933475 0.00000000 -0.46621158 Н -0.75933475 0.00000000 -0.46621158 END BASIS * library cc-pVTZ END SCF ROHF DOUBLET THRESH 1.0e-10 TOL2E 1.0e-10 END TCE CCSD END TASK TCE ENERGY

The same result can be obtained by the following input:

```
START h2o
TITLE "ROHF-UCCSD/cc-pVTZ H20"
CHARGE 1
GEOMETRY
 0
       0.0000000
                      0.00000000
                                      0.12982363
 Н
       0.75933475
                      0.0000000
                                     -0.46621158
      -0.75933475
 Н
                      0.00000000
                                     -0.46621158
```

```
END
BASIS
* library cc-pVTZ
END
SCF
ROHF
DOUBLET
THRESH 1.0e-10
TOL2E 1.0e-10
END
TASK UCCSD ENERGY
```

EOMCCSD calculations with EOMSOL 2 algorithm. In these claculations the diis value of 8 will be used both in the CCSD and EOMCCSD iterations.

```
TITLE "tce eomccsd eomsol2"
ECH0
START tce_eomccsd_eomsol2
GEOMETRY UNITS ANGSTROM
Ν
              .034130
                         -.986909
                                       .000000
Ν
           -1.173397
                          .981920
                                       .000000
С
           -1.218805
                         -.408164
                                       .000000
С
            -.007302
                         1.702153
                                       .000000
С
            1.196200
                         1.107045
                                       .000000
С
            1.289085
                         -.345905
                                       .000000
0
            2.310232
                         -.996874
                                       .000000
                                       .000000
0
           -2.257041
                        -1.026495
н
              .049329
                      -1.997961
                                       .000000
Н
           -2.070598
                        1.437050
                                       .000000
Н
            -.125651
                         2.776484
                                       .000000
Н
            2.111671
                         1.674079
                                       .000000
END
BASIS
* library 6-31G
END
SCF
 THRESH 1.0e-10
 TOL2E 1.0e-10
 SINGLET
 RHF
END
TCE
 FREEZE ATOMIC
 CREOMSD(T)
 EOMSOL 2
 DIIS 8
 TILESIZE 15
 THRESH 1.0d-5
```

2EORB 2EMET 13 NROOTS 1 END TASK TCE ENERGY

EOM-CCSDT calculation for excitation energies, excited-state dipole, and transition moments.

```
START tce h2o eomcc
GEOMETRY UNITS BOHR
 н
      1.474611052297904
                          0.0000000000000000
                                              0.863401706825835
 0
      0.000000000000000
                          0.000000000000000
                                             -0.215850436155089
 Н
     -1.474611052297904
                          0.000000000000000
                                              0.863401706825835
END
BASIS
* library sto-3g
END
SCF
 SINGLET
 RHF
END
TCE
 CCSDT
 DIPOLE
 FREEZE CORE ATOMIC
 NROOTS 1
END
TASK TCE ENERGY
```

Active-space CCSDt/EOMCCSDt calculations (version I) of several excited states of the Be_3 molecule. Three highest-lying occupied α and β orbitals (active_oa and active_ob) and nine lowest-lying unoccupied α and β orbitals (active_va and active_vb) define the active space.

```
START TCE ACTIVE CCSDT
ECH0
GEOMETRY UNITS ANGSTROM
SYMMETRY C2V
 BE 0.00 0.00
                  0.00
 BE 0.00 1.137090 -1.96949
end
BASIS spherical
# --- DEFINE YOUR BASIS SET ---
END
SCF
 THRESH 1.0e-10
 TOL2E 1.0e-10
 SINGLET
 RHF
```

END
TCE
FREEZE ATOMIC
CCSDTA
TILESIZE 15
THRESH 1.0d-5
ACTIVE_OA 3
ACTIVE_OB 3
ACTIVE_VA 9
ACTIVE_VB 9
T3A_LVL 1
NROOTS 2
END
TASK TCE ENERGY

Completely renormalized EOMCCSD(T) (CR-EOMCCSD(T)) calculations for the ozone molecule as described by the POL1 basis set. The CREOMSD(T) directive automatically initialize three-step procedure: (1) CCSD calculations; (2) EOMCCSD calculations; (3) non-iterative CR-EOMCCSD(T) corrections.

START TCE_CR_EOM_T_0ZONE ECH0 GEOMETRY UNITS BOHR SYMMETRY C2V 0 0.000000000 0.0000000000 0.000000000 0 0.0000000000 -2.0473224350 -1.25952116600 0.000000000 2.0473224350 -1.2595211660END BASIS SPHERICAL 0 S 10662.285000000 0.00079900 1599.709700000 0.00615300 364.725260000 0.03115700 103.651790000 0.11559600 33.905805000 0.30155200 0 S 12.287469000 0.44487000 4.756805000 0.24317200 0 S 1.004271000 1.00000000 0 S 0.300686000 1.00000000 0 S 0.090030000 1.00000000 0 Ρ 34.856463000 0.01564800 7.843131000 0.09819700 2.306249000 0.30776800

		0.723164000	0.49247000		
0	Ρ				
•	-	0.214882000	1.00000000		
0	Р	0.062050000	1 00000000		
0	Р	0.003850000	1.00000000		
0	U	2 306200000	0 20270000		
		0 723200000	0.20270000		
0	D	01725200000	0.57510000		
•	-	0.214900000	0.78545000		
		0.063900000	0.53387000		
END					
SCF					
THRESH 1.0e-10					
T0L2E 1.0e-10					
SINGLET					
RHF					
END					
TCE					
FREEZE ATOMIC					
CREUMSD (T)					
	515	2			
TASK	тсе	F ENERGY			

The input for the active-space CR-EOMCCSD(T) calculations (the uracil molecule in the 6-31G* basis set). In this example, the model space is specified by defining the number of highest occupied orbitals (noact) and the number of lowest unoccupied orbitals (nuact) that will be considered as the active orbitals. In any type of the active-space CR-EOMCCSD(T) calculatoins based on the RHF and ROHF references more efficient versions of the orbital 4-index transformation can be invoked (i.e., 2emet 13 or 2emet 14).

```
title "uracil-6-31-Gs-act"
echo
start uracil-6-31-Gs-act
memory stack 1000 mb heap 100 mb global 1000 mb noverify
geometry units angstrom
Ν
               .034130
                           -.986909
                                         .000000
                           .981920
Ν
            -1.173397
                                        .000000
С
            -1.218805
                          -.408164
                                        .000000
С
             -.007302
                         1.702153
                                        .000000
С
            1.196200
                         1.107045
                                        .000000
С
                         -.345905
             1.289085
                                        .000000
0
            2.310232
                         -.996874
                                        .000000
0
            -2.257041
                        -1.026495
                                        .000000
Н
              .049329
                        -1.997961
                                        .000000
```

Н -2.070598 1.437050 .000000 н -.125651 2.776484 .000000 н 2.111671 1.674079 .000000 end basis cartesian * library 6-31G* end scf thresh 1.0e-10 tol2e 1.0e-10 singlet rhf end tce freeze atomic creom(t)ac oact 21 uact 99 tilesize 15 thresh 1.0d-5 2eorb 2emet 13 nroots 1 symmetry targetsym a' end task tce energy

The active-space in the active-space CR-EOMCCSD(T) calculations can be alternatively specified by defining the energy "window" [emin_act,emax_act]. All orbitals with orbital energies falling into this widnow will considered as active (the active space in the following example is different from the one used in the previous example).

```
title "uracil-6-31-Gs-act"
echo
start uracil-6-31-Gs-act
memory stack 1000 mb heap 100 mb global 1000 mb noverify
geometry units angstrom
Ν
               .034130
                           -.986909
                                        .000000
Ν
            -1.173397
                          .981920
                                       .000000
С
            -1.218805
                         -.408164
                                       .000000
С
                         1.702153
             -.007302
                                       .000000
С
             1.196200
                         1.107045
                                       .000000
С
             1.289085
                         -.345905
                                       .000000
0
             2.310232
                         -.996874
                                       .000000
0
            -2.257041
                        -1.026495
                                       .000000
н
                        -1.997961
              .049329
                                       .000000
Н
            -2.070598
                         1.437050
                                       .000000
```

Н	125651	2.776484	.000000
Н	2.111671	1.674079	.000000
end			
basis carte	esian		
* library 6	5-31G*		
end			
scf			
thresh 1.0e	e-10		
tol2e 1.0e-	-10		
singlet			
rhf			
end			
tce			
freeze atom	nic		
creom(t)ac			
emin_act -0	0.5		
emax_act 1.	. 0		
tilesize 15	5		
thresh 1.0c	1-5		
2eorbe			
2emet 13			
nroots 1			
symmetry			
targetsym a	à '		
end			
task tce er	nergy		

The LR-CCSD(T) calculations for the glycine molecule in the aug-cc-pVTZ basis set. Option 2EORB is used in order to minimize memory requirements associated with the storage of two-electron integrals.

START	START TCE_LR_CCSD_T					
ECH0	ECHO					
GEOME	GEOMETRY UNITS BOHR					
0	-2.8770919486	1.5073755650	0.3989960497			
С	-0.9993929716	0.2223265108	-0.0939400216			
С	1.6330980507	1.1263991128	-0.7236778647			
0	-1.3167079358	-2.3304840070	-0.1955378962			
Ν	3.5887721300	-0.1900460352	0.6355723246			
Н	1.7384347574	3.1922914768	-0.2011420479			
Н	1.8051078216	0.9725472539	-2.8503867814			
Н	3.3674278149	-2.0653924379	0.5211399625			
Н	5.2887327108	0.3011058554	-0.0285088728			
Н	-3.0501350657	-2.7557071585	0.2342441831			
END						
BASIS						
* library aug-cc-pVTZ						
END						

```
SCF
THRESH 1.0e-10
TOL2E 1.0e-10
SINGLET
RHF
END
TCE
FREEZE ATOMIC
2EORB
TILESIZE 15
LR-CCSD(T)
THRESH 1.0d-7
END
TASK TCE ENERGY
```

The CCSD calculations for the triplet state of the C_{20} molecule. New algorithms for 4-index transformation are used.

title "c20 cage" echo start c20 cage memory stack 2320 mb heap 180 mb global 2000 mb noverify geometry print xyz units bohr symmetry c2 С -0.761732 -1.112760 3.451966 С 0.761732 1.112760 3.451966 С 0.543308 -3.054565 2.168328 С -0.543308 3.054565 2.168328 С 3.190553 0.632819 2.242986 С -3.190553 -0.632819 2.242986 С 2.896910 -1.982251 1.260270 С -2.896910 1.982251 1.260270 С -0.951060 -3.770169 0.026589 С 0.951060 3.770169 0.026589 С 3.113776 2.128908 0.076756 С -3.113776 -2.128908 0.076756 С 3.012003 -2.087494 -1.347695 С -3.012003 2.087494 -1.347695 С 0.535910 -2.990532 -2.103427 С -0.535910 2.990532 -2.103427 С 3.334106 0.574125 -2.322563 С -3.334106 -0.574125 -2.322563 С -0.764522 -1.081362 -3.453211 С 0.764522 1.081362 -3.453211 end basis spherical * library cc-pvtz end

```
scf
  triplet
  rohf
  thresh 1.e-8
  maxiter 200
end
tce
  ccsd
  maxiter 60
  diis 5
  thresh 1.e-6
  2eorb
  2emet 3
  attilesize 40
  tilesize 30
  freeze atomic
end
task tce energy
```

TCE Response Properties

Introduction

Response properties can be calculated within the TCE. Ground-state dipole polarizabilities can be performed at the CCSD, CCSDT and CCSDTQ levels of theory. Neither CCSDT-LR nor CCSDTQ-LR are compiled by default. Like the rest of the TCE, properties can be calculated with RHF, UHF, ROHF and DFT reference wavefunctions.

Specific details for the implementation of CCSD-LR and CCSDT-LR can be found in the following papers:

- J. R. Hammond, M. Valiev, W. A. deJong and K. Kowalski, J. Phys. Chem. A, 111, 5492 (2007).
- J. R. Hammond, K. Kowalski and W. A. de Jong, J. Chem. Phys., 127, 144105 (2007).
- J. R. Hammond, W. A. de Jong and K. Kowalski , J. Chem. Phys., 128, 224102 (2008).

An appropriate background on coupled-cluster linear response (CC-LR) can be found in the references of those papers.

Performance

The coupled-cluster response codes were generated in the same manner as the rest of the TCE, thus all previous comments on performance apply here as well. The improved offsets available in the CCSD and EOM-CCSD codes is now also available in the CCSD- Λ and CCSD-LR codes. The bottleneck for CCSD-LR is the same as EOM-CCSD, likewise for CCSDT-LR and EOM-CCSDT. The CCSD-LR code has been tested on as many as 1024 processors for systems with more than 2000 spin-orbitals, while the CCSDT-LR code has been run on as many as 1024 processors. The CCSDTQ-LR code is not particularly useful due to the extreme memory requirements of quadruples amplitudes, limited scalability and poor convergence in the CCSDTQ equations in general.

Input

The input commands for TCE response properties exclusively use set directives (see SET) instead of TCE input block keywords. There are currently only three commands available:

```
set tce:lineresp <logical lineresp default: F>
set tce:afreq <double precision afreq(9) default: 0.0>
set tce:respaxis <logical respaxis(3) default: T T T>
```

The boolean variable lineresp invokes the linear response equations for the corresponding coupled-cluster method (only CCSD and CCSDT possess this feature) and evaluates the dipole polarizability. When lineresp is true, the Λ -equations will also be solved, so the dipole moment is also calculated. If no other options are set, the complete dipole polarizability tensor will be calculated at zero frequency (static). Up to nine real frequencies can be set; adding more should not crash the code but it will calculate meaningless quanities. If one desires to calculate more frequencies at one time, merely change the line double precision afreq(9) in $(NWCHEM_TOP)/src/tce/include/tce.fh appropriately and recompile.$

The user can choose to calculate response amplitudes only for certain axis, either because of redundancy due to symmetry or because of memory limitations. The boolean vector of length three respaxis is used to determine whether or not a given set of response amplitudes are allocated, solved for, and used in the polarizability tensor evaluation. The logical variables represent the X, Y, Z axes, respectively. If respaxis is set to T F T, for example, the responses with respect to the X and Z dipoles will be calculated, and the four (three unique) tensor components will be evaluated. This feature is also useful for conserving memory. By calculating only one axis at a time, memory requirements can be reduced by \$25\%\$ or more, depending on the number of DIIS vectors used. Reducing the number of DIIS vectors also reduces the memory requirements.

It is strongly advised that when calculating polarizabilities at high-frequencies, that user set the frequencies in increasing order, preferably starting with zero or other small value. This approach is computationally efficient (the initial guess for subsequent responses is the previously converged value) and mitigates starting from a zero vector for the response amplitudes.

Examples

This example runs in-core on a large workstation.

geometry units	angstrom		
symmetry d2h			
С	0.000	1.390	0.000
Н	0.000	2.470	0.000
С	1.204	0.695	0.000
Н	2.139	1.235	0.000
С	0.000	-1.390	0.000
Н	0.000	-2.470	0.000
С	-1.204	-0.695	0.000
Н	-2.139	-1.235	0.000
С	1.204	-0.695	0.000
Н	2.139	-1.235	0.000
С	-1.204	0.695	0.000

```
Н
                 -2.139
                           1.235
                                     0.000
end
basis spherical
* library aug-cc-pvdz
end
tce
 freeze atomic
 ccsd
 io ga
 2eorb
 tilesize 16
end
set tce:lineresp T
set tce:afreq 0.000 0.072
set tce:respaxis T T T
task tce energy
```

This is a relatively simple example for CCSDT-LR.

```
geometry units au
symmetry c2v
Η Θ
           0
                     0
                     1.7328795
F 0
           0
end
basis spherical
* library aug-cc-pvdz
end
tce
ccsdt
io ga
2eorb
end
set tce:lineresp T
set tce:afreq 0.0 0.1 0.2 0.3 0.4
set tce:respaxis T F T
task tce energy
```

TCE Restart Capability

Overview

Check-pointing and restart are critical for computational chemistry applications of any scale, but particularly those done on supercomputers, or run for an extended period on workstations and clusters. The TCE supports parallel check-pointing and restart using the Shared Files (SF) library in the Global Arrays Tools. The SF library requires that the file system be accessible by every node, so reading and writing restart files can only be performed on a shared file system. For workstations, this condition is trivially met. Restart files must be persistent to be useful, so volatile file systems or those which are periodicly erased should not be used for check-pointing.

Restart is possible for all ground-state amplitudes (T, Λ and $T^{(1)}$) but not for excited-state amplitudes, as in an EOM-CC calculation. The latter functionality is under development. Restart capability is useful in the following situations:

- The total run time is limited, as is the case for most supercomputing facilities.
- The system is volatile and jobs die randomly.
- When doing property calculations which require a large number of responses which cannot all be stored in-core simultaneously.

At the present time, restarting the amplitudes during a potential energy surface scan or numerical geometry optmization/frequency calculation is not advised due to the phase issue in the molecular orbital coefficients. If the phase changes, the amplitudes will no longer be a useful guess and may lead to nonsense results. Expert users may be able to use restart when the geometry varies using careful choices in the SCF input by using the "rotate" and "lock" options but this use of restart is not supported.

If SF encounters a failure during restart I/O, the job will fail. The capability to ignore a subset of failures, such as when saving the amplitudes prior to convergence, will be available in the future. This is useful on some large machines when the filesystem is being taxed by another job and may be appear unavailable at the moment a check-point write is attempted.

The performance of SF I/O for restart is excellent and the wall time for reading and writing integrals and amplitudes is negligible, even on a supercomputer (such systems have very fast parallel file systems in most cases). The only platform for which restart may cause I/O problems is BlueGene, due to ratio of compute to I/O nodes (64 on BlueGene/P).

Input

```
set tce:read_integrals <logical read_integrals default: F F F F F F
set tce:read_t <logical read_t default: F F F F>
set tce:read_t <logical read_t default: F F F F>
set tce:read_tr <logical read_tr default: F F F F>
set tce:save_integrals <logical save_integrals default: F F F F>
set tce:save_t <logical save_t default: F F F F>
set tce:save_l <logical save_l default: F F F F>
set tce:save_tr <logical save_tr default: F F F F>
set tce:save_tr <logical save_tr default: F F F F>
set tce:save_tr <logical save_tr default: F F F F>
```

The boolean variables read_integrals and save_integrals control which integrals are read/saved. The first location is the 1-e integrals, the second is for the 2-e integrals, and the third is for dipole integrals. The fourth and fifth positions are reserved for quadrupole and octupole integrals but this functionality is not available. The read_t, read_l, read_tr, save_t, save_l and save_tr variables control the reading/saving of the T, Λ and $T^{(1)}$ (response) amplitudes. Restart control on the response amplitudes is implicitly controlled by the value of respaxis (see above). Requesting amplitudes that are beyond the scope of a given calculation, such as T_3 in a CCSD calculation, does not produce an error as these commands will never be processed.

Attempting to restart with a set of amplitudes without the corresponding integrals is ill-advised, due to the phase issue discussed above. For the same reason, one cannot save a subset of the integrals, so if it is even remotely possible that the dipole moment or polarizabilities will be desired for a given molecule, the dipole integrals should be saved as well. It is possible to save the dipole integrals without setting dipole in the TCE input block; setting save_integrals(3) true is sufficient for this to occur.

The save_interval variable controls the frequency with which amplitudes are saved. By default, the amplitudes are saved only when the iterative process has converged, meaning that if the iterations do not converge in less than the maximum, one must start the calculation again from scratch. The solution is to set save_interval to a smaller value, such as the number of DIIS cycles being used.

The user shall not change the tilesize when reading in saved amplitudes. The results of this are catastrophic and under no circumstance will this lead to physically meaningful results. Restart does not work for 2eorb and 2emet 9; no error will be produced but the results may be meaningless.

Examples

```
geometry units au
 symmetry c2v
Η Θ
           0
                     0
F 0
           0
                     1.7328795
end
basis spherical
* library aug-cc-pvdz
end
tce
ccsdt
io ga
end
set tce:lineresp T
set tce:afreq 0.0 0.1 0.2 0.3 0.4
set tce:respaxis T F T
task tce energy
```

Maximizing performance

The following are recommended parameters for getting the best performance and efficiency for common methods on various hardware configurations. The optimal settings are far from extensible and it is extremely important that users take care in how they apply these recommendations. Testing a variety of settings on a simple example is recommended when optimal settings are desired. Nonetheless, a few guiding principles will improve the performance of TCE jobs markedly, including making otherwise impossible jobs possible.

Memory considerations

The default memory settings for NWChem are not optimal for TCE calculations. When 2 GB of memory is available per process, the following settings are close to optimal for CCSD jobs

memory stack 800 mb heap 100 mb global 1000 mb

for property jobs, which require more amplitudes to be stored, it is wise to favor the global allocation

memory stack 500 mb heap 100 mb global 1300 mb

If you get an error for ga_create during the iterative steps, reduce the number of DIIS vectors. If this error occurs during the four-index transformation (after d_v^2 filesize appears) you need more GA space, a different 2emet, or more nodes.

The memory requirements for CCSD(T) are quite different because the triples are generated in local memory. The value of tilesize should not be larger than 30 in most cases and one should set something similar to the following

memory stack 1200 mb heap 100 mb global 600 mb

The local memory requires will be $\sim tilesize^N$ where N=4 for CCSD, N=6 for CCSD(T) and CCSDT, and N=8 for CCSDTQ. One should set $tilesize^{\sim 15}$ for CCSDT and CCSDTQ, although symmetry will affect the local memory use significantly. The local memory usage of the CR-EOMCCSD(T) approach has recently been significantly reduced to the level of the CCSD(T) approach ($2 * (tilesize)^6$).

SCF options

For parallel jobs on clusters with poor disk performance on the filesystem used for scratch_dir, it is a good idea to disable disk IO during the SCF stage of the calculation. This is done by adding semidirect memsize N filesize 0, where N is 80% of the stack memory divided by 8, as the value in this directive is the number of dwords, rather than bytes. With these settings, if the aggregate memory is sufficient to store the integrals, the SCF performance will be excellent, and it will be better than if direct is set in the SCF input block. If scratch_dir is set to a local disk, then one should use as much disk as is permissible, controlled by the value of filesize. On many high-performance computers, filling up the local scratch disk will crash the node, so one cannot be careless with these settings. In addition, on many such machines, the shared file system performance is better than that of the local disk (this is true for many NERSC systems).

Convergence criteria

It makes no sense to converge a calculation to a precision not relevant to experiment. However, the relationship between convergence criteria and calculated quantities is not fully known for some properties. For example, the effect of the convergence criteria on the polarizability is significant in some cases. In the case of CN, convergence of 10^{-11} is necessary to resolve the polarizability tensor components to 10^{-2} . However, for many systems 10^{-7} convergence is sufficient to get accurate results for all properties. It is important to calibrate the effect of convergence on property calculations, particularly for open-shell and post-CCSD methods, on a modest basis set before relaxing the convergence

criteria too much.

IO schemes and integral transformation algorithms

The effect on memory use of using the 2eorb keyword is huge. However, this option can only be used with IO=GA and an RHF/ROHF reference. There are a number of choices for the integral transformation algorithm when using spin-free integrals. The fastest algorithm is 2EMET=5, but significant disk IO is required for this algorithm. One must set permanent_dir to a fast, shared file system for this algorithm to work. If disk performance is not good, one should use either 2EMET=3 or 2EMET=4 depending on how much memory is available. If one sees a ga_create error with 2EMET=3, then switch to algorithm 4 and add split 8 to the TCE input block.

References

http://dx.doi.org/10.1021/ct200809m
 http://dx.doi.org/10.1063/1.4747698

Release65:MP2

__NOTITLE_

MP2

There are (at least) three algorithms within NWChem that compute the Møller-Plesset (or many-body) perturbation theory second-order correction^[1] to the Hartree-Fock energy (MP2). They vary in capability, the size of system that can be treated and use of other approximations

Semi-direct -- this is recommended for most large applications (up to about 2800 basis functions), especially on the IBM SP and other machines with significant disk I/O capability. Partially transformed integrals are stored on disk, multi-passing as necessary. RHF and UHF references may be treated including computation of analytic derivatives. This is selected by specifying mp2 on the task directive, e.g.

TASK MP2

• Fully-direct^[2] -- this is of utility if only limited I/O resources are available (up to about 2800 functions). Only RHF references and energies are available. This is selected by specifying direct_mp2 on the task directive, e.g.

TASK DIRECT_MP2

Resolution of the identity (RI) approximation MP2 (RI-MP2)^[3] -- this uses the RI approximation and is therefore only exact in the limit of a complete fitting basis. However, with some care, high accuracy may be obtained with relatively modest fitting basis sets. An RI-MP2 calculation can cost over 40 times less than the corresponding exact MP2 calculation. RHF and UHF references with only energies are available. This is selected by specifying rimp2 on the task directive, e.g.,

TASK RIMP2

All three MP2 tasks share the same input block.

```
MP2
[FREEZE |
<integer nfzc default 0>)] \
      [virtual <integer nfzv default 0>
[TIGHT]
[PRINT]
[NOPRINT]
[VECTORS <string filename default scf-output-vectors> \
      [swap [(alpha||beta)] <integer pair-list>] ]
    [RIAPPROX <string riapprox default V>]
    [FILE3C <string filename default $file_prefix$.mo3cint">]
    [SCRATCHDISK <integer>]
END
```

FREEZE --Freezing orbitals

All MP2 modules support frozen core orbitals, however, only the direct MP2 and RI-MP2 modules support frozen virtual orbitals.

By default, no orbitals are frozen. The atomic keyword causes orbitals to be frozen according to the rules in the table below. Note that no orbitals are frozen on atoms on which the nuclear charge has been modified either by the user or due to the presence of an ECP. The actual input would be

freeze atomic

For example, in a calculation on $Si(OH)_2$, by default the lowest seven orbitals would be frozen (the oxygen 1 ^s, and the silicon 1 ^s, 2 ^s and 2 ^p).

Number of orbitals considered "core" in the "freeze by atoms" algorithm

Period	Elements	Core Orbitals	Number of Core
0	H - He	-	0
1	Li - Ne	1 8	1
2	Na - Ar	$1 s_2 s_2 p$	5
3	K - Kr	$1 s_2 s_2 p_3 s_3 p$	9
4	Rb - Xe	$_{1}s_{2}s_{2}p_{3}s_{3}p_{4}s_{3}d_{4}p$	18
5	Cs - Rn	$_{1}s_{2}s_{2}p_{3}s_{3}p_{4}s_{3}d_{4}p_{5}s_{4}d_{5}p$	27
6	Fr - Lr	$_{1}s_{2}s_{2}p_{3}s_{3}p_{4}s_{3}d_{4}p_{5}s_{4}d_{5}p_{6}s_{4}f_{5}d_{6}p$	43

Caution: The rule for freezing orbitals "by atoms" are rather unsophisticated: the number of orbitals to be frozen is computed from the Table 16.1 by summing the number of core orbitals in each atom present. The corresponding number of lowest-energy orbitals are frozen -- if for some reason the actual core orbitals are not the lowest lying, then correct results will not be obtained. From limited experience, it seems that special attention should be paid to systems including third- and higher- period atoms.

The user may also specify the number of orbitals to be frozen by atom. Following the $Si(OH)_2$ example, the user could specify

freeze atomic 0 1 Si 3

In this case only the lowest four orbitals would be frozen. If the user does not specify the orbitals by atom, the rules default to Table 16.1.

Caution: The system does not check for a valid number of orbitals per atom. If the user specifies to freeze more orbitals then are available for the atom, the system will not catch the error. The user must specify a logical number of orbitals to be frozen for the atom.

The FREEZE directive may also be used to specify the number of core orbitals to freeze. For instance, to freeze the first 10 orbitals

freeze 10

or equivalently, using the optional keyword core

freeze core 10

Again, note that if the 10 orbitals to be frozen do not correspond to the first 10 orbitals, then the swap keyword of the VECTORS directive must be used to order the input orbitals correctly (MO vectors).

To freeze the highest virtual orbitals, use the virtual keyword. For instance, to freeze the top 5 virtuals

freeze virtual 5

Again, note that this only works for the direct-MP2 and RI-MP2 energy codes.

TIGHT --Increased precision

The TIGHT directive can be used to increase the precision in the MP2 energy and gradients.

By default the MP2 gradient package should compute energies accurate to better than a micro-Hartree, and gradients accurate to about five decimal places (atomic units). However, if there is significant linear dependence in the basis set the precision might not be this good. Also, for computing very accurate geometries or numerical frequencies, greater precision may be desirable.

This option increases the precision to which both the SCF (from 10^{-6} to 10^{-8}) and CPHF (from 10^{-4} to 10^{-6}) are solved, and also tightens thresholds for computation of the AO and MO integrals (from 10^{-9} to 10^{-11}) within the MP2 code.
SCRATCHDISK --Limiting I/O usage

This directive - used only in the semi-direct algorithm - allows to limit the per process disk usage. Mandatory argument for this keyword is the maximum number of MBytes. For example, the following input line

scratchdisk 512

puts an upper limit of 512 MBytes to the semi-direct MP2 usage of disk (again, on a per process base).

PRINT and NOPRINT

The standard print control options are recognized. The list of recognized names are given in the table below.

Printable items in the MP2 modules and their default print levels

Item	Print Level	Description		
RI-MP2				
"2/3 ints"	debug	Partial 3-center integrals		
"3c ints"	debug	MO 3-center integrals		
"4c ints b"	debug	"B" matrix with approx. 4c integrals		
"4c ints"	debug	Approximate 4-center integrals		
"amplitudes"	debug	"B" matrix with denominators		
"basis"	high			
"fit xf"	debug	Transformation for fitting basis		
"geombas"	debug	Detailed basis map info		
"geometry"	high			
"information"	low	General information about calc.		
"integral i/o"	high	File size information		
"mo ints"	debug			
"pair energies"	debug	(working only in direct_mp2)		
"partial pair energies"	debug	Pair energy matrix each time it is updated		
"progress reports"	default	Report completion of time-consuming steps		
"reference"	high	Details about reference wavefunction		
"warnings"	low	Non-fatal warnings		

VECTORS --MO vectors

All of the (supported) MP2 modules require use of converged canonical SCF (RHF or UHF) orbitals for correct results. The vectors are by default obtained from the preceding SCF calculation, but it is possible to specify a different source using the VECTORS directive. For instance, to obtain vectors from the file /tmp/h2o.movecs, use the directive

vectors /tmp/h2o.movecs

As noted above (FREEZE) if the SCF orbitals are not in the correct order, it is necessary to permute the input orbitals using the swap keyword of the VECTORS directive. For instance, if it is desired to freeze a total six orbitals corresponding to the SCF orbitals 1-5, and 7, it is necessary to swap orbital 7 into the 6th position. This is accomplished by

```
vectors swap 6 7
```

The swap capability is examined in more detail in Input/output of MO vectors.

RI-MP2 fitting basis

The RI-MP2 method requires a fitting basis, which must be specified with the name "ri-mp2 basis" (see Basis). For instance,

```
basis "ri-mp2 basis"
    0 s; 10000.0 1
    0 s; 1000.0 1
    0 s; 100.0 1
    ...
end
```

Alternatively, using a standard capability of basis sets (Basis) another named basis may be associated with the fitting basis. For instance, the following input specifies a basis with the name "small fitting basis" and then defines this to be the "ri-mp2 basis".

```
basis "small fitting basis"
H s; 10 1
H s; 3 1
H s; 1 1
H s; 0.1 1
H s; 0.01 1
end
set "ri-mp2 basis" "small fitting basis"
```

FILE3C -- RI-MP2 3-center integral filename

The default name for the file used to store the transformed 3-center integrals is "\$file_prefix\$.mo3cint" in the scratch directory. This may be overridden using the FILE3C directive. For instance, to specify the file /scratch/h2o.3c, use this directive

```
file3c /scratch/h2o.3c
```

RIAPPROX -- RI-MP2 Approximation

The type of RI approximation used in the RI-MP2 calculation is controlled by means of the RIAPPROX directive. The two possible values are V and SVS (case sensitive), which correspond to the approximations with the same names described by Vahtras et al.^[4]. The default is V.

Advanced options for RI-MP2

These options, which functioned at the time of writing, are not currently supported.

Control of linear dependence

Construction of the RI fit requires the inversion of a matrix of fitting basis integrals which is carried out via diagonalization. If the fitting basis includes near linear dependencies, there will be small eigenvalues which can ultimately lead to non-physical RI-MP2 correlation energies. Eigenvectors of the fitting matrix are discarded if the corresponding eigenvalue is less than *mineval* which defaults to 10^{-8} . This parameter may be changed by setting the a parameter in the database. For instance, to set it to 10^{-10}

set "mp2:fit min eval" 1e-10

Reference Spin Mapping for RI-MP2 Calculations

The user has the option of specifying that the RI-MP2 calculations are to be done with variations of the SCF reference wavefunction. This is accomplished with a SET directive of the form,

set "mp2:reference spin mapping" <integer array default 0>

Each element specified for array is the SCF spin case to be used for the corresponding spin case of the correlated calculation. The number of elements set determines the overall type of correlated calculation to be performed. The default is to use the unadulterated SCF reference wavefunction.

For example, to perform a spin-unrestricted calculation (two elements) using the alpha spin orbitals (spin case 1) from the reference for both of the correlated reference spin cases, the SET directive would be as follows,

```
set "mp2:reference spin mapping" 1 1
```

The SCF calculation to produce the reference wavefunction could be either RHF or UHF in this case.

The SET directive for a similar case, but this time using the beta-spin SCF orbitals for both correlated spin cases, is as follows,

```
set "mp2:reference spin mapping" 2 2
```

The SCF reference calculation must be UHF in this case.

The SET directive for a spin-restricted calculation (one element) from the beta-spin SCF orbitals using this option is as follows,

set "mp2:reference spin mapping" 2

The SET directive for a spin-unrestricted calculation with the spins flipped from the original SCF reference wavefunction is as follows,

set "mp2:reference spin mapping" 2 1

Batch Sizes for the RI-MP2 Calculation

The user can control the size of each batch in the transformation and energy evaluation in the MP2 calculation, and consequently the memory requirements and number of passes required. This is done using two SET directives of the following form,

```
set "mp2:transformation batch size" <integer size default -1>
set "mp2:energy batch size" <integer isize jsize default -1 -1>
```

The default is for the code to determine the batch size based on the available memory. Should there be problems with the program-determined batch sizes, these variables allow the user to override them. The program will always use the smaller of the user's value of these entries and the internally computed batch size.

The transformation batch size computed in the code is the number of occupied orbitals in the (occ vir|fit) three-center integrals to be produced at a time. If this entry is less than the number of occupied orbitals in the system, the transformation will require multiple passes through the two-electron integrals. The memory requirements of this stage are two global arrays of dimension < batch size > x vir x fit with the "fit" dimension distributed across all processors (on shell-block boundaries). The compromise here is memory space versus multiple integral evaluations.

The energy evaluation batch sizes are computed in the code from the number of occupied orbitals in the two sets of three-center integrals to be multiplied together to produce a matrix of approximate four-center integrals. Two blocks of integrals of dimension (*<batch isize> x vir*) and (*<batch jsize> x vir*) by fit are read in from disk and multiplied together to produce *<batch isize> <batch jsize> vir^2* approximate integrals. The compromise here is performance of the distributed matrix multiplication (which requires large matrices) versus memory space.

Energy Memory Allocation Mode: RI-MP2 Calculation

The user must choose a strategy for the memory allocation in the energy evaluation phase of the RI-MP2 calculation, either by minimizing the amount of I/O, or minimizing the amount of computation. This can be accomplished using a SET directive of the form,

set "mp2:energy mem minimize" <string mem_opt default I>

A value of I entered for the string mem_opt means that a strategy to minimize I/O will be employed. A value of C tells the code to use a strategy that minimizes computation.

When the option to minimize I/O is selected, the block sizes are made as large as possible so that the total number of passes through the integral files is as small as possible. When the option to minimize computation is selected, the blocks are chosen as close to square as possible so that permutational symmetry in the energy evaluation can be used most effectively.

Local Memory Usage in Three-Center Transformation

For most applications, the code will be able to size the blocks without help from the user. Therefore, it is unlikely that users will have any reason to specify values for these entries except when doing very particular performance measurements.

The size of xf3ci:AO 1 batch size is the most important of the three, in terms of the effect on performance.

Local memory usage in the first two steps of the transformation is controlled in the RI-MP2 calculation using the following SET directives,

```
set "xf3ci:A0 1 batch size" <integer max>
set "xf3ci:A0 2 batch size" <integer max>
set "xf3ci:fit batch size" <integer max>
```

The size of the local arrays determines the sizes of the two matrix multiplications. These entries set limits on the size of blocks to be used in each index. The listing above is in order of importance of the parameters to performance, with xf3ci:AO 1 batch size being most important.

Note that these entries are only upper bounds and that the program will size the blocks according to what it determines as the best usage of the available local memory. The absolute maximum for a block size is the number of functions in the AO basis, or the number of fitting basis functions on a node. The absolute minimum value for block size is the size of the largest shell in the appropriate basis. Batch size entries specified for max that are larger than these limits are automatically reset to an appropriate value.

One-electron properties and natural orbitals

If an MP2 energy gradient is computed, all contributions are available to form the MP2 linear-response density. This is the density that when contracted with any spin-free, one-electron operator yields the associated property defined as the derivative of the energy. Thus, the reported MP2 dipole moment is the derivative of the energy w.r.t. an external electric field and is not the expectation value of the operator over the wavefunction. It has been shown that evaluating the MP2 density through a derivative provides more accurate results, presumably because this matches the way experiments probe the electron density more closely^[5] [6] [7] [8].

Only dipole moments are printed by the MP2 gradient code, but natural orbitals are produced and stored in the permanent directory with a file extension of ".mp2nos". These may be fed into the property package to compute more general properties. Note that the MP2 linear response density matrix is not necessarily positive definite so it is not unusual to see a few small negative natural orbital occupation numbers. Significant negative occupation numbers have been argued to be a sign that the system might be near degenerate^[9].

SCS-MP2 -- Spin-Component Scaled MP2

Each MP2 output contains the calculation of the SCS-MP2 correlation energies as suggested by $\rm S.Grimme^{[10]}$

The SCF keyword is only required for gradients calculations:

MP2 [SCS] END

Scaling factors for the two components (parallel and opposite spin) can be defined by using the keywords FSS (same spin factor) and FOS (opposite spin factor):

mp2 scs fss 1.13 fos 0.56 end

Default values are FSS=1.2, FOS=0.3 for MP2, and FSS=1.13, FOS=1.27 for CCSD.

References

- Møller, C. and Plesset, M.S. (1934) "Note on an approximation treatment for many-electron systems", *Physical Review* 46 618-622, doi: 10.1103/PhysRev.46.618 (http://dx.doi.org/10.1103/PhysRev.46.618).
- [2] Wong, A.T.; Harrison, R.J. and Rendell, A.P. (1996) "Parallel direct four-index transformations", *Theoretica Chimica Acta* 93 317-331, doi: 10.1007/BF01129213 (http://dx.doi.org/10.1007/BF01129213)
- [3] Bernholdt, D.E. and Harrison, R.J. (1996) "Large-scale correlated electronic structure calculations: the RI-MP2 method on parallel computers", *Chemical Physics Letters* 250 (5-6) 477-484, doi: 10.1016/0009-2614(96)00054-1 (http://dx.doi.org/10.1016/0009-2614(96)00054-1)
- [4] Vahtras, O.; Almlöf, J. and Feyereisen, M. W. (1993) "Integral approximations for LCAO-SCF calculations", *Chem. Phys. Lett.* 213, 514-518, doi: 10.1016/0009-2614(93)89151-7 (http://dx.doi.org/10.1016/ 0009-2614(93)89151-7)
- [5] Raghavachari, K. and Pople, J. A. (1981) "Calculation of one-electron properties using limited configuration interaction techniques", *Int. J. Quantum Chem.* 20, 1067-1071, doi: 10.1002/qua.560200503 (http://dx.doi. org/10.1002/qua.560200503).
- [6] Diercksen, G. H. F.; Roos, B. O. and Sadlej, A. J. (1981) "Legitimate calculation of first-order molecular properties in the case of limited CI functions. Dipole moments", *Chem. Phys.* 59, 29-39, doi: 10.1016/0301-0104(81)80082-1 (http://dx.doi.org/10.1016/0301-0104(81)80082-1).
- [7] Rice, J. E. and Amos, R. D. (1985) "On the efficient evaluation of analytic energy gradients", *Chem. Phys. Lett.* 122, 585-590, doi: 10.1016/0009-2614(85)87275-4 (http://dx.doi.org/10.1016/0009-2614(85)87275-4).
- [8] Wiberg, K. B.; Hadad, C. M.; LePage, T. J.; Breneman, C. M. and Frisch, M. J. (1992) "Analysis of the effect of electron correlation on charge density distributions", *J. Phys. Chem.* 96, 671-679, doi: 10.1021/j100181a030 (http://dx.doi.org/10.1021/j100181a030).
- [9] Gordon, M. S.; Schmidt, M. W.; Chaban, G. M.; Glaesemann, K. R.; Stevens, W. J. and Gonzalez, C. (1999) "A natural orbital diagnostic for multiconfigurational character in correlated wave functions", *J. Chem. Phys.* 110, 4199-4207, doi: 10.1063/1.478301 (http://dx.doi.org/10.1063/1.478301).
- [10] S. Grimme, "Improved second-order Møller-Plesset perturbation theory by separate scaling of parallel- and antiparallel-spin pair correlation energies", J. Chem. Phys., 118, (2003), 9095-9102, doi: 10.1063/1.1569242 (http://dx.doi.org/10.1063/1.1569242).

Release65:CCSD

__NOTITLE__

Coupled Cluster Calculations

The NWChem coupled cluster energy module is primarily the work of Alistair Rendell and Rika Kobayashi^{[1] [2]}, with contributions from Bert de Jong, David Bernholdt and Edo Apra^[3].

The coupled cluster code can perform calculations with full iterative treatment of single and double excitations and non-iterative inclusion of triple excitation effects. It is presently limited to closed-shell (RHF) references.

Note that symmetry is not used within most of the CCSD(T) code. This can have a profound impact on performance since the speed-up from symmetry is roughly the square of the number of irreducible representations. In the absence of symmetry, the performance of this code is competitive with other programs.

The operation of the coupled cluster code is controlled by the input block

```
CCSD

[MAXITER <integer maxiter default 20>]

[THRESH <real thresh default 10e-6>]

[TOL2E <real tol2e default min(10e-12 , 0.01*$thresh$)>]

[DIISBAS <integer diisbas default 5>]

[FREEZE |

<integer nfzc default 0>] \

[virtual <integer nfzv default 0>

[NODISK]

[IPRT <integer IPRT default 0>]

[PRINT ...]

[NOPRINT ...]

END
```

Note that the keyword CCSD is used for the input block regardless of the actual level of theory desired (specified with the TASK directive). The following directives are recognized within the CCSD group.

MAXITER -- Maximum number of iterations

The maximum number of iterations is set to 20 by default. This should be quite enough for most calculations, although particularly troublesome cases may require more.

```
MAXITER <integer maxiter default 20>
```

THRESH --Convergence threshold

Controls the convergence threshold for the iterative part of the calculation. Both the RMS error in the amplitudes and the change in energy must be less than thresh.

```
THRESH <real thresh default 10e-6>
```

TOL2E --integral screening threshold

TOL2E <real tol2e default min(10e-12 , 0.01*''thresh'')>

The variable tol2e is used in determining the integral screening threshold for the evaluation of the energy and related quantities.

CAUTION! At the present time, the tol2e parameter only affects the three- and four-virtual contributions, and the triples, all of which are done "on the fly". The transformations used for the other parts of the code currently have a hard-wired threshold of 10^{-12} . The default for tol2e is set to match this, and since user input can only make the threshold smaller, setting this parameter can only make calculations take longer.

DIISBAS --DIIS subspace dimension

Specifies the maximum size of the subspace used in DIIS convergence acceleration. Note that DIIS requires the amplitudes and errors be stored for each iteration in the subspace. Obviously this can significantly increase memory requirements, and could force the user to reduce DIISBAS for large calculations.

Measures to alleviate this problem, including more compact storage of the quantities involved, and the possibility of disk storage are being considered, but have not yet been implemented.

DIISBAS <integer diisbas default 5>

FREEZE --Freezing orbitals

[FREEZE | <integer nfzc default 0>)] \ [virtual <integer nfzv default 0>

This directive is idential to that used in the MP2 module.

NODISK --On-the-fly computation of integrals

The CCSD modules by default computes once and stores on disk the integrals. To avoid this kind of I/O operations, specify the keyword NODISK

IPRT -- **Debug** printing

This directive controls the level of output from the code, mostly to facilitate debugging and the like. The larger the value, the more output printed. From looking at the source code, the interesting values seem to be IPRT > 5, 10, and 50.

```
IPRT <integer IPRT default 0>
```

PRINT and NOPRINT

The coupled cluster module supports the standard NWChem print control keywords, although very little in the code is actually hooked into this mechanism yet.

Item	Print Level	Description
"reference"	high	Wavefunction information

"guess pair energies"	debug	MP2 pair energies
"byproduct energies"	default	Intermediate energies
"term debugging switches"	debug	Switches for individual terms

Methods (Tasks) Recognized

Currently available methods are

```
* CCSD - Full iterative inclusion of single and double excitations
```

```
* CCSD+T(CCSD) - The fourth order triples contribution computed with converged singles and doubles amplitudes
```

```
* CCSD(T) - The linearized triples approximation due to
```

```
Raghavachari.
```

The calculation is invoked using the the TASK directive, so to perform a CCSD+T(CCSD) calculation, for example, the input file should include the directive

TASK CCSD+T(CCSD)

Lower-level results which come as by-products (such as MP3/MP4) of the requested calculation are generally also printed in the output file and stored on the run-time database, but the method specified in the TASK directive is considered the primary result.

Debugging and Development Aids

The information in this section is intended for use by experts (both with the methodology and with the code), primarily for debugging and development work. Messing with stuff in listed in this section will probably make your calculation quantitatively wrong! Consider yourself warned!

Switching On and Off Terms

The /DEBUG/ common block contains a number of arrays which control the calculation of particular terms in the program. These are 15-element integer arrays (although from the code only a few elements actually effect anything) which can be set from the input deck. See the code for details of how the arrays are interpreted.

Printing of this data at run-time is controlled by the "term debugging switches" print option. The values are checked against the defaults at run-time and a warning is printed to draw attention to the fact that the calculation does not correspond precisely to the requested method.

References

- [1] Rendell, A.P., Lee, T.J., Komornicki, A., and Wilson, S. (1992) "Evaluation of the contribution from triply excited intermediates to the fourth-order perturbation theory energy on Intel distributed memory supercomputers", *Theor. Chem. Acc.*, 84, 271-287, doi: 10.1007/BF01113267 (http://dx.doi.org/10.1007/BF01113267)
- Kobayashi, R. and Rendell, A.P. (1997) "A direct coupled cluster algorithm for massively parallel computers", *Chem. Phys. Lett.*, 265, 1-11, doi: 10.1016/S0009-2614(96)01387-5 (http://dx.doi.org/10.1016/ S0009-2614(96)01387-5)
- [3] Apra, E., Harrison, R.J., de Jong, W.A., Rendell, A.P., Tipparaju, V. and Xantheas, S.S. (2009) "Liquid Water: Obtaining the Right Answer for the Right Reasons", *Proc. SC'09*, doi: 10.1145/1654059.1654127 (http://dx.doi. org/10.1145/1654059.1654127)

Release65:Multiconfiguration SCF

```
__NOTITLE__
```

MCSCF

The NWChem multiconfiguration SCF (MCSCF) module can currently perform complete active space SCF (CASSCF) calculations with at most 20 active orbitals and about 500 basis functions.

```
MCSCF
```

```
STATE <string state>
  ACTIVE <integer nactive>
  ACTELEC <integer nactelec>
  MULTIPLICITY <integer multiplicity>
   [SYMMETRY <integer symmetry default 1>]
   [VECTORS [[input] <string input file default
file prefix.movecs>]
          [swap <integer vec1 vec2> ...] \
          [output <string output file default input file>] \
          [lock]
   [HESSIAN (exact||onel)]
   [MAXITER <integer maxiter default 20>]
   [THRESH <real thresh default 1.0e-4>]
   [TOL2E <real tol2e default 1.0e-9>]
   [LEVEL <real shift default 0.1d0>]
END
```

Note that the ACTIVE, ACTELEC, and MULTIPLICITY directives are required. The symmetry and multiplicity may alternatively be entered using the STATE directive.

ACTIVE --Number of active orbitals

The number of orbitals in the CASSCF active space must be specified using the ACTIVE directive.

E.g.,

active 10

The input molecular orbitals (see the vectors directive in MCSCF Vectors and SCF Vectors) must be arranged in order

- 1. doubly occupied orbitals,
- 2. active orbitals, and
- 3. unoccupied orbitals.

ACTELEC --Number of active electrons

The number of electrons in the CASSCF active space must be specified using the the ACTELEC directive. An error is reported if the number of active electrons and the multiplicity are inconsistent.

The number of closed shells is determined by subtracting the number of active electrons from the total number of electrons (which in turn is derived from the sum of the nuclear charges minus the total system charge).

MULTIPLICITY

The spin multiplicity must be specified and is enforced by projection of the determinant wavefunction.

E.g., to obtain a triplet state

multiplicity 3

SYMMETRY --Spatial symmetry of the wavefunction

This species the irreducible representation of the wavefunction as an integer in the range 1--8 using the same numbering of representations as output by the SCF program. Note that only Abelian point groups are supported.

E.g., to specify a B_1 state when using the C_{2v} group

```
symmetry 3
```

STATE --Symmetry and multiplicity

The electronic state (spatial symmetry and multiplicity) may alternatively be specified using the conventional notation for an electronic state, such as ${}^{3}B_{2}$ for a triplet state of B_{2} symmetry. This would be accomplished with the input

state 3b2

which is equivalent to

symmetry 4
multiplicity 3

VECTORS --Input/output of MO vectors

Calculations are best started from RHF/ROHF molecular orbitals (see SCF), and by default vectors are taken from the previous MCSCF or SCF calculation. To specify another input file use the VECTORS directive. Vectors are by default output to the input file, and may be redirected using the output keyword. The swap keyword of the VECTORS directive may be used to reorder orbitals to obtain the correct active space.

The LOCK keyword allows the user to specify that the ordering of orbitals will be locked to that of the initial vectors, insofar as possible. The default is to order by ascending orbital energies within each orbital space. One application where locking might be desirable is a calculation where it is necessary to preserve the ordering of a previous geometry, despite flipping of the orbital energies. For such a case, the LOCK directive can be used to prevent the SCF calculation from changing the ordering, even if the orbital energies change.

Output orbitals of a converged MCSCF calculation are canonicalized as follows:

- Doubly occupied and unoccupied orbitals diagonalize the corresponding blocks of an effective Fock operator. Note that in the case of degenerate orbital energies this does not fully determine the orbitals.
- Active-space orbitals are chosen as natural orbitals by diagonalization of the active space 1-particle density matrix. Note that in the case of degenerate occupations that this does not fully determine the orbitals.

HESSIAN --Select preconditioner

The MCSCF will use a one-electron approximation to the orbital-orbital Hessian until some degree of convergence is obtained, whereupon it will attempt to use the exact orbital-orbital Hessian which makes the micro iterations more expensive but potentially reduces the total number of macro iterations. Either choice may be forced throughout the calculation by specifying the appropriate keyword on the HESSIAN directive.

E.g., to specify the one-electron approximation throughout

hessian onel

LEVEL --Level shift for convergence

The Hessian used in the MCSCF optimization is by default level shifted by 0.1 until the orbital gradient norm falls below 0.01, at which point the level shift is reduced to zero. The initial value of 0.1 may be changed using the LEVEL directive. Increasing the level shift may make convergence more stable in some instances.

E.g., to set the initial level shift to 0.5

level 0.5

PRINT and NOPRINT

Specific output items can be selectively enabled or disabled using the print control mechanism with the available print options listed in the table below.

MCSCF Print Options	Option	Class	Synopsis
ci energy	default	CI energy eigenvalue	
fock energy	default	Energy derived from Fock matrices	
gradient norm	default	Gradient norm	
movecs	default	Converged occupied MO vectors	
trace energy	high	Trace Energy	
converge info	high	Convergence data and monitoring	
precondition	high	Orbital preconditioner iterations	
microci	high	CI iterations in line search	
canonical	high	Canonicalization information	
new movecs	debug	MO vectors at each macro-iteration	
ci guess	debug	Initial guess CI vector	
density matrix	debug	One- and Two-particle density matrices	

Release65:SELCI

__NOTITLE__

Selected CI

The selected CI module is integrated into NWChem but as yet no input module has been $written^{[1]}$. The input thus consists of setting the appropriate variables in the database.

It is assumed that an initial SCF/MCSCF calculation has completed, and that MO vectors are available. These will be used to perform a four-index transformation, if this has not already been performed.

Background

This is a general spin-adapted, configuration-driven CI program which can perform arbitrary CI calculations, the only restriction being that all spin functions are present for each orbital occupation. CI wavefunctions may be specified using a simple configuration generation program, but the prime usage is intended to be in combination with perturbation correction and selection of new configurations. The second-order correction (Epstein-Nesbet) to the CI energy may be computed, and at the same time configurations that interact greater than a certain threshold with the current CI wavefunction may be chosen for inclusion in subsequent calculations. By repeating this process (typically twice is adequate) with the same threshold until no new configurations are added, the CI expansion may be made consistent with the selection threshold, enabling tentative extrapolation to the full-CI limit. A typical sequence of calculations is as follows:

- 1. Pick as an initial CI reference the previously executed SCF/MCSCF.
- 2. Define an initial selection threshold.
- 3. Determine the roots of interest in the current reference space.
- 4. Compute the perturbation correction and select additional configurations that interact greater than the current threshold.
- 5. Repeat steps 3 and 4.
- 6. Lower the threshold (a factor of 10 is common) and repeat steps 3, 4, and 5. The first pass through step 4 will yield the approximately self-consistent CI and CI+PT energies from the previous selection threshold.

To illustrate this, below is some abbreviated output from a calculation on water in an augmented cc-PVDZ basis set with one frozen core orbital. The SCF was converged to high precision in C_{2v} symmetry with the following input

```
start h2o
geometry; symmetry c2v
    0 0 0 0; H 0 1.43042809 -1.10715266
end
basis
    H library aug-cc-pvdz; 0 library aug-cc-pvdz
end
task scf
scf; thresh 1d-8; end
```

The following input restarts from the SCF to perform a sequence of selected CI calculations with the specified tolerances, starting with the SCF reference.

```
restart h2o
set fourindex:occ_frozen 1
set selci:mode select
set "selci:selection thresholds" \
            0.001 0.001 0.0001 0.00001 0.00001 0.000001
task selci
```

The table below summarizes the output from each of the major computational steps that were performed.

		CI	
		01	
Step	Description	dimension	Energy
1	Four-index, one frozen-core		
2	Config. generator, SCF default	1	
3+4	CI diagonalization	1	$E_{CI} = -76.041983$
5	PT selection T=0.001	1	$E_{CI+PT} = -76.304797$
6+7	CI diagonalization	75	$E_{CI} = -76.110894$
8	PT selection T=0.001	75	$E_{CI+PT} = -76.277912$

Summary of steps performed in a selected CI calculation on water.

9+10	CI diagonalization	75	$E_{CI}(T=0.001) = -76.110894$
11	PT selection T=0.0001	75	$E_{CI+PT}(T=0.001) = -76.277912$
12+13	CI diagonalization	823	$E_{CI} = -76.228419$
14	PT selection T=0.0001	823	$E_{CI+PT} = -76.273751$
15+16	CI diagonalization	841	$E_{CI}(T = 0.0001) = -76.2300544$
17	PT selection T=0.00001	841	$E_{CI+PT}(T=0.0001) = -76.274073$
18+19	CI diagonalization	2180	$E_{CI} = -76.259285$
20	PT selection T=0.00001	2180	$E_{CI+PT} = -76.276418$
21+22	CI diagonalization	2235	$E_{CI}(T = 0.00001) = -76.259818$
23	PT selection T=0.000001	2235	$E_{CI+PT}(T=0.00001) = -76.276478$
24	CI diagonalization	11489	

Files

Currently, no direct control is provided over filenames. All files are prefixed with the standard file-prefix, and any files generated by all nodes are also postfixed with the processor number. Thus, for example the molecular integrals file, used only by process zero, might be called h2o.moints whereas the off-diagonal Hamiltonian matrix element file used by process number eight would be called h2o.hamil.8.

- ciconf -- the CI configuration file, which holds information about the current CI expansion, indexing vectors, etc. This is the most important file and is required for all restarts. Note that the CI configuration generator is only run if this file does not exist. Referenced only by process zero.
- moints -- the molecular integrals, generated by the four-index transformation. As noted above these must currently be manually deleted, or the database entry selci:moints:force set, to force regeneration. Referenced only by process zero.
- civecs -- the CI vectors. Referenced only by process zero.
- wmatrx -- temporary file used to hold coupling coefficients. Deleted at calculation end. Referenced only by process zero.
- rtname, roname -- restart information for the PT selection. Should be automatically deleted if no restart is necessary. Referenced only by process zero.
- hamdg -- diagonal elements of the Hamiltonian. Deleted at calculation end. Referenced only by process zero.
- hamil -- off-diagonal Hamiltonian matrix elements. All processes generate a file containing a subset of these elements. These files can become very large. Deleted at calculation end.

Configuration Generation

If no configuration is explicitly specified then the previous SCF/MCSCF wavefunction is used, adjusting for any orbitals frozen in the four-index transformation. The four-index transformation must have completed successfully before this can execute. Orbital configurations for use as reference functions may also be explicitly specified.

Once the default/user-input reference configurations have been determined additional reference functions may be generated by applying multiple sets of creation-annihilation operators, permitting for instance, the ready specification of complete or restricted active spaces.

Finally, a uniform level of excitation from the current set of configurations into all orbitals may be applied, enabling, for instance, the simple creation of single or single+double excitation spaces from an MCSCF reference.

Specifying the reference occupation

A single orbital configuration or occupation is specified by

```
ns (socc(i),i=1,ns) (docc(i),i=1,nd)
```

where ns specifies the number of singly occupied orbitals, socc() is the list of singly occupied orbitals, and docc() is the list of doubly occupied orbitals (the number of doubly occupied orbitals, nd, is inferred from ns and the total number of electrons). All occupations may be strung together and inserted into the database as a single integer array with name "selci:conf". For example, the input

```
set "selci:conf" \
```

0				1	2	3	4	١
0				1	2	3	27	١
0				1	3	4	19	١
2	11	19		1	3	4	\	
2	8	27		1	2	3	\	
0				1	2	4	25	١
4	3	4 25	27	1	2	\		
4	2	3 19	20	1	4 \			
4	2	4 20	23	1	3			

specifies the following nine orbital configurations

1(2)	2(2)	3(2)	4(2)		
1(2)	2(2)	3(2)	27(2)		
1(2)	3(2)	4(2)	19(2)		
1(2)	3(2)	4(2)	11(1)	19(1)	
1(2)	2(2)	3(2)	8(1)	27(1)	
1(2)	2(2)	4(2)	25(2)		
1(2)	2(2)	3(1)	4(1)	25(1)	27(1)
1(2)	2(1)	3(1)	4(2)	19(1)	20(1)
1(2)	2(1)	3(2)	4(1)	20(1)	23(1)

The optional formatting of the input is just to make this arcane notation easier to read. Relatively few configurations can be currently specified in this fashion because of the input line limit of 1024 characters.

Applying creation-annihilation operators

Up to 10 sets of creation-annihilation operator pairs may be specified, each set containing up to 255 pairs. This suffices to specify complete active spaces with up to ten electrons.

The number of sets is specified as follows,

set selci:ngen 4

which indicates that there will be four sets. Each set is then specified as a separate integer array

```
set "selci:refgen
                   1" 5 4
                             6 4
                                   53
                                         63
set "selci:refgen
                   2" 5 4
                             6 4
                                   53
                                         63
set "selci:refgen
                  3" 5 4
                                   53
                             64
                                         63
set "selci:refgen
                  4" 5 4
                                   53
                                         63
                             6 4
```

In the absence of friendly, input note that the names "selci:refgen n" must be formatted with n in I2 format. Each set specifies a list of creation-annihilation operator pairs (in that order). So for instance, in the above example each set is the same and causes the excitations

4->5 4->6 3->5 3->6

If orbitals 3 and 4 were initially doubly occupied, and orbitals 5 and 6 initially unoccupied, then the application of this set of operators four times in succession is sufficient to generate the four electron in four orbital complete active space.

The precise sequence in which operators are applied is

- 1. loop through sets of operators
- 2. loop through reference configurations
- 3. loop through operators in the set
- 4. apply the operator to the configuration, if the result is new add it to the new list
- 5. end the loop over operators
- 6. end the loop over reference configurations
- 7. augment the configuration list with the new list
- 8. end the loop over sets of operators

Uniform excitation level

By default no excitation is applied to the reference configurations. If, for instance, you wanted to generate a single excitation CI space from the current configuration list, specify

```
set selci:exci 1
```

Any excitation level may be applied, but since the list of configurations is explicitly generated, as is the CI Hamiltonian matrix, you will run out of disk space if you attempt to use more than a few tens of thousands of configurations.

Number of roots

By default, only one root is generated in the CI diagonalization or perturbation selection. The following requests that 2 roots be generated

set selci:nroot 2

There is no imposed upper limit. If many roots are required, then, to minimize root skipping problems, it helps to perform an initial approximate diagonalization with several more roots than required, and then resetting this parameter once satisfied that the desired states are obtained.

Accuracy of diagonalization

By default, the CI wavefunctions are converged to a residual norm of 10^{-6} which provides similar accuracy in the perturbation corrections to the energy, and much higher accuracy in the CI eigenvalues. This may be adjusted with

set "selci:diag tol" 1d-3

the example setting much lower precision, appropriate for the approximate diagonalization discussed in the preceding section.

Selection thresholds

When running in the selected-CI mode the program will loop through a list of selection thresholds (T), performing the CI diagonalization, computing the perturbation correction, and augmenting the CI expansion with configurations that make an energy lowering to any root greater than T. The list of selection thresholds is specified as follows

There is no default for this parameter.

Mode

By default the program runs in "ci+davids" mode and just determines the CI eigenvectors/values in the current configuration space. To perform a selected-CI with perturbation correction use the following

set selci:mode select

and remember to define the selection thresholds.

Memory requirements

No global arrays are used inside the selected-CI, though the four-index transformation can be automatically invoked and it does use GAs. The selected CI replicates inside each process

```
    * all unique two-electron integrals in the MO basis that are
non-zero by symmetry, and
    * all CI information, including the CI vectors.
```

These large data structures are allocated on the local stack. A fatal error will result if insufficient memory is available.

18.9 Forcing regeneration of the MO integrals

When scanning a potential energy surface or optimizing a geometry the MO integrals need to be regenerated each time. Specify

set selci:moints:force logical .true.

to accomplish this.

Disabling update of the configuration list

When computing CI+PT energy the reference configuration list is normally updated to reflect all configurations that interact more than the specified threshold. This is usually desirable. But when scanning a potential energy surface or optimizing a geometry the reference list must be kept fixed to keep the potential energy surface continuous and well defined. To do this specify

```
set selci:update logical .false.
```

Orbital locking in CI geometry optimization

The selected CI wavefunction is not invariant to orbital rotations or to swapping two or more orbitals. Orbitals could be swapped or rotated when the geometry is changed in a geometry optimization step. The keyword lock has to be set in the SCF/MCSCF (vectors) input block to keep the orbitals in the same order throughout the geometry optimization.

References

[1] <refbase>521</refbase>

Classical Methods

Release65:Prepare

NOTITLE

Prepare

The prepare module is used to set up the necessary files for a molecular dynamics simulation with NWChem. User supplied coordinates can be used to generate topology and restart files. The topology file contains all static information about a molecular system, such as lists of atoms, bonded interactions and force field parameters. The restart file contains all dynamic information about a molecular system, such as coordinates, velocities and properties.

Without any input, the prepare module checks the existence of a topology and restart file for the molecular systems. If these files exist, the module returns to the main task level without action. The module will generate these files when they do not exist. Without any input to the module, the generated system will be for a non-solvated isolated solute system.

To update existing files, including solvation, the module requires input directives read from an input deck,

prepare ... end

The prepare module performs three sub-tasks:

• sequence generation :

This sub-task analyzes the supplied coordinates from a PDB-formatted file or from the input geometry, and generates a sequence file, containing the description of the system in terms of basic building blocks found as fragment or segment files in the database directories for the force field used. If these files do not exist, they are generated based on the supplied coordinates. This process constists of generating a fragment file with the list of atoms with their force field dependent atom types, partial atomic charges calculated from a Hartree Fock calculation for the fragment, followed by a restrained electrostatic potential fit, and a connectivity list. From the information on this fragment file the lists of all bonded interactions are generated, and the complete lists are written to a segment file.

• topology generation :

Based on the generated or user-supplied sequence file and the force field specific segment database files, this sub-task compiles the lists of atoms, bonded interactions, excluded pairs, and substitutes the force field parameters. Special commands may be given to specify interaction parameters that will be changing in a free energy evaluation.

• restart generation :

Using the user supplied coordinates and the topology file for the chemical system, this sub-task generates a restart file for the system with coordinates, velocities and other

dynamic information. This step may include solvation of the chemical system and specifying periodic boundary conditions.

Files involved in the preparation phase exist in the following hierarchy:

• standards :

The standard database files contain the original force field information. These files are to reside in a directory that is specified in the file \$HOME/.nwchemrc. There will be such a directory for each supported force field. These directories contain fragment files (with extension frg), segment files (with extension sgm) and a parameter file (with the name of the force field and with extension par).

extensions : These database files contain generally accepted extensions to the original force field and are to reside in a separate directory that is specified in the file \$HOME/.nwchemrc. There will be such a directory for each supported force field. These directories contain fragment files (with extension frg), segment files (with extension sgm) and a parameter file (with the name of the force field and with extension par).

• contributed :

These database files contain contributed definitions, also required for the quality assurance tests and are to reside in a separate directory that is specified in the file \$HOME/.nwchemrc. There will be such a directory for each supported force field. These directories contain fragment files (with extension frg), segment files (with extension sgm) and a parameter file (with the name of the force field and with extension par).

• user preferences :

These database files contain user preferred extensions to the original force field and are to reside in a separate directory that is specified in the file \$HOME/.nwchemrc. Separate directories of this type should be defined for each supported force field. This directory may contain fragment files (with extension frg), segment files (with extension sgm) and a parameter file (with the name of the force field and with extension par).

• temporary files :

Temporary database files contain user preferred extensions to the original force field and are to reside in a separate directory that is specified in the file \$HOME/.nwchemrc. There may be such a directory for each supported force field. This directory may contain fragment files (with extension frg), segment files (with extension sgm) and a parameter file (with the name of the force field and with extension par).

• current files :

Database files that contain user preferred extensions to the original force field and are to reside in a separate directory that is specified in the file \$HOME/.nwchemrc. Typically this will be the current working directory, although it may be defined as a specific directory. This directory may contain fragment files (with extension frg), segment files (with extension sgm) and a parameter file (with the name of the force field and with extension par). If not specified, files will be taken from the current directory.

Data is taken from the database files searched in the above order. If data is specified more than once, the last found values are used. For example, if some standard segment is redefined in a temporary file, the latter one will be used. This allows the user to redefine standards or extensions without having to modify those database files, which may reside in a generally available, non-modifyable directory. If a filename is specified rather than a directory, the filename indicates the parameter file definition. All other files (frg and sgm files) will be take from the specified directory. The most common problems with the prepare module are

- The format of the pdb file does not conform to the pdb standard. In particular, atom names need to correspond with definitions in the fragment and segment database files, and should adhere to IUPAC recommendations as adopted by the pdb standard. If this problem occurs, the pdb file will need to be corrected.
- Non-standard segments may contain atoms that could not be atom typed with the existing typing rules in the force field parameter files. When this happens, additional typing rules can be included in the parameter file, or the fragment file may be manually typed.
- 1. Parameters for atom types or bonded interactions do not exist in the force field. When this happens, additional parameters may be defined in the parameter files, or the segment file may be edited to include explicit parameters.

Default database directories

The file \$HOME/.nwchemrc may contain the following entries that determine which files are used by the prepare module.

ffield <string ffname>

This entry specifies the default force field. Database files supplied with NWChem currently support values for ffname of amber, referring to AMBER95, and charmm, referring to the academic CHARMM22 force field.

```
<string ffname>_(1-9) <string ffdir>[\{<string parfile>\}]
```

Entries of this type specify the directory ffdir in which force field database files can be found. Optionally the parameterfile in this directory may be specified as parfile. The prepare module will only use files in directories specified here. One exception is that files in the current work directory will be used if no directory with current files is specified. The directories are read in the order 1-9 with duplicate parameters taken from the last occurrence found. Note that multiple parameter files may be specified that will be read in the order in which they are specified.

<string solvnam> <string solvfil>

This entry may be used to identify a pure solvent restart file solvfil by a name solvnam

An example file \$HOME/.nwchemrc is:

```
ffield amber
amber_1 /soft/nwchem/share/amber/amber_s/amber99.par,spce.par
amber_2 /soft/nwchem/share/amber/amber_x/
amber_3 /usr/people/username/data/amber/amber_u/
spce /soft/nwchem/share/solvents/spce.rst
charmm_1 /soft/nwchem/share/charmm/charmm_s/
charmm_2 /soft/nwchem/share/charmm/charmm_x/
```

System name and coordinate source

system <string sys_calc>

The system name can be explicitly specified for the prepare module. If not specified, the system name will be taken from a specification in a previous md input block, or derived from the run time database name.

```
source ( pdb | rtdb )
```

The source of the coordinates can be explicitly specified to be from a PDB formatted file sys.pdb, or from a geometry object in the run time database. If not specified, a pdb file will be used when it exists in the current directory or the rtdb geometry otherwise.

```
model <integer modpdb default 0>
```

If a PDB formatted source file contains different MODELs, the model keyword can be used to specify which MODEL will be used to generate the topology and restart file. If not specified, the first MODEL found on the PDB file will be read.

altloc <character locpdb default ' '>

The altloc keyword may be used to specify the use of alternate location coordinates on a PDB file.

chain <character chnpdb default ' '>

The chain keyword may be used to specify the chain identifier for coordinates on a PDB file.

histidine (hid | hie | hip)

specifies the default protonation state of histidine.

sscyx

Keyword sscyx may be used to rename cysteine residues that form sulphur bridges to CYX.

hbuild

Keyword hbuild may be used to add hydrogen atoms to the unknown segments of the structure found on the pdb file. Placement of hydrogen atoms is based on geometric criteria, and the resulting fragment and segment files should be carefully examined for correctness.

The database directories are used as specified in the file \$.nwchemrc\$. Specific definitions for the force field used may be changed in the input file using

directory_(1-9) <string ffdir>[<string parfile>]

Sequence file generation

If no existing sequence file is present in the current directory, or if the new_seq keyword was specified in the prepare input deck, a new sequence file is generated from information from the pdb file, and the following input directives.

maxscf <integer maxscf default 20>

Variable maxscf specifies the maximum number of atoms in a segment for which partial atomic charges will be determined from an SCF calculation followed by RESP charge fitting. For larger segments a crude partial charge guestimation will be done.

qscale <real qscale default 1.0>

Variable qscale specifies the factor with which SCF/RESP determined charges will be multiplied.

modify sequence { <integer sgmnum>:<string sgmnam> }

This command specifies that segment symnam should be used for segment with number symnum. This command can be used to specify a particular protonation state. For example, the following command specifies that residue 114 is a hystidine protonated at the N\$_\epsilon\$ site and residue 202 is a hystidine protonated at the N\$_\delta\$ site:

modify sequence 114:HIE 202:HID

Links between atoms can be enforced with

link <string atomname> <string atomname>

For example, to link atom SG in segment 20 with atom FE in segment 55, use:

link 20:_SG 55:FE

The format of the sequence file is given in Table 36.9. In addition to the list of segments this file also includes links between non-standard segments or other non-standard links. These links are generated based on distances found between atoms on the pdb file. When atoms are involved in such non-standard links that have not been identified in the fragment of segment files as a non-chain link atom, the prepare module will ignore these links and report them as skipped. If one or more of these links are required, the user has to include them with explicit link directives in the sequence file, making them forced links. Alternatively, these links can be made forced-links by changing link into LINK in the sequence file.

fraction { <integer imol> }

Directive fraction can be used to separate solute molecules into fractions for which energies will be separately reported during molecular dynamics simulations. The listed molecules will be the last molecule in a fraction. Up to 10 molecules may be specified in this directive.

counter <integer num> <string ion>

Directive counter adds num counter ions of type ion to the sequence file. Up to 10 counter directives may appear in the input block.

counter <real factor>

This directive scales the counter ion charge by the specified factor in the determination of counter ions positions.

Topology file generation

new_top [new_seq]

Keyword new_top is used to force the generation of a new topology file. An existing topology file for the system in the current directory will be overwritten. If keyword new_seq is also specified, an existing sequence file will also be overwritten with a newly generated file.

amber | charmm

The prepare module generates force field specific fragment, segment and topology files. The force field may be explicitly specified in the prepare input block by specifying its name. Currently AMBER and CHARMM are the supported force fields. A default force field may be specified in the file \$HOME/.nwchemrc.

```
standard <string dir_s>[<string par_s>]
extensions <string dir_x>[<string par_x>]
contributed <string dir_q>[<string par_q>]
user <string dir_u>[<string par_u>]
temporary <string dir_t>[<string par_t>]
current <string dir_c>[<string par_c>]
```

The user can explicitly specify the directories where force field specific databases can be found. These include force field standards, extensions, quality assurance tests, user preferences, temporary , and current database files. Defaults for the directories where database files reside may be specified in the file \$HOME/.nwchemrc for each of the supported force fields. Fragment, segment and sequence files generated by the prepare module are written in the temporary directory. When not specified, the current directory will be used. Topology and restart files are always created in the current directory.

The following directives control the modifications of a topology file. These directives are executed in the order in which they appear in the prepare input deck. The topology modifying commands are not stored on the run-time database and are, therefor, not persistent.

(type <string atomtyp> | charge <real atomcharge> | \ polar <real atompolar> | dummy | self | quantum | quantum_high)

These modify commands change the atom type, partial atomic charge, atomic polarizability, specify a dummy, self-interaction and quantum atom, respectively. If mset is specified, the modification will only apply to the specified set, which has to be 1, 2 or 3. If not specified, the modification will be applied to all three sets. The quantum region in QM/MM simulations is defined by specifying atoms with the quantum or quantum_high label. For atoms defined quantum_high basis sets labeled X_H will be used. The atomnam should be

specified as <integer isgm>:<string name>, where isgm is the segment number, and name is the atom name. A leading blank in an atom name should be substituted with an underscore. The modify commands may be combined. For example, the following directive changes for the specified atom the charge and atom type in set 2 and specifies the atom to be a dummy in set 3.

modify atom 12:_C1 set 2 charge 0.12 type CA set 3 dummy

With the following directives modifications can be made for entire segments.

```
modify segment <integer isgm> \
  [protonation <integer iprot> | set <integer mset> |
initial | final] \
  ( dummy | self | uncharged | quantum | quantum_high )
```

where protonation specifies a modification of the default protonation state of the segment as specified in the segment file. This option only applies to Q-HOP simulations.

Modifications to bonded interaction parameters can be made with the following modify commands.

```
modify ( bond <string atomtyp> <string atomtyp> | \
```

angle <string atomtyp> <string atomtyp> | \

```
torsion <string atomtyp> <string atomtyp> <string
atomtyp>  \
```

<string atomtyp> [multiplicity <integer multip>] | \ plane <string atomtyp> <string
atomtyp> <string atomtyp> \ <string atomtyp>) [set <integer mset> | initial | final] \
<real value> <real forcon>

where atomtyp and mset are defined as above, multip is the torsion ultiplicity for which the modification is to be applied, value is the reference bond, angle, torsion angle of out-of-plane angle value respectively, and forcon is the force constant for bond, angle, torsion angle of out-of-plane angle. When multip or mset are not defined the modification will be applied to all multiplicities and sets, respectively, for the identified bonded interaction.

After modifying atoms to quantum atoms the bonded interactions in which only quantum atoms are involved are removed from the bonded lists using

update lists

Error messages resulting from parameters not being defined for bonded interaction in which only quantum atoms are involved are ignored using

ignore

To specify that a free energy calculation will be carried out using the topology file, the following keyword needs to be specified,

free

To specify that a Q-HOP simulation will be carried out using the topology file, the following keyword needs to be specified,

qhop

To specify that only the first set of parameters should be used, even if multiple sets have been defined in the fragment or segment files, the following keyword needs to be specified,

first

Note that keywords free, qhop and qhop are mutually exclusive.

Appending to an existing topology file

noe <string atom1> <string atom3> \

<real dist1> <real dist2> <real dist3> <real
forc1> <real forc2>

This directive specifies a distance restraint potential between atoms atom1 and atom2, with a harmonic function with force constant *forc1* between *dist1* and *dist2*, and a harmonic function with force constant *forc2* between *dist2* and *dist3*. For distances shorter than *dist1* or larger than *dist3*, a constant force is applied such that force and energy are continuous at *dist1* and *dist3*, respectively. Distances are given in nm, force constants in $kJmol^{-1}nm^{-2}$

select <integer isel> { <string atoms> }

Directive select specifies a group of atoms used in the definition of potential of mean force potentials.

The selected atoms are specified by the string atoms which takes the form

[{isgm [- jsgm] [,]} [:] [{aname[,]}]

For example, all carbon and oxygen atoms in segments 3 and 6 through 12 are selected for group 1 by

```
3,6-12:_C????,_0????
```

```
pmf [all] [bias] zalign <integer isel> <real forcon1>
<real forcon2>
pmf [combine] [bias] xyplane <integer isel> <real forcon1>
<real forcon2>
pmf [constraint] [bias] (distance | zdistance) <integer isel>
<integer jsel> \
            <real dist1> <real dist2> <real forcon1>
<real forcon2>
pmf [bias] angle <integer isel> <integer jsel> <integer</pre>
ksel> \
            <real angle1> <real angle2> <real
forcon1> <real forcon2>
pmf [bias] torsion <integer isel> <integer jsel>
<integer ksel> <integer lsel> \
            <real angle1> <real angle2> <real
forcon1> <real forcon2>
pmf [bias] basepair <integer isel> <integer jsel> \
```

Directive pmf specifies a potential of mean force potential in terms of the specified atom selection. Option zalign specifies the atoms in the selection to be restrained to a line parallel to the z-axis. Option xyplane specifies the atoms in the selection to be restrained to a plane perpendicular to the z-axis. Options distance, angle and torsion, are defined in terms of the center of geometry of the specified atom selections. Keyword basepair is used to specify a harmonic potential between residues isel and jsel. Keywords zaxis and zaxis-cog can be used to pull atoms toward the z-axis. Option all may be specified to apply an equivalent pmf to each of the equivalent solute molecules in the system. Option combine may be specified to apply the specified pmf to the atoms in all of the equivalent solute molecules. Option constraint may be specified to a distance pmf to treat the distance as a contraint. Option bias may be specified to indicate that this function should be treated as a biasing potential. Appropriate corrections to free energy results will be evaluated.

Generating a restart file

new_rst

Keyword new_rst will cause an existing restart file to be overwritten with a new file.

The follwing directives control the manipulation of restart files, and are executed in the order in which they appear in the prepare input deck.

```
solvent name <string*3 slvnam default ``HOH''> \
    model <string slvmdl default ``spce''>
```

The solvent keyword can be used to specify the three letter solvent name as expected on the PDB formatted file, and the name of the solvent model for which solvent coordinates will be used.

```
solvate [ < real rshell default 1.2 > ] \
    ( [ cube [ <real edge> ]] \
    [ box [ <real xedge> [ <real xedge> [ <real
xedge>]] \
    [ sphere <real radius> ]
```

١

```
[ sphere <real radius> ]
```

Solvation can be specified to be in a cubic box with specified edge, rectangular box with specified edges, or in a sphere with specified radius. Solvation in a cube or rectangular box will automatically also set periodic boundary conditions. Solvation in a sphere will only allow simulations without periodic boundary conditions. The size of the cubic and rectangular boxes will be expanded by a length specified by the expand variable. If no shape is specified, solvation will be done for a cubic box with an edge that leaves rshell nm between any solute atom and a periodic image of any solute atom after the solute has been

centered. An explicit write is not needed to write the restart file. The solvate will write out a file sys_calc.rst. If not specified, the dimension of the solvation cell will be as large as to have at least a distance of rshell nm between any solute atom and the edge of the cell. The experimental troct directive generates a truncated octrahedral box.

```
touch
  <real touch default 0.23>
```

The variable touch specifies the minimum distance between a solvent and solute atom for which a solvent molecule will be accepted for solvation.

```
envelope
<real xpndw default 0.0>
```

sets the expand vealues to be used in solvate operations.

```
expand <real xpndw default 0.1>
```

The variable xpndw specifies the size in nm with which the simulation volume will be increased after solvation.

[sphere <real radius>]

\

١

```
[ sphere <real radius> ] ( [large] pdb | xyz)]
<string filename>
```

These directives read and write the file filename in the specified format. The solute option instructs to write out the coordinates for solute and all, or if specified the first nsolvent, crystal solvent molecules only. If no format is specified, it will be derived from the extension of the filename. Recognized extensions are rst, rst_old (read only), pdb, xyz (write only) and pov (write only). Reading and then writing the same restart file will cause the sub-block size information to be lost. If this information needs to be retained a shell copy command needs to be used. The large keyword allows PDB files to be written with more than 9999 residues. Since the PDB file will not conform to the PDB convention, this option should only be used if required. NWChem will be able to read the resulting PDB file, but other codes may not.

scale <real scale default -1.0>

This directive scales the volume and coordinates written to povray files. A negative value of scale (default) scales the coordinates to lie in [-1:1].

```
cpk [<real cpk default 1.0>]
```

This directive causes povray files to contain cpk model output. The optional value is used to scale the atomic radii. A neagtive value of cpk resets the rendering to stick.

center | centerx | centery | centerz

These directives center the solute center of geometry at the origin, in the y-z plane, in the x-z plane or in the x-y plane, respectively.

orient

This directive orients the solute principal axes.

This directive translates solute atoms in the indicated range by xtran, without checking for bad contacts in the resulting structure.

rotate [atom | segment | molecule] \ <integer itran> <integer itran> <real angle> <real
xrot(3)>

This directive rotates solute atoms in the indicated range by angle around the vector given by xrot,, without checking for bad contacts in the resulting structure.

```
remove solvent [inside | outside] [x <real xmin> <real
xmax>] \
[y <real ymin> <real ymax>] [z <real zmin> <real
zmax>]
```

This directive removes solvent molecules inside or outside the specified coordinate range.

periodic

This directive enables periodic boundary conditions.

vacuo

This directive disables periodic boundary conditions.

```
grid <integer mgrid default 24> <real rgrid default 0.2>
```

This directive specifies the grid size of trial counter-ion positions and minimum distance between an atom in the system and a counter-ion.

crop

prints minimum and maximum solute coordinates.

boxsize

specifies to redetermine the box size.

cube

specifies to redetermine the smallest cubic box size.

```
box <real xsize> <real ysize> <real zsize>
```

The box directive resets the box size.

align <string atomi> <string atomj> <string atomk>

The align directive orients the system such that atomi and atomj are on the z-axis, and atomk in the x=y plane.

```
repeat [randomx | randomy | randomz] [chains | molecules | fractions ]
\
  <integer nx> <integer ny> <integer nz> [<real</pre>
```

dist>] [<real zdist>]

The repeat directive causes a subsequent write pdb directive to write out multiple copies of the system, with nx copies in the x, ny copies in the y, and nz copies in the z-direction, with a minimum distance of dist between any pair of atoms from different copies. If nz is -2, an inverted copy is placed in the z direction, with a separation of zdist nm. If dist is negative, the box dimensions will be used. For systems with solvent, this directive should be used with a negative dist. Optional keywords chains, molecules and fractions specify to write each repeating solute unit as a chain, to repeat each solute molecule, or each solute fraction separately. Optional keywords randomx, randomy, and randomz can be used to apply random rotations for each repeat unit around a vector through the center of geometry of the solute in the x, y or z direction.

skip <integer ix> <integer iy> <integer iz>

The skip directive can be used to skip single repeat unit from the repeat directive. Up to 100 skip directives may be specified, and will only apply to the previously specified repeat directive.

(collapsexy | collapsez) [<integer nmoves>]

specifies to move all solute molecules toward the z-axis or x=y-plane, respectively, to within a distance of touch nm between any pair of atoms from different solute molecules. Parameter nmoves specifies the number of collapse moves that will be made. Monatomic ions will move with the nearest multi-atom molecule.

collapse_group <integer imol> <integer jmol>

specifies that molecule jmol will move together with molecule imol in collapse operations.

merge <real xtran(3)> <string pdbfile>

specifies to merge the coordinates found on the specified pdb file into the current structure after translation by xtran(3).

Release65:MD

__NOTITLE__

Molecular dynamics

Introduction

Spacial decomposition

The molecular dynamics module of NWChem uses a distribution of data based on a spacial decomposition of the molecular system, offering an efficient parallel implementation in terms of both memory requirements and communication costs, especially for simulations of large molecular systems.

Inter-processor communication using the global array tools and the design of a data structure allowing distribution based on spacial decomposition are the key elements in taking advantage of the distribution of memory requirements and computational work with minimal communication.

In the spacial decomposition approach, the physical simulation volume is divided into rectangular cells, each of which is assigned to a processor. Depending on the conditions of the calculation and the number of available processors, each processor contains one or more of these spacially grouped cells. The most important aspects of this decomposition are the dependence of the cell sizes and communication cost on the number of processors and the shape of the cells, the frequent reassignment of atoms to cells leading to a fluctuating number of atoms per cell, and the locality of communication which is the main reason for the efficiency of this approach for very large molecular systems.

To improve efficiency, molecular systems are broken up into separately treated solvent and solute parts. Solvent molecules are assigned to the domains according to their center of geometry and are always owned by a one node. This avoids solvent-solvent bonded interactions crossing node boundaries. Solute molecules are broken up into segments, with each segment assigned to a processor based on its center of geometry. This limits the number of solute bonded interactions that cross node boundaries. The processor to which a particular cell is assigned is responsible for the calculation of all interactions between atoms within that cell. For the calculation of forces and energies in which atoms in cells assigned to different processors are involved, data are exchanged between processors. The number of neighboring cells is determined by the size and shape of the cells and the range of interaction. The data exchange that takes place every simulation time step represents the main communication requirements. Consequently, one of the main efforts is to design algorithms and data structures to minimize the cost of this communication. However, for very large molecular systems, memory requirements also need to be taken into account.

To compromise between these requirements exchange of data is performed in successive point to point communications rather than using the shift algorithm which reduces the number of communication calls for the same amount of communicated data.

For inhomogeneous systems, the computational load of evaluating atomic interactions will generally differ between cell pairs. This will lead to load imbalance between processors. Two algorithms have been implemented that allow for dynamically balancing the workload of each processor. One method is the dynamic resizing of cells such that cells gradually become smaller on the busiest node, thereby reducing the computational load of that node. Disadvantages of this method are that the efficiency depends on the solute distribution in the simulation volume and the redistribution of work depends on the number of nodes which could lead to results that depend on the number of nodes used. The second method is based on the dynamic redistribution of intra-node cell-cell interactions. This method represents a more coarse load balancing scheme, but does not have the disadvantages of the cell resizing algorithm. For most molecular systems the cell pair redistribution is the more efficient and preferred method.

The description of a molecular system consists of static and dynamic information. The static information does not change during a simulation and includes items such as connectivity, excluded and third neighbor lists, equilibrium values and force constants for all bonded and non-bonded interactions. The static information is called the topology of the molecular system, and is kept on a separate topology file. The dynamic information includes coordinates and velocities for all atoms in the molecular system, and is kept in a so-called restart file.

Topology

The static information about a molecular system that is needed for a molecular simulation is provided to the simulation module in a topology file. Items in this file include, among many other things, a list of atoms, their non-bonded parameters for van der Waals and electrostatic interactions, and the complete connectivity in terms of bonds, angles and dihedrals.

In molecular systems, a distinction is made between solvent and solute, which are treated separately. A solvent molecule is defined only once in the topology file, even though many solvent molecules usually are included in the actual molecular system. In the current implementation only one solvent can be defined. Everything that is not solvent in the molecular system is solute. Each solute atom in the system must be explicitly defined in the topology.

Molecules are defined in terms of one or more segments. Typically, repetitive parts of a molecule are each defined as a single segment, such as the amino acid residues in a protein. Segments can be quite complicated to define and are, therefore, collected in a set of database files. The definition of a molecular system in terms of segments is a sequence.

Topology files are created using the prepare module.

Files

File names used have the form *system_calc.ext*, with exception of the topology file, which is named *system*.top. Anything that refers to the definition of the chemical system can be used for *system*, as long as no periods or underlines are used. The identifier *calc* can be anything that refers to the type of calculation to be performed for the system with the topology defined. This file naming convention allows for the creation of a single topology file *system*.top that can be used for a number of different calculations, each identified with a different *calc*. For example, if crown.top is the name of the topology file for a crown ether, crown_em, crown_md, crown_ti could be used with appropriate extensions for the filenames for energy minimization, molecular dynamics simulation and multi-configuration thermodynamic integration, respectively. All of these calculations would use the same

topology file crown.top.

The extensions <ext> identify the kind of information on a file, and are pre-determined.

List of file extensions for nwchem chemical	system files.
---	---------------

dbg	debug file
frg	fragment file
gib	free energy data file
mri	free energy multiple run input file
mro	free energy multiple run output file
nw	NWChem input file
nwout	NWChem output file
out	molecular dynamics output file
pdb	PDB formatted coordinate file
prp	property file
qrs	quenched restart file, resulting from an energy minimization
rst	restart file, used to start or restart a simulation
seq	sequence file, describing the system in segments
sgm	segment file, describing segments
syn	synchronization time file
tst	test file
tim	timing analysis file
top	topology file, contains the static description of a system
trj	trajectory file

Databases

Database file supplied with NWChem and used by the prepare module are found in directories with name ffield_*level*, where *ffield* is any of the supported force fields. The source of the data is identified by *level*, and can be

level	Description
S	original published data
x	additional published data
q	contributed data
u	user preferred data
t	user defined temporary data

The user is can replace these directories or add additional database files by specifying them in the *.nwchemrc* file. or in the prepare input file.

The extension 1-9 defines the priority of database file.

frg	fragments
par	parameters

seq	sequences
sgm	segments

Force fields

Force fields recognized are

Keyword	Force field	Status
amber	AMBER99	AMBER95,GLYCAM also available
charmm	CHARMM	

Format of fragment files

Fragment files contain the basic information needed to specify all interactions that need to be considered in a molecular simulation. Normally these files are created by the prepare module. Manual editing is needed when, for example, the prepare module could not complete atom typing, or when modified charges are required.

The formats of files used in NWChem are listed here.

Creating segment files

The prepare module is used to generate segment files from corresponding fragment files. A segment file contains all information for the calculation of bonded and non-bonded interactions for a given chemical system using a specific force field.

Which atoms form a fragment is specified in the coordinate file, currently only in PDB format. The segment entries define three sets of parameters for each interaction.

Free energy perturbations can be performed using set 1 for the generation of the ensemble while using sets 2 and/or 3 as perturbations. Free energy multiconfiguration thermodynamic integration and multistep thermodynamic perturbation calculations are performed by gradually changing the interactions in the system from parameter set 2 to parameter set 3. These modifications can be edited into the segment files manually, or introduced directly into the topology file using the modify commands in the input for the prepare module.

Creating sequence files

A sequence file describes a molecular system in terms of segments. This file is generated by the prepare module for the molecular system provided on a PDB-formatted coordinate file

Creating topology files

The topology describes all static information that describes a molecular system. This includes the connectivity in terms of bond-stretching, angle-bending and torsional interactions, as well as the non-bonded van der Waals and Coulombic interactions.

The topology of a molecular system is generated by the prepare module from the sequence in terms of segments as specified on the PDB file. For each unique segment specified in this file the segment database directories are searched for the segment definition. For segments not found in one of the database directories a segment definition is generated in the temporary directory if a fragment file was found. If a fragment file could not be found, it is generated by the prepare module base on what is found on the PDB file.

When all segments are found or created, the parameter substitutions are performed, using force field parameters taken from the parameter databases. After all lists have been generated the topology is written to a local topology file <system>.top.

Creating restart files

Restart files contain all dynamical information about a molecular system and are created by the prepare module if a topology file is available. The prepare module will automatically generate coordinates for hydrogen atoms and monatomic counter ions not found on the PDB formatted coordinate file, if no fragment or segment files were generated using that PDB file.

The prepare module has a number of other optional input command, including solvation.

Molecular simulations

The type of molecular dynamics simulation is specified by the NWChem task directive.

task md [energy | optimize | dynamics | thermodynamics]

where the theory keyword md specifies use of the molecular dynamics module, and the operation keyword is one of

- energy for single configuration energy evaluation
- optimize for energy minimization
- *dynamics* for molecular dynamics simulations and single step thermodynamic perturbation free energy molecular dynamics simulations
- *thermodynamics* for combined multi-configuration thermodynamic integration and multiple step thermodynamic perturbation free energy molecular dynamics simulations.

System specification

The chemical system for a calculation is specified in the topology and restart files. These files should be created using the utilities nwtop and nwrst before a simulation can be performed. The names of these files are determined from the required system directive.

```
system <string systemid>_<string calcid>
```

where the strings systemid and calcid are user defined names for the chemical system and the type of calculation to ber performed, respectively. These names are used to derive the filenames used for the calculation. The topoly file used will be systemid.top, while all other files are named systemid_calcid.ext.
Restarting and continuing simulations

finish

Specifies that the current job will finish a previous, incomplete simulation, using the input data that have been recorded by that previous run in the restart file. Most of the input in the current md input block will be ignored.

resume

Specifies that the current job will be an extension of a previous simulation, using most of the input data that have been recorded by that previous run in the restart file. Typically the input in the current md input block defines a larger number of steps than the previous job.

Parameter set

set <integer iset>

Specifies the use of parameter set <iset> for the molecular dynamics simulation. The topology file contains three separate parameters sets that can be used. The default for <iset> is 1.

lambda <integer ilambda> <integer ilambda>

Specifies the use of parameter set for the ilambda-th of mlambda steps.

pset <integer isetp1> [<integer isetp2>]

Specifies the parameter sets to be used as perturbation potentials in single step thermodynamic perturbation free energy evaluations, where <isetp1> specifies the first perturbation parameter set and <isetp2> specifies the second perturbation parameter set. Legal values for <isetp1> are 2 and 3. Legal value for <isetp2> is 3, in which case <isetp1> can only be 2. If specified, <iset> is automatically set to 1.

```
pmf [ equilharm <integer npmfc> scale <real facpmf>]
```

Specifies that any potential of mean force functions defined in the topology files are to be used. If equilharm is specified, the first npmfc dynamics steps will use a harmonic potential in stead of any pmf constraint. If scale is specified, all pmf force constants are scaled by a factor facpmf.

```
distar [draver [<integer ndaver default 1>
  [scale <real drsscl>]
  [after <integer nfdrss>]
```

Specifies that any distance restraint functions defined in the topology files are to be used.

```
qhop [<integer nfhop default 10>]
  [<real rhop default 0.35>]
  [<real thop default 0.02>]
```

Specifies that a Q-HOP simulation is to be carried out with attempted proton hops every *nfhop* steps, a cutoff for the donor-acceptor pair distance of *rhop* nm, and a minimum time

before back hopping can occur of *thop* ps.

Energy minimization algorithms

The energy minimization of the system as found in the restart file is performed with the following directives. If both are specified, steepest descent energy minimization precedes conjugate gradient minimization.

```
sd <integer msdit> [init <real dx0sd>] [min <real
dxsdmx>] \
        [max <real dxmsd>]
```

Specifies the variables for steepest descent energy minimizations, where <msdit> is the maximum number of steepest descent steps taken, for which the default is 100, <dx0sd> is the initial step size in nm for which the default is 0.001, <dxsdmx> is the threshold for the step size in nm for which the default is 0.0001, and <dxmsd> is the maximum allowed step size in nm for which the default is 0.05.

```
cg <integer mcgit> [init <real dx0cg>] [min <real
dxcgmx>] \
        [cy <integer ncgcy>]
```

Specifies the variables for conjugate gradient energy minimizations, where <mcgit> is the maximum number of conjugate gradient steps taken, for which the default is 100, <dx0cg> is the initial search interval size in nm for which the default is 0.001, <dxcgmx> is the threshold for the step size in nm for which the default is 0.0001, and <ncgcy> is the number of conjugate gradient steps after which the gradient history is discarded for which the default is 10. If conjugate gradient energy minimization is preceded by steepest descent energy minimization, the search interval is set to twice the final step of the steepest descent descent energy minimization.

Multi-configuration thermodynamic integration

The following keywords control free energy difference simulations. Multi-configuration thermodynamic integrations are always combined with multiple step thermodynamic perturbations.

```
(forward | reverse) [[<integer mrun> of] <integer
maxlam>]
```

Specifies the direction and number of integration steps in free energy evaluations, with forward being the default direction. <mrun> is the number of ensembles that will be generated in this calculation, and <maxlam> is the total number of ensembles to complete the thermodynamic integration. The default value for <maxlam> is 21. The default value of <mrun> is the value of <maxlam>.

```
error <real edacq>
```

Specifies the maximum allowed statistical error in each generated ensemble, where <edacq> is the maximum error allowed in the ensemble average derivative of the Hamiltonian with respect to $\lambda = 0.01 \text{ Jmol}^{-1}$.

drift <real ddacq>

Specifies the maximum allowed drift in the free energy result, where <ddacq> is the maximum drift allowed in the ensemble average derivative of the Hamiltonian with respect to λ with a default of 5.0 $kJmol^{-1}ps^{-1}$.

factor <real fdacq>

Specifies the maximum allowed change in ensemble size where < fdacq > is the minimum size of an ensemble relative to the previous ensemble in the calculation with a default value of 0.75.

decomp

Specifies that a free energy decomposition is to be carried out. Since free energy contributions are path dependent, results from a decomposition analysis can no be unambiguously interpreted, and the default is not to perform this decomposition.

sss [delta <real delta>]

Specifies that atomic non-bonded interactions describe a dummy atom in either the initial or final state of the thermodynamic calculation will be calculated using separation-shifted scaling, where <delta> is the separation-shifted scaling factor with a default of $0.075nm^2$. This scaling method prevents problems associated with singularities in the interaction potentials.

new | renew | extend

Specifies the initial conditions for thermodynamic calculations. new indicates that this is an initial mcti calculation, which is the default. renew instructs to obtain the initial conditions for each λ from the mro-file from a previous mcti calculation, which has to be renamed to an mri-file. The keyword extend will extend a previous mcti calculation from the data read from an mri-file.

Time and integration algorithm directives

Following directives control the integration of the equations of motion.

leapfrog leapfrog_bc

Specifies the integration algorithm, where leapfrog specifies the default leap frog integration, and leapfrog_bc specifies the Brown-Clarke leap frog integrator.

guided [<real fguide default 0.2> [<real tguide default 0.2>]

Specifies the use of the guided molecular dynamics simulation technique. Variable *fguide* defines the fraction of the averaged forces g to be added to the forces f^{f} evaluated using the force field functions to obtain the forces f used to advance the coordinates.

 $f_i = f_i^J + fguide * g_{i-1}$ Variable tguide defines the length of the averaging relative to the timestep Δt .

$$g_i = rac{\Delta t}{tguide} f_i + \left(1 - rac{\Delta t}{tguide}
ight) g_{i-1}$$

The current implementation is still under development.

equil <integer mequi>

Specifies the number of equilibration steps <mequi>, with a default of 100.

data <integer mdacq> [over <integer ldacq>]]

Specifies the number of data gathering steps <mdacq> with a default of 500. In multi-configuration thermodynamic integrations <mequi> and <mdacq> are for each of the ensembles, and variable <ldacq> specifies the minimum number of data gathering steps in each ensemble. In regular molecular dynamics simulations <ldacq> is not used. The default value for <ldacq> is the value of <mdacq>.

time <real stime>

Specifies the initial time <stime> of a molecular simulation in ps, with a default of 0.0.

step <real tstep>

Specifies the time step <tstep> in ps, with 0.001 as the default value.

Ensemble selection

Following directives control the ensemble type.

```
isotherm [<real tmpext> [<real tmpext2>]] [trelax
<real tmprlx> [<real tmsrlx>]] \
      [anneal [<real tann1>] <real tann2>]
```

Specifies a constant temperature ensemble using Berendsen's thermostat, where <tmpext> is the external temperature with a default of 298.15 K, and <tmprlx> and <tmsrlx> are temperature relaxation times in ps with a default of 0.1. If only <tmprlx> is given the complete system is coupled to the heat bath with relaxation time <tmprlx>. If both relaxation times are supplied, solvent and solute are independently coupled to the heat bath with relaxation times <tmprlx> and <tmsrlx>, respectively. If keyword anneal is specified, the external temperature will change from tmpext to tempext2 between simulation time tann1 and tann2

```
isobar [<real prsext>] [trelax <real prsrlx> ] \
    [compress <real compr>] [anisotropic] [xy | z | xy-z]
```

Specifies a constant pressure ensemble using Berendsen's piston, where preset> is the external pressure with a default of $1.02510^5 Pa$, pressure is the pressure relaxation time in ps with a default of 0.5, and <compr> is the system compressibility in $m^2 N^{-1}$ with a default of 4.53E-10. Optional keywords xy, z and xy-z may be used to specify that pressure scaling is to be applied in the x and y dimension only, the z dimension only, or, in all three dimensions with identical scaling in the x and y dimension. The last option requires that anisotropic is also specified.

Velocity reassignments

Velocities can be periodically reassigned to reflect a certain temperature.

```
vreass <integer nfgaus> <real tgauss>
   [fraction [<real frgaus default 0.5]]
   [once]
   [(first | initial)] [(last | final)]</pre>
```

Specifies that velocities will be reassigned every <nfgaus> molecular dynamics steps, reflecting a temperature of <tgauss> K. The default is not to reassign velocities, i.e. <nfgaus> is 0. Keyword fraction allows the specification of the fraction of the new velocities are random. Keyword once specifies that velocity reassignment only should be done in the first step. Keywords first or initial and last or final specify that velocity reassignment should only be applied in the first and last window of multiple run simulations.

Cutoff radii

Cutoff radii can be specified for short range and long range interactions.

```
cutoff [short] <real rshort> [long <real rlong>] \
    [qmmm <real rqmmm>]
```

Specifies the short range cutoff radius <rshort>, and the long range cutoff radius <rlong> in nm. If the long range cutoff radius is larger than the short range cutoff radius the twin range method will be used, in which short range forces and energies are evaluated every molecular dynamics step, and long range forces and energies with a frequency of <nflong> molecular dynamics steps. Keyword qmmm specifies the radius of the zone around quantum atoms defining the QM/MM bare charges. The default value for <rshort>, <rlong> and <rqmmm> is 0.9 nm.

Polarization

First order and self consistent electronic polarization models have been implemented.

polar (first | scf [[<integer mpolit>] <real ptol>])

Specifies the use of polarization potentials, where the keyword first specifies the first order polarization model, and scf specifies the self consistent polarization field model, iteratively determined with a maximum of <mpolit> iterations to within a tolerance of <ptol> D in the generated induced dipoles. The default is not to use polarization models.

External electrostatic field

```
field <real xfield> [freq <real xffreq>] [vector
<real xfvect(1:3)>]
```

Specifies an external electrostatic field, where <xfield> is the field strength, <xffreq> is the frequency in MHz and <xfvect> is the external field vector.

Constraints

Constraints are satisfied using the SHAKE coordinate resetting procedure.

```
shake [<integer mshitw> [<integer mshits>]] \
    [<real tlwsha> [<real tlssha>]]
```

Specifies the use of SHAKE constraints, where <mshitw> is the maximum number of solvent SHAKE iterations, and <mshits> is the maximum number of solute SHAKE iterations. If only <mshitw> is specified, the value will also be used for <mshits>. The default maximum number of iterations is 100 for both. <tlwsha> is the solvent SHAKE tolerance in nm, and <tlssha> is the solute SHAKE tolerance in nm. If only <tlwsha> is specified, the value given will also be used for <tlssha>. The default tolerance is 0.001 nm for both.

noshake (solvent | solute)

Disables SHAKE and treats the bonded interaction according to the force field.

Long range interaction corrections

Long range electrostatic interactions are implemented using the smooth particle mesh Ewald technique, for neutral periodic cubic systems in the constant volume ensemble, using pair interaction potentials. Particle-mesh Ewald long range interactions can only be used in molecular dynamics simulations using effective pair potentials, and not in free energy simulations, QMD or QM/MM simulations.

pme [grid <integer ng>] [alpha <real ealpha>] \
 [order <integer morder>] [fft <integer imfft>]\
 [procs <integer nprocs>] [solvent]

Specifies the use of smooth particle-mesh Ewald long range interaction treatment, where ng is the number of grid points per dimension, ealpha is the Ewald coefficient in nm^{-1} , with a default that leads to a tolerance of 10^{-4} at the short range cutoff radius, and morder is order of the Cardinal B-spline interpolation which must be an even number and at least 4 (default value). A platform specific 3D fast Fourier transform is used, if available, when imfft is set to 2. nprocs can be used to define a subset of processors to be used to do the FFT calculations. If solvent is specified, the charge grid will be calculated from the solvent charges only.

```
react [<real dielec default 80.0>]
```

Specifies that a simple reaction field correction is used with a dielectric constant dielec. This is an experimental option that has not been well tested.

Fixing coordinates

Solvent or solute may be fixed using the following keywords.

For solvent the molecule numbers idfirst and idlastmay be specified to be the first and last molecule to which the directive applies. If omitted, the directive applies to all molecules. For solute, the segment numbers idfirst and idlastmay be specified to be the first and last segment to which the directive applies. If omitted, the directive applies to all segments. In addition, the keyword heavy may be specified to apply to all non hydrogen atoms in the solute, or a set of atom names may be specified in which a wildcard character ? may be used. Keyword permanent is used to keep the specification on the restart file for subsequent simulations.

Special options

```
import [<integer impfr default 1> [<integer impto default
impfr> \
        [<integer nftri default 1>]]]
```

Specifies the import of frames impfr to impto with frequency nftri from a trajectory file with extension tri for which energies and forces are to be recalculated. This option only applied to task md energy.

detail

Specifies that moments of inertia and radii of gyration will be part of the recorded properties.

profile

Specifies that execution time profiling data will be part of the recorded properties.

scale <real scaleq>

Specifies that all charges will be scaled by the factro scaleq.

collapse [<real fcoll default 10.0> [segment | z | xy]

Specifies that additional forces directed to the origin of the simulation cell with strength fcoll will be applied to all solute molecules. If z or xy is specified, these forces will only apply in the specified dimension(s).

include fixed

Specifies that energies will be evaluated between fixed atoms. Normally these interactions are excluded from the pairlists.

eqm <real eqm>

Specifies the zero point of energy in QMD simulations.

atomlist

Specifies that pairlists will be atom based. Normally pairlist are charge group based.

Autocorrelation function

For the evaluation of the statistical error of multi-configuration thermodynamic integration free energy results a correlated data analysis is carried out, involving the calculation of the autocorrelation function of the derivative of the Hamiltonian with respect to the control variable \$\lambda &.

```
auto <integer lacf> [fit <integer nfit>] [weight
<real weight>]
```

Controls the calculation of the autocorrelation, where <|acf> is the length of the autocorrelation function, with a default of 1000, <nfit> is the number of functions used in the fit of the autocorrelation function, with a default of 15, and <weight> is the weight factor for the autocorrelation function, with a default value of 0.0.

Print options

Keywords that control print to the output file, with extension out. Print directives may be combined to a single directive.

```
print [topol [nonbond] [solvent] [solute]] \
  [step <integer nfoutp> [extra] [energy]] \
  [stat <integer nfstat>] \
  [energies [<integer nfener>]] \
  [forces [<integer nfforce>]] \
  [matrix] \
  [expect <integer npxpct>] \
  [timing] \
  [pmf [<integer iprpmf>]] \
  [dayout]
```

- Keyword topol specifies printing the topology information, where nonbond refers to the non-bonded interaction parameters, solvent to the solvent bonded parameters, and solute to the solute bonded parameters. If only topol is specified, all topology information will be printed to the output file.
- Keyword step specifies the frequency nfoutp of printing molecular dynamics step information to the output file. If the keyword extra is specified additional energetic data are printed for solvent and solute separately. If the keyword energy is specified, information is printed for all bonded solute interactions. The default for nfoutp is 0. For molecular dynamics simulations this frequency is in time steps, and for multi-configuration thermodynamic integration in λ -steps.

- Keyword stat specifies the frequency <nfstat> of printing statistical information of properties that are calculated during the simulation. For molecular dynamics simulation this frequency is in time steps, for multi-configuration thermodynamic integration in λ -steps.
- Keyword energies specifies the frequency nfener of printing solute bonded energies the output file for energy/import calculations. The default for nfener is 0.
- Keyword forces specifies the frequency nfforc of printing solute forces the output file for energy/import calculations. The default for nfforc is 0.
- Keyword matrix specifies that a solute distance matrix is to be printed.
- Keyword expect is obsolete.
- Keyword timing specifies that timing data is printed.
- Keyword pmf specifies that pmf data is printed every iprpmf steps. Keyword out6 specifies that output is written to standard out in stead of the output file with extension out.
- Keyword dayout is obsolete.

Periodic updates

Following keywords control periodic events during a molecular dynamics or thermodynamic integration simulation. Update directives may be combined to a single directive.

```
update [pairs <integer nfpair default 1>] \
    [long <integer nflong default 1>] \
    [center <integer nfcntr default 0> [zonly | xyonly] \
        [fraction <integer idscb(1:5)>] \
    [motion <integer nfslow default 0>] \
    [analysis <integer nfanal default 0>] \
    [rdf <integer nfrdf default 0> \
    [range <real rrdf>] [bins <integer ngl>] \
}
```

- Keyword pairs specifies the frequency <nfpair> in molecular dynamics steps of updating the pair lists. The default for the frequency is 1. In addition, pair lists are also updated after each step in which recording of the restart or trajectory files is performed. Updating the pair lists includes the redistribution of atoms that changed domain and load balancing, if specified.
- Keyword long specifies the frequency <nflong> in molecular dynamics steps of updating the long range forces. The default frequency is 1. The distinction of short range and long range forces is only made if the long range cutoff radius was specified to be larger than the short range cutoff radius. Updating the long range forces is also done in every molecular dynamics step in which the pair lists are regenerated.
- Keywrod center specifies the frequency <nfcntr> in molecular dynamics steps in which the center of geometry of the solute(s) is translated to the center of the simulation volume. Optional keyword zonly or xyonly can be used to specify that centering will take place in the z-direction or in the xy-plane only. The solute fractions determining the solutes that will be centered are specified by the keyword fraction and the vector <idscb>, with a maximum of 5 entries. This translation is implemented such that it has

no effect on any aspect of the simulation. The default is not to center, i.e. nfcntr is 0. The default fraction used to center solute is 1.

- Keyword motion specifies the frequency <nfslow> in molecular dynamics steps of removing the overall rotational and center of mass translational motion.
- Keyword analysis specifies the frequency <nfanal> in molecular dynamics steps of invoking the analysis module. This option is obsolete.
- Keyword rdf specifies the frequency <nfrdf> in molecular dynamics steps of calculating contributions to the radial distribution functions. The default is 0. The range of the radial distribution functions is given by <rrdf> in nm, with a default of the short range cutoff radius. Note that radial distribution functions are not evaluated beyond the short range cutoff radius. The number of bins in each radial distribution function is given by <ngl>, with a default of 1000. This option is no longer supported. If radial distribution function are to be calculated, a rdi files needs to be available in which the contributions are specified as follows.

Card	Format	Description
I-1	i	Type, 1=solvent-solvent, 2=solvent-solute, 3-solute-solute
I-2	i	Number of the rdf for this contribution
I-3	i	First atom number
I-4	i	Second atom number

Recording

The following keywords control recording data to file. Record directives may be combined to a single directive.

```
record [rest <integer nfrest> [keep]]
                                          \
       [coord <integer nfcoor default 0>] \
       [wcoor <integer nfwcoo default 0>] \
       [scoor <integer nfscoo default 0>] \
       [veloc <integer nfvelo default 0>] \
       [wvelo <integer nfwvel default 0>] \
       [svelo <integer nfsvel default 0>] \
       [force <integer nfvelo default 0>] \
       [wforc <integer nfwvel default 0>] \
       [sforc <integer nfsvel default 0>] \
       [(prop | prop average) <integer nfprop default 0>] \
       [free <integer nffree default 1>] \
       [sync <integer nfsync default 0>] \
       [times <integer nftime default 0>] \
       [acf] [cnv] [fet]
       [binary] [ascii] [ecce] [argos]
```

• Keyword rest specifies the frequency <nfrest> in molecular dynamics steps of rewriting the restart file, with extension rst. For multi-configuration thermodynamic integration simulations the frequency is in steps in \$\lambda\$. The default is not to record. The restart file is used to start or restart simulations. The keyword keep causes all restart

files written to be kept on disk, rather than to be overwritten.

- Keyword coord specifies the frequency <nfcoor> in molecular dynamics steps of writing coordinates to the trajectory file. This directive redefines previous coord, wcoor and scoor directives. The default is not to record.
- Keyword wcoor specifies the frequency <nfcoor> in molecular dynamics steps of writing solvent coordinates to the trajectory file. This keyword takes precedent over coord. This directive redefines previous coord, wcoor and scoor directives. The default is not to record.
- Keyword scoor specifies the frequency <nfscoo> in molecular dynamics steps of writing solute coordinates to the trajectory file. This keyword takes precedent over coord. This directive redefines previous coord, wcoor and scoor directives. The default is not to record.
- Keyword veloc specifies the frequency <nfvelo> in molecular dynamics steps of writing velocities to the trajectory file. This directive redefines previous veloc, wvelo and svelo directives. The default is not to record.
- Keyword wvelo specifies the frequency <nfvelo> in molecular dynamics steps of writing solvent velocities to the trajectory file. This keyword takes precedent over veloc. This directive redefines previous veloc, wvelo and svelo directives. The default is not to record.
- Keyword svelo specifies the frequency <nfsvel> in molecular dynamics steps of writing solute velocities to the trajectory file. This keyword takes precedent over veloc. This directive redefines previous veloc, wvelo and svelo directives. The default is not to record.
- Keyword force specifies the frequency <nfvelo> in molecular dynamics steps of writing forces to the trajectory file. This directive redefines previous vforce, wforc and sforc directives. The default is not to record.
- Keyword wforc specifies the frequency <nfvelo> in molecular dynamics steps of writing solvent forcesto the trajectory file. This keyword takes precedent over force. This directive redefines previous vforce, wforc and sforc directives. The default is not to record.
- Keyword sforc specifies the frequency <nfsvel> in molecular dynamics steps of writing solute forces to the trajectory file. This keyword takes precedent over force. This directive redefines previous vforce, wforc and sforc directives. The default is not to record.
- Keyword prop specifies the frequency <nfprop> in molecular dynamics steps of writing information to the property file, with extension prp. The default is not to record.
- Keyword prop_average specifies the frequency <nfprop> in molecular dynamics steps of writing average information to the property file, with extension prp. The default is not to record.
- Keyword free specifies the frequency <nffree> in multi-configuration thermodynamic integration steps to record data to the free energy data file, with extension gib. The default is 1, i.e. to record at every \$\lambda\$. This option is obsolete. All data are required to do the final analysis.
- Keyword sync specifies the frequency <nfsync> in molecular dynamics steps of writing information to the synchronization file, with extension syn. The default is not to record.

The information written is the simulation time, the wall clock time of the previous MD step, the wall clock time of the previous force evaluation, the total synchronization time, the largest synchronization time and the node on which the largest synchronization time was found. The recording of synchronization times is part of the load balancing algorithm. Since load balancing is only performed when pair-lists are updated, the frequency <nfsync> is correlated with the frequency of pair-list updates <nfpair>. This directive is only needed for analysis of the load balancing performance. For normal use this directive is not used.

- Keyword times specifies the frequency <nfsync> in molecular dynamics steps of writing information to the timings file, with extension tim. The default is not to record. The information written is wall clock time used by each of the processors for the different components in the force evaluation. This directive is only needed for analysis of the wall clock time distribution. For normal use this directive is not used.
- Keywords acf, cnv and fet are obsolete.
- Keywords binary, ascii, ecce and argos are obsolete.

Program control options

```
load [reset]
  ( none |
    size [<real factld>] |
    sizez [<real factld>] | pairs |
    (pairs [<integer ldpair>] size [<real factld>]) )
  [last]
  [minimum]
  [average]
  [combination]
  [iotime]
  [experimental]
```

Determines the type of dynamic load balancing performed, where the default is none. Load balancing option size is resizing cells on a node, and pairs redistributes the cell-cell interactions over nodes. Keyword reset will reset the load balancing read from the restart file. The level of cell resizing can be influenced with *factld*. The cells on the busiest node are resized with a factor

$$\left(1 - factld * \frac{\frac{T_{sync}}{n_p} - t_{sync}^{min}}{t_{wall}}\right)^{\frac{1}{3}}$$

Where T_{sync} is the accumulated synchronization time of all nodes, n_p is the total number of nodes, t_{sync}^{min} is the synchronization time of the busiest node, and t_{walt} is the wall clock time of the molecular dynamics step. For the combined load balancing, ldpair is the number of successive pair redistribution load balancing steps in which the accumulated synchronization time increases, before a resizing load balancing step will be attempted. Load balancing is only performed in molecular dynamics steps in which the pair-list is updated. The default load balancing is equivalent to specifying

load pairs 10 size 0.75

Keyword last specifies that the load balancing is based on the synchronization times of the last step. This is the default. Keyword average specifies that the load balancing is based on the average synchronization times since the last load balancing step. Keyword minimum specifies that the load balancing is based on the minimum synchronization times since the last load balancing step. Keywords combination, iotime and experimental are experimental load balancing options that should not be used in production runs.

(pack | nopack)

Specifies if data are communicated in packed or unpacked form. The default is pack.

procs <integer npx> <integer npy> <integer npz>

Specifies the distribution of the available processors over the three Cartesian dimensions. The default distribution is chosen such that, $\langle npx \rangle^* \langle npy \rangle^* \langle npz \rangle = \langle npz \rangle$ and $\langle npx \rangle$, $\langle npy \rangle$ and $\langle npz \rangle$ are the processors in the x, y and z dimension respectively, and $\langle np \rangle$ is the number of processors allocated for the calculation. Where more than one combination of $\langle npx \rangle$, $\langle npy \rangle$ and $\langle npz \rangle$ are possible, the combination is chosen with the minimum value of $\langle npx \rangle + \langle npy \rangle + \langle npz \rangle$. To change the default setting the following optional input option is provided.

cells <integer nbx> <integer nby> <integer nbz>

Specifies the distribution of cells, where <nbx>, <nby> and <nbz> are the number of cells in x, y and z direction, respectively. The molecular system is decomposed into cells that form the smallest unit for communication of atomic data between nodes. The size of the cells is per default set to the short-range cutoff radius. If long-range cutoff radii are used the cell size is set to half the long-range cutoff radius if it is larger than the short-range cutoff. If the number of cells in a dimension is less than the number of processors in that dimension, the number of cells is set to the number of processors.

extra <integer madbox>

Sets the number of additional cells for which memory is allocated. In rare events the amount of memory set aside per node is insufficient to hold all atomic coordinates assigned to that node. This leads to execution which aborts with the message that mwm or msa is too small. Jobs may be restarted with additional space allocated by where <madbox> is the number of additional cells that are allocated on each node. The default for <madbox> is 6. In some cases <madbox> can be reduced to 4 if memory usage is a concern. Values of 2 or less will almost certainly result in memory shortage.

mwm <integer mwmreq>

Sets the maximum number of solvent molecules <mwmreq> per node, allowing increased memory to be allocated for solvent molecules. This option can be used if execution aborted because mwm was too small.

msa <integer msareq>

Sets the maximum number of solute atoms <msareq> per node, allowing increased memory to be allocated for solute atoms. This option can be used if execution aborted because msa was too small.

mcells <integer mbbreq>

Sets the maximum number of cell pairs <mbbreq> per node, allowing increased memory to be allocated for the cell pair lists. This option can be used if execution aborted because mbbl was too small.

boxmin <real rbox>

Sets the minimum size of a cell. This directive is obsolete. The use of mcells is preferred.

segmentsize <real rsgm>

Sets the maximum size of a segment. This value is used to determine which segments at the boundary of the cutoff radius should be considered in the generation of the pairlists. This value is also determined by the prepare module and written to the restart file. Use of this directive is not needed for simulations that use the current prepare module to generate the restart file.

memory <integer memlim>

Sets a limit <memlim> in kB on the allocated amount of memory used by the molecular dynamics module. Per default all available memory is allocated. Use of this command is required for QM/MM simulations only.

expert

Enables the use of certain combinations of features that are considered unsafe. This directive should not be used for production runs.

develop <integer idevel>

Enables the use of certain development options specified by the integer idevel. This option is for development purposes only, and should not be used for production runs.

control <integer icntrl>

Enables the use of certain development options specified by the integer icntrl. This option is for development purposes only, and should not be used for production runs.

numerical

Writes out analytical and finite difference forces for test purposes.

server <string servername> <integer serverport>

Allows monitoring over a socket connection to the specified port on the named server of basic data as a simulation is running.

For development purposes debug information can be written to the debug file with extension dbg with

debug <integer idebug>

where *idebug* specifies the type of debug information being written.

For testing purposes test information can be written to the test file with extension tst with

test <integer itest>

where *itest* specifies the number of steps test information is written.

On some platforms prefetching of data can improve the efficiency. This feature can be turned on using

prefetch [<integer nbget>]

where *nbget* is the number of outstanding communication operations.

Application of periodic boundary conditions for the evaluation of forces can be controlled with

pbc (atom | residue | molecule)

This option rarely needs to be used.

Autocorrelation functions for error analysis are controlled using

auto [fit <integer iapprx> | weight <real weight>]

This option is disabled in the current release.

Membrane system equilibration can be made more efficient using

membrane [rotations]

Constraining the center of mass of solute molecules in the xy plane is accomplished using

scmxy [<integer icmopt default 1>]

where *icmopt* determines if the constraint is mass weighted (2).

Radius of gyration calculations are enabled using

radius_gyration

Calculations of diffusion coefficients is enabled using

diffusion

This option is disabled in the current release.

```
comlim ( on | off )
```

is disabled

To limit the size of recoding files, new files are opened every *nfnewf* md steps using batch <integer nfnewf>

Release65:Analysis

__NOTITLE__

Analysis

The analysis module is used to analyze molecular trajectories generated by the NWChem molecular dynamics module, or partial charges generated by the NWChem electrostatic potential fit module. This module should not de run in parallel mode.

Directives for the analysis module are read from an input deck,

```
analysis
...
end
```

The analysis is performed as post-analysis of trajectory files through using the task directive

task analysis

or

task analyze

System specification

```
system <string systemid>_<string calcid>
```

where the strings systemid and calcid are user defined names for the chemical system and the type of calculation to ber performed, respectively. These names are used to derive the filenames used for the calculation. The topoly file used will be systemid.top, while all other files are named systemid_calcid.ext.

Reference coordinates

Most analyses require a set of reference coordinates. These coordinates are read from a NWChem restart file by the directive,

reference <string filename>

where filename is the name of an existing restart file. This input directive is required.

File specification

The trajectory file(s) to be analyzed are specified with

```
file <string filename> [<integer firstfile> <integer
lastfile>]
```

where filename is an existing trj trajectory file. If firstfile and lastfile are specified, the specified filename needs to have a ? wild card character that will be substituted by the 3-character integer number from firstfile to lastfile, and the analysis will be performed on the series of files. For example,

file tr_md?.trj 3 6

will instruct the analysis to be performed on files tr_md003.trj, tr_md004.trj, tr_md005.trj and tr md006.trj.

From the specified files the subset of frames to be analyzed is specified by

For example, to analyze the first 100 frames from the specified trajectory files, use

frames 100

To analyze every 10-th frame between frames 200 and 400 recorded on the specified trajectory files, use

frames 200 400 10

A time offset can be specified with

time <real timoff>

Solute coordinates of the reference set and ech subsequent frame read from a trajectory file are translated to have the center of geometry of the specified solute molecule at the center of the simulation box. After this translation all molecules are folded back into the box according to the periodic boundary conditions. The directive for this operation is

center <integer imol> [<integer jmol default imol>]

Coordinates of each frame read from a trajectory file can be rotated using

rotate (off \boldsymbol{x}

х

If center was defined, rotation takes place after the system has been centered. The rotate directives only apply to frames read from the trajectory files, and not to the reference coordinates. Up to 100 rotate directives can be specified, which will be carried out in the order in which they appear in the input deck. rotate off cancels all previously defined rotate directives.

х

To perform a hydrogen bond analysis:

х

x] \

[solvent [<integer numwhb>]]

Selection

Analyses can be applied to a selection of solute atoms and solvent molecules. The selection is determined by

```
select ( [ super ] [ { <string atomlist> } ] |
      solvent <real range> | save <string filename> | read
<string filename> )
```

where {atomlist} is the set of atom names selected from the specified residues. By default all solute atoms are selected. When keyword super is specified the selecion applies to the superimposition option.

The selected atoms are specified by the string atomlist which takes the form

[{isgm [- jsgm] [,]} [:] [{aname[,]}]

where isgm and jsgm are the first and last residue numbers, and aname is an atom name. In the atomname a question mark may be used as a wildcard character.

For example, all protein backbone atoms are selected by

select _N,_CA,_C

To select the backbone atoms in residues 20 to 80 and 90 to 100 only, use

```
select 20-80,90-100:_N,_CA,_C
```

This selection is reset to apply to all atoms after each file directive.

Solvent molecules within range nm from any selected solute atom are selected by

select solvent <real range>

After solvent selection, the solute atom selection is reset to being all selected.

The current selection can be saved to, or read from a file using the save and read keywords, respectively.

Some analysis are performed on groups of atoms. These groups of atoms are defined by

```
define <integer igroup> [<real rsel>] [solvent] {
  <string atomlist> }
```

The string atom in this definitions again takes the form

```
[{isgm [ - jsgm ] [,]} [:] [{aname[,]}]
```

where isgm and jsgm are the first and last residue numbers, and aname is an atom name. In the atomname a question mark may be used as a wildcard character.

Multiple define directive can be used to define a single set of atoms.

Coordinate analysis

To analyze the root mean square deviation from the specified reference coordinates:

rmsd

To analyze protein $\phi = \$ and backbone hydrogen bonding:

ramachandran

To define a distance:

distance <integer ibond> <string atomi> <string atomj>

To define an angle:

angle <integer iangle> <string atomi> <string atomj>
<string atomk>

To define a torsion:

torsion <integer itorsion> <string atomi> <string
atomj> \

<string atomk> <string atoml>

To define a vector:

vector <integer ivector> <string atomi> <string atomj>

The atom string in these definitions takes the form

<integer segment>:<string atomname> w<integer molecule>:<string atomname>

for solute and solvent atom specification, respectively.

To define charge distribution in z-direction:

charge distribution <integer bins>

Analyses on atoms in a predefined group are specified by

group [<integer igroup> [periodic <integer ipbc>] \

(local [<real rsel default 0.0>] [<real rval default rsel>]

<string function>)

where igroup specifies the group of atoms defined with a define directive. Keyword periodic can be used to specify the periodicity, ipbc=1 for periodicity in z, ipbc=2 for periodicity in x and y, and ipbc=3 for periodicity in x, y and z. Currently the only option is local which prints all selected solute atom with a distance between rsel and rval from the atoms defined in igroup. The actual analysis is done by the scan deirective. A formatted report is printed from group analyses using report <string filename> local

Analyses on pairs of atoms in predefined groups are specified by

where *igroup* and *jgroup* are groups of atoms defined with a define directive. Keyword periodic specifies that periodic boundary conditions need to be applied in *ipbc* dimensions. The type of analysis is define by *function*, *value1* and *value2*. If *filename* is specified, the analysis is applied to the reference coordinates and written to the specified file. If no filename is given, the analysis is applied to the specified trajectory and performed as part of the scan directive. Implemented analyses defined by <string function> [<real value1> [<real value2>]] include

- distance to calculate the distance between the centers of geometry of the two specified groups of atoms, and
- distances to calculate all atomic distances between atoms in the specified groups that lie between *value1* and *value2*.

Coordinate histograms are specified by

```
histogram <integer idef> [<integer length>] zcoordinate
<string filename>
```

where *idef* is the atom group definition number, *length* is the size of the histogram, zcoordinate is the currently only histogram option, and \$filename\$ is the filname to which the histogram is written.

Order parameters are evalated using

```
order <integer isel> <integer jsel> <string atomi>
<string atomj>
```

This is an experimental feature.

To write the average coordinates of a trajectory

average [super] <string filename>

To perform the coordinate analysis:

scan [super] <string filename>

which will create, depending on the specified analysis options files filename.rms and filename.ana. After the scan directive previously defined coordinate analysis options are all reset. Optional keyword super specifies that frames read from the trajectory file(s) are superimposed to the reference structure before the analysis is performed.

Essential dynamics analysis

Essential dynamics analysis is performed by

essential

This can be followed by one or more

project <integer vector> <string filename>

to project the trajectory onto the specified vector. This will create files filename with extensions frm or trj, val, vec, _min.pdb and _max.pdb, with the projected trajectory, the projection value, the eigenvector, and the minimum and maximum projection structure.

For example, an essential dynamics analysis with projection onto the first vector generating files firstvec.{trj, val, vec, _min.pdb, _max.pdb} is generated by

```
essential
project 1 firstvec
```

Trajectory format conversion

To write a single frame in PDB or XYZ format, use

```
write [<integer number default 1>] [super] [solute] <string
filename>
```

To copy the selected frames from the specified trejctory file(s), onto a new file, use

copy [solute] [rotate <real tangle>] <string filename>

To superimpose the selected atoms for each specified frame to the reference coordinates before copying onto a new file, use

super [solute] [rotate <real tangle>] <string filename>

The rotate directive specifies that the structure will make a full ratation every tangle ps. This directive only has effect when writing povray files.

The format of the new file is determined from the extension, which can be one of

amb	AMBER formatted trajectory file (obsolete)
arc	DISCOVER archive file
bam	AMBER unformatted trajectory file
crd	AMBER formatted trajectory file
dcd	CHARMM formatted trajectory file
esp	gOpenMol formatted electrostatic potential files
frm	ecce frames file (obsolete)
pov	povray input files
trj	NWChem trajectory file

If no extension is specified, a trj formatted file will be written.

A special tag can be added to frm and pov formatted files using

label <integer itag> <string tag> [<real rval default
1.0>] \\
 [<integer iatag> [<integer jatag default iatag>] [

```
<real rtag default 0.0> ] ]
[ <string anam> ]
```

where tag number *itag* is set to the string *tag* for all atoms anam within a distance *rtag* from segments *iatag* through *jatag*. A question mark can be used in anam as a wild card character.

Atom rendering is specified using

```
render ( cpk | stick ) [ <real rval default 1.0> ] \\
      [ <integer iatag> [ <integer jatag default iatag> ]
[ <real rtag default 0.0> ] ]
      [ <string anam> ]
```

for all atoms anam within a distance \$rtag\$ from segments \$iatag\$ through \$jatag\$, and a scaling factor of \$rval\$. A question mark can be used in anam as a wild card character.

Atom color is specified using

```
color ( <string color> | atom ) \\
    [ <integer iatag> [ <integer jatag default iatag> ] [
    <real rtag default 0.0> ] ]
    [ <string anam> ]
```

for all atoms anam within a distance *rtag* from segments *iatag* through *jatag*. A question mark can be used in anam as a wild card character.

For example, to display all carbon atoms in segments 34 through 45 in green and rendered cpk in povray files can be specified with

```
render cpk 34 45 _C??
color green 34 45 _C??
```

Coordinates written to a pov file can be scaled using

```
scale <real factor>
```

A zero or negative scaling factor will scale the coordinates to lie within [-1,1] in all dimensions.

The cpk rendering in povray files can be scaled by

cpk <real factor default 1.0>

The stick rendering in povray files can be scaled by

stick <real factor default 1.0>

The initial sequence number of esp related files is defined by

index <integer index default 1>

A sequence of trajectory files with unequal lengths can be converted to files with all \$nclean\$ frames using

clean <integer nclean>

Electrostatic potentials

A file in plt format of the electrostatic potential resulting from partial charges generated by the ESP module is generated by the command

```
esp [ <integer spacing default 10> ] \
    [ <real rcut default 1.0> ] [periodic [<integer iper
default 3>]] \
    [ <string xfile> [ <string pltfile> ] ]
```

The input coordinates are taken from the xyzq file that can be generated from a rst by the prepare module. Parameter spacing specifies the number of gridpoints per nm, rcut specifies extent of the charge grid beyond the molecule. Periodic boundaries will be used if periodic is specified. If iper is set to 2, periodic boundary conditions are applied in x and y dimensions only. If periodic is specified, a negative value of rcut will extend the grid in the periodic dimensions by abs(rcut), otherwise this value will be ignored in the periodic dimensions. The resulting plt formatted file pltfile can be viewed with the gOpenMol program. The resulting electrostatic potential grid is in units of $kJmol^{-1}e^{-1}$. If no files are specified, only the parameters are set. This analysis applies to solute(s) only.

The electrostatic potential at specific point are evaluated using

esp_points [<string filpin> [<string filhol> [<string filpou> [<string filavg>]]]]

Hybrid Approaches

Release65:COSMO Solvation Model

_NOTITLE__

COSMO Solvation Model

COSMO is the continuum solvation `COnductor-like Screening MOdel' of A. Klamt and G. Schüürmann to describe dielectric screening effects in solvents^[1]. This model has been enhanced by D.M. York and M. Karplus^[2] to create a smooth potential energy surface. The latter facilitates geometry optimization and dynamics and the implementation has been adapted to take advantage of those ideas.

The NWChem COSMO module implements algorithm for calculation of the energy for the following methods:

- 1. Restricted Hartree-Fock (RHF),
- 2. Restricted open-shell Hartree-Fock (ROHF),
- 3. Restricted Kohn-Sham DFT (DFT),
- 4. Unrestricted Kohn-Sham DFT (ODFT),

by determining the solvent reaction field self-consistently with the solute charge distribution from the respective methods. Note that COSMO for unrestricted Hartree-Fock (UHF) method can also be performed by invoking the DFT module with appropriate keywords.

Correlation energy of solvent molecules may also be evaluated at

- 1. MP2,
- 2. CCSD,
- 3. CCSD+T(CCSD),
- 4. CCSD(T),

levels of theory. It is cautioned, however, that these correlated COSMO calculations determine the solvent reaction field using the HF charge distribution of the solute rather than the charge distribution of the correlation theory and are not entirely self consistent in that respect. In other words, these calculations assume that the correlation effect and solvation effect are largely additive, and the combination effect thereof is neglected. COSMO for MCSCF has not been implemented yet.

In the current implementation the code calculates the gas-phase energy of the system followed by the solution-phase energy, and returns the electrostatic contribution to the solvation free energy. At the present gradients are calculated analytically, but frequencies are calculated by finite difference of the gradients. Known problems include that the code does not work with spherical basis functions. The code does not calculate the non-electrostatic contributions to the free energy, except for the cavitation/dispersion contribution to the solvation free energy, which is computed and printed. It should be noted that one must in general take into account the standard state correction besides the electrostatic and cavitation/dispersion contribution to the solvation free energy, when a comparison to experimental data is made.

Invoking the COSMO solvation model is done by specifying the input COSMO input block with the input options as:

```
cosmo
  [off]
  [dielec <real dielec default 78.4>]
  [parameters <filename>]
  [radius <real atom1>
           <real atom2>
      . . .
           <real atomN>]
  [iscren <integer iscren default 0>]
  [minbem <integer minbem default 2>]
  [ificos <integer ificos default 0>]
          <integer lineq default 1>]
  [lineq
  [zeta <real zeta default 0.98>]
  [gamma s <real gammas default 1.0>]
  [sw tol <real swtol default 1.0e-4>]
  [do_gasphase <logical do_gasphase default True>]
end
```

followed by the task directive specifying the wavefunction and type of calculation, e.g., "task scf energy", "task mp2 energy", "task dft optimize", etc.

"off' can be used to turn off COSMO in a compound (multiple task) run. By default, once the COSMO solvation model has been defined it will be used in subsequent calculations. Add the keyword "off" if COSMO is not needed in subsequent calculations.

"Dielec" is the value of the dielectric constant of the medium, with a default value of 78.4 (the dielectric constant for water).

"parameters" specifies COSMO radii parameters file that stores custom setting for COSMO parameters. The format for such file consists of the atom or element name followed by the radii. The program will first attempt to match based on atom name and only then the element name. Otherwise radius will be set based on default parameters. The file has to present in one of the three location (in the order of preference) - directory specified by the environmental variable NWCHEM_COSMO_LIBRARY, permanent directory, and run directory. This directive is replacing previous facility of loading COSMO radii parameters through "set cosmo:map cosmo.par" directive. See example at the end of this section.

"Radius" is an array that specifies the radius of the spheres associated with each atom and that make up the molecule-shaped cavity. These values will override default radii setting including those specified in the COSMO parameter file (if any) Default values are Van der Waals radii. Values are in units of angstroms. The codes uses the following Van der Waals radii by default:

Default radii provided by Andreas Klamt (Cosmologic) vdw radii: 1.17 (+/- 0.02) * Bondi radius^[3] optimal vdw radii for H, C, N, O, F, S, Cl, Br, I^[4] for heavy elements: 1.17*1.9

```
data (vander(i),i=1,102)
1 / 1.300,1.638,1.404,1.053,2.0475,2.00,
2
    1.830, 1.720, 1.720, 1.8018, 1.755, 1.638,
3
    1.404,2.457,2.106,2.160,2.05,2.223,
4
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223,
5
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223,
6
    2.223, 2.223, 2.223, 2.223, 2.160, 2.223,
7
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223,
8
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223,
9
    2.223, 2.223, 2.223, 2.223, 2.320, 2.223,
1
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223,
2
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223,
3
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223,
4
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223,
5
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223,
6
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223,
7
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223,
7
    2.223, 2.223, 2.223, 2.223, 2.223, 2.223/
```

For examples see Stefanovich et al.^[5] and Barone et al.^[6]

"Rsolv" is no longer used.

"Iscren' is a flag to define the dielectric charge scaling option. "iscren 1" implies the original scaling from Klamt and Schüürmann, mainly " $(\epsilon - 1)/(\epsilon + 1/2)$ ", where ϵ is the dielectric constant. "iscren 0" implies the modified scaling suggested by Stefanovich and Truong^[7], mainly " $(\epsilon - 1)/\epsilon$ ". Default is to use the modified scaling. For high dielectric the difference between the scaling is not significant.

The next two parameters define the tesselation of the unit sphere. The approach still follows the original proposal by Klamt and Schüürmann to some degree. Basically a tesselation is generated from "minbem" refining passes starting from either an octahedron or an icosahedron. Each level of refinement partitions the triangles of the current tesselation into four triangles. This procedure is repeated recursively until the desired granularity of the tesselation is reached. The induced point charges from the polarization of the medium are assigned to the centers of the tesselation. The default value is "minbem 2". The flag +ificos+ serves to select the original tesselation, "ificos 0" for an octahedron (default) and "ificos 1" for an icoshedron. Starting from an icosahedron yields a somewhat finer tesselation that converges somewhat faster. Solvation energies are not really sensitive to this choice for sufficiently fine tesselations. The old "maxbem" directive is no longer used.

The "lineq" parameter serves to select the numerical algorithm to solve the linear equations yielding the effective charges that represent the polarization of the medium. "lineq 0" selects an iterative method (default), "lineq 1" selects a dense matrix linear equation solver. For large molecules where the number of effective charges is large, the codes selects the iterative method.

"zeta" sets the width of the Gaussian charge distributions that were suggested by York and Karplus to avoid singularities when two surface charges coincide. The default value is "zeta 0.98" this value was chosen to ensure that the results of the current implementation are as close as possible to those of the original Klamt and Schuurmann based implementation. "gamma_s" modifies the width of the smooth switching function that eliminates surface charges when their positions move into the sphere of a neighboring atom. "gamma_s 0.0" leads to a heavyside or abrupt switching function, whereas "gamma_s 1.0" maximizes the width of the switching function. The default value is "gamma_s 1.0".

"sw_tol" specifies the cutoff of the switching function below which a surface charge at a particular point is eliminated. The values of the switching function lie in the domain from 0 to 1. This value should not be set too small as that leads to instabilities in the linear system solvers. The default value is "sw_tol 1.0e-4".

"do_gasphase" is a flag to control whether the calculation of the solvation energy is preceded by a gas phase calculation. The default is to always perform a gas phase calculation first and then calculate the solvation starting from the converged gas phase electron density. However, in geometry optimizations this approach can double the cost. In such a case setting "do_gasphase false" suppresses the gas phase calculations and only the solvated system calculations are performed. This option needs to be used with care as in some cases starting the COSMO solvation from an unconverged electron density can generate unphysical charges that lock the calculation into strange electron distributions.

The following example is for a water molecule in `water', using the $HF/6-31G^{**}$ level of theory:

```
start
echo
title "h2o"
geometry
0
                     .0000000000
                                           .0000000000
                                                               -.0486020332
h
                     .7545655371
                                           .0000000000
                                                                .5243010666
h
                    -.7545655371
                                           .0000000000
                                                                .5243010666
end
basis segment cartesian
o library 6-31g**
h library 6-31g**
end
cosmo
 dielec 78.0
 radius 1.40
        1.16
        1.16
lineq
        0
end
task scf energy
```

Alternatively, instead of listing COSMO radii parameters in the input, the former can be loaded using an external file through the "parameters" directive

```
start
echo
title "h2o"
geometry
ow .000000000 .00000000 -.0486020332
```

```
.0000000000
hw
                      .7545655371
                                                                 .5243010666
h
                     -.7545655371
                                           .0000000000
                                                                .5243010666
end
basis segment cartesian
* library 6-31g**
end
cosmo
dielec 78.0
lineg 0
parameters water.par
end
task scf energy
```

where "water.par" may the following form:

0 1.40 H 1.16

This will set radii of all oxygen atoms to 1.4 and all hydrogen atoms to 1.16. More fine grained control may be achieved using specific atom names. For example, the following parameter file

0 1.40 H 1.16 HW 1.06

will set a different radii of 1.06 to hydrogen atoms named HW. Note that, as per general rule in NWChem, all names are case insensitive.

and placed in one of the these locations - directory specified by the environmental variable NWCHEM_COSMO_LIBRARY, permanent directory, or run directory.

References

- [1] <refbase>514</refbase>
- [2] <refbase>520</refbase>
- [3] <refbase>515</refbase>
- [4] <refbase>516</refbase>
- [5] <refbase>517</refbase>
- [6] <refbase>518</refbase>
- [7] <refbase>517</refbase>

Release65:SMD Model

__NOTITLE___NOTITLE__

SMD (Solvation Model Based on Density) Model

SMD denotes "solvation model based on density" and it is described in detail in the following paper:

Marenich, A. V.; Cramer, C. J.; Truhlar, D. G. Universal solvation model based on solute electron density and on a continuum model of the solvent defined by the bulk dielectric constant and atomic surface tensions. J. Phys. Chem. B 2009, 113, 6378-6396; http://dx. doi.org/10.1021/jp810292n.

The SMD model is a universal continuum solvation model where "universal" denotes its applicability to any charged or uncharged solute in any solvent or liquid medium for which a few key descriptors are known. The word "continuum" denotes that the solvent is not represented explicitly as a collection of discrete solvent molecules but rather as a dielectric medium with surface tensions at the solute-solvent interface.

SMD directly calculates the free energy of solvation of an ideal solvation process that occurs at fixed concentration (for example, from an ideal gas at a concentration of 1 mol/L to an ideal solution at a liquid-phase concentration of 1 mol/L) at 298 K, but this may converted by standard thermodynamic formulas to a standard-state free energy of solvation, which is defined as the transfer of molecules from an ideal gas at 1 bar to an ideal 1 molar solution.

The SMD model separates the fixed-concentration free energy of solvation into two components. The first component is the bulk-electrostatic contribution arising from a self-consistent reaction field (SCRF) treatment. The SCRF treatment involves an integration of the nonhomogeneous-dielectric Poisson equation for bulk electrostatics in terms of the COSMO model of Klamt and Schüürmann with the modified COSMO scaling factor suggested by Stefanovich and Truong and by using the SMD intrinsic atomic Coulomb radii. These radii have been optimized for H, C, N, O, F, Si, P, S, Cl, and Br. For any other atom the current implementation of the SMD model uses scaled values of the van der Waals radii of Mantina et al.

Mantina, M.; Valero, R.; Cramer, C. J.; Truhlar, D. G. "Atomic Radii of the Elements." In CRC Handbook of Chemistry and Physics, 91st Edition, 2010-2011; Haynes, W. M., Ed.; CRC Press: Boca Raton, FL, 2010; pp 9-49 – 9-50.

The scaling factor equals 1.52 for group 17 elements heavier than Br (i.e., for I and At) and 1.18 for all other elements for which there are no optimized SMD radii.

The second contribution to the fixed-concentration free energy of solvation is the contribution arising from short-range interactions between the solute and solvent molecules This in the first solvation shell. contribution is called the cavity-dispersion-solvent-structure (CDS) term, and it is a sum of terms that are proportional (with geometry-dependent proportionality constants called atomic surface tensions) to the solvent-accessible surface areas (SASAs) of the individual atoms of the solute.

At the moment the SMD model is available in NWChem only with the DFT block

The SMD input options are as follows:

```
do_cosmo_smd (logical input)
.true. (perform a ground-state SMD calculation) or
.false. (default)
solvent (keyword)
```

a solvent keyword from a list of available SMD solvent names below:

Keyword	Name
h2o	water (default)
water	water (default)
acetacid	acetic acid
acetone	acetone
acetntrl	acetonitrile
acetphen	acetophenone
aniline	aniline
anisole	anisole
benzaldh	benzaldehyde
benzene	benzene
benzntrl	benzonitrile
benzylcl	benzyl chloride
brisobut	1-bromo-2-methylpropane
brbenzen	bromobenzene
brethane	bromoethane
bromform	bromoform
broctane	1-bromooctane
brpentan	1-bromopentane
brpropa2	2-bromopropane
brpropan	1-bromopropane
butanal	butanal
butacid	butanoic acid
butanol	1-butanol
butanol2	2-butanol
butanone	butanone
butantrl	butanonitrile
butile	butyl acetate
nba	butylamine
nbutbenz	n-butylbenzene
sbutbenz	sec-butylbenzene
tbutbenz	tert-butylbenzene

cs2	carbon disulfide
carbntet	carbon tetrachloride
clbenzen	chlorobenzene
secbutcl	sec-butyl chloride
chcl3	chloroform
clhexane	1-chlorohexane
clpentan	1-chloropentane
clpropan	1-chloropropane
ocltolue	o-chlorotoluene
m-cresol	m-cresol
o-cresol	o-cresol
cychexan	cyclohexane
cychexon	cyclohexanone
cycpentn	cyclopentane
cycpntol	cyclopentanol
cycpnton	cyclopentanone
declncis	cis-decalin
declntra	trans-decalin
declnmix	decalin (cis/trans mixture)
decane	n-decane
decanol	1-decanol
edb12	1,2-dibromoethane
dibrmetn	dibromomethane
butyleth	dibutyl ether
odiclbnz	o-dichlorobenzene
edc12	1,2-dichloroethane
c12dce	cis-dichloroethylene
t12dce	trans-dichloroethylene
dcm	dichloromethane
ether	diethyl ether
et2s	diethyl sulfide
dietamin	diethylamine
mi	diiodomethane
dipe	diisopropyl ether
dmds	dimethyl disulfide
dmso	dimethyl sulfoxide
dma	N,N-dimethylacetamide
cisdmchx	cis-1,2-dimethylcyclohexane
dmf	N,N-dimethylformamide

dmepen24	2,4-dimethylpentane
dmepyr24	2,4-dimethylpyridine
dmepyr26	2,6-dimethylpyridine
dioxane	1,4-dioxane
phoph	diphenyl ether
dproamin	dipropylamine
dodecan	n-dodecane
meg	1,2-ethanediol
etsh	ethanethiol
ethanol	ethanol
etoac	ethyl acetate
etome	ethyl formate
eb	ethylbenzene
phenetol	ethyl phenyl ether
c6h5f	fluorobenzene
foctane	1-fluorooctane
formamid	formamide
formacid	formic acid
heptane	n-heptane
heptanol	1-heptanol
heptnon2	2-heptanone
heptnon4	4-heptanone
hexadecn	n-hexadecane
hexane	n-hexane
hexnacid	hexanoic acid
hexanol	1-hexanol
hexanon2	2-hexanone
hexene	1-hexene
hexyne	1-hexyne
c6h5i	iodobenzene
iobutane	1-iodobutane
c2h5i	iodoethane
iohexdec	1-iodohexadecane
ch3i	iodomethane
iopentan	1-iodopentane
iopropan	1-iodopropane
cumene	isopropylbenzene
p-cymene	p-isopropyltoluene
mesityln	mesitylene

methanol	methanol
egme	2-methoxyethanol
meacetat	methyl acetate
mebnzate	methyl benzoate
mebutate	methyl butanoate
meformat	methyl formate
mibk	4-methyl-2-pentanone
mepropyl	methyl propanoate
isobutol	2-methyl-1-propanol
terbutol	2-methyl-2-propanol
nmeaniln	N-methylaniline
mecychex	methylcyclohexane
nmfmixtr	N-methylformamide (E/Z mixture)
isohexan	2-methylpentane
mepyrid2	2-methylpyridine
mepyrid3	3-methylpyridine
mepyrid4	4-methylpyridine
c6h5no2	nitrobenzene
c2h5no2	nitroethane
ch3no2	nitromethane
ntrprop1	1-nitropropane
ntrprop2	2-nitropropane
ontrtolu	o-nitrotoluene
nonane	n-nonane
nonanol	1-nonanol
nonanone	5-nonanone
octane	n-octane
octanol	1-octanol
octanon2	2-octanone
pentdecn	n-pentadecane
pentanal	pentanal
npentane	n-pentane
pentacid	pentanoic acid
pentanol	1-pentanol
pentnon2	2-pentanone
pentnon3	3-pentanone
pentene	1-pentene
e2penten	E-2-pentene
pentacet	pentyl acetate

pentamin	pentylamine
pfb	perfluorobenzene
benzalcl	phenylmethanol
propanal	propanal
propacid	propanoic acid
propanol	1-propanol
propnol2	2-propanol
propntrl	propanonitrile
propenol	2-propen-1-ol
propacet	propyl acetate
propamin	propylamine
pyridine	pyridine
c2cl4	tetrachloroethene
thf	tetrahydrofuran
sulfolan	tetrahydrothiophene-S,S-dioxide
tetralin	tetralin
thiophen	thiophene
phsh	thiophenol
toluene	toluene
tbp	tributyl phosphate
tca111	1,1,1-trichloroethane
tca112	1,1,2-trichloroethane
tce	trichloroethene
et3n	triethylamine
tfe222	2,2,2-trifluoroethanol
tmben124	1,2,4-trimethylbenzene
isoctane	2,2,4-trimethylpentane
undecane	n-undecane
m-xylene	m-xylene
o-xylene	o-xylene
p-xylene	p-xylene
xylenemx	xylene (mixture)

When a solvent is specified by name, the descriptors for the solvent are based on the Minnesota Solvent Descriptor Database:

Winget, P.; Dolney, D. M.; Giesen, D. J.; Cramer, C. J.; Truhlar, D. G. Minnesota Solvent Descriptor Database. University of Minnesota: Minneapolis, MN, 2010. http://comp.chem.umn.edu/solvation/mnsddb.pdf

The user can specify a solvent that is not on the list by omitting the solvent keyword and instead introducing user-provided values for the following solvent descriptors:

```
dielec (real input)
dielectric constant at 298 K
sola (real input)
Abraham's hydrogen bond acidity
solb (real input)
Abraham's hydrogen bond basicity
solc (real input)
aromaticity as a fraction of non-hydrogenic solvent atoms that are
aromatic carbon atoms
solg (real input)
macroscopic surface tension of the solvent at an air/solvent interface
at 298 K in units of cal mol-1 Å-2 (note that 1 dyne/cm = 1.43932 cal
mol-1 Å-2)
solh (real input)
electronegative halogenicity as the fraction of non-hydrogenic solvent
atoms that are F, Cl, or Br
soln (real input)
index of refraction at optical frequencies at 293 K
An example of an SMD input file is as follows:
echo
title 'SMD/M06-2X/6-31G(d) solvation free energy for CF3C00- in water'
start
charge -1
geometry nocenter
С
   0.512211 0.000000 -0.012117
C -1.061796 0.000000 -0.036672
0 -1.547400 1.150225 -0.006609
0 -1.547182 -1.150320 -0.006608
    1.061911 1.087605 -0.610341
F
    1.061963 -1.086426 -0.612313
F
    0.993255 -0.001122 1.266928
F
symmetry c1
end
basis
* library 6-31G*
end
dft
XC m06-2x
end
cosmo
do_cosmo_smd true
solvent water
end
```

task dft energy

Release65:VEM Model

__NOTITLE___NOTITLE__

VEM (Vertical Excitation or Emission) Model

The VEM is a model for calculating the vertical excitation (absorption) or vertical emission (fluorescence) energy in solution according to a two-time-scale model of solvent polarization. The model is described in

Marenich, A. V.; Cramer, C. J.; Truhlar, D. G.; Guido, C. A.; Mennucci, B.; Scalmani, G.; Frisch, M. J. Practical computation of electronic excitation in solution: vertical excitation model. Chem. Science 2011, 2, 2143-2161; http://dx.doi.org/10.1039/C1SC00313E

The current implementation is based on the VEM(d,RD) algorithm as described in the above paper. The method is available only at the TDDFT level of theory, including both full-linear response TDDFT (sometimes called LR-TDDFT or regular TDDFT) and the Tamm-Dancoff approximation, TDDFT-TDA (sometimes just called TDA). The configuration interaction singles (CIS) wave function method can also be used along with VEM by considering CIS to be a special case of TDDFT-TDA.

The abbreviation VEM originally referred to the vertical excitation model of

Li, J.; Cramer, C. J.; Truhlar, D. G. Two-response-time model based on CM2/INDO/S2 electrostatic potentials for the dielectric polarization component of solvatochromic shifts on vertical excitation energies. Int. J. Quantum Chem. 2000, 77, 264-280; DOI: 10.1002/(SICI)1097-461X(2000)77:1<264::AID-QUA24>3.0.CO;2-J^[1], however, the current implementation of VEM extends to both excitation and emission calculations in solution, and the E in VEM now stands for excitation/emission. Note that the current version of VEM, which is based on the Marenich et al. reference given above, does not reduce to the original VEM of Li et al., but is improved as described in the Marenich et al. paper.

The VEM model is based on a nonequilibrium dielectric-continuum approach in terms of two-time-scale solvent response. The solvent's bulk-electrostatic polarization is described by using the reaction field partitioned into slow and fast components, and only the fast component is self-consistently (iteratively) equilibrated with the charge density of the solute molecule in its final state. During the VEM calculation, the slow component is kept in equilibrium with the initial state's solute charge density but not with the final state's one. In the case of vertical absorption the initial state is the ground electronic state of the solute molecule in solution and the final state is an excited electronic state in solution (and vice versa in the case of an emission spectrum). Both the ground- and excited-state calculations involve an integration of the nonhomogeneous-dielectric Poisson equation for bulk electrostatics in terms of the COSMO model as implemented in NWChem with the modified COSMO scaling factor ("iscren 0") and by using the SMD intrinsic atomic Coulomb radii (by default; see the section of the manual describing SMD). The excited-state electron density is calculated using the Z-Vector "relaxed density" approach.

The VEM excitation or emission energy includes only a bulk-electrostatic contribution without any cavity-dispersion-solvent-structure (CDS) contributions (such contributions are used in SMD ground-state calculations as described in the SMD section of this manual, but
are not used in VEM calculations). When one considers solvatochromic shifts, the main contributions beyond bulk electrostatics are solute-solvent dispersion interactions, hydrogen bonding (the latter is most important in protic solvents), and perhaps charge transfer between the solute and the solvent. To explicitly account for solute-solvent charge transfer and hydrogen bonding, the user can run a VEM calculation on a supersolute that involves a solute-solvent molecular cluster with one or a few solvent molecules added explicitly to a bare solute. The solute-solvent dispersion contribution to the solvatochromic shift, if desired, can be estimated by the solvation model with state-specific polarizability (SMSSP) described in:

Marenich, A. V.; Cramer, C. J.; Truhlar, D. G. Uniform treatment of solute-solvent dispersion in the ground and excited electronic states of the solute based on a solvation model with state-specific polarizability. J. Chem. Theory Comput. 2013, 9, 3649-3659; http://dx.doi. org/10.1021/ct400329u

In this case, the user needs to provide values of ground- and excited-state spherically averaged molecular polarizabilities of the solvent.

The VEM-specific input options are as follows:

```
do_cosmo_vem (integer input))
0 (do not do any VEM calculation even if the task tddft gradient line
is present; default)
1 (do a nonequilibrium VEM excitation energy calculation; in this case
the task tddft gradient line should be present, too)
2 (do an equilibrium VEM excitation energy calculation followed by a
nonequilibrium emission energy calculation; task tddft gradient line
should be present)
```

The VEM solvent (which is water by default) can be specified by using the solvent keyword described in the SMD section of this manual or by specifying the VEM solvent descriptors such as

```
dielec (real input)
static dielectric constant
```

```
dielecinf (real input)
optical dielectric constant which is set (by default) to the squared
value of the solvent's index of refraction (see the keyword soln, but
note
that if the solvent is specified with the solvent keyword, the
refractive index is set by the program without needing the user to
supply it.
```

Solvent descriptors set by the program are based on the Minnesota Solvent Descriptor Database:

Winget, P.; Dolney, D. M.; Giesen, D. J.; Cramer, C. J.; Truhlar, D. G. Minnesota Solvent Descriptor Database. University of Minnesota: Minneapolis, MN, 2010. http://comp.chem.umn.edu/solvation/mnsddb.pdf

If the option 'do_cosmo_vem 1' or 'do_cosmo_vem 2' is specified the program will run VEM ground- and excited-state bulk-electrostatic calculations using the COSMO algorithm with the SMD Coulomb radii by default. If the user wants to use the default COSMO radii in such

calculations (this is not recommended) the option 'do_cosmo_smd .false.' should be specified.

If the SMSSP estimate of a solute-solvent dispersion contribution to the solvatochromic shift is desired, the following options should be used:

```
polgs_cosmo_vem (real input)
user-provided value of the spherically-averaged molecular
polarizability of the solute in the ground state (in Å3)
```

```
poles_cosmo_vem (real input)
user-provided value of the spherically-averaged molecular
polarizability of the solute in an exited state of interest (in Å3)
```

An example of the VEM input file is provided below.

```
echo
title
       'VEM/TDDFT-B3LYP/6-311+G(d) vertical excitation energy + SMSSP
for formaldehyde in methanol'
start
geometry nocenter
 0
     0.0000000000
                      0.000000000
                                      0.6743110000
 С
      0.0000000000
                      0.0000000000
                                     -0.5278530000
 н
      0.0000000000
                      0.9370330000
                                     -1.1136860000
 н
      0.0000000000
                   -0.9370330000
                                     -1.1136860000
symmetry c1
end
basis
* library 6-311+G*
end
dft
XC b3lyp
end
cosmo
 do cosmo smd true
 do cosmo vem 1
 solvent methanol
 polgs cosmo vem 2.429
 poles_cosmo_vem 3.208
end
tddft
 nroots 10
 target 1
 singlet
 notriplet
 algorithm 1
 civecs
 grad
    root 1
    solve thresh 1d-05
```

end end

task tddft gradient

References

[1] http://dx.doi.org/10.1002/(SICI)1097-461X(2000)77:1<264::AID-QUA24>3.0.CO;2-J

Release65:ONIOM

__NOTITLE___

Hybrid Calculations with ONIOM

ONIOM is the hybrid method of Morokuma and co-workers that enables different levels of theory to be applied to different parts of a molecule/system and combined to produce a consistent energy expression. The objective is to perform a high-level calculation on just a small part of the system and to include the effects of the remainder at lower levels of theory, with the end result being of similar accuracy to a high-level calculation on the full system.

- 1. M. Svensson, S. Humbel, R.D.J. Froese, T. Mastubara, S. Sieber, and K. Morokuma, J. Phys. Chem., 100, 19357 (1996).
- 2. S. Dapprich, I. Komaromi, K.S. Byun, K. Morokuma, and M.J. Frisch, J. Mol. Struct. (Theochem), 461-462, 1 (1999).
- 3. R.D.J. Froese and K. Morokuma in ``Encylopedia of Computational Chemistry, volume 2, pp.1244-1257, (ed. P. von Rague Schleyer, John Wiley and Sons, Chichester, Sussex, 1998).

The NWChem ONIOM module implements two- and three-layer ONIOM models for use in energy, gradient, geometry optimization, and vibrational frequency calculations with any of the pure quantum mechanical methods within NWChem. At the present time, it is not possible to perform ONIOM calculations with either solvation models or classical force fields. Nor is it yet possible to compute properties except as derivatives of the total energy.

Using the terminology of Morokuma et al., the full molecular geometry including all atoms is referred to as the "real" geometry and it is treated using a "low"-level of theory. A subset of these atoms (referred to as the "model" geometry) are treated using both the "low"-level and a "high"-level of theory. A three-layer model also introduces an "intermediate" model geometry and a "medium" level of theory.

The two-layer model requires a high and low level of theory and a real and model molecular geometry. The energy at the high-level of theory for the real geometry is estimated as

E(High,Real) = E(Low,Real) + [E(High,Model) - E(Low,Model)].

The three-layer model requires high, medium and low levels of theory, and real, intermediate and model geometries and the corresponding energy estimate is

E(High,Real) = E(Low,Real) + [E(High,Model) - E(Medium,Model)] + [E(Medium,Inter) - E(Low,Inter)]. When does ONIOM work well? The approximation for a two-layer model will be good if

- the model system includes the interactions that dominate the energy difference being computed and the high-level of theory describes these to the required precision, and
- the interactions between the model and the rest of the real system (substitution effects) are described to sufficient accuracy at the lower level of theory.

ONIOM is used to compute energy differences and the absolute energies are not all that meaningful even though they are well defined. Due to cancellation of errors, ONIOM actually works better than you might expect, but a poorly designed calculation can yield very bad results. Please read and heed the caution at the end of the article by Dapprich et al.

The input options are as follows

```
ONIOM
 HIGH
         <string theory> [basis <string basis default "ao
basis">] \
                           [ecp <string ecp>] [input <string</pre>
input>]
 [MEDIUM <string theory> [basis <string basis default "ao
basis">] \
                           [ecp <string ecp>] [input <string</pre>
input>]]
  LOW
         <string theory> [basis <string basis default "ao
basis">] \
                           [ecp <string ecp>] [input <string</pre>
input>]
 MODEL <integer natoms> [charge <double charge>] \
                           [<integer i1 j1> <real g1>
[<string tag1>] ...]
 [INTER <integer natoms> [charge <double charge>] \
                           [<integer i1 j1> <real g1>
[<string tag1>] ...]]
 [VECTORS [low-real <string mofile>] [low-model <string
mofile>] \
          [high-model <string mofile>] [medium-model <string</pre>
mofile]
          [medium-inter <string mofile>] [low-inter <string</pre>
mofile>]]
 [PRINT ...]
 [NOPRINT ...]
END
```

which are described in detail below.

For better validation of user input, the HIGH, LOW and MODEL directives must always be specified. If the one of the MEDIUM or INTER directives are specified, then so must the other.

Real, model and intermediate geometries

The geometry and total charge of the full or real system should be specified as normal using the geometry directive. If N_{model} of the atoms are to be included in the model system, then these should be specified first in the geometry. Similarly, in a three-layer calculation, if there are N_{inter} atoms to be included in the intermediate system, then these should also be arranged together at the beginning of the geometry. The implict assumption is that the model system is a subset of the intermediate system which is a subset of the real system. The number of atoms to be included in the model and intermediate systems are specified using the MODEL and INTER directives. Optionally, the total charge of the model and intermediate systems may be adjusted. The default is that all three systems have the same total charge.

Example 1. A two-layer calculation on $K^+(H_2O)$ taking the potassium ion as the model system. Note that no bonds are broken so no link atoms are introduced. The real geometry would be specified with potassium (the model) first.

geometry		autosym	
Κ	0	0.00	1.37
0	0	0.00	-1.07
Н	0	-0.76	-1.68
Н	0	0.76	-1.68
end			

and the following directive in the ONIOM input block indicates that one atom (implicitly the first in the geometry) is in the model system

model 1

Link atoms

Link atoms for bonds spanning two regions are automatically generated from the bond information. The additional parameters on the MODEL and INTER directives describe the broken bonds including scale factors for placement of the link atom and, optionally, the type of link atom. The type of link atom defaults to hydrogen, but any type may be specified (actually here you are specifying a geometry tag which is used to associate a geometrical center with an atom type and basis sets, etc. For each broken bond specify the numbers of the two atoms (i and j), the scale factor (g) and optionally the tag of the link atom. Link atoms are placed along the vector connecting the the first to the second atom of the bond according to the equation

$$\underline{R}_{link} = (1-g)\underline{R}_1 + g * \underline{R}_2$$

where g is the scale factor. If the scale factor is one, then the link atom is placed where the second atom was. More usually, the scale factor is less than one, in which case the link atom is placed between the original two atoms. The scale factor should be chosen so that the link atom (usually hydrogen) is placed near its equilibrium bond length from the model atom. E.g., when breaking a single carbon-carbon bond (typical length 1.528 Angstrøms) using a hydrogen link atom we will want a carbon-hydrogen bond length of about 1.084 Angstrøms, so the scale factor should be chosen as $1.084/1.528 \sim 0.709$.

Example 2. A calculation on acetaldehyde ($H_3C - CHO$) using aldehyde (H - CHO) as the model system. The covalent bond between the two carbon atoms is broken and a link

atom must be introduced to replace the methyl group. The link atom is automatically generated -- all you need to do is specify the atoms in the model system that are also in the real system (here CHO) and the broken bonds. Here is the geometry of acetaldehyde with the CHO of aldehyde first

geometry					
С	-0.383	0.288	0.021		
Н	-1.425	0.381	0.376		
0	0.259	1.263	-0.321		
Н	0.115	-1.570	1.007		
Н	-0.465	-1.768	-0.642		
Н	1.176	-1.171	-0.352		
С	0.152	-1.150	0.005		
end					

There are three atoms (the first three) of the real geometry included in the model geometry, and we are breaking the bond between atoms 1 and 7, replacing atom 7 with a hydrogen link atom. This is all accomplished by the directive

model 3 1 7 0.709 H

Since the default link atom is hydrogen there is actually no need to specify the ``H.

See also the three-layer example for a more complex example.

Numbering of the link atoms

The link atoms are appended to the atoms of the model or intermediate systems in the order that the broken bonds are specified in the input. This is of importance only if manually constructing an initial guess.

High, medium and low theories

The two-layer model requires both the high-level and low-level theories be specified. The three-layer model also requires the medium-level theory. Each of these includes a theory (such as SCF, MP2, DFT, CCSD, CCSD(T), etc.), an optional basis set, an optional ECP, and an optional string containing general NWChem input.

Basis specification

The basis name on the theory directive (high, medium, or low) is that specified on a basis set directive (see Section 7) and not the name of a standard basis in the library. If not specified, the basis set for the high-level theory defaults to the standard "ao basis". That for the medium level defaults to the high-level basis, and the low-level basis defaults to the medium-level basis. Other wavefunction parameters are obtained from the standard wavefunction input blocks. See Effective core potential for an example.

Effective core potentials

If an effective core potential is specified in the usual fashion outside of the ONIOM input then this will be used in all calculations. If an alternative ECP name (the name specified on the ECP directive in the same manner as done for basis sets) is specified on one of the theory directives, then this ECP will be used in preference for that level of theory. See teh three-layer example for sample input.

General input strings

For many purposes, the ability to specify the theory, basis and effective core potential is adequate. All of the options for each theory are determined from their independent input blocks. However, if the same theory (e.g., DFT) is to be used with different options for the ONIOM theoretical models, then the general input strings must be used. These strings are processed as NWChem input each time the theoretical model is invoked. The strings may contain any NWChem input, except for options pertaining to ONIOM and the task directive. The intent that the strings be used just to control the options pertaining to the theory being used.

A word of caution. Be sure to check that the options are producing the desired results. Since the NWChem database is persistent and the ONIOM calculations happen in an undefined order, the input strings should fully define the calculation you wish to have happen.

For instance, if the high model is DFT/B3LYP/6-311g** and the low model is DFT/LDA/3-21g, the ONIOM input might look like this

```
oniom
  model 3
  low dft basis 3-21g input "dft\; xc\; end"
  high dft basis 6-311g** input "dft\; xc b3lyp\; end"
end
```

The empty XC directive restores the default LDA exchange-correlation option (see Section 11.3). Note that semi-colons and other quotation marks inside the input string must be preceded by a backslash to avoid special interpretation.

See |DFT with and without charge fitting for another example.

Use of symmetry

Symmetry should work just fine as long as the model and intermediate regions respect the symmetry -- i.e., symmetry equivalent atoms need to be treated equivalently. If symmetry equivalent atoms must be treated in separate regions then the symmetry must be lowered (or completely switched off).

Molecular orbital files

The VECTORS directive in the ONIOM block is different to that elsewhere in NWChem. For each of the necessary combinations of theory and geometry you can specify a different file for the molecular orbitals. By default each combination will store the MO vectors in the permanent directory using a file name created by appending to the name of the calculation the following string

- low-real -- ".lrmos"
- low-inter -- ".limos"
- low-model -- ".lmmos"
- medium-inter -- ".mimos"
- medium-model -- ".mmmos"
- high-model -- ".hmmos"

Each calculation will utilize the appropriate vectors which is more efficient during geometry optimizations and frequency calculations, and is also useful for the initial calculation. In the absence of existing MO vectors files, the default atomic guess is used (see |Input/output of MO vectors).

If special measures must be taken to converge the initial SCF, DFT or MCSCF calculation for one or more of the systems, then initial vectors may be saved in a file with the default name, or another name may be specified using the VECTORS directive. Note that subsequent vectors (e.g., from a geometry optimization) will be written back to this file, so take a copy if you wish to preserve it. To generate the initial guess for the model or intermediate systems it is necessary to generate the geometries which is most readily done, if there are link atoms, by just running NWChem on the input for the ONIOM calculation on your workstation. It will print these geometries before starting any calculations which you can then terminate.

E.g., in a calculation on Fe(III) surrounded by some ligands, it is hard to converge the full (real) system from the atomic guess so as to obtain a d^5 configuration for the iron atom since the d orbitals are often nominally lower in energy than some of the ligand orbitals. The most effective mechanism is to converge the isolated Fe(III) and then to use the fragment guess as a starting guess for the real system. The resulting converged molecular orbitals can be saved either with the default name (as described above in this section), in which case no additional input is necessary. If an alternative name is desired, then the VECTORS directive may be used as follows

```
vectors low-real /u/rjh/jobs/fe_ether_water.mos
```

Restarting

Restart of ONIOM calculations does not currently work as smoothly as we would like. For geometry optimizations that terminated gracefully by running out of iterations, the restart will work as normal. Otherwise, specify in the input of the restart job the last geometry of the optimization. The Hessian information will be reused and the calculation should proceed losing at most the cost of one ONIOM gradient evaluation. For energy or frequency calculations, restart may not currently be possible.

Examples

Hydrocarbon bond energy

A simple two-layer model changing just the wavefunction with one link atom.

This reproduces the two-layer ONIOM (MP2:HF) result from Dapprich et al. for the reaction $R - CH_3 = R - CH_2 + H$ with $R = CH_3$ using CH_4 as the model. The geometries of $R - CH_3$ and $R - CH_2$ are optimized at the DFT-B3LYP/6-311++G** level of theory, and then ONIOM is used to compute the binding energy using UMP2 for the model system and

HF for the real system. The results, including MP2 calculations on the full system for comparison, are as given in the table below.

Energies for ONIOM example 1, hydrocarbon bond energy using MP2:HF two-layer model.

Theory	Me-CH2	Me-Me	Н	De(Hartree)	De(kcal/mol)
B3LYP	-79.185062	-79.856575	-0.502256	0.169257	106.2
HF	-78.620141	-79.251701	-0.499817	0.131741	82.7
MP2	-78.904716	-79.571654	-0.499817	0.167120	104.9
MP2:HF	-78.755223	-79.422559	-0.499817	0.167518	105.1

The following input first performs a calculation on $CH_3 - CH_2$, and then on $CH_3 - CH_3$. Note that in the second calculation we cannot use the full symmetry since we are breaking the C-C bond in forming the model system (the non-equivalence of the methyl groups is perhaps more apparent if we write $R - CH_3$).

```
start
```

```
basis spherical
     H library 6-311++G**; C library 6-311++G**
  end
  title "ONIOM Me-CH2"
  geometry autosym
    Н
          -0.23429328
                          1.32498565
                                          0.92634814
    н
          -0.23429328
                          1.32498565
                                         -0.92634814
     С
          -0.13064265
                          0.77330370
                                          0.0000000
    Н
          -1.01618703
                         -1.19260361
                                          0.0000000
    н
           0.49856072
                         -1.08196901
                                         -0.88665533
    Н
           0.49856072
                         -1.08196901
                                          0.88665533
     С
          -0.02434414
                         -0.71063687
                                          0.0000000
   end
  scf; uhf; doublet; thresh 1e-6; end
  mp2; freeze atomic; end
  oniom
     high mp2
     low scf
    model 3
               3 7 0.724
  end
  task oniom
  title "ONIOM Me-Me"
  geometry
              # Note cannot use full D3D symmetry here, either specify
noautosym, or change an atom tag (here C -> C1)
    Н
         -0.72023641
                         0.72023641
                                        -1.16373235
```

```
-1.16373235
  Н
       0.98386124
                      0.26362482
  Н
      -0.26362482
                     -0.98386124
                                     -1.16373235
  С
       0.00000000
                      0.00000000
                                     -0.76537515
  Н
       0.72023641
                     -0.72023641
                                      1.16373235
      -0.98386124
                     -0.26362482
                                      1.16373235
  Н
  Н
       0.26362482
                      0.98386124
                                      1.16373235
  C1
       0.0000000
                      0.00000000
                                      0.76537515
end
scf; rhf; singlet; end
oniom
  high mp2
  low scf
  model 4 4 8 0.724
end
task oniom
```

Optimization and frequencies

A two-layer model including modification of theory, basis, ECP and total charge and no link atoms.

This input reproduces the ONIOM optimization and vibrational frequency calculation of $Rh(CO)_2Cp$ of Dapprich et al. The model system is $Rh(CO)_2^+$. The low theory is the Gaussian LANL2MB model (Hay-Wadt n+1 ECP with minimal basis on Rh, STO-3G on others) with SCF. The high theory is the Gaussian LANL2DZ model (another Hay-Wadt ECP with a DZ basis set on Rh, Dunning split valence on the other atoms) with DFT/B3LYP. Note that different names should be used for the basis set and ECP since the same mechanism is used to store them in the database.

```
start
  ecp LANL2DZ ECP
     rh library LANL2DZ ECP
  end
  basis LANL2DZ spherical
     rh library LANL2DZ_ECP
     o library SV_(Dunning-Hay); c library SV_(Dunning-Hay); h library
SV (Dunning-Hay)
  end
  ecp Hay-Wadt MB (n+1) ECP
     rh library Hay-Wadt_MB_(n+1)_ECP
  end
  # This is the minimal basis used by Gaussian. It is not the same
  # as the one in the EMSL basis set library for this ECP.
   basis Hay-Wadt MB (n+1) spherical
    Rh s; .264600D+01 -.135541D+01; .175100D+01 .161122D+01;
```

```
.571300D+00 .589381D+00
    Rh s; .264600D+01 .456934D+00; .175100D+01 -.595199D+00;
.571300D+00 -.342127D+00
          .143800D+00 .410138D+00; .428000D-01 .780486D+00
    Rh p; .544000D+01 -.987699D-01; .132900D+01 .743359D+00;
.484500D+00 .366846D+00
    Rh p; .659500D+00 -.370046D-01; .869000D-01 .452364D+00;
.257000D-01 .653822D+00
    Rh d; .366900D+01 .670480D-01; .142300D+01 .455084D+00;
.509100D+00 .479584D+00
          .161000D+00 .233826D+00
    o library sto-3g; c library sto-3g; h library sto-3g
  end
  charge 0
  geometry autosym
    rh
            0.00445705
                         -0.15119674
                                         0.0000000
            -0.01380554
                          -1.45254070
    С
                                         1.35171818
                          -1.45254070
    С
            -0.01380554
                                        -1.35171818
    0
           -0.01805883
                          -2.26420212
                                        2.20818932
           -0.01805883
                         -2.26420212
                                        -2.20818932
    0
            1.23209566
                          1.89314720
                                         0.0000000
    С
    С
            0.37739392
                          1.84262319
                                        -1.15286640
            -1.01479160
                           1.93086461
                                        -0.70666350
    С
            -1.01479160
                           1.93086461
                                         0.70666350
    С
    С
            0.37739392
                           1.84262319
                                        1.15286640
    h
            2.31251453
                           1.89903673
                                         0.00000000
    h
            0.70378132
                           1.86131979
                                        -2.18414218
    h
           -1.88154273
                           1.96919306
                                        -1.35203550
    h
            -1.88154273
                           1.96919306
                                        1.35203550
             0.70378132
    h
                           1.86131979
                                         2.18414218
  end
  dft; grid fine; convergence gradient 1e-6 density 1e-6; xc b3lyp; end
  scf; thresh le-6; end
  oniom
    low scf basis Hay-Wadt_MB_(n+1) ecp Hay-Wadt_MB_(n+1)_ECP
    high dft basis LANL2DZ ecp LANL2DZ ECP
    model 5 charge 1
    print low
  end
  task oniom optimize
  task oniom freq
```

A three-layer example

A three layer example combining CCSD(T), and MP2 with two different quality basis sets, and using multiple link atoms.

The full system is tetra-dimethyl-amino-ethylene (TAME) or (N(Me)2)2-C=C-(N(Me)2)2. The intermediate system is (NH2)2-C=C-(NH2)2 and H2C=CH2 is the model system. CCSD(T)+aug-cc-pvtz is used for the model region, MP2+aug-cc-pvtz for the intermediate region, and MP2+aug-cc-pvdz for everything.

In the real geometry the first two atoms (C, C) are the model system (link atoms will be added automatically). The first six atoms (C, C, N, N, N, N) describe the intermediate system (again with link atoms to be added automatically). The atoms have been numbered using comments to make the bonding input easier to generate.

To make the model system, four C-N bonds are broken between the ethylene fragment and the dimethyl-amino groups and replaced with C-H bonds. To make the intermediate system, eight C-N bonds are broken between the nitrogens and the methyl groups and replaced with N-H bonds. The scaling factor could be chosen differently for each of the bonds.

start

geometry					
C 0.40337795	-0.17516305	-0.51505208	# 1		
C -0.40328664	0.17555927	0.51466084	# 2		
N 1.87154979	-0.17516305	-0.51505208	# 3		
N -0.18694782	-0.60488524	-1.79258692	# 4		
N 0.18692927	0.60488318	1.79247594	# 5		
N -1.87148219	0.17564718	0.51496494	# 6		
C 2.46636552	1.18039452	-0.51505208	# 7		
C 2.48067731	-1.10425355	0.46161675	# 8		
C -2.46642715	-1.17982091	0.51473105	# 9		
C -2.48054940	1.10495864	-0.46156202	# 1	9	
C 0.30027136	0.14582197	-2.97072148	# 1	1	
C -0.14245927	-2.07576980	-1.96730852	# 1	2	
C -0.29948109	-0.14689874	2.97021079	# 1	3	
C 0.14140463	2.07558249	1.96815181	# 1	4	
H 0.78955302	2.52533887	1.19760764			
H -0.86543435	2.50958894	1.88075113			
and 22 oth	er hydrogen	atoms on the	met	hyl	groups
end					
basis aug-cc-pvt	z spherical				
C librarv aug-	cc-pvtz: H]	librarv aug-c	c - pv	tz	
end		, ,	•		
basis aug-cc-pvd	z spherical				
C library aug-	cc-pvtz; H 1	library aug-c	c-pv	tz	
end					
oniom					
high ccsd(t) b	asis aug-cc	-pvtz			
medium mp2 basis aug-cc-pvtz					

```
low mp2 basis aug-cc-pvdz
  model 2
           1 3 0.87
                       14
                            0.87
                                   2 5 0.87
                                               2 6 0.87
  inter 6
           3 7 0.69
                       38
                            0.69
                                   4 11 0.69
                                               4 12 0.69 \
           5 13 0.69
                       5 14 0.69
                                   6 9 0.69
                                               6 10 0.69
end
```

task oniom

DFT with and without charge fitting

Demonstrates use of general input strings.

A two-layer model for anthracene (a linear chain of three fused benzene rings) using benzene as the model system. The high-level theory is DFT/B3LYP/TZVP with exact Coulomb. The low level is DFT/LDA/DZVP2 with charge fitting.

Note the following.

- 1. The semi-colons and quotation marks inside the input string must be quoted with backslash.
- 2. The low level of theory sets the fitting basis set and the high level of theory unsets it.

```
start
geometry
  symmetry d2h
                                       0.0
 С
       0.71237329
                      -1.21458940
  С
                                       0.0
      -0.71237329
                      -1.21458940
 С
       0.71237329
                       1.21458940
                                       0.0
  С
                       1.21458940
                                       0.0
      -0.71237329
  С
                                       0.0
      -1.39414269
                       0.0000000
 С
      1.39414269
                       0.0000000
                                       0.0
 Н
                                       0.0
      -2.47680865
                       0.0000000
                                       0.0
 Н
       2.47680865
                       0.0000000
 С
       1.40340535
                      -2.48997027
                                       0.0
  С
                                       0.0
      -1.40340535
                      -2.48997027
  С
       1.40340535
                       2.48997027
                                       0.0
 С
      -1.40340535
                       2.48997027
                                       0.0
  С
                                       0.0
       0.72211503
                       3.64518615
  С
      -0.72211503
                       3.64518615
                                       0.0
 С
       0.72211503
                                       0.0
                      -3.64518615
  С
                                       0.0
      -0.72211503
                      -3.64518615
 Н
       2.48612947
                       2.48094825
                                       0.0
 Н
                                       0.0
       1.24157357
                       4.59507342
 Н
      -1.24157357
                       4.59507342
                                       0.0
      -2.48612947
                       2.48094825
                                       0.0
 Н
                                       0.0
 Н
       2.48612947
                      -2.48094825
 Н
       1.24157357
                      -4.59507342
                                       0.0
      -1.24157357
                      -4.59507342
                                       0.0
 н
                                       0.0
 Н
      -2.48612947
                      -2.48094825
end
```

```
basis small
     h library DZVP (DFT Orbital)
     c library DZVP (DFT Orbital)
   end
  basis fitting
     h library DGauss A1 DFT Coulomb Fitting
     c library DGauss_A1_DFT_Coulomb_Fitting
  end
  basis big
     h library TZVP_(DFT_Orbital)
     c library TZVP (DFT Orbital)
  end
  oniom
     model 8
             1 \ 9 \ 0.75 \ 2 \ 10 \ 0.75 \ 3 \ 11 \ 0.75
                                                   4 12 0.75
     high dft basis big input "unset \"cd basis\"\; dft\; xc b3lyp\;
end"
     low dft basis small input "set \"cd basis\" fitting\; dft\; xc\;
end"
  end
```

task oniom

Release65:QMMM

__NOTITLE__

QMMM Simulations

- Introduction
- Topology and Restart Files
 - Prerequisites
 - QM region definition
 - Solvation
 - Permanent Constraints
- Input File
 - QM Parameters
 - MM Parameters
 - QM/MM Parameters
- Single Point Calculations
 - Ground State Energy and Gradient
 - Excited State Energy
 - Properties
 - ESP Charge Analysis
- Potential Energy Surface Analysis

- Optimization
- Transition States
- Hessians and Frequency
- Reaction Pathway Calculations with NEB
- Dynamics
- Free Energy Calculations
- Appendix
 - Format of NWChem parameter file
 - Conversion from AMBER program parameter files to NWChem

Release65:Bq

__NOTITLE__ Bq module provides a way to perform QM calculations in the presence of point charges or Bq's, (as typically referred to in quantum chemistry community). Using Bq module versus geometry block is a recommended way to include point charges in your calculations, in particular if number of charges are big.

The format for including external point charges using the Bq module is shown below, supporting both explicit charge definition in the body of the block and/or loading from external files.

```
bq [units aupm|ang|...] [namespace]
 [clear]
 [force|noforce]
 [load <file> [charges <chargefile>] [format ix iy iz iq]
 [units au|nm|pm|ang|...] [ scale <factor>
 x y z q
 ...
end
```

- **units** specify the global units for the coordinates of point charges. Allowed values are au, bohr, nanometers, nm, pm, picometers, angstrom (note that only first 3 characters are important). The default units are angstrom
- **namespace** an optional name that can be used to distinguish between potentially several point charge sets. The default value for namespace is "default", and only the set that has this namespace value will be actually used in the calculation. If for example different namespace is used, this point charge set will be processed into the run time database but not actually used unless the following set directive is encountered

set bq <namespace>

Here is an example that illustrates this

```
...
#store point charge in namespace foo
bq foo
...
end
```

```
#perform calculation without actually loading charges in foo
task dft energy
#activate charges in foo
set bq foo
# now DFT calculation will performed in the presence of charges in foo
task dft energy
```

- **clear** this directive erases all the previously specified point charges in a given namespace, prior to new setup (if any).
- force <output_file> | noforce this directive triggers|disables calculation of forces on Bq charges. Default value is noforce, which disables force calculation. The forces will be written to <output_file> if provided or to <prefix>.bqforce.dat file. The format of the file is

#comment line
fx fy fz
....

- load <file> [charges <chargefile>] [format ix iy iz iq] [units au|nm|pm|ang|...] [scale
 <factor>] this directive allows to load point charges from external file(s). You can load charges and their coordinates from a single file, or from separate files. The files do not have to follow any specific format, but blank lines and comments (starting with #) will be ignored. The actual specification of how the coordinates/charges are laid out in in the file is given by format keyword. Multiple load directives are a supported.
 - <file> the name of the file where Bq coordinates and charges are stored.
 - charges <chargefile> this optional keyword allows to load charges (NOT the coordinates) from a separate <chargefile>. In this case, only coordinates would be loaded from <file>
 - format ix iy iz iq this optional keyword allows to set the fields (separated by blanks) where x,y,z coordinates and respective charge values are to be found. If a specified field doe nor exist or contains no numerical value, the processing will skip to the next line. The default value for format is 2 3 4 5, which will work for the following example (note that the second line will not be processed here)

```
#this is a comment
coordinates are in fields 2,3,4 and charge is field 5
0 2.384 1.738 1.380 -0.9
H 2.448 1.608 0.416 0.45
H 1.560 1.268 1.608 0.45
```

- units au|nm|pm|ang|... this optional keyword sets the local coordinate units valid only for this particular load directive. Otherwise global unit definition will apply (see above)
- scale <factor> this optional keyword allows to scale loaded charge values by some factor
- x y z q explicit definition of coordinates and charge values of point charges. These can be mixed in with load directive at will.

start w1

```
BASIS "ao basis" PRINT
* library "3-21G"
END
dft
 mult 1
 XC b3lyp
 iterations 5000
end
geometry nocenter noautosym units angstrom noautoz print
0
           2.045
                  1.011 -1.505
Η1
           1.912
                   0.062 -1.314
           1.119 1.318 -1.544
H2
end
#example of explicit Bq input
bq
2.384
       1.738 1.380 -0.9
2.448
       1.608
                0.416 0.45
1.560
        1.268
               1.608
                        0.45
end
task dft energy
#example of implicit Bq input using load directive
bq
load bq.xyz format 1 2 3 4
end
task dft energy
#example of loading coordinates and charges separately
bq
       bq.xyz charges bq.xyz format 1 2 3 4
load
end
task dft energy
#example of loading Bq's with default format (1 2 3 4) and scaling
charges (to zero)
bq
load bq.xyz scale 0.0
end
task dft energy
#example of mixed Bq input
bq
load bq0.xyz format 2 3 4 6
2.448
        1.608
                0.416
                        0.45
1.560
        1.268 1.608
                        0.45
end
```

task dft energy

#example of erasing Bq's
bq
clear
end
task dft energy
#example of storing Bq's in custom namespace (not activated)
bq marat
load bq.xyz format 1 2 3 4
end
task dft energy
#example of activating Bq's stored in custom namespace
set bq marat
task dft energy

• Increasing the limit on the number of bq charges

There is an internal limit of 25000 bq charges. To increase this use the following set directive in the input file

set bq:max_nbq 30000

Potential Energy Surface Analysis

Release65:Constraints

```
__NOTITLE__
```

Constraints

The constraints directive allows the user to specify which constraints should be imposed on the system during the analysis of potential energy surface. Currently such constraints are limited to fixed atom positions and harmonic restraints (springs) on the distance between the two atoms. The general form of constraints block is presented below:

```
CONSTRAINTS [string name ] \

[clear] \

[enable||disable] \

[fix atom <integer list>] \

[spring bond <integer atom1> <integer atom2>

<real k> <real r0> ]

END
```

The keywords are described below

• name - optional keyword that associates a name with a given set of constraints. Any unnamed set of constraints will be given a name *default* and will be automatically loaded prior to a calculation. Any constraints with the name other than *default* will have to be loaded manually using SET directive. For example,

```
CONSTRAINTS one
spring bond 1 3 5.0 1.3
fix atom 1
END
#the above constraints can be loaded using the set directive
set constraints one
....
task ....
```

- clear destroys any prior constraint information. This may be useful when the same constraints have to be redefined or completely removed from the runtime database.
- enable||disable enables or disables particular set of constraints without actually removing the information from the runtime database.
- fix atom fixes atom positions during geometry optimization. This directive requires an integer list that specifies which atoms are to be fixed. This directive can be repeated within a given constraints block. To illustrate the use "fix atom" directive let us consider a situation where we would like to fix atoms 1, 3, 4, 5, 6 while performing an optimization on some hypothetical system. There are actually several ways to enter this particular

constraint.

• There is a straightforward option which requires the most typing:

```
constraints
  fix atom 1 3 4 5 6
end
```

• Second method uses list input:

```
constraints
  fix atom 1 3:6
end
```

• Third approach illustrates the use of multiple fix atom directives:

```
constraints
  fix atom 1
  fix atom 3:6
end
```

• spring bond $\langle ijkr_0 \rangle$ - places a spring with a spring constant k and equilibrium length r_0 between atoms i and j (all in atomic units). Please note that this type of constraint adds an additional term to the total energy expression

$$E = E_{total} + \frac{1}{2}k(r_{ij} - r_0)^2$$

This additional term forces the distance between atoms i and j to be in the vicinity of r_0 but never exactly that. In general the spring energy term will always have some nonzero residual value, and this has to be accounted for when comparing total energies. The "spring bond" directive can be repeated within a given constraints block. If the spring between the same pair of atoms is defined more than once, it will be replaced by the latest specification in the order it appears in the input block.

Release65:Geometry Optimization

__NOTITLE__

Geometry Optimization with DRIVER

The DRIVER module is one of two drivers (also see documentation on STEPPER) to perform a geometry optimization function on the molecule defined by input using the GEOMETRY directive. Geometry optimization is either an energy minimization or a transition state optimization. The algorithm programmed in DRIVER is a quasi-newton optimization with line searches and approximate energy Hessian updates.

DRIVER is selected by default out of the two available modules to perform geometry optimization. In order to force use of DRIVER (e.g., because a previous optimization used STEPPER) provide a DRIVER input block (below) -- even an empty block will force use of DRIVER.

Optional input for this module is specified within the compound directive,

```
DRIVER
  (LOOSE || DEFAULT || TIGHT)
  GMAX <real value>
  GRMS <real value>
  XMAX <real value>
  XRMS <real value>
  EPREC <real eprec default 1e-7>
  TRUST <real trust default 0.3>
  SADSTP <real sadstp default 0.1>
  CLEAR
  REDOAUTOZ
  INHESS <integer inhess default 0>
  (MODDIR || VARDIR) <integer dir default 0>
  (FIRSTNEG || NOFIRSTNEG)
  MAXITER <integer maxiter default 20>
  BSCALE <real BSCALE default 1.0>
  ASCALE <real ASCALE default 0.25>
  TSCALE <real TSCALE default 0.1>
  HSCALE <real HSCALE default 1.0>
     PRINT ...
  XYZ <string xyz default ''file_prefix''>]
  NOXYZ
END
```

On each optimization step a line search is performed. To speed up calculations (up to two times), it may be beneficial to turn off the line search using following directive:

set driver:linopt 0

Convergence criteria

```
(LOOSE || DEFAULT || TIGHT)
GMAX <real value>
GRMS <real value>
XMAX <real value>
XRMS <real value>
```

The defaults may be used, or the directives LOOSE, DEFAULT, or TIGHT specified to use standard sets of values, or the individual criteria adjusted. All criteria are in atomic units. GMAX and GRMS control the maximum and root mean square gradient in the coordinates being used (Z-matrix, redundant internals, or Cartesian). XMAX and XRMS control the maximum and root mean square of the Cartesian step.

	L00SE	DEFAULT	TIGHT
GMAX	0.00450	0.00045	0.000015
GRMS	0.00300	0.00030	0.00001
XMAX	0.01800	0.00180	0.00006
XRMS	0.01200	0.00120	0.00004

Note that GMAX and GRMS used for convergence of geometry may significantly vary in different coordinate systems such as Z-matrix, redundant internals, or Cartesian. The coordinate system is defined in the input file (default is Z-matrix). Therefore the choice of coordinate system may slightly affect converged energy. Although in most cases XMAX and XRMS are last to converge which are always done in Cartesian coordinates, which insures convergence to the same geometry in different coordinate systems.

The old criterion may be recovered with the input

```
gmax 0.0008; grms 1; xrms 1; xmax 1
```

Available precision

```
EPREC <real eprec default 1e-7>
```

In performing a line search the optimizer must know the precision of the energy (this has nothing to do with convergence criteria). The default value of 1e-7 should be adjusted if less, or more, precision is available. Note that the default EPREC for DFT calculations is 5e-6 instead of 1e-7.

Controlling the step length

```
TRUST <real trust default 0.3>
SADSTP <real sadstp default 0.1>
```

A fixed trust radius (trust) is used to control the step during minimizations, and is also used for modes being minimized during saddle-point searches. It defaults to 0.3 for minimizations and 0.1 for saddle-point searches. The parameter sadstp is the trust radius used for the mode being maximized during a saddle-point search and defaults to 0.1.

Maximum number of steps

MAXITER <integer maxiter default 20>

By default at most 20 geometry optimization steps will be taken, but this may be modified with this directive.

Discard restart information

CLEAR

By default Driver reuses Hessian information from a previous optimization, and, to facilitate a restart also stores which mode is being followed for a saddle-point search. This option deletes all restart data.

Regenerate internal coordinates

REDOAUTOZ

Deletes Hessian data and regenerates internal coordinates at the current geometry. Useful if there has been a large change in the geometry that has rendered the current set of coordinates invalid or non-optimal.

Initial Hessian

INHESS <integer inhess default 0>

- 0 = Default ... use restart data if available, otherwise use diagonal guess.
- 1 = Use diagonal initial guess.
- 2 = Use restart data if available, otherwise transform Cartesian Hessian from previous frequency calculation.

In addition, the diagonal elements of the initial Hessian for internal coordinates may be scaled using separate factors for bonds, angles and torsions with the following

BSCALE <real bscale default 1.0> ASCALE <real ascale default 0.25> TSCALE <real tscale default 0.1>

These values typically give a two-fold speedup over unit values, based on about 100 test cases up to 15 atoms using 3-21g and 6-31g* SCF. However, if doing many optimizations on physically similar systems it may be worth fine tuning these parameters.

Finally, the entire Hessian from any source may be scaled by a factor using the directive

HSCALE <real hscale default 1.0>

It might be of utility, for instance, when computing an initial Hessian using SCF to start a large MP2 optimization. The SCF vibrational modes are expected to be stiffer than the MP2, so scaling the initial Hessian by a number less than one might be beneficial.

Mode or variable to follow to saddle point

(MODDIR || VARDIR) <integer dir default 0>
(FIRSTNEG || NOFIRSTNEG)

When searching for a transition state the program, by default, will take an initial step uphill and then do mode following using a fuzzy maximum overlap (the lowest eigen-mode with an overlap with the previous search direction of 0.7 times the maximum overlap is selected). Once a negative eigen-value is found, that mode is followed regardless of overlap.

The initial uphill step is appropriate if the gradient points roughly in the direction of the saddle point, such as might be the case if a constrained optimization was performed at the starting geometry. Alternatively, the initial search direction may be chosen to be along a specific internal variable (using the directive VARDIR) or along a specific eigen-mode (using MODDIR). Following a variable might be valuable if the initial gradient is either very small or very large. Note that the eigen-modes in the optimizer have next-to-nothing to do with the output from a frequency calculation. You can examine the eigen-modes used by the optimizer with

driver; print hvecs; end

The selection of the first negative mode is usually a good choice if the search is started in the vicinity of the transition state and the initial search direction is satisfactory. However, sometimes the first negative mode might not be the one of interest (e.g., transverse to the reaction direction). If NOFIRSTNEG is specified, the code will not take the first negative direction and will continue doing mode-following until that mode goes negative.

Optimization history as XYZ files

```
XYZ [<string xyz default $fileprefix>]
NOXYZ
```

The XYZ directive causes the geometry at each step (but not intermediate points of a line search) to be output into separate files in the permanent directory in XYZ format. The optional string will prefix the filename. The NOXYZ directive turns this off.

For example, the input

driver; xyz test; end

will cause files test-000.xyz, test-001.xyz, ... to be created in the permanent directory.

The script rasmolmovie in the NWChem contrib directory can be used to turn these into an animated GIF movie.

Print options

The UNIX command "egrep '^@' < output" will extract a pretty table summarizing the optimization.

If you specify the NWChem input

scf; print none; end driver; print low; end task scf optimize

you'll obtain a pleasantly terse output.

For more control, these options for the standard print directive are recognized

- debug prints a large amount of data. Don't use in parallel.
- high print the search direction in internals
- default prints geometry for each major step (not during the line search), gradient in internals (before and after application of constraints)
- low prints convergence and energy information. At convergence prints final geometry, change in internals from initial geometry

and these specific print options

- finish (low) print geometry data at end of calculation
- bonds (default) print bonds at end of calculation
- angles (default) print angles at end of calculation
- hvecs (never) print eigen-values/vectors of the Hessian
- searchdir (high) print the search direction in internals
- "internal gradient" (default) print the gradient in internals
- sadmode (default) print the mode being followed to the saddle point

Geometry Optimization with STEPPER

The STEPPER module performs a search for critical points on the potential energy surface of the molecule defined by input using the GEOMETRY directive. Since STEPPER is not the primary geometry optimization module in NWChem the compound directive is required; the DRIVER module is the default. Input for this module is specified within the compound directive,

```
STEPPER
```

... END

The presence of the STEPPER compound directive automatically turns off the default geometry optimization tool DRIVER. Input specified for the STEPPER module must appear in the input file after the GEOMETRY directive, since it must know the number of atoms that are to be used in the geometry optimization. In the current version of NWChem, STEPPER can be used only with geometries that are defined in Cartesian coordinates. STEPPER removes translational and rotational components before determining the step direction (5 components for linear systems and 6 for others) using a standard Eckart algorithm. The default initial guess nuclear Hessian is the identity matrix.

The default in STEPPER is to minimize the energy as a function of the geometry with a maximum of 20 geometry optimization iterations. When this is the desired calculation, no

input is required other than the STEPPER compound directive. However, the user also has the option of defining different tasks for the STEPPER module, and can vary the number of iterations and the convergence criteria from the default values. The input for these options is described in the following sections.

MIN and TS --Minimum or transition state search

The default is for STEPPER to minimize the energy with respect to the geometry of the system. This default behavior may be forced with the directive

MIN

STEPPER can also be used to find the transition state by following the lowest eigenvector of the nuclear Hessian. This is usually invoked by using the saddle keyword on the TASK directive, but it may also be selected by specifying the directive

ΤS

in the STEPPER input.

TRACK -- Mode selection

STEPPER has the ability to ``track a specific mode during an optimization for a transition state search, the user can also have the module track the eigenvector corresponding to a specific mode. This is done by specifying the directive

TRACK [nmode <integer nmode default 1>]

The keyword TRACK tells STEPPER to track the eigenvector corresponding to the integer value of <nmode> during a transition state walk. (Note: this input is invalid for a minimization walk since following a specific eigenvector will not necessarily give the desired local minimum.) The step is constructed to go up in energy along the nmode eigenvector and down in all other degrees of freedom.

MAXITER --Maximum number of steps

In most applications, 20 stepper iterations will be sufficient to obtain the energy minimization. However, the user has the option of specifying the maximum number of iterations allowed, using the input line,

```
MAXITER <integer maxiter default 20>
```

The value specified for the integer <maxiter> defines the maximum number of geometry optimization steps. The geometry optimization will restart automatically.

TRUST --Trust radius

The size of steps that can be taken in STEPPER is controlled by the trust radius which has a default value of 0.1. Steps are constrained to be no larger than the trust radius. The user has the option of overriding this default using the keyword TRUST, with the following input line,

TRUST <real radius default 0.1>

The larger the value specified for the variable radius, the larger the steps that can be taken by STEPPER. Experience has shown that for larger systems (i.e., those with 20 or more atoms), a value of 0.5, or greater, usually should be entered for <radius>.

CONVGGM, CONVGG and CONVGE --Convergence criteria

Three convergence criteria can be specified explicitly for the STEPPER calculations. The keyword CONVGGM allows the user to specify the convergence tolerance for the largest component of the gradient. This is the primary convergence criterion, as per the default settings, although all three criteria are in effect. this default setting is consistent with the other optimizer module DRIVER. The input line for CONVGGM has the following form,

CONVGGM <real convggm default 8.0d-04>

The keyword CONVGG allows the user to specify the convergence tolerance for the gradient norm for all degrees of freedom. The input line is of the following form,

CONVGG <real convgg default 1.0d-02>

The entry for the real variable <convgg> should be approximately equal to the square root of the energy convergence tolerance.

The energy convergence tolerance is the convergence criterion for the energy difference in the geometry optimization in STEPPER. It can be specified by input using a line of the following form,

CONVGE <real convge default 1.0d-04>

Backstepping in STEPPER

If a step taken during the optimization is too large (e.g., the step causes the energy to go up for a minimization or down for a transition state search), the STEPPER optimizer will automatically ``backstep and correct the step based on information prior to the faulty step. If you have an optimization that "backsteps" frequently then the initial trust radius should most likely be decreased.

Initial Nuclear Hessian Options

Stepper uses a modified Fletcher-Powell algorithm to find the transition state or energy minimum on the potential energy hypersurface. There are two files left in the user's permanent directory that are used to provide an initial hessian to the critical point search algorithm. If these files do not exist then the default is to use a unit matrix as the initial hessian. Once Stepper executes it generates a binary dump file by the name of name.stpr41 which will be used on all subsequent stepper runs and modified with the current updated hessian. The default file prefix is the "name" that is used (see START). It also stores the

information for the last valid step in case the algorithm must take a "backstep". This file is the working data store for all stepper-based optimizations. This file is never deleted by default and is the first source of an initial hessian. The second source of an initial hessian is an ascii file that contains the lower triangular values of the initial hessian. This is stored in file name.hess, where "name" is again the default file prefix. This is the second source of an initial hessian and is the method used to incorporate an initial hessian from any other source (e.g., another ab initio code, a molecular mechanics code, etc.,). To get a decent starting hessian at a given point you can use the task specification task scf hessian, with a smaller basis set, which will by default generate the name.hess file. Then you may define your basis set of choice and proceed with the optimization you desire.

Release65:Hessians & Vibrational Frequencies

__NOTITLE__

Hessians

This section relates to the computation of analytic hessians which are available for open and closed shell SCF, except ROHF and for closed shell and unrestricted open shell DFT ^[1]. Analytic hessians are not currently available for SCF or DFT calculations relativistic all-electron methodologies or for charge fitting with DFT. The current algorithm is fully in-core and does not use symmetry. This will be changed in the next release.

There is no required input for the Hessian module. This module only impacts the hessian calculation. For options for calculating the frequencies, please see the Vibrational module.

Hessian Module Input

All input for the Hessian Module is optional since the default definitions are usually correct for most purposes. The generic module input begins with hessian and has the form:

```
hessian
  thresh <real tol default 1d-6>
  print ...
  profile
end
```

Defining the wavefunction threshold

You may modify the default threshold for the wavefunction. This keyword is identical to THRESH in the SCF, and the CONVERGENCE gradient in the DFT. The usual defaults for the convergence of the wavefunction for single point and gradient calculations is generally not tight enough for analytic hessians. Therefore, the hessian, by default, tightens these up to 1d-6 and runs an additional energy point if needed. If, during an analytic hessian calculation, you encounter an error:

```
cphf_solve:the available MOs do not satisfy the SCF equations
```

the convergence criteria of the wavefunction generally needs to be tightened.

Profile

The PROFILE keyword provides additional information concerning the computation times of different sections of the hessian code. Summary information is given about the maximum, minimum and average times that a particular section of the code took to complete. This is normally only useful for developers.

Print Control

Known controllable print options are shown in the table below:

Name	Print Level	Description
"hess_follow"	high	more information about where the calculation is
"cphf_cont"	debug	detailed CPHF information
"nucdd_cont"	debug	detailed nuclear contribution information
"onedd_cont"	debug	detailed one electron contribution information
"twodd_cont"	debug	detailed two electron contribution information
"fock_xc"	debug	detailed XC information during the fock builds

Hessian Print Control Specifications

Vibrational frequencies

The nuclear hessian which is used to compute the vibrational frequencies can be computed by finite difference for any ab initio wave-function that has analytic gradients or by analytic methods for SCF and DFT (see Hessians for details). The appropriate nuclear hessian generation algorithm is chosen based on the user input when TASK <theory> frequencies is the task directive.

The vibrational package was integrated from the Utah Messkit and can use any nuclear hessian generated from the driver routines, finite difference routines or any analytic hessian modules. There is no required input for the "VIB" package. VIB computes the Infra Red frequencies and intensities for the computed nuclear hessian and the "projected" nuclear hessian. The VIB module projects out the translations and rotations of the nuclear hessian using the standard Eckart projection algorithm. It also computes the zero point energy for the molecular system based on the frequencies obtained from the projected hessian.

The default mass of each atom is used unless an alternative mass is provided via the geometry input or redefined using the vibrational module input. The default mass is the mass of the most abundant isotope of each element. If the abundance was roughly equal, the mass of the isotope with the longest half life was used.

In addition, the vibrational analysis is given at the default standard temperature of 298.15 degrees.

Vibrational Module Input

All input for the Vibrational Module is optional since the default definitions will compute the frequencies and IR intensities. The generic module input can begin with vib, freq, frequency and has the form:

Hessian File Reuse

By default the task <theory> frequencies directive will recompute the hessian. To reuse the previously computed hessian you need only specify reuse in the module input block. If you have stored the hessian in an alternate place you may redirect the reuse directive to that file by specifying the path to that file.

reuse /path_to_hessian_file

This will reuse your saved Hessian data but one caveat is that the geometry specification at the point where the hessian is computed must be the default "geometry" on the current run-time-data-base for the projection to work properly.

Redefining Masses of Elements

You may also modify the mass of a specific center or a group of centers via the input.

To modify the mass of a specific center you can simply use:

mass 3 4.00260324

which will set the mass of center 3 to 4.00260324 AMUs. The lexical index of centers is determined by the geometry object.

To modify all Hydrogen atoms in a molecule you may use the tag based mechanism:

mass hydrogen 2.014101779

The mass redefinitions always start with the default masses and change the masses in the order given in the input. Care must be taken to change the masses properly. For example, if you want all hydrogens to have the mass of Deuterium and the third hydrogen (which is the 6th atomic center) to have the mass of Tritium you must set the Deuterium masses first with the tag based mechanism and then set the 6th center's mass to that of Tritium using the lexical center index mechanism.

The mass redefinitions are not fully persistent on the run-time-data-base. Each input block that redefines masses will invalidate the mass definitions of the previous input block. For example,

```
freq
  reuse
  mass hydrogen 2.014101779
end
task scf frequencies
freq
  reuse
  mass oxygen 17.9991603
end
task scf frequencies
```

will use the new mass for all hydrogens in the first frequency analysis. The mass of the oxygen atoms will be redefined in the second frequency analysis but the hydrogen atoms will use the default mass. To get a modified oxygen and hydrogen analysis you would have to use:

```
freq
  reuse
  mass hydrogen 2.014101779
end
task scf frequencies
freq
  reuse
  mass hydrogen 2.014101779
  mass oxygen 17.9991603
end
task scf frequencies
```

Temp or Temperature

The "VIB" module can generate the vibrational analysis at various temperatures other than at standard room temperature. Either temp or temperature can be used to initiate this command.

To modify the temperature of the computation you can simply use:

temp 4 298.15 300.0 350.0 400.0

At this point, the temperatures are persistant and so the user must "reset" the temperature if the standard behavior is required after setting the temperatures in a previous "VIB" command, i.e.

temp 1 298.15

Animation

The "VIB" module also can generate mode animation input files in the standard xyz file format for graphics packages like RasMol or XMol There are scripts to automate this for RasMol in \$NWCHEM_TOP/contrib/rasmolmovie. Each mode will have 20 xyz files generated that cycle from the equilibrium geometry to 5 steps in the positive direction of the mode vector, back to 5 steps in the negative direction of the mode vector, and finally back to the equilibrium geometry. By default these files are not generated. To activate this mechanism simply use the following input directive

animate

anywhere in the frequency/vib input block.

Controlling the Step Size Along the Mode Vector

By default, the step size used is 0.15 a.u. which will give reliable animations for most systems. This can be changed via the input directive

animate real <step_size>

where <step_size> is the real number that is the magnitude of each step along the eigenvector of each nuclear hessian mode in atomic units.

Specifying filenames for animated normal modes

By default, normal modes will be stored in files that start with "freq.m-<mode number>". This is inconvenient if more than vibrational analysis is run in a single input file. To specify different filename for a particular vibrational analysis use the directive

filename <file_set_name> [overwrite]

where <file_set_name> is the name that will be prepended to the usual filenames. In addition the code by default requires all files to be new files. When the option "overwrite" is provided any pre-existing files will simply be overwritten.

An Example Input Deck

This example input deck will optimize the geometry for the given basis set, compute the frequencies for H_2O , H_2O at different temperatures, D_2O , HDO, and TDO.

```
start h2o
title Water
geometry units au autosym
 0
         0.00000000
                       0.00000000
                                     0.0000000
 Η
         0.00000000
                       1.93042809
                                    -1.10715266
 н
         0.00000000
                      -1.93042809
                                    -1.10715266
end
basis noprint
 H library sto-3g
 0 library sto-3g
end
scf; thresh 1e-6; end
driver; tight; end
task scf optimize
scf; thresh le-8; print none; end
task scf freq
freq
 reuse; temp 4 298.15 300.0 350.0 400.0
end
```

task scf freq

```
freq
  reuse; mass H 2.014101779
  temp 1 298.15
end
task scf freq
```

freq

```
reuse; mass 2 2.014101779
end
task scf freq
```

freq
 reuse; mass 2 2.014101779 ; mass 3 3.01604927
end
task scf freq

References

 Johnson, B.G. and Frisch, M.J. (1994) "An implementation of analytic second derivatives of the gradient-corrected density functional energy", *Journal of Chemical Physics* 100 7429-7442, doi: 10.1063/1.466887 (http://dx.doi.org/10.1063/1.466887)

Release65:Nudged Elastic Band (NEB) and Zero Temperature String Methods

__NOTITLE__

Nudged Elastic Band (NEB) method

The NEB module is an implementation of the nudged elastic band (NEB) method of Jonsson et al., and it is one of two drivers in NWChem that can be used to perform minimum energy path optimizations. NEB can be used at all levels of theory, including SCF, HF, DFT, PSPW, BAND, MP2, RIMP2, CCSD, TCE.

Input to the NEB modules is contained with the NEB block

NEB ... END

To run a NEB calculation the following the following task directives is used

```
TASK <theory> NEB
TASK <theory> NEB ignore
```

where <theory> is SCF, HF, DFT, PSPW, BAND, MP2, CCSD, TCE, etc.. The Task directive with the ignore option is recommended, otherwise NWChem will crash if the path is not

optimized in the allowed maximum number of iterations.

Optional input for this module is specified within the compound directive,

```
NEB
   NBEADS <integer nbeads default 5>
   KBEADS <float kbeads default 0.1>
   MAXITER <integer maxiter default 5>
   STEPSIZE <integer stepsize default 1.0>
   NHIST <integer nhist default 5>
   ALGORITHM <integer algorithm default 0>
   [loose | default | tight]
   GMAX <float gmax default 0.00045>
   GRMS <float grms default 0.00030>
   XMAX <float xmax default 0.00018>
   XMRS <float xmrs default 0.00012>
   [IMPOSE]
   [HASMIDDLE]
   [XYZ_PATH <string xyzfilename>]
   [RESET]
   [PRINT SHIFT <integer print shift default 0>]
END
```

The following list describes the input for the NEB block

- <nbeads> number of beads (or images) used to represent the path
- <kbeads> value for the NEB spring constant
- <maxiter> maximum number of NEB path optimizations to be performed
- <stepsize> value for the stepsize used in the optimization. Typically less than 1.
- <nhist> number of histories to use for quasi-Newton optimization (algorithm =0)
- LOOSE|DEFAULT|TIGHT options specifying thresholds for convergence
- <gmax> value for the maximum gradient used to determine convergence
- <grms> value for the root mean square gradient used to determine convergence
- <xmax> value for the maximum cartesian step used to determine convergence
- <xrmx> value for the root mean square cartesian step used to determine convergence
- <algorithm> 0: quasi-Newton Fixed Point optimization, 1: dampled Verlet optimization,
 2: refining conjugate gradient optimization
- IMPOSE if specified causes the initial geometries used to specify the path to be aligned with one another
- HASMIDDLE if specified causes the initial path to use the "midgeom" geometry to be used as the midpoint, i.e. the initial path is defined as a linear morphing from "geometry" --> "midgeom" --> "endgeom"
- XYZ_PATH if specified the initial path is defined from the sequence of geometries contained in <xyzfilename>
- RESET if specified causes the NEB optimization and path to be started from scratch
- <print_shift> setting the PRINT_SHIFT directive causes the path energies and geometries to be outputed every <print_shift> steps. The current path energies are appended to the file jobname.neb_epath and the current geometries are appended to the

file jobname.nebpath_"current iteration".xyz.

Setting up initial path

There are three different ways to define the initial path for NEB optimization.

• Linear interpolation between two geometries

The geometries in the path are defined by

$$\vec{R}_{xyz}^{i} = \vec{R}_{xyz}^{1} + \frac{i-1}{nbeads-1} (\vec{R}_{xyz}^{nbeads} - \vec{R}_{xyz}^{1}), \ for \ i = 1, nbeads$$

where the starting geometry (\vec{R}_{xyz}^1) is entered in the geometry block labeled "geometry", e.g.

```
geometry nocenter noautosym noautoz
```

0	0.00000000	-0.02293938	0.0000000
Н	0.00000000	0.55046969	0.75406534
Н	0.00000000	0.55046969	-0.75406534
en	d		

and the last geometry in the path (\vec{R}_{xyz}^{nbeads}) in entered in the geometry block label "endgeom", e.g.

```
geometry endgeom nocenter noautosym noautoz

0 0.00000000 0.02293938 0.00000000

H 0.00000000 -0.55046969 0.75406534

H 0.00000000 -0.55046969 -0.75406534

end
```

• Linear interpolation between three geometries

The geometries for this path are defined by

$$\vec{R}_{xyz}^{i} = \vec{R}_{xyz}^{1} + \frac{i-1}{nbeads/2 - 1} (\vec{R}_{xyz}^{nbeads/2} - \vec{R}_{xyz}^{1}), \text{ for } i = 1, nbeads/2$$

and

$$\vec{R}_{xyz}^i = \vec{R}_{xyz}^{nbeads/2} + \frac{i - nbeads/2}{nbeads/2 - 1} (\vec{R}_{xyz}^{nbeads} - \vec{R}_{xyz}^{nbeads/2}), \ for \ i = nbeads/2 + 1, nbeads/2 + 1$$

where the starting (\vec{R}_{xyz}^{1}), middle ($\vec{R}_{xyz}^{nbeads/2}$) and last (\vec{R}_{xyz}^{nbeads}) geometries are entered in the geometry blocks "geometry", "midgeom" and "endgeom" respectively, e.g.

geo	Jilletry	nocenter	noautosym	noauto	02
0	0.000	00000	-0.0229393	8	0.00000000
Н	0.0000	00000	0.5504696	9	0.75406534
Н	0.000	00000	0.5504696	9 - (0.75406534
end	t				

```
geometry midgeom nocenter noautosym noautoz
O 0.00000000 0.0000000 0.00000000
H 0.00000000 0.0000000 1.00000000
H 0.00000000 0.0000000 -1.00000000
end
```

geometry endgeom nocenter noautosym noautoz 0 0.00000000 0.02293938 0.00000000 H 0.00000000 -0.55046969 0.75406534 H 0.00000000 -0.55046969 -0.75406534 end

• Using xyz_path to explicitly input a path of geometries

The "xyz_path" option can also be used to define the initial path.

```
...
NEB
...
XYZ_PATH path.xyz
END
...
```

where path.xyz contains a list of geometries in xyz format, e.g.

	path.>	(yz		
	3			
energy=	-17.107207699	9285738		
0	0.00000	-0.022939	0.000000	
Н	0.00000	0.550469	0.754065	
Н	0.00000	0.550469	-0.754065	
	3			
energy=	-17.094903833	3074170		
0	-0.000003	-0.110080	-0.000000	
Н	-0.00000	0.273180	0.847029	
Н	-0.00000	0.273180	-0.847029	
	3			
energy=	-17.063823680	5395292		
0	-0.00000	-0.000080	-0.000000	
Н	0.00000	-0.000002	0.941236	
Н	0.00000	-0.000002	-0.941236	
	3			
energy=	-17.094944036	5147005		
0	-0.00000	0.110472	-0.000000	
Н	-0.00000	-0.273172	0.846957	
Н	-0.00000	-0.273172	-0.846957	
	3			
energy=	-17.107208157	7343706		
0	0.00000	0.022939	0.00000	
Н	0.00000	-0.550469	0.754065	
Н	0.00000	-0.550469	-0.754065	
path.xyz				
Convergence criteria

The defaults may be used, or the directives LOOSE, DEFAULT, or TIGHT specified to use standard sets of values, or the individual criteria adjusted. All criteria are in atomic units. GMAX and GRMS control the maximum and root mean square gradient in the coordinates. XMAX and XRMS control the maximum and root mean square of the Cartesian step.

	L00SE	DEFAULT	TIGHT
GMAX	0.0045d0	0.00045	0.000015
GRMS	0.0030d0	0.00030	0.00001
XMAX	0.0054d0	0.00180	0.00006
XRMS	0.0036d0	0.00120	0.00004

NEB Tutorial 1: H2O Inversion

(input:Media:h2o-neb.nw, output:Media:h2o-neb.nwout, datafiles: Media:h2o-neb.neb_epath.dat Media:h2o-neb.neb_final_epath.dat)

(xyzfiles: Media: h2o-neb.nebpath_000001.xyz Media: h2o-neb.nebpath_000005.xyz Media: h2o-neb.nebpath_000010.xyz Media: h2o-neb.nebpath_000020.xyz Media: h2o-neb.nebpath final.xyz)

```
Title "H20 inversion calculation"
echo
start h2o-neb
memory 1600 mb
permanent_dir ./perm2
scratch dir
                 ./perm2
geometry nocenter noautosym noautoz
0 0.0000000
                 -0.02293938
                                 0.0000000
H 0.0000000
                  0.55046969
                                 0.75406534
H 0.0000000
                  0.55046969
                                -0.75406534
end
geometry endgeom nocenter noautosym noautoz
0 0.0000000
                  0.02293938
                                 0.0000000
H 0.0000000
                                 0.75406534
                 -0.55046969
H 0.0000000
                 -0.55046969
                                -0.75406534
end
#### Gaussian DFT ####
basis
* library 3-21G
end
dft
  xc b3lyp
  maxiter 5001
  cgmin
end
```

neb nbeads 10 kbeads 1.0 maxiter 10 stepsize 0.10 print_shift 1 end task dft neb ignore neb # increase the number of images nbeads 20 kbeads 1.0

kbeads 1.0 stepsize 1.0 maxiter 30 loose end task dft neb ignore

After each optimization step the path energies are outputed as follows

neb: Path Energy #		9
neb:	1	-75.970000166349976
neb:	2	-75.973958450556779
neb:	3	-75.973964391052448
neb:	4	-75.973965560274110
neb:	5	-75.973961077512683
neb:	6	-75.973087554095144
neb:	7	-75.965847261117744
neb:	8	-75.950292780255126
neb:	9	-75.932932759963109
neb:	10	-75.921912278179292
neb:	11	-75.921834552460439
neb:	12	-75.932680002200939
neb:	13	-75.949868818688529
neb:	14	-75.965372754426866
neb:	15	-75.972788885848303
neb:	16	-75.973958649400714
neb:	17	-75.973965255113598
neb:	18	-75.973964962774133
neb:	19	-75.973959526041568
neb:	20	-75.970000163960066

Another way to keep track of the optimization process is to run the following grep command on the output file.

[WE24397:NWChem/NEB/Example2] bylaska% grep @ h2o-neb.nwout @neb @neb NEB Method @neb algorithm = 0 @neb maxiter = 10 @neb nbeads = 10 5 @neb nhist = @neb natoms 3 = @neb stepsize = 0.100E+01 @neb trust = 0.100E+00 @neb kbeads = 0.100E+00 @neb Gmax tolerance = 0.450E-03 @neb Grms tolerance = 0.300E-03 @neb Xmax tolerance = 0.180E-03 @neb Xrms tolerance = 0.120E-03 @neb @neb Step Intrinsic E Mid-Point E Minimum E Maximum E Gmax Grms Xrms Xmax Walltime @neb ---- ------75.921109 -75.970632 -75.921109 1 -75.951572 @neb 0.55875 0.01606 0.14221 1.54029 454.9 -75.972590 @neb 2 -75.953755 -75,923180 -75.923177 0.38930 0.01116 0.01588 0.45644 624.4 @neb 3 -75.956726 -75.924391 -75.972861 -75.924387 0.25587 0.00961 0.03673 0.83118 805.2 @neb 4 -75.957861 -75.924279 -75.973059 -75.924275 0.23572 0.00894 0.01793 0.24399 971.8 @neb 5 -75.959613 -75.925045 -75.973869 -75.925036 0.10257 0.00464 0.03197 0.20350 1152.8 -75.925503 -75.973957 @neb 6 -75.959964 -75.925486 0.04762 0.00196 0.00905 0.10433 1316.4 -75.925822 @neb 7 -75.960068 -75.973956 -75.925791 0.03897 0.00141 0.00308 0.04432 1519.9 @neb 8 -75.960091 -75.925914 -75.973959 -75.925877 0.03707 0.00127 0.00070 0.01691 2055.8 @neb 9 -75.960129 -75.926078 -75.973962 -75.926028 0.03353 0.00108 0.00127 0.03707 2297.2 -75,926142 @neb 10 -75.960142 -75.973963 -75.926085 0.03199 0.00101 0.00054 0.00420 2756.6 @neb NEB calculation not converged @neb @neb NEB Method @neb algorithm 0 = @neb maxiter = 30 @neb nbeads = 20 @neb nhist 5 = @neb natoms 3 = @neb stepsize = 0.100E+01 @neb trust = 0.100E+00@neb kbeads = 0.100E+01

@neb Gmax tolerance = 0.450E-02 @neb Grms tolerance = 0.300E-02 @neb Xmax tolerance = 0.540E-02 @neb Xrms tolerance = 0.360E-02 @neb @neb Step Intrinsic E Mid-Point E Minimum E Maximum E Gmax Grms Xrms Xmax Walltime @neb ---- -----@neb 1 -75.960225 -75.921704 -75.973965 -75.921669 0.24799 0.00398 0.00272 0.08741 3966.5 @neb 2 -75.960339 -75.921782 -75.973965 -75.921745 0.24794 0.00328 0.00199 0.12148 5023.2 @neb 3 -75.960424 -75.921742 -75.973965 -75.921701 0.19390 0.00286 0.00164 0.08342 5741.4 @neb 4 -75.960494 -75.921849 -75.973965 -75.921804 0.19681 0.00266 0.00143 0.09030 6079.7 -75.960646 -75.921874 @neb 5 -75.973965 -75.921820 0.17459 0.00240 0.00241 0.22047 6751.5 @neb 6 -75.960674 -75.921856 -75.973965 -75.921797 0.14246 0.00165 0.00060 0.00256 7572.3 @neb 7 -75.960724 -75.921884 -75.973966 -75.921817 0.13004 0.00153 0.00082 0.05401 7893.3 -75.960747 @neb 8 -75.921892 -75.973966 -75.921822 0.12809 0.00149 0.00038 0.00237 8631.2 @neb 9 -75.960792 -75.921912 -75.973966 -75.9218350.12267 0.00142 0.00075 0.05081 9222.0 @neb 10 -75.960813 -75.921923 -75.973966 -75.921841 0.11902 0.00138 0.00035 0.00212 10163.2 -75.960834 @neb 11 -75.921934 -75.973966 -75.9218460.11569 0.00135 0.00035 0.00203 10478.3 @neb 12 -75.961060 -75.922060 -75.973966 -75.9218890.07709 0.00104 0.00365 0.30944 10863.8 @neb 13 -75.961255 -75.922186 -75.973966 -75.921919 0.04600 0.00087 0.00309 0.19999 11357.0 @neb 14 -75.961405 -75.922286 -75.973966 -75.9219270.03549 0.00079 0.00244 0.03857 11860.0 @neb NEB calculation converged

Zero Temperature String Method

The STRING module is an implementation of the zero temperature string method of vanden Eijden et al., and it is one of two drivers in NWChem that can be used to perform minimum energy path optimizations. STRING can be used at all levels of theory, including SCF, HF, DFT, PSPW, BAND, MP2, RIMP2, CCSD, TCE.

Input to the STRING module is contained with the STRING block

```
STRING
...
END
```

To run a STRING calculation the following the following task directives is used

TASK <theory> STRING TASK <theory> STRING ignore

where <theory> is SCF, HF, DFT, PSPW, BAND, MP2, CCSD, TCE, etc.. The Task directive with the ignore option is recommended, otherwise NWChem will crash if the path is not optimized in the allowed maximum number of iterations.

Optional input for this module is specified within the compound directive,

```
STRING
   NBEADS <integer nbeads default 5>
   MAXITER <integer maxiter default 5>
   STEPSIZE <integer stepsize default 1.0>
   NHIST <integer nhist default 5>
   INTERPOL <integer algorithm default 1>
   FREEZE1 <logical freezel default .false.>
   FREEZEN <logical freezen default .false.>
   TOL <float tol default 0.00045>
   [IMPOSE]
   [HASMIDDLE]
   [XYZ_PATH <string xyzfilename>]
   [RESET]
   PRINT_SHIFT <integer print_shift default 0>
END
```

The following list describes the input for the NEB block

- <nbeads> number of beads (or images) used to represent the path
- <maxiter> maximum number of NEB path optimizations to be performed
- <stepsize> value for the stepsize used in the optimization. Typically less than 1.
- <nhist> number of histories to use for quasi-Newton optimization (algorithm =0)
- <tol> value for the maximum gradient used to determine convergence
- <freeze1> .true.: first bead of simulation frozen, .false.:first bead of simulation not frozen.
- <freezen> .true.:last bead of simulation frozen, .false.:last bead of simulation not frozen
- <interpol> 1: linear, 2: spline, 3: Akima spline

- IMPOSE if specified causes the initial geometries used to specify the path to be aligned with one another
- HASMIDDLE if specified causes the initial path to use the "midgeom" geometry to be used as the midpoint, i.e. the initial path is defined as a linear morphing from "geometry" --> "midgeom" --> "endgeom"
- XYZ_PATH if specified the initial path is defined from the sequence of geometries contained in <xyzfilename>
- RESET if specified causes the NEB optimization and path to be started from scratch
- <print_shift> setting the PRINT_SHIFT directive causes the path energies and geometries to be outputed every <print_shift> steps. The current path energies are appended to the file jobname.neb_epath and the current geometries are appended to the file jobname.nebpath_"current iteration".xyz.

Setting up the initial path

There are three different ways to define the initial path for NEB optimization.

• Linear interpolation between two geometries

The geometries in the path are defined by

$$\vec{R}_{xyz}^{i} = \vec{R}_{xyz}^{1} + \frac{i-1}{nbeads-1} (\vec{R}_{xyz}^{nbeads} - \vec{R}_{xyz}^{1}), \ for \ i = 1, nbeads$$

where the starting geometry (\vec{R}_{xyz}^1) is entered in the geometry block labeled "geometry", e.g.

```
geometry nocenter noautosym noautoz
```

0	0.00000000	-0.02293938	0.0000000
Н	0.00000000	0.55046969	0.75406534
Н	0.00000000	0.55046969	-0.75406534
end	b		

and the last geometry in the path (\vec{R}_{xyz}^{nbeads}) in entered in the geometry block label "endgeom", e.g.

geometry endgeom nocenter noautosym noautoz O 0.00000000 0.02293938 0.00000000 H 0.00000000 -0.55046969 0.75406534 H 0.00000000 -0.55046969 -0.75406534 end

• Linear interpolation between three geometries

The geometries for this path are defined by

 $\vec{R}_{xyz}^{i} = \vec{R}_{xyz}^{1} + \frac{i-1}{nbeads/2 - 1} (\vec{R}_{xyz}^{nbeads/2} - \vec{R}_{xyz}^{1}), \text{ for } i = 1, nbeads/2$ and

$$\vec{R}_{xyz}^i = \vec{R}_{xyz}^{nbeads/2} + \frac{i - nbeads/2}{nbeads/2 - 1} (\vec{R}_{xyz}^{nbeads} - \vec{R}_{xyz}^{nbeads/2}), \ for \ i = nbeads/2 + 1, nbeads/2 + 1$$

where the starting (\vec{R}_{xyz}^{1}), middle ($\vec{R}_{xyz}^{nbeads/2}$) and last (\vec{R}_{xyz}^{nbeads}) geometries are entered in the geometry blocks "geometry", "midgeom" and "endgeom" respectively, e.g.

```
geometry nocenter noautosym noautoz
0 0.0000000
                -0.02293938
                               0.0000000
H 0.0000000
                 0.55046969
                               0.75406534
H 0.0000000
                 0.55046969
                               -0.75406534
end
geometry midgeom nocenter noautosym noautoz
0 0.0000000
                 0.00000000
                               0.0000000
H 0.0000000
                 0.00000000
                               1.00000000
H 0.0000000
                 0.00000000
                              -1.00000000
end
geometry endgeom nocenter noautosym noautoz
0 0.0000000
                0.02293938
                               0.0000000
H 0.0000000
                -0.55046969
                               0.75406534
H 0.0000000
                -0.55046969
                              -0.75406534
end
```

• Using xyz_path to explicitly input a path of geometries

The "xyz_path" option can also be used to define the initial path, e.g.

```
...
STRING
...
XYZ_PATH path.xyz
END
...
```

String Tutorial 1:HCN --> HNC path optimization

```
(input:Media:HCN-string1.nw, output:Media:HCN-string1.nwout, datafiles:
Media:HCN-string1.string_epath.dat Media:HCN-string1.string_final_epath.dat )
(xyzfiles: Media: HCN-string1.stringpath_000001.xyz Media:
HCN-string1.stringpath_000005.xyz Media: HCN-string1.stringpath_000010.xyz Media:
HCN-string1.stringpath_000020.xyz Media: HCN-string1.stringpath_000030.xyz Media:
```

```
HCN-string1.stringpath final.xyz)
```

In this example, the path energy for the reaction HCN --> HNC is calculated.

```
#
# The initial path has the Carbon moving through the Nitrogen.
# So for this simulation to work that atom avoidance code needs to
work.
# Because the initial path is so stiff the wavefunction optimizer needs
to requires
# lots of iterations during the early stages of the path optimization.
#
#
Title "HCN --> HNC Zero-Temperature String Simulation"
echo
start hcn-hnc-dft
```

```
permanent_dir ./perm
scratch dir ./perm
geometry noautoz noautosym
С
          0.00000000
                         0.00000000
                                      -0.49484657
Ν
          0.0000000
                         0.0000000
                                        0.64616359
Н
          0.00000000
                         0.00000000
                                       -1.56151539
end
geometry endgeom noautoz noautosym
          0.00000000
С
                         0.00000000
                                        0.73225318
Ν
          0.00000000
                         0.0000000
                                       -0.42552059
Н
          0.00000000
                         0.00000000
                                       -1.42351006
end
#### Gaussian DFT ####
basis
* library 3-21G
end
dft
  xc b3lyp
  maxiter 501
end
string
  nhist 10
  nbeads 10
  maxiter 10
  stepsize 0.10
  print shift 1
  # don't allow the end points of the path to move
  freezel .true.
  freezeN .true.
end
task dft string ignore
string
  # increase the number of images
  nbeads 20
  maxiter 20
  # allow the end points of the path to move
  freezel .false.
  freezeN .false.
end
task dft string ignore
```

After each optimization step the path energies are outputed as follows

string:	Path	Energy	#		2
string:				1	-92.906682492969779
string:				2	-92.743446565848473
string:				3	-92.751945829987775
string:				4	-92.756507971834026
string:				5	-92.726984154346979
string:				6	-92.701651474021503
string:				7	-92.672613497521183
string:				8	-92.825096796032099
string:				9	-92.716422030970662
string:				10	-92.881713271394148

Another way to keep track of the optimization process is to run the following grep command on the output file.

[WE24397:NWChem/NEB/Example2] bylaska% grep @ HCN-dft.out @zts @zts String method. @zts Temperature = 0.00000 @zts Covergence Tolerance = 0.00010 @zts Step Size 0.10000 = @zts Maximum Time Steps = 10 @zts Number of replicas = 10 @zts Number of histories = 10 @zts String Interpolator = 1 @zts First Replica = frozen @zts Last Replica = frozen @zts @zts Step xrms xmax E start E middle E max end E average @zts 1 0.460700 2.602234 -92.9066825 -83.4767173 -92.8817133 -83.4767173 -91.6169775 2 0.862226 5.405612 -92.9066825 -92.3028437 @zts -92.8817133 -92.3028437 -92.6631831 @zts 3 0.105285 0.530157 -92.9066825 -92.3289676 -92.3289676 -92.6702949 -92.8817133 @zts 4 0.134687 0.740991 -92.9066825 -92.3512584 -92.8817133 -92.3512584 -92.6821949 5 0.117113 0.916210 -92.9066825 @zts -92.3767826 -92.8817133 -92.3767826 -92.6899234 6 0.124464 0.844439 -92.9066825 -92.4195957 @zts -92.4195957 -92.8817133 -92.7045117 @zts 7 0.092105 0.731434 -92.9066825 -92.4510785 -92,4510785 -92,7156403 -92.8817133 8 0.049227 0.330651 @zts -92.9066825 -92.4690983 -92.8817133 -92.4690983 -92.7288274 -92.4827444 @zts 9 0.032819 0.177356 -92,9066825 -92.8817133 -92.4827444 -92.7344806

Е

10 0.076249 0.444246 @zts -92.9066825 -92.4930430 -92.8817133 -92.4930430 -92.7381477 @zts The string calculation failed to converge @zts Bead number 1 Potential Energy = -92.906682487840 @zts Bead number 2 Potential Energy = -92.850640135623 @zts Bead number 3 Potential Energy = -92.819370566454 @zts Bead number 4 Potential Energy = -92.680821335407 @zts Bead number 5 Potential Energy = -92.505231918657@zts Bead number 6 Potential Energy = -92.493042984646 @zts Bead number 7 Potential Energy = -92.637367419044@zts Bead number 8 Potential Energy = -92.775376312982@zts Bead number 9 Potential Energy = -92.831230727986 @zts Bead number 10 Potential Energy = -92.881713271394 @zts @zts String method. @zts Temperature = 0.00000 @zts Covergence Tolerance = 0.00010 @zts Step Size 0.10000 = @zts Maximum Time Steps = 20 @zts Number of replicas 20 = @zts Number of histories = 10 @zts String Interpolator = 1 @zts First Replica = moves @zts Last Replica = moves @zts @zts Step xrms xmax E start E middle end E max E average @zts 1 1.039809 5.039486 -92.9071472 -92.4998400 -92.4998400 -92.8820628 -92.7500136 @zts 2 0.192562 0.999019 -92.9073958 -92.5259828 -92.8821500 -92.5259828 -92.7624061 3 0.244943 1.236459 -92.9075306 @zts -92.5735140 -92.8821223 -92.5735140 -92.7816692 @zts 4 0.207031 1.093667 -92.9075888 -92.6229190 -92.6154678 -92.8821177 -92.7979112 @zts 5 0.056648 0.293829 -92.9075975 -92.6672565 -92.8821033 -92.6507897 -92.8101666 6 0.078950 0.555245 -92.9076044 @zts -92.7245122 -92.8822536 -92.7014407 -92.8241914 7 0.065564 0.521110 -92.7539982 @zts -92.9076101 -92.7376310 -92.8822915 -92.8326007 @zts 8 0.050188 0.319477 -92.9076113 -92.7695725 -92,7612604 -92.8378464 -92.8824219 9 0.055301 0.322130 @zts -92.9076168 -92.7754581-92.8825732 -92.7740099 -92.8408900 -92,7775695 @zts 10 0.038769 0.195102 -92,9076177 -92.8826652 -92.7775695 -92.8425440

Е

@zts 1	1 0.064900	9 0.273480	-92.907	6215	-92.7800330
-92.882/1	/5 -92	. /800330	-92.84435	/4	
@zts 1	2 0.062593	3 0.266337	-92.907	6224	-92.7823972
-92.88269	93 -92	.7823972	-92.84589	76	
@zts 1	3 0.20543	7 0.948190	-92.907	6243	-92.7842034
-92.88264	08 -92	.7842034	-92.84698	10	
@zts 1	4 0.015025	5 0.068924	-92.907	6247	-92.7844362
-92.88265	36 - 92	.7844362	-92.84722	27	
@zts 1	5 0.129208	8 0.602636	-92.907	6254	-92.7849856
-92.88266	76 -92	.7849856	-92.84771	69	
@zts 1	6 0.013479	9 0.056561	-92.907	6260	-92.7855201
-92.88267	83 - 92	.7855201	-92.848162	26	
@zts 1	7 0.472858	8 2.220715	-92.907	6271	-92.7878088
-92.88269	13 - 92	.7878088	-92.84979	19	
@zts 1	8 0.162617	7 0.766201	-92.907	6273	-92.7879912
-92.88269	34 - 92	.7879912	-92.84991	97	
@zts 1	9 0.013204	4 0.060562	-92.907	6276	-92.7885097
-92.88269	94 - 92	.7885097	-92.85026	75	
@zts 2	0 0.718205	5 3.423813	-92.907	6278	-92.7905066
-92.88270	09 - 92	.7895258	-92.85148	63	
@zts The	string ca	lculation [.]	failed to c	onverge	
@zts Bead	number	1 Poten	tial Energy	=	-92.907627751439
@zts Bead	number	2 Poten	tial Energy	=	-92.905047596626
@zts Bead	number	3 Poten	tial Energy	=	-92.897944354806
@zts Bead	number	4 Poten	tial Energy	=	-92.887494117302
@zts Bead	number	5 Poten	tial Energy	=	-92.874059841858
@zts Bead	number	6 Poten	tial Energy	=	-92.857382758537
@zts Bead	number	7 Poten	tial Energy	=	-92.837207959079
@zts Bead	number	8 Poten	tial Energy	=	-92.815902497386
@zts Bead	number	9 Poten	tial Energy	=	-92.798474907121
@zts Bead	number	10 Poten	tial Energy	=	-92.789525765222
@zts Bead	number	11 Poten	tial Energy	=	-92.790506632257
@zts Bead	number	12 Poten	tial Energy	=	-92.799861168980
@zts Bead	number	13 Poten	tial Energy	=	-92.814252430183
@zts Bead	number	14 Poten	tial Energy	=	-92.830704548760
@zts Bead	number	15 Poten	tial Energy	=	-92.847248091296
@zts Bead	number	16 Poten	tial Energy	=	-92.861557132126
@zts Bead	number	17 Poten	tial Energy	=	-92.871838446832
@zts Bead	number	18 Poten	tial Energy	=	-92.878543965696
@zts Bead	number	19 Poten	tial Energy	=	-92.881844751735
@zts Bead	number	20 Poten	tial Energy	=	-92.882700859222

A plotting program (e.g. gnuplot, xmgrace) can be used to look at final path as well as the the convergence of the path i.e.,

[WE24397:NEB/Example2/perm] bylaska% gnuplot

G N U P L O T Version 4.6 patchlevel 0 last modified 2012-03-04

Build System: Darwin x86_64 Copyright (C) 1986-1993, 1998, 2004, 2007-2012 Thomas Williams, Colin Kelley and many others gnuplot home: http://www.gnuplot.info faq, bugs, etc: type "help FAQ" immediate help: type "help" (plot window: hit 'h') Terminal type set to 'aqua' gnuplot> set xlabel "Reaction Coordinate" gnuplot> set ylabel "Energy (kcal/mol)" gnuplot> set yrange [0:100] gnuplot> set grid gnuplot> set style data linespoints gnuplot> plot "hcn-hnc-dft.string epath" using 1:(\$2+92.908)*27.2116*23.06,"hcn-hnc-dft.string final epath" using 1:(\$2+92.908)*27.2116*23.06 gnuplot>

String Tutorial 2:

Title "2Si04H4 --> H303Si-0-Si03H3 + H20" echo start sio4h4-dimer

memory 1800 mb

```
permanent_dir ./perm
scratch_dir ./perm
```

```
geometry noautoz noautosym
```

•	•	•	
Si	-3.90592	-0.11789	0.03791
0	-2.32450	-0.24327	-0.05259
0	-4.45956	-1.13247	1.13159
0	-4.53584	-0.45118	-1.38472
0	-4.28179	1.37363	0.44838
Si	1.27960	0.06912	0.14555
0	2.85122	0.23514	0.32761
0	0.54278	0.38513	1.52092
0	0.94484	-1.42248	-0.29913
0	0.75605	1.07390	-0.97272
Н	-1.66762	-0.74425	-0.29362
Н	-4.05734	2.06481	0.90983
Н	-4.30983	-1.85807	1.57116
Н	-4.43621	-0.88060	-2.12508
Н	3.59374	-0.16315	0.50572
Н	0.36896	0.10990	2.31839
Н	0.53993	-2.15495	-0.09488
Н	0.43207	1.85525	-1.13531

end	
Ellu	

geometry Si	endgeom noaut	oz noautosym 0.18232	-0.24945		
0	-1 50707	0 23823	-0 53062		
0	-3 36758	-0 03058	0.35002		
0	-3 83058	-0.99090	-1 50101		
0	-3 57003	1 50735	0 27/71		
0 Si	-0.05186	0 25441	0.27471		
0	0.00100	-0 58168	-0.80206		
0	-0 10001	-0.30100	1 55838		
0	1 41035	-3 75872	1 22031		
0	0 47135	1 75206	0 24209		
н	1 03624	-4 62405	0.24205		
н	-3 81554	2 06102	0.92020		
н	-3 97094	-1 38510	1 26383		
Н	-4 39754	-0 73964	-1 96563		
Н	1.45990	-0.57144	-1.49361		
Н	-0 44444	-0 37536	2 34765		
Н	2 15751	-4 00850	1 82933		
Н	0 77180	2 44229	-0 17616		
end	0.77100	2144225	0.1/010		
cina					
nwpw simulat SC 1 end cutoff lmbfgs	tion_cell 18.0 30.0				
enu					
string nhist 10 nbeads 10 maxiter 10 stepsize 0.10 print_shift 1					
<pre># don't freezel freezeN end task pspw</pre>	<pre># don't allow the end points of the path to move freeze1 .true. freezeN .true. end task pspw string ignore</pre>				
string # increase the number of images nbeads 20 maxiter 20					

allow the end points of the path to move freezel .false. freezeN .false. end task pspw string ignore

String Tutorial 3: Combining NEB and String path optimizations

Electronic Structure Analysis

Release65:Properties

__NOTITLE__

Properties

Properties can be calculated for both the Hartree-Fock and DFT wave functions. The properties that are available are:

- Natural bond analysis
- Dipole, quadrupole, and octupole moment
- Mulliken population analysis and bond order analysis
- Electrostatic potential (diamagnetic shielding) at nuclei
- Electric field and field gradient at nuclei
- Electric field gradients with relativistic effects
- Electron and spin density at nuclei
- NMR shielding (GIAO method)
- NMR hyperfine coupling (Fermi-Contact and Spin-Dipole expectation values)
- NMR indirect spin-spin coupling
- Gshift
- Response
- Raman

The properties module is started when the task directive TASK <theory> property is defined in the user input file. The input format has the form:

```
PROPERTY
  [property keyword]
  [CENTER ((com || coc || origin || arb <real x y z>) default
coc)]
  END
```

Most of the properties can be computed for Hartree-Fock (closed-shell RHF, open-shell ROHF, and open-shell UHF), and DFT (closed-shell and open-shell spin unrestricted) wavefunctions. The NMR hyperfine and indirect spin-spin coupling require a UHF or ODFT wave function.

Property keywords

Each property can be requested by defining one of the following keywords:

NBOFILE DIPOLE QUADRUPOLE OCTUPOLE MULLIKEN

```
ESP

EFIELD

EFIELDGRAD

EFIELDGRADZ4

GSHIFT

ELECTRONDENSITY

HYPERFINE

SHIELDING [<integer> number_of_atoms <integer> atom_list]

SPINSPIN [<integer> number_of_pairs <integer> pair_list]

ALL
```

The "ALL" keyword generates all currently available properties.

Both the NMR shielding and spin-spin coupling have additional optional parameters that can be defined in the input. For the shielding the user can define the number of atoms for which the shielding tensor should be calculated, followed by the list of specific atom centers. In the case of spin-spin coupling the number of atom pairs, followed by the atom pairs, can be defined (i.e., spinspin 1 1 2 will calculate the coupling for one pair, and the coupling will be between atoms 1 and 2).

For both the NMR spin-spin and hyperfine coupling the isotope that has the highest abundance and has spin, will be chosen for each atom under consideration.

Calculating EPR and paramagnetic NMR parameters: The following tutorial illustrates how to combine the hyperfine, gshift and shielding to calculate the EPR and paramagnetic NMR parameters of an open-shell system.

For theoretical and computational details, please refer to the following references:

- J. Autschbach, S. Patchkovskii, B. Pritchard, "Calculation of Hyperfine Tensors and Paramagnetic NMR Shifts Using the Relativistic Zeroth-Order Regular Approximation and Density Functional Theory", Journal of Chemical Theory and Computation 7, 2175 (2011)
- 2. F. Aquino, B. Pritchard, J. Autschbach, "Scalar relativistic computations and localized orbital analysis of nuclear hyperfine coupling and paramagnetic NMR chemical shifts", J. Chem. Theory Comput. 2012, 8, 598–609.
- F. Aquino, N. Govind, J. Autschbach, "Scalar relativistic computations of nuclear magnetic shielding and g-shifts with the zeroth-order regular approximation and range-separated hybrid density functionals", J. Chem. Theory Comput. 2011, 7, 3278–3292.

The user also has the option to choose the center of expansion for the dipole, quadrupole, and octupole calculations.

[CENTER ((com || coc || origin || arb <real x y z>) default coc)]

com is the center of mass, coc is the center of charge, origin is (0.0, 0.0, 0.0) and arb is any arbitrary point which must be accompanied by the coordinated to be used. Currently the x, y, and z coordinates must be given in the same units as UNITS in GEOMETRY.

Response calculations can be calculated as follows:

```
property
response 1 7.73178E-2 # response order and frequency in hartree
```

velocity # use modified velocity gauge for electric dipole end

Response calculations are currently supported only for order 1 (linear response), single frequency, electric field and mixed electric-magnetic field perturbations. The output consists of the electric polarizability and optical rotation tensors (alpha, beta for optical rotation) in atomic units. If the 'velocity' keyword is absent, the dipole-length form will be used for the dipole integrals. This is a bit faster. The isotropic optical rotation is origin independent when using the velocity gauge. Works with HF and density functionals for which linear response kernels are implemented in NWChem.

Please refer to the following papers for further details:

- 1. J. Autschbach, Comp. Lett. 3, 131(2007)
- 2. M. Krykunov, J. Autschbach, J. Chem. Phys. 123, 114103 (2005)
- 3. J.R. Hammond, N. Govind, K. Kowalski, J. Autschbach, S.S. Xantheas, J. Chem. Phys. 131, 214103 (2009)

Raman calculations can be performed by specifying the Raman block. These calculations are performed in conjunction with polarizability calculations.

RAMAN

```
[ (NORMAL | | RESONANCE) default NORMAL ]
[ (LORENTZIAN | | GAUSSIAN) default LORENTZIAN ]
[ LOW <double low default 0.0> ]
[ HIGH <double high default 'highest normal mode'> ]
[ FIRST <integer first default '7'> ]
[ LAST < integer last default 'number of normal modes' > ]
[ WIDTH <double width default 20.0> ]
[ DQ!<double dq default 0.01> ]
END
task dft raman
```

or

task dft raman numerical

Sample input block:

property response 1 8.8559E-2 damping 0.007 end raman normal lorentzian end

Nbofile

The keyword NBOFILE does not execute the Natural Bond Analysis code, but simply creates an input file to be used as input to the stand-alone NBO code. All other properties are calculated upon request.

Following the successful completion of an electronic structure calculation, a Natural Bond Orbital (NBO) analysis may be carried out by providing the keyword NBOFILE in the PROPERTY directive. NWChem will query the rtdb and construct an ASCII file, <file_prefix>.gen, that may be used as input to the stand alone version of the NBO program, gennbo. <file_prefix> is equal to string following the START directive. The input deck may be edited to provide additional options to the NBO calculation, (see the NBO user's manual for details.)

Users that have their own NBO version can compile and link the code into the NWChem software. See the INSTALL file in the source for details.

Gaussian Cube Files

Electrostatic potential (keyword *esp*) and the magnitude of the electric field (keyword *efield*) on the grid can be generated in the form of the Gaussian Cube File. This behavior is triggered by the inclusion of grid keyword as shown below

grid [pad dx [dy dz]] [rmax x y z] [rmin x y z] [ngrid nx [ny nz]]
[output filename]

where

- pad dx [dy dz] specifies amount of padding (in angstroms) in x,y, and z dimensions that will be applied in the automatic construction of the rectangular grid volume based on the geometry of the system. If only one number is provided then the same amount of padding will be applied in all dimensions. The default setting is 4 angstrom padding in all dimensions.
- rmin x y z specifies the coordinates (in angstroms) of the minimum corner of the rectangular grid volume. This will override any padding in this direction.
- rmax x y z specifies the coordinates (in angstroms) of the maximum corner of the rectangular grid volume. This will override any padding in this direction.
- ngrid nx [ny nz] specifies number of grid points along each dimension. If only one number is provided then the same number of grid points are assumed all dimensions. In the absence of this directive the number of grid points would be computed such that grid spacing will be close to 0.2 angstrom, but not exceeding 50 grid points in either dimension.
- output filename specifies name of the output cube file. The default behavior is to use <prefix>-elp.cube or <prefix>-elf.cube file names for electrostatic potential or electric field respectively. Here <prefix> denotes the system name as specified in start directive. Note that Gaussian cube files will be written in the run directory (where the input file resides).

Example input file

echo start nacl

```
permanent_dir ./perm
scratch dir ./data
memory total 2000 Mb
geometry nocenter noautoz noautosym
                      -0.00000000
                                      0.00000000
                                                    -0.70428494
Na
 Cl
                       0.00000000
                                     -0.00000000
                                                     1.70428494
end
basis
  * library 6-31g*
end
#electric field would be written out to nacl.elf.cube file
#with
#ngrid
           : 20 20 20
           : 4.000
#rmax
                     4.000
                                 5.704
           :-4.000
#rmin
                    -4.000
                               -4.704
property
efield
grid pad 4.0 ngrid 20
end
task dft property
#electrostatic potential would be written to esp-pad.cube file
# with the same parameters as above
property
esp
grid pad 4.0 ngrid 20 output esp-pad.cube
end
task dft property
#illustrating explicit specification of minumum box coordinates
property
esp
grid pad 4.0 rmax 4.000 4.000 5.704 ngrid 20
end
```

task dft property

Release65:ESP

__NOTITLE__

Electrostatic potentials

The NWChem Electrostatic Potential (ESP) module derives partial atomic charges that fit the quantum mechanical electrostatic potential on selected grid points.

The ESP module is specified by the NWChem task directive

```
task esp
```

The input for the module is taken from the ESP input block

ESP

... END

Grid specification

The grid points for which the quantum mechanical electrostatic potential is evaluated and used in the fitting procedure of the partial atomic charges all lie outside the van der Waals radius of the atoms and within a cutoff distance from the atomic centers. The following input parameters determine the selection of grid points.

• If a grid file is found, the grid will be read from that file. If no grid file is found, or the keyword

recalculate

is given, the grid and the electrostatic potential is recalculated.

• The extent of the grid is determined by

range <real rcut>

where rcut is the maximum distance in nm between a grid point and any of the atomic centers.

When omitted, a default value for rcut of 0.3 nm is used.

• The grid spacing is specified by

spacing <real spac>

where spac is the grid spacing in \$nm\$ for the regularly spaced grid points.

If not specified, a default spacing of 0.05 nm is used.

• The van der Waals radius of an element can be specified by

radius <integer iatnum> <real atrad>

where iatnum is the atomic number for which a van der Waals radius of atrad in nm will be used in

the grid point determination. Default values will be used for

atoms not specified.

• The probe radius in nm determining the envelope around the molecule is specified by

probe <real probe default 0.07>

• The distance between atomic center and probe center can be multiplied by a constant factor specified by

factor <real factor default 1.0>

All grid points are discarded that lie within a distance factor*(radius(i)+probe) from any atom *i*.

• Schwarz screening is applied using

```
screen [<real scrtol default 1.0D-5>]
```

Constraints

Additional constraints to the partial atomic charges can be imposed during the fitting procedure.

• The net charge of a subset of atoms can be constrained using

constrain <real charge> {<integer iatom>}

where charge is the net charge of the set of atoms {iatom}. A negative atom number iatom can be

used to specify that the partial charge of that atom is substracted in the sum for the set.

• The net charge of a sequence of atoms can be constrained using

```
constrain <real charge> <integer iatom> through <integer jatom>
```

where charge is the net charge of the set of atoms {[iatom:jatom]}.

• A group of atoms can be constrained to have the same charge with

constrain equal {<integer iatom>}

• The individual charge of a group of atoms can be constrained to be equal to those of a second group of atoms with

```
constrain group <integer iatom> <integer jatom> to
<integer katom> <integer latom>
```

resulting in the same charge for atoms iatom and katom, for atoms iatom+1 and ${\bf k}$

atom+1, ... for atoms jatom and latom.

• A special constraint

```
constrain xhn <integer iatom> {<integer jatom>}
```

```
can be used to constrain the set {iatom,{jatom}} to zero charge,
and constrain all atoms
    in {jatom} to have the same charge. This can be used, for example,
    to restrain a methyl
      group to zero charge, and have all hydrogen carrying identical
charges.
```

Restraints

Restraints can be applied to each partial charge using the RESP charge fitting procedure.

• The directive for charge restraining is

```
restrain [hfree] (harmonic [<real scale>] \
hyperbolic [<real scale> [<real tight> \
       [maxiter <integer maxit>] [tolerance <real
toler>])
```

Here hfree can be specified to exclude hydrogen atoms from the restaining procedure. Variable scale is the strength of the restraint potential, with a default of 0.005 au for the harmonic restraint and a default value of 0.001 au for the hyperbolic restraint. For the hyperbolic restraints the tightness tight can be specified to change the default value of 0.1 e. The iteration count that needs to be carried out for the hyperbolic restraint is determined by the maximum number of allowed iterations maxiter, with a default value of 25, and the tolerance in the convergence of the partial charges toler, with a default of 0.001 e.

Plotting

The electrostatic potential computed on a grid can be displayed using the gOpenMol [1] code.

A necessary step requires to convert the .plt file computed by the ESP module from human readable to machine readable format; this can be achieved by using the gOpenMol Pltfile converter.

In practice, you would need to follow the following steps

- 1. rename *filename.plt* to *filename.plt.txt*
- 2. start gOpenMol
- 3. open the $\underline{\mathbf{R}}\mathbf{un}$ menu
- 4. select the Pltfile (conversion) utility
- 5. choose *filename.plt.txt* as input file name and *filename.plt* as the output file name
- 6. select Formatted ==> Unformatted
- read the *filename.xyz* file by going to: File -> Import -> Coord -> Browse -> Apply; you should see your system in the main graphical window as connections between atoms
- 8. plot the density by going to **Plot -> Contour**
- 9. first click $\underline{\mathbf{B}}rowse$ and read the gOpenMol filename.plt file:
- 10. then click Import
- 11. define desired Contour level
- 12. click \underline{Apply}

More details at: http://www.cmmp.ucl.ac.uk/~lev/codes/lev00/node71.html

References

[1] http://www.csc.fi/english/pages/g0penMol

Release65:DPLOT

__NOTITLE___

DPLOT

DPLOT

This directive is used to obtain the plots of various types of electron densities (or orbitals) of the molecule. The electron density is calculated on a specified set of grid points using the molecular orbitals from SCF or DFT calculation. The output file is either in MSI Insight II contour format (default) or in the Gaussian Cube format. DPLOT is not executed until the "task dplot" directive is given. Different sub-directives are described below.

The implementation of the dplot functionality uses mostly local memory. The quantities stored in local memory are:

- the positions of the grid points
- the property of interest expressed at the grid points

The stack memory setting in the input file must be sufficient to hold these quantities in local memory on a processor.

GAUSSIAN --Gaussian Cube format

GAUSSIAN

A outputfile is generate in Gaussian Cube format. You can visualize this file using gOpenMol (after converting the Gaussian Cube file with gcube2plt), Molden or Molekel.

TITLE --Title directive

TITLE <string Title default Unknown Title>

This sub-directive specifies a title line for the generated input to the Insight program or for the Gaussian cube file. Only one line is allowed.

LIMITXYZ --Plot limits

LIMITXYZ [units <string Units default angstroms>] <real X_From> <real X_To> <integer No_Of_Spacings_X> <real Y_From> <real Y_To> <integer No_Of_Spacings_Y> <real Z_From> <real Z_To> <integer No_Of_Spacings_Z>

This sub-directive specifies the limits of the cell to be plotted. The grid is generated using $No_Of_Spacings + 1$ points along each direction. The known names for Units are angstroms, au and bohr.

SPIN -- Density to be plotted

```
SPIN <string Spin default total>
```

This sub-directive specifies, what kind of density is to be computed. The known names for Spin are total, alpha, beta and spindens, the last being computed as the difference between α and β electron densities.

OUTPUT --Filename

OUTPUT <string File_Name default dplot>

This sub-directive specifies the name of the generated input to the Insight program or the generated Gaussian cube file. The name OUTPUT is reserved for the standard NWChem output.

VECTORS --MO vector file name

```
VECTORS <string File_Name default movecs> [<string
File_Name2>]
```

This sub-directive specifies the name of the molecular orbital file. If the second file is optionally given the density is computed as the difference between the corresponding electron densities. The vector files have to match.

WHERE -- Density evaluation

```
WHERE <string Where default grid>
```

This sub-directive specifies where the density is to be computed. The known names for Where are grid (the calculation of the density is performed on the set of a grid points specified by the sub-directive LimitXYZ and the file specified by the sub-directive Output is generated), nuclei (the density is computed at the position of the nuclei and written to the NWChem output) and g+n (both).

ORBITAL --Orbital sub-space

ORBITALS [<string Option default density>]
<integer No_Of_Orbitals>
<integer Orb_No_1 Orb_No_2 ...>

This sub-directive specifies the subset of the orbital space for the calculation of the electron density. The density is computed using the occupation numbers from the orbital file modified according to the Spin directive. If the contours of the orbitals are to be plotted Option should be set to view (instead of the implicit default value density). Note, that in this case No_Of_Orbitals should be set to 1 and sub-directive Where is automatically set to grid. Also specification of two orbital files conflicts with the view option. alpha orbitals are always plotted unless Spin is set to beta.

CIVECS --CI vectors

CIVECS [<string Name of civecs file>]

DENSMAT -- **Density** matrix

DENSMAT [<string Name of density matrix file>]

Examples

Charge Density

Example of charge density plot (with Gaussian Cube output):

```
start n2
geometry
  n 00
           0.53879155
 n 0 0 -0.53879155
end
basis; n library cc-pvdz;end
scf
vectors output n2.movecs
end
dplot
 TITLE HOMO
 vectors n2.movecs
   LimitXYZ
 -3.0 3.0 10
 -3.0 3.0 10
 -3.0 3.0 10
 spin total
 gaussian
 output chargedensity.cube
end
task scf
task dplot
```

Molecular Orbital

Example of orbital plot (with Insight II contour output):

```
start n2
geometry
  n 0 0 0.53879155
  n 0 0 -0.53879155
end
basis; n library cc-pvdz;end
scf
vectors output n2.movecs
end
dplot
  TITLE HOMO
  vectors n2.movecs
   LimitXYZ
 -3.0 3.0 10
 -3.0 3.0 10
 -3.0 3.0 10
  spin total
  orbitals view; 1; 7
  output homo.grd
end
task scf
task dplot
```

Transition Density

TDDFT calculation followed by a calculation of the transition density for a specific excited state using the DPLOT block

```
echo
start h2o-td
title h2o-td
memory total 800 stack 400 heap 50 global 350 mb
charge 0
geometry units au noautoz nocenter
symmetry group cl
                           0.0000000000000
0
     0.0000000000000
                                                 0.00000000000000
     0.47043554760291
н
                          1.35028113274600
                                                 1.06035416576826
                      -0.23369304784300
Н
    -1.74335410533480
                                                 0.27360785442967
end
basis "ao basis" print
Н
     S
   13.0107010
                           0.19682158E-01
    1.9622572
                           0.13796524
    0.44453796
                           0.47831935
Н
    S
    0.12194962
                           1.0000000
```

```
Ρ
Н
    0.800000
                          1.0000000
0
     S
 2266.1767785
                          -0.53431809926E-02
  340.87010191
                          -0.39890039230E-01
   77.363135167
                         -0.17853911985
   21.479644940
                          -0.46427684959
    6.6589433124
                         -0.44309745172
0
    S
    0.80975975668
                          1.0000000
0
    S
    0.25530772234
                      1.0000000
0
     Ρ
   17.721504317
                           0.43394573193E-01
    3.8635505440
                           0.23094120765
    1.0480920883
                           0.51375311064
    Р
0
    0.27641544411
                     1.0000000
0
    D
    1.2000000
                       1.0000000
end
dft
xc bhlyp
grid fine
direct
convergence energy 1d-5
end
tddft
rpa
nroots 5
thresh 1d-5
singlet
notriplet
civecs
end
task tddft energy
dplot
civecs h2o-td.civecs_singlet
root 2
LimitXYZ
 -3.74335 2.47044 50
 -2.23369 3.35028 50
 -2 3.06035 50
  gaussian
  output root-2.cube
end
task dplot
```

Plot the excited state density

```
echo
start tddftgrad_co_exden
geometry
С
                      0.0000000
       0.00000000
                                    -0.64628342
 0
       0.00000000
                      0.0000000
                                      0.48264375
 symmetry cl
end
basis spherical
* library "3-21G"
end
dft
xc pbe0
direct
end
tddft
nroots 3
notriplet
 target 1
 civecs
 grad
  root 1
end
end
task tddft gradient
dplot
densmat tddftgrad_co_exden.dmat
LimitXYZ
-4.0 4.0 50
-4.0 4.0 50
-4.0 4.0 50
gaussian
output co_exden.cube
end
```

task dplot

Other Capabilities

Release65:Electron Transfer

__NOTITLE__

EΤ

The NWChem electron transfer (ET) module calculates the electronic coupling energy (also called the electron transfer matrix element) between ET reactant and product states. The electronic coupling (V_{RP}), activation energy (ΔG^*), and nuclear reorganization energy (λ) are all components of the electron transfer rate defined by Marcus' theory, which also depends on the temperature (see Reference 1 below):

$$k_{ET} = \frac{2\pi}{\hbar} V_{RP}^2 \frac{1}{\sqrt{4\pi\lambda k_B T}} \exp\left(\frac{-\Delta G^*}{k_B T}\right)$$

The ET module utilizes the method of *Corresponding Orbital Transformation* to calculate V_{RP} . The only input required are the names of the files containing the open-shell (UHF) MO vectors for the ET reactant and product states (*R* and *P*).

The basis set used in the calculation of V_{RP} must be the same as the basis set used to calculate the MO vectors of R and P. The magnitude of V_{RP} depends on the amount of overlap between R and P, which is important to consider when choosing the basis set. Diffuse functions may be necessary to fill in the overlap, particularly when the ET distance is long.

The MO's of R and P must correspond to localized states. for instance, in the reaction $A^-B \rightarrow AB^-$ the transferring electron is localized on A in the reactant state and is localized on B in the product state. To verify the localization of the electron in the calculation of the vectors, carefully examine the Mulliken population analysis. In order to determine which orbitals are involved in the electron transfer, use the print keyword "mulliken ao" which prints the Mulliken population of each basis function.

An effective core potential (ECP) basis can be used to replace core electrons. However, there is one caveat: the orbitals involved in electron transfer must not be replaced with ECP's. Since the ET orbitals are valence orbitals, this is not usually a problem, but the user should use ECP's with care.

Suggested references are listed below. The first two references gives a good description of Marcus' two-state ET model, and the appendix of the third reference details the method used in the ET module.

- 1. R.A. Marcus, N. Sutin, Biochimica Biophysica Acta 35, 437, (1985).
- 2. J.R. Bolton, N. Mataga, and G. McLendon in "Electron Transfer in Inorganic, Organic and Biological Systems" (American Chemical Society, Washington, D.C., 1991)
- 3. A. Farazdel, M. Dupuis, E. Clementi, and A. Aviram, J. Am. Chem. Soc., 112, 4206 (1990).

VECTORS --input of MO vectors for ET reactant and product states

VECTORS [reactants] <string reactants_filename>
VECTORS [products] <string products_filename>

In the VECTORS directive the user specifies the source of the molecular orbital vectors for the ET reactant and product states. This is required input, as no default filename will be set by the program. In fact, this is the only required input in the ET module, although there are other optional keywords described below.

FOCK/NOFOCK --method for calculating the twoelectron contribution to V_{RP}

```
<string (FOCK||NOFOCK) default FOCK>
```

This directive enables/disables the use of the NWChem's Fock matrix routine in the calculation of the two-electron portion of the ET Hamiltonian. Since the Fock matrix routine has been optimized for speed, accuracy and parallel performance, it is the most efficient choice.

Alternatively, the user can calculate the two-electron contribution to the ET Hamiltonian with another subroutine which may be more accurate for systems with a small number of basis functions, although it is slower.

TOL2E --integral screening threshold

```
TOL2E <real tol2e default max(10e-12,min(10e-7, S(RP)*10e-7 )>
```

The variable tol2e is used in determining the integral screening threshold for the evaluation of the two-electron contribution to the Hamiltonian between the electron transfer reactant and product states. As a default, tol2e is set depending on the magnitude of the overlap between the ET reactant and product states (S_{RP}), and is not less than 1.0d-12 or greater than 1.0d-7.

The input to specify the threshold explicitly within the ET directive is, for example:

tol2e 1e-9

Example

The following example is for a simple electron transfer reaction, $He \rightarrow He^+$. The ET calculation is easy to execute, but it is crucial that ET reactant and product wavefunctions reflect localized states. This can be accomplished using either a fragment guess, or a charged atomic density guess. For self-exchange ET reactions such as this one, you can use the REORDER keyword to move the electron from the first helium to the second. Example input :

```
#ET reactants:
charge 1
scf
  doublet; uhf; vectors input fragment HeP.mo He.mo output HeA.mo
# HeP.mo are the vectors for He(+),
```

```
# He.mo are the vectors for neutral He.
end
task scf
#ET products:
charge 1
scf
 doublet; uhf; vectors input HeA.mo reorder 2 1 output HeB.mo
end
task scf
et
vectors reactants HeA.mo
vectors products HeB.mo
end
task scf et
Here is what the output looks like for this example:
                         Electron Transfer Calculation
                         MO vectors for reactants: HeA.mo
MO vectors for products : HeB.mo
                                            -5.3402392824
Electronic energy of reactants
                                 H(RR)
Electronic energy of products
                                 H(PP)
                                            -5.3402392824
Reactants/Products overlap
                                 S(RP)
                                            -0.0006033839
Reactants/Products interaction energy:
One-electron contribution
                                             0.0040314092
                                H1(RP)
Beginning calculation of 2e contribution
Two-electron integral screening (tol2e) : 6.03E-11
Two-electron contribution
                                H2(RP)
                                            -0.0007837138
Total interaction energy
                                 H(RP)
                                             0.0032476955
Electron Transfer Coupling Energy |V(RP)|
                                             0.0000254810
                                                    5.592 cm-1
                                                 0.000693 eV
                                                    0.016 kcal/mol
```

The overlap between the ET reactant and product states (S_{RP}) is small, so the magnitude of the coupling between the states is also small. If the fragment guess or charged atomic density guess were not used, the Mulliken spin population would be 0.5 on both He atoms, the overlap between the ET reactant and product states would be 100 % and an infinite V_{RP} would result.

Release65:VSCF

__NOTITLE__

VSCF

The VSCF module can be used to calculate the anharmonic contributions to the vibrational modes of the molecule of interest. Energies are calculated on a one-dimensional grid along each normal mode, on a two-dimensional grid along each pair of normal modes, and optionally on a three-dimensional grid along each triplet of normal modes. These energies are then used to calculate the vibrational nuclear wavefunction at an SCF- (VSCF) and MP2-like (cc-VSCF) level of theory.

VSCF can be used at all levels of theory, SCF and correlated methods, and DFT. For correlated methods, only the SCF level dipole is evaluated and used to calculate the IR intensity values.

The VSCF module is started when the task directive TASK <theory> vscf is defined in the user input file. The input format has the form:

```
VSCF
 [coupling <string couplelevel default "pair">]
 [ngrid <integer default 16 >]
 [iexcite <integer default 1 >]
 [vcfct <real default 1.0>]
END
```

The order of coupling of the harmonic normal modes included in the calculation is controlled by the specifying:

coupling <string couplelevel default "pair">

For coupling=diagonal a one-dimensional grid along each normal mode is computed. For coupling=pair a two-dimensional grid along each pair of normal modes is computed. For coupling=triplet a three-dimensional grid along each triplet of normal modes is computed.

The number of grid points along each normal mode, or pair of modes can be defined by specifying:

ngrid <integer default 16>

This VSCF module by default calculates the ground state (v=0), but can also calculate excited states (such as v=1). The number of excited states calculated is defined by specifying:

iexcite <integer default 1>

With iexcite=1 the fundamental frequencies are calculated. With iexcite=2 the first overtones are calculated. With iexcite=3 the second overtones are calculated.

In certain cases the pair coupling potentials can become larger than those for a single normal mode. In this case the pair potentials need to be scaled down. The scaling factor used can be defined by specifying:

vcfct <real default 1.0>

Release65:DNTMC

__NOTITLE__

Dynamical Nucleation Theory Monte Carlo

The Dynamical Nucleation Theory Monte Carlo (DNTMC) module utilizes Dynamical Nucleation Theory (DNT) to compute monomer evaporation rate constants at a given temperature^{[1] [2] [3]}. The reactant is a molecular cluster of *i* rigid monomers while the product is a molecular cluster with *i*-1 monomers plus a free monomer. A Metropolis Monte Carlo (MC) methodology is utilized to sample the configurational space of these *i* rigid monomers. Both homogenous and heterogenous clusters are supported.

SubGroups

The DNTMC module supports the use of subgroups in the MC simulations. The number of subgroups is defined in the input through a set directive:

set subgroup_number <integer number>

where the number of subgroups requested is the argument. The number of processors that each subgroup has access to is determined by Total/subgroup_number. A separate MC simulation is performed within each subgroup. To use this functionality, NWChem must be compiled with the USE_SUBGROUPS environmental variable set.

Each MC simulation starts at a different starting configuration, which is equally spaced along the reaction coordinate. The statistical distributions which these MC simulations produce are averaged to form the final statistical distribution. Output from these subgroups consists of various files whose names are of the form (*.#num). These files include restart files and other data files. The NWChem runtime database (RTDB) is used as input for these subgroups and must be globally accessible (set through the Permanent_Dir directive) to all processes.

Input Syntax

The input block has the following form:

```
DNTMC
   [nspecies <integer number>]
   [species <list of strings name[nspecies]]</pre>
              <list of integers number[nspecies]>]
   [nmol
             <real temperature>]
   [temp
             <real rmin>]
   [rmin
              <real rmax>]
   [rmax
   [nob
             <integer nob>]
   [mcsteps <integer number>]
   [tdisp
              <real disp>]
   [rdisp
              <real rot>]
   [rsim || rconfig]
```

```
[mprnt <integer number>]
[convergence <real limit>]
[norestart]
[dntmc_dir <string directory>]
[print &&|| noprint]
[procrestart <integer number>]
END
```

Definition of Monomers

Geometry information is required for each unique monomer (species). See the geometry input section 6 for more information. A unique label must be given for each monomer geometry. Additionally, the noautosym and nocenter options are suggested for use with the DNTMC module to prevent NWChem from changing the input geometries. Symmetry should also not be used since cluster configurations will seldom exhibit any symmetry; although monomers themselves may exhibit symmetry.

```
GEOMETRY [<string name species_1>] noautosym nocenter ...
symmetry c1
END
GEOMETRY [<string name species_2>] noautosym nocenter ...
...
symmetry c1
END
```

• • •

The molecular cluster is defined by the number of unique monomers (nspecies). The geometry labels for each unique monomer is given in a space delimited list (species). Also required are the number of each unique monomer in the molecular cluster given as a space delimited list (nmol). These keywords are required and thus have no default values.

```
[nspecies <integer number>]
[species <list of strings name[nspecies]]
[nmol <list of integers number[nspecies]>]
```

An example is shown for a 10 monomer cluster consisting of a 50/50 mixture of water and ammonia.

DNTMC runtime options

Several options control the behavior of the DNTMC module. Some required options such as simulation temperature (temp), cluster radius (rmin and rmax), and maximum number of MC steps (mcsteps) are used to control the MC simulation.

```
[temp <real temperature>]
```

This required option gives the simulation temperature in which the MC simulation is run. Temperature is given in kelvin.

[rmin <real rmin>]
[rmax <real rmax>]
[nob <integer nob>]

These required options define the minimum and maximum extent of the projected reaction coordinate (The radius of a sphere centered at the center of mass). Rmin should be large enough to contain the entire molecular cluster of monomers and Rmax should be large enough to include any relevant configurational space (such as the position of the reaction bottleneck). These values are given in Angstroms.

The probability distributions obtain along this projected reaction coordinate has a minimum value of Rmin and a maximum value of Rmax. The distributions are created by chopping this range into a number of smaller sized bins. The number of bins (nob) is controlled by the option of the same name.

```
[mcsteps <integer number>]
[tdisp <real disp default 0.04>]
[rdisp <real rot default 0.06>]
[convergence <real limit default 0.00>]
```

These options define some characteristics of the MC simulations. The maximum number of MC steps (mcsteps) to take in the course of the calculation run is a required option. Once the MC simulation has performed this number of steps the calculation will end. This is a per Markov chain quantity. The maximum translational step size (tdisp) and rotational step size (rdisp) are optional inputs with defaults set at 0.04 Angstroms and 0.06 radians, respectively. The convergence keyword allows the convergence threshold to be set. The default is 0.00 which effectively turns off this checking. Once the measure of convergence goes below this threshold the calculation will end.

[rsim || rconfig]

These optional keywords allow the selection of two different MC sampling methods. rsim selects a Metropolis MC methodology which samples configurations according to a Canonical ensemble. The rconfig keyword selects a MC methodology which samples configurations according to a derivative of the Canonical ensemble with respect to the projected reaction coordinate. These keywords are optional with the default method being rconfig.

```
[mprnt <integer number default 10>]
[dntmc_dir <string directory default ./>]
[norestart]
```

These three options define some of the output and data analysis behavior. mprnt is an option which controls how often data analysis occurs during the simulation. Currently, every mprnt*nob MC steps data analysis is performed and results are output to files and/or to the log file. Restart files are also written every mprnt number of MC steps during the simulation. The default value is 10. The keyword dntmc_dir allows the definition of an alternate directory to place DNTMC specific ouputfiles. These files can be very large so be sure enough space is available. This directory should be accessible by every process (although not necessarily globally accessible). The default is to place these files in the directory which NWChem is run (./). The keyword norestart turns off the production of restart files. By default restart files are produced every mprnt number of MC steps.

Print Control

The DNTMC module supports the use of PRINT and NOPRINT Keywords. The specific labels which DNTMC recognizes are included below.

Name	Print Level	Description
"debug"	debug	Some debug information written in Output file.
"information"	none	Some information such as energies and geometries.
"mcdata"	low	Production of a set of files (Prefix.MCdata.\#num). These files are a concatenated list of structures, Energies, and Dipole Moments for each accepted configuration sampled in the MC run.
"alldata"	low	Production of a set of files (Prefix.Alldata.#num). These files include the same information as MCdata files. However, they include ALL configurations (accepted or rejected).
"mcout"	debug - low	Production of a set of files (Prefix.MCout.#num). These files contain a set of informative and debug information. Also included is the set of information which mirrors the Alldata files.
"fdist"	low	Production of a file (Prefix.fdist) which contains a concatenated list of distributions every mprnt*100 MC steps.
"timers"	debug	Enables some timers in the code. These timers return performance statistics in the output file every time data analysis is performed. Two timers are used. One for the mcloop itself and one for the communication step.

Selected File Formats

Several output files are available in the DNTMC module. This section defines the format for some of these files.

1. *.fdist

This file is a concatenated list of radial distribution functions printed out every mprnt MC steps. Each distribution is normalized (sum equal to one) with respect to the entire (all species) distribution. The error is the RMS deviation of the average at each point. Each entry is as follows: [1] # Total Configurations [2] Species number # [3](R coordinate in Angstroms) (Probability) (Error) [Repeats nob times] [2 and 3 Repeats for each species] [4] *** separator.

2. *.MCdata.#

This file is a concatenated list of accepted configurations. Each file corresponds to a single Markov chain. The dipole is set to zero for methods which do not produce a dipole
moment with energy calculations. Rsim is either the radial extent of the cluster (r-config) or the simulation radius (r-simulation). Each entry is as follows: [1] (Atomic label) (X Coord.) (Y Coord.) (Z Coord.) [1 Repeats for each atom in the cluster configuration, units are in angstroms] [2] Ucalc = # hartree [3] Dipole = (X) (Y) (Z) au [4] Rsim = # Angstrom [1 through 4 repeats for each accepted configuration]

3. *.MCout.#

This file has the same format and information content as the MCdata file except that additional output is included. This additional output includes summary statistics such as acceptance ratios, average potential energy, and average radius. The information included for accepted configurations does not include dipole moment or radius.

4. *.MCall.#

This file has the same format as the MCdata file expect that it includes information for all configurations for which an energy is determined. All accepted and rejected configurations are included in this file.

5. *.restart.#

This file contains the restart information for each subgroup. Its format is not very human readable but the basic fields are described in short here. Random number seed Potential energy in hartrees Sum of potential energy Average potential energy Sum of the squared potential energy Squared potential energy Dipole moment in au (x) (Y) (Z) Rmin and Rmax Rsim (Radius corresponds to r-config or r-sim methods) Array of nspecies length, value indicates the number of each type of monomer which lies at radius Rsim from the center of mass [r-simulation sets these to zero] Sum of Rsim Average of Rsim Number of accepted translantional moves Number of accepted rotational moves Number of accepted volume moves Number of attempted moves (volume) (translational) (rotational) Number of accepted moves (Zero) Number of accepted moves (Zero) Number of MC steps completed [1] (Atom label) (X Coord.) (Y Coord.) (Z Coord.) [1 repeats for each atom in cluster configurations, units are in angstroms] [2] Array of nspecies length, number of configurations in bin [3] Array of nspecies length, normalized number of configurations in each bin [4] (Value of bin in Angstroms) (Array of nspecies length, normalized probability of bin) [2 through 4 repeats nob times]

DNTMC Restart

[procrestart <integer number>]

Flag to indicate restart postprocessing. It is suggested that this postprocessing run is done utilizing only one processor.

In order to restart a DNTMC run, postprocessing is required to put required information into the runtime database (RTDB). During a run restart information is written to files (Prefix.restart.#num) every mprnt MC steps. This information must be read and deposited into the RTDB before a restart run can be done. The number taken as an argument is the number of files to read and must also equal the number of subgroups the calculation utilizes. The start directive must also be set to restart for this to work properly. All input is read as usual. However, values from the restart files take precedence over input values. Some keywords such as mcsteps are not defined in the restart files. Task directives are ignored. You must have a RTDB present in your permanent directory.

Once postprocessing is done a standard restart can be done from the RTDB by removing the procrestart keyword and including the restart directive.

Task Directives

The DNTMC module can be used with any level of theory which can produce energies. Gradients and Hessians are not required within this methodology. If dipole moments are available, they are also utilized. The task directive for the DNTMC module is shown below:

```
task <string theory> dntmc
```

Example

This example is for a molecular cluster of 10 monomers. A 50/50 mixture of water and ammonia. The energies are done at the SCF/6-31++G** level of theory.

```
start
# start or restart directive if a restart run
MEMORY 1000 mb
PERMANENT DIR /home/bill
# Globally accessible directory which the
# rtdb (*.db) file will/does reside.
basis "ao basis" spherical noprint
    * library 6-31++G**
end
# basis set directive for scf energies
scf
    singlet
    rhf
    tol2e 1.0e-12
    vectors input atomic
    thresh 1.0e-06
    maxiter 200
    print none
end
# scf directive for scf energies
geometry geom1 units angstroms noautosym nocenter noprint
0 0.393676503613369
                          -1.743794626956820
                                                  -0.762291912129271
H -0.427227157125777
                          -1.279138812526320
                                                  -0.924898279781319
                          -1.095883929075060
                                                  -0.940073459864222
H 1.075463952717060
symmetry cl
end
# geometry of a monomer with title "geom1"
geometry geom2 units angstroms noautosym nocenter noprint
Ν
      6.36299e-08
                      0.00000
                                  -0.670378
Н
      0.916275
                   0.00000
                               -0.159874
                    0.793517
Н
      -0.458137
                                 -0.159874
Н
      -0.458137
                   -0.793517
                                 -0.159874
symmetry c1
```

```
end
# geometry of another monomer with title "geom2"
# other monomers may be included with different titles
set subgroups number 8
# set directive which gives the number of subgroups
# each group runs a separate MC simulation
dntmc
# DNTMC input block
    nspecies 2
    # The number of unique species (number of titled geometries
    # above)
    species geom1 geom2
    # An array of geometry titles (one for each
    # nspecies/geometry)
    nmol
            5 5
    # An array stating the number of each
    # monomer/nspecies/geometry in simulation.
    temp 243.0
    mcsteps 1000000
    rmin 3.25
    rmax 12.25
    mprnt 10
    tdisp 0.04
    rdisp 0.06
    print none fdist mcdata
    # this print line first sets the print-level to none
    # then it states that the *.fdist and *.mcdata.(#num)
    # files are to be written
    rconfig
    dntmc dir /home/bill/largefile
    # An accessible directory which to place the *.fdist,
    # *.mcdata.(#num), and *.restart.(#num) files.
    convergence 1.0D+00
end
```

task scf dntmc
task directive stating that energies are to be done at the scf
#level of theory.

References

- [1] <refbase>522</refbase>
- [2] <refbase>523</refbase>
- [3] <refbase>524</refbase>

Release65:CCCA

Correlation consistent Composite Approach (ccCA)

The CCCA module calculates the total energy using the correlation consistent Composite Approach (ccCA). At present the ccCA module is designed for the study of main group species only.

 $E_{ccCA} = \Delta E_{MP2/CBS} + \Delta E_{CC} + \Delta E_{CV} + \Delta E_{SR} + \Delta E_{ZPE}$

where EMP2/CBS is the complete basis set extrapolation of MP2 energies with the aug-cc-pVnZ (n=T,D,Q) series of basis sets, ΔE_{CC} is the correlation correction,

 $\Delta E_{CC} = E_{CCSD(T)/cc-pVTZ} - E_{MP2/cc-pVTZ}$ $\Delta E_{CV} \text{ is the core-valence correction,}$ $\Delta E_{CV} = E_{MP2(FC1)/aug-cc-pCVTZ} - E_{MP2/aug-cc-pVTZ}$ $\Delta E_{SR} \text{ is the scalar-relativistic correction,}$ $\Delta E_{SR} = E_{MP2/cc-pVTZ-DK} - E_{MP2/cc-pVTZ}$

and ΔE_{ZPE} is the zero-point energy correction or thermal correction. Geometry optimization and subsequent frequency analysis are performed with B3LYP/cc-pVTZ.

Suggested reference: N.J. DeYonker, B. R. Wilson, A.W. Pierpont, T.R. Cundari, A.K. Wilson, Mol. Phys. 107, 1107 (2009). Earlier variants for ccCA algorithms can also be found in: N. J. DeYonker, T. R. Cundari, A. K. Wilson, J. Chem. Phys. 124, 114104 (2006).

The ccCA module can be used to calculate the total single point energy for a fixed geometry and the zero-point energy correction is not available in this calculation. Alternatively the geometry optimization by B3LYP/cc-pVTZ is performed before the single point energy evaluation. For open shell molecules, the number of unpaired electrons must be given explicitly.

CCCA

>]

END

```
[(ENERGY||OPTIMIZE)
                       default ENERGY]
[(DFT||DIRECT)
                 default DFT]
[(MP2||MBPT2)
                default MP2]
[(RHF||ROHF||UHF)
                    default RHF]
                  default CCSD(T)]
[(CCSD(T)||TCE)]
         <integer number of unpaired electrons</pre>
[NOPEN
                                                   default
                                                              0
[(THERM||NOTHERM)
                    default THERM]
[(PRINT||NOPRINT) default NOPRINT]
[BASIS <basis name for orbital projection guess>]
[MOVEC <file name for orbital projection guess>]
```

One example of input file for single point energy evaluation is given here:

start h2o_ccca

title "H2O, ccCA test"

geometry units au

H0.0000000001.4140780900-1.1031626600H0.0000000000-1.4140780900-1.1031626600O0.00000000000.000000000-0.0080100000

 $\quad \text{end} \quad$

task ccca

An input file for the ground state of O2 with geometry optimization is given below:

start o2_ccca

title "O2, ccCA test"

geometry units au

0 0	0.0000000000 0.0000000000	0.0000000000 0.00000000000	-2.0000 0.0000	
end				
ccca				
optimiz dft nopen 2	e			
end task ccca				

Release65:Python

__NOTITLE__

Controlling NWChem with Python

Python (version 1.5.1) programs may be embedded into the NWChem input and used to control the execution of NWChem. Python is a very powerful and widely used scripting language that provides useful things such as variables, conditional branches and loops, and is also readily extended. Example applications include scanning potential energy surfaces, computing properties in a variety of basis sets, optimizing the energy w.r.t. parameters in the basis set, computing polarizabilities with finite field, and simple molecular dynamics.

Look in the NWChem contrib directory for useful scripts and examples. Visit the Python web-site http://www.python.org for a full manual and lots of useful code and resources.

How to input and run a Python program inside NWChem

A Python program is input into NWChem inside a Python compound directive.

```
python [print|noprint]
   ...
end
```

The END directive must be flush against the left margin (see the Troubleshooting section for the reason why).

The program is by default printed to standard output when read, but this may be disabled with the noprint keyword. Python uses indentation to indicate scope (and the initial level of indentation must be zero), whereas NWChem uses optional indentation only to make the input more readable. For example, in Python, the contents of a loop, or conditionally-executed block of code must be indented further than the surrounding code. Also, Python attaches special meaning to several symbols also used by NWChem. For these reasons, the input inside a PYTHON compound directive is read verbatim except that if the first line of the Python program is indented, the same amount of indentation is removed from all subsequent lines. This is so that a program may be indented inside the PYTHON input block for improved readability of the NWChem input, while satisfying the constraint that when given to Python the first line has zero indentation.

E.g., the following two sets of input specify the same Python program.

```
python
  print 'Hello'
  print 'Goodbye'
end
python
print 'Hello'
print 'Goodbye'
end
```

whereas this program is in error since the indentation of the second line is less than that of the first.

```
python
    print 'Hello'
print 'Goodbye'
end
```

The Python program is not executed until the following directive is encountered

task python

which is to maintain consistency with the behavior of NWChem in general. The program is executed by all nodes. This enables the full functionality and speed of NWChem to be accessible from Python, but there are some gotchas

- Print statements and other output will be executed by all nodes so you will get a lot more output than probably desired unless the output is restricted to just one node (by convention node zero).
- The calls to NWChem functions are all collective (i.e., all nodes must execute them). If these calls are not made collectively your program may deadlock (i.e., cease to make progress).
- When writing to the database (rtdb_put()) it is the data from node zero that is written.
- NWChem overrides certain default signal handlers so care must be taken when creating processes (see Section 38.3.11).

NWChem extensions

Since we have little experience using Python, the NWChem-Python interface might change in a non-backwardly compatible fashion as we discover better ways of providing useful functionality. We would appreciate suggestions about useful things that can be added to the NWChem-Python interface. In principle, nearly any Fortran or C routine within NWChem can be extended to Python, but we are also interested in ideas that will enable users to build completely new things. For instance, how about being able to define your own energy functions that can be used with the existing optimizers or dynamics package?

Python has been extended with a module named "nwchem" which is automatically imported and contains the following NWChem-specific commands. They all handle NWChem-related errors by raising the exception "NWChemError", which may be handled in the standard Python manner.

- input_parse(string) -- invokes the standard NWChem input parser with the data in string as input. Note that the usual behavior of NWChem will apply -- the parser only reads input up to either end of input or until a TASK directive is encountered (the task directive is not executed by the parser).
- task_energy(theory) -- returns the energy as if computed with the NWChem directive TASK ENERGY <THEORY>.
- task_gradient(theory) -- returns a tuple (energy,gradient) as if computed with the NWChem directive TASK GRADIENT <THEORY>.
- task_optimize(theory) -- returns a tuple (energy,gradient) as if computed with the NWChem directive TASK OPTIMIZE <THEORY>. The energy and gradient will be those at the last point in the optimization and consistent with the current geometry in the

database.

- ga_nodeid() -- returns the number of the parallel process.
- rtdb_print(print_values) -- prints the contents of the RTDB. If print_values is 0, only the keys are printed, if it is 1 then the values are also printed.
- rtdb_put(name, values) or rtdb_put(name, values, type) -- puts the values into the database with the given name. In the first form, the type is inferred from the first value, and in the second form the type is specified using the last argument as one of INT, DBL, LOGICAL, or CHAR.
- rtdb_get(name) -- returns the data from the database associated with the given name.

An example below explains, in lieu of a Python wrapper for the geometry object, how to obtain the Cartesian molecular coordinates directly from the database.

Examples

Several examples will provide the best explanation of how the extensions are used, and how Python might prove useful.

Hello world

```
python
    print 'Hello world from process ', ga_nodeid()
end
```

task python

This input prints the traditional greeting from each parallel process.

Scanning a basis exponent

```
geometry units au
  0 0 0 0; H 0 1.430 -1.107; H 0 -1.430 -1.107
end
python
  exponent = 0.1
  while (exponent <= 2.01):
     input_parse(
        basis noprint
           H library 3-21g; 0 library 3-21g; 0 d; %f 1.0
        end
      % (exponent))
     print ' exponent = ', exponent, ' energy = ', task_energy('scf')
     exponent = exponent + 0.1
end
print none
task python
```

This program augments a 3-21g basis for water with a d-function on oxygen and varies the exponent from 0.1 to 2.0 in steps of 0.1, printing the exponent and energy at each step.

The geometry is input as usual, but the basis set input is embedded inside a call to input_parse() in the Python program. The standard Python string substitution is used to put the current value of the exponent into the basis set (replacing the %f) before being parsed by NWChem. The energy is returned by task_energy('scf') and printed out. The print none in the NWChem input switches off all NWChem output so all you will see is the output from your Python program.

Note that execution in parallel may produce unwanted output since all process execute the print statement inside the Python program.

Look in the NWChem contrib directory for a routine that makes the above task easier.

Scanning a basis exponent revisited

```
geometry units au
 0 0 0 0; H 0 1.430 -1.107; H 0 -1.430 -1.107
end
print none
python
  if (ga_nodeid() == 0): plotdata = open("plotdata",'w')
 def energy_at_exponent(exponent):
     input parse('''
        basis noprint
           H library 3-21g; 0 library 3-21g; 0 d; %f 1.0
        end
     ''' % (exponent))
     return task_energy('scf')
 exponent = 0.1
 while exponent <= 2.01:
     energy = energy_at_exponent(exponent)
     if (ga nodeid() == 0):
        print ' exponent = ', exponent, ' energy = ', energy
        plotdata.write('%f %f\n' % (exponent , energy))
     exponent = exponent + 0.1
 if (ga_nodeid() == 0): plotdata.close()
end
```

```
task python
```

This input performs exactly the same calculation as the previous one, but uses a slightly more sophisticated Python program, also writes the data out to a file for easy visualization with a package such as gnuplot, and protects write statements to prevent duplicate output in a parallel job. The only significant differences are in the Python program. A file called "plotdata" is opened, and then a procedure is defined which given an exponent returns the energy. Next comes the main loop that scans the exponent through the desired range and

prints the results to standard output and to the file. When the loop is finished the additional output file is closed.

Scanning a geometric variable

```
python
  geometry = '''
   geometry noprint; symmetry d2h
    C 0 0 %f; H 0 0.916 1.224
   end
   . . .
  x = 0.6
  while (x < 0.721):
    input parse(geometry % x)
    energy = task energy('scf')
    print ' x = %5.2f energy = %10.6f' % (x, energy)
    x = x + 0.01
end
basis; C library 6-31g*; H library 6-31g*; end
print none
task python
```

This scans the bond length in ethene from 1.2 to 1.44 in steps of 0.2 computing the energy at each geometry. Since it is using D_{2h} symmetry the program actually uses a variable (x) that is half the bond length.

Look in the NWChem contrib directory for a routine that makes the above task easier.

Scan using the BSSE counterpoise corrected energy

```
basis spherical
Ne library cc-pvdz; BqNe library Ne cc-pvdz
He library cc-pvdz; BqHe library He cc-pvdz
end
mp2; tight; freeze core atomic; end
print none
python noprint
supermolecule = 'geometry noprint; Ne 0 0 0; He 0 0 %f; end\n'
fragment1 = 'geometry noprint; Ne 0 0 0; BqHe 0 0 %f; end\n'
fragment2 = 'geometry noprint; BqNe 0 0 0; He 0 0 %f; end\n'
```

```
def energy(geometry):
    input_parse(geometry + 'scf; vectors atomic; end\n')
    return task_energy('mp2')
def bsse_energy(z):
    return energy(supermolecule % z) - \
        energy(fragment1 % z) - \
        energy(fragment2 % z)
z = 3.3
while (z < 4.301):
    e = bsse_energy(z)
    if (ga_nodeid() == 0):
        print ' z = %5.2f energy = %10.7f ' % (z, e)
    z = z + 0.1
end
```

task python

This example scans the He--Ne bond-length from 3.3 to 4.3 and prints out the BSSE counterpoise corrected MP2 energy.

The basis set is specified as usual, noting that we will need functions on ghost centers to do the counterpoise correction. The Python program commences by defining strings containing the geometry of the super-molecule and two fragments, each having one variable to be substituted. Next, a function is defined to compute the energy given a geometry, and then a function is defined to compute the counterpoise corrected energy at a given bond length. Finally, the bond length is scanned and the energy printed. When computing the energy, the atomic guess has to be forced in the SCF since by default it will attempt to use orbitals from the previous calculation which is not appropriate here.

Since the counterpoise corrected energy is a linear combination of other standard energies, it is possible to compute the analytic derivatives term by term. Thus, combining this example and the next could yield the foundation of a BSSE corrected geometry optimization package.

Scan the geometry and compute the energy and gradient

```
basis noprint; H library sto-3g; O library sto-3g; end
python noprint
 print '
                                             gradient'
          У
                Z
                       energy
 print ' -----
 y = 1.2
 while y <= 1.61:
     z = 1.0
    while z <= 1.21:
        input parse('''
           geometry noprint units atomic
              00
                   0
                       0
```

```
H 0 %f -%f
              H 0 -%f -%f
           end
        ''' % (y, z, y, z))
        (energy,gradient) = task gradient('scf')
        print ' %5.2f %5.2f %9.6f' % (y, z, energy),
        i = 0
        while (i < len(gradient)):</pre>
           print '%5.2f' % gradient[i],
           i = i + 1
        print ''
        z = z + 0.1
     y = y + 0.1
end
print none
task python
```

This program illustrates evaluating the energy and gradient by calling task_gradient(). A water molecule is scanned through several C_{2v} geometries by varying the y and z coordinates of the two hydrogen atoms. At each geometry the coordinates, energy and gradient are printed.

The basis set (sto-3g) is input as usual. The two while loops vary the y and z coordinates. These are then substituted into a geometry which is parsed by NWChem using input_parse(). The energy and gradient are then evaluated by calling task_gradient() which returns a tuple containing the energy (a scalar) and the gradient (a vector or list). These are printed out exploiting the Python convention that a print statement ending in a comma does not print end-of-line.

Reaction energies varying the basis set

task python

In this example the reaction energy for $2H_2 + C_2H_4 \rightarrow 2CH_4$ is evaluated using MP2 in several basis sets. The geometries are fixed, but could be re-optimized in each basis. To illustrate the useful associative arrays in Python, the reaction energies are put into the associative array energies -- note its declaration at the top of the program.

Using the database

```
python
  rtdb_put("test_int2", 22)
  rtdb_put("test_int", [22, 10, 3],
                                      INT)
  rtdb_put("test_dbl", [22.9, 12.4, 23.908],
                                             DBL)
  rtdb put("test str", "hello", CHAR)
  rtdb_put("test_logic", [0,1,0,1,0,1], LOGICAL)
  rtdb_put("test_logic2", 0, LOGICAL)
  rtdb_print(1)
 print "test_str = ", rtdb_get("test_str")
 print "test_int = ", rtdb_get("test_int")
 print "test_in2 = ", rtdb_get("test_int2")
 print "test dbl = ", rtdb get("test dbl")
 print "test_logic = ", rtdb_get("test_logic")
 print "test_logic2 = ", rtdb_get("test_logic2")
end
```

```
task python
```

This example illustrates how to access the database from Python.

Handling exceptions from NWChem

```
geometry; he 0 0 0; he 0 0 2; end
basis; he library 3-21g; end
scf; maxiter 1; end
python
  try:
    task_energy('scf')
  except NWChemError, message:
    print 'Error from NWChem ... ', message
end
```

task python

The above test program shows how to handle exceptions generated by NWChem by forcing an SCF calculation on He_2 to fail due to insufficient iterations.

If an NWChem command fails it will raise the exception "NWChemError" (case sensitive) unless the error was fatal. If the exception is not caught, then it will cause the entire Python program to terminate with an error. This Python program catches the exception, prints out the message, and then continues as if all was well since the exception has been handled.

If your Python program detects an error, raise an unhandled exception. Do not call exit(1) since this may circumvent necessary clean-up of the NWChem execution environment.

Accessing geometry information --a temporary hack

In an ideal world the geometry and basis set objects would have full Python wrappers, but until then a back-door solution will have to suffice. We've already seen how to use input_parse() to put geometry (and basis) data into NWChem, so it only remains to get the geometry data back after it has been updated by a geometry optimzation or some other operation.

The following Python procedure retrieves the coordinates in the same units as initially input for a geometry of a given name. Its full source is included in the NWChem contrib directory.

```
def geom_get_coords(name):
    try:
        actualname = rtdb_get(name)
    except NWChemError:
        actualname = name
    coords = rtdb_get('geometry:' + actualname + ':coords')
    units = rtdb_get('geometry:' + actualname + ':user units')
    if (units == 'a.u.'):
        factor = 1.0
    elif (units == 'angstroms'):
        factor = rtdb_get('geometry:'+actualname+':angstrom_to_au')
    else:
        raise NWChemError,'unknown units'
        i = 0
```

```
while (i < len(coords)):
    coords[i] = coords[i] / factor
    i = i + 1
return coords</pre>
```

A geometry with name NAME has its coordinates (in atomic units) stored in the database entry geometry:NAME:coords. A minor wrinkle here is that indirection is possible (and used by the optimizers) so that we must first check if NAME actually points to another name. In the program this is done in the first try...except sequence. With the actual name of the geometry, we can get the coordinates. Any exceptions are passed up to the caller. The rest of the code is just to convert back into the initial input units -- only atomic units or Angstrøms are handled in this simple example. Returned is a list of the atomic coordinates in the same units as your initial input.

The routine is used as follows

coords = geom_get_coords('geometry')

or, if you want better error handling

```
try:
    coords = geom_get_coords('geometry')
except NWChemError,message:
    print 'Coordinates for geometry not found ', message
else:
    print coords
```

This is very dirty and definitely not supported from one release to another, but, browsing the output of rtdb_print() at the end of a calculation is a good way to find stuff. To be on safer ground, look in the programmers manual since some of the high-level routines do pass data via the database in a well-defined and supported manner. Be warned -- you must be very careful if you try to modify data in the database. The input parser does many important things that are not immediately apparent (e.g., ensure the geometry is consistent with the point group, mark the SCF as not converged if the SCF options are changed, ...). Where at all possible your Python program should generate standard NWChem input and pass it to input_parse() rather than setting parameters directly in the database.

Scaning a basis exponent yet again --plotting and handling child processes

```
geometry units au
  0 0 0; H 0 1.430 -1.107; H 0 -1.430 -1.107
end
print none
python
  import Gnuplot, time, signal
  def energy_at_exponent(exponent):
      input parse('''
```

```
basis noprint
         H library 3-21g; 0 library 3-21g; 0 d; %f 1.0
      end
   ''' % (exponent))
   return task energy('scf')
data = []
exponent = 0.5
while exponent <= 0.6:
   energy = energy_at_exponent(exponent)
   print ' exponent = ', exponent, ' energy = ', energy
   data = data + [[exponent,energy]]
   exponent = exponent + 0.02
if (ga nodeid() == 0):
   signal.signal(signal.SIGCHLD, signal.SIG DFL)
   g = Gnuplot.Gnuplot()
   g('set style data linespoints')
   g.plot(data)
   time.sleep(30) # 30s to look at the plot
```

end

task python

This illustrates how to handle signals from terminating child processes and how to generate simple plots on UNIX systems. The scanning example is modified so that instead of writing the data to a file for subsequent visualization, it is saved for subsequent visualization with Gnuplot (you'll need both Gnuplot and the corresponding package for Python in your PYTHONPATH. Look at http://monsoon.harvard.edu/~mhagger/download).

The issue is that NWChem traps various signals from the O/S that usually indicate bad news in order to provide better error handling and reliable clean-up of shared, parallel resources. One of these signals is SIGCHLD which is generated whenever a child process terminates. If you want to create child processes within Python, then the NWChem handler for SIGCHLD must be replaced with the default handler. There seems to be no easy way to restore the NWChem handler after the child has completed, but this should have no serious side effect.

Troubleshooting

Common problems with Python programs inside NWChem.

1. You get the message

0:python_input: indentation must be >= that of first line: 4

This indicates that NWChem thinks that a line is less indented than the first line. If this is not the case then perhaps there is a tab in your input which NWChem treats as a single space character but appears to you as more spaces. Try running untabify in Emacs. The problem could also be the END directive that terminates the PYTHON compound directive -- since Python also has an end statement. To avoid confusion the END directive for NWChem must be at the start of the line.

2. Your program hangs or deadlocks -- most likely you have a piece of code that is restricted to executing on a subset of the processors (perhaps just node 0) but is calling (perhaps indirectly) a function that must execute on all nodes.

Release65:Interface

__NOTITLE___

Interfaces to Other Programs

NWChem has interfaces to several different packages which are listed below. In general, the NWChem authors work with the authors of the other packages to make sure that the interface works. However, any problems with the interface should be reported to the nwchem-users@emsl.pnl.gov e-mail list.

DIRDYVTST --DIRect Dynamics for Variational Transition State Theory

by Bruce C. Garrett, Environmental Molecular Sciences Laboratory, Pacific Northwest Laboratory, Richland, Washington

Yao-Yuan Chuang and Donald G. Truhlar, Department of Chemistry and Super Computer Institute, University of Minnesota, MN 55455-0431

and interfaced to NWChem by

Ricky A. Kendall, Scalable Computing Laboratory, Ames Laboratory and Iowa State University, Ames, IA 50011

Theresa L. Windus, Environmental Molecular Sciences Laboratory, Pacific Northwest Laboratory, Richland, Washington

If you use the DIRDYVTST portion of NWChem, please use following citation in addition to the usual NWChem citation:

DIRDYVTST, Yao-Yuan Chuang and Donald G. Truhlar, Department of Chemistry and Super Computer Institute,

```
University of Minnesota; Ricky A. Kendall,Scalable Computing
Laboratory, Ames Laboratory and Iowa State
```

University; Bruce C. Garrett and Theresa L. Windus, Environmental Molecular Sciences Laboratory,

Pacific Northwest Laboratory.

Introduction

By using DIRDYVTST, a user can carry out electronic structure calculations with NWChem and use the resulting energies, gradients, and Hessians for direct dynamics calculations with POLYRATE. This program prepares the file30 input for POLYRATE from NWChem electronic structure calculations of energies, gradients and Hessians at the reactant, product, and saddle point geometries and along the minimum energy path. Cartesian geometries for the reactants, products, and saddle points need to be input to this program; optimization of geometries is not performed in this program. Note that DIRDYVTST is based on the DIRDYGAUSS program and is similar to two other programs: DDUTILITIES and GAUSSRATE. Users of this module are encouraged to read the POLYRATE manual since they will need to create the file fu5 input to run calculations with POLYRATE.

Notes about the code:

Input. The code has been written to parallel, as much as possible, the POLYRATE code.

Output. There is one default output file for each DIRDYVTST run - .file30.

Integrators for following the reaction path. Currently the Euler and three Page-McIver (PM) methods are implemented. The PM methods are the local quadratic approximation (LQA), the corrected LQA (CLQA), and the cubic (CUBE) algorithm. The PM methods are implemented so that the Hessian can be reused at intermediate steps at which only the gradient is updated.

Files

Test runs are located in directories in \$NWCHEM_TOP/QA/tests. Test runs are available for two systems: $H + H_2$ and $OH + H_2$.

The $H + H_2$ test uses the Euler integration method at the SCF/3-21G level of theory to calculate points along the reaction path. This test is located in the $NWCHEM_TOP/QA/tests/h3tr1$ directory.

The $OH + H_2$ test uses the Page-McIver CUBE algorithm to calculate points on the SCF/3-21G surface and does additional single point calculations at the SCF/6-31G* level of theory. This test is located in the \$NWCHEM_TOP/QA/tests/oh3tr3 directory.

Note: These tests are set up with SCF, however, other levels of theory can be used. The initial hessian calculations at the reactants, products and saddle point can cause some problems when numerical hessians are required (especially when there is symmetry breaking in the wavefunction).

Detailed description of the input

The input consists of keywords for NWChem and keywords related to POLYRATE input. The first set of inputs are for NWChem with the general input block of the form:

```
DIRDYVTST [autosym [real tol default 1d-2] noautosym]
  [THEORY <string theory> [basis <string basis default "ao
  basis">]\
        [ecp <string ecp>][input <string
  input>
      [SPTHEORY <string theory> [basis <string basis default "ao
  basis">] \
        [ecp <string ecp>] [input <string
  input>]
        [ecp <string ecp>] [input <string
  input>]]
    ...
  END
```

Use of symmetry

The use of symmetry in the calculation is controlled by the keyword autosym | noautosym which is used as described in the geometry directive. Autosym is on by default. A couple words of warning here. The tolerance related to autosym can cause problems when taking the initial step off of the transition state. If the tolerance is too large and the initial step relatively small, the resulting geometry will be close to a higher symmetry than is really wanted and the molecule will be symmetrized into the higher symmetry. To check this, the code prints out the symmetry at each geometry along the path. It is up to the user to check the symmetry and make sure that it is the required one. In preverse cases, the user may need to turn autosym off (noautosym) if changing the tolerance doesn't produce the desired results. In the case that autosym is used, the user does not need to worry about the different alignment of the molecule between NWChem and POLYRATE, this is taken care of internally in the DIRDYVTST module.

Basis specification

The basis name on the theory or sptheory directive is that specified on a basis set directive and not the name of a standard basis in the library. If not specified, the basis set for the sptheory defaults to the theory basis which defaults to "ao basis".

Effective core potentials

If an effective core potential is specified in the usual fashion outside of the DIRDYVTST input then this will be used in all calculations. If an alternative ECP name (the name specified on the ECP directive in the same manner as done for basis sets) is specified on one of the theory directives, then this ECP will be used in preference for that level of theory.

General input strings

For many purposes, the ability to specify the theory, basis and effective core potential is adequate. All of the options for each theory are determined from their independent input blocks. However, if the same theory (e.g., DFT) is to be used with different options for theory and sptheory, then the general input strings must be used. These strings are processed as NWChem input each time the theoretical calculation is invoked. The strings may contain any NWChem input, except for options pertaining to DIRDYVTST and the task directive. The intent is that the strings be used just to control the options pertaining to the theory being used.

A word of caution. Be sure to check that the options are producing the desired results. Since the NWChem database is persistent, the input strings should fully define the calculation you wish to have happen.

For instance, if the theory model is DFT/LDA/3-21g and the sptheory model is DFT/B3LYP/6-311g**, the DIRDYVTST input might look like this

```
dirdyvtst
  theory dft basis 3-21g input "dft\; xc\; end"
  sptheory dft basis 6-311g** input "dft\; xc b3lyp\; end"
  ....
end
```

The empty XC directive restores the default LDA exchange-correlation functional. Note that semi-colons and other quotation marks inside the input string must be preceded by a backslash to avoid special interpretation.

POLYRATE related options

These keyword options are similar to the POLYRATE input format, except there are no ENERGETICS, OPTIMIZATION, SECOND, TUNNELING, and RATE sections.

GENERAL section

The GENERAL section has the following format:

```
• GENERAL
```

```
[TITLE <string title>]
ATOMS
    <integer num> <string tag> [<real mass>]
    ...
END
[SINGLEPOINT]
[SAVEFILE (vecs || hess || spc)
```

Descriptions

TITLE is a keyword that allows the user to input a description of the calculation. In this version, the user can only have a single-line description.

For example:

```
TITLE Calculation of D + HCl reaction
```

ATOMS is a list keyword that is used to input a list of the atoms. It is similar to POLYRATE in that the order of the atom and the atomic symbol are required in a single line. If isotope of the element is considered then the atomic mass is required in units of amu.

For example:

ATOMS		
1	Н	2.014
2	Н	
3	Cl	
END		

SINGLEPOINT is a keyword that specifies that a single point calculation is to be performed at the reactants, products and saddle point geometries. The type of single point calculation is specified in the sptheory line.

SAVEFILE is a keyword that specifies that NWChem files are to be saved. Allowed values of variable input to SAVEFILE are vecs, hess, and spc for saving the files base theory movecs, base theory hessian and singlepoint calculation movecs.

REACT1, REACT2, PROD1, PROD2, and START sections

These sections have the following format:

REACT1 and REACT2 are input for each of the reactants and PROD1 and PROD2 are input for each of the products. REACT1 and PROD1 are required. START is the input for the transition state if one exists, or starting point to follow downhill the MEP.

Descriptions

GEOM is a list keyword that indicates the geometry of the molecule in Cartesian coordinates with atomic unit.

For example:

GEOM			
1	0.0	0.0	0.0
2	0.0	0.0	1.5
=ND			

SPECIES is a variable keyword that indicates the type of the molecule. Options are: ATOMIC (atomic reactant or product), LINRP (linear reactant or product), NONLINRP (nonlinear reactant or product), LINTS (linear transition state), and NONLINTS (nonlinear transition state).

For example:

SPECIES atomic

PATH section

The Path section has the format:

*PATH

```
[SCALEMASS <real scalemass default 1.0>]
[SSTEP <real sstep default 0.01>]
[SSAVE <real ssave default 0.1>]
[SHESS <real shess default SSAVE>]
[SLP <real slp default 1.0>]
[SLM <real slm default -1.0>]
[SIGN (REACTANT || PRODUCT default REACTANT)]
[INTEGRA (EULER || LQA || CLQA || CUBE default EULER)]
[PRINTFREQ (on || off default off)]
```

Descriptions

SCALEMASS is a variable keyword that indicates the arbitrary mass (in amu) used for mass-scaled Cartesian coordinates. This is the variable called mu in published papers. Normally, this is taken as either 1.0 amu or, for bimolecular reactions, as the reduced mass

of relative translation of the reactants.

SSTEP is a variable keyword that indicates the numerical step size (in bohrs) for the gradient grid. This is the step size for following the minimum energy path.

SSAVE is a variable keyword that indicates the numerical step size (in bohrs) for saving the Hessian grid. At each save point the potential and its first and second derivatives are recalculated and written to the .file30 file. For example, if SSTEP=0.01 and SSAVE=0.1, then the potential information is written to .file30 every 10 steps along the gradient grid.

SHESS is a variable keyword that indicates the numerical step size (in bohrs) for recomputing the Hessian when using a Page-McIver integrator (e.g., LQA, CLQA, or CUBE). For Euler integration SHESS = SSAVE. For intermediate points along the gradient grid, the Hessian matrix from the last Hessian calculation is reused. For example, if SSTEP=0.01 and SHESS=0.05, then the Hessian matrix is recomputed every 5 steps along the gradient grid.

SLP is a variable keyword that indicates the positive limit of the reaction coordinate (in bohrs).

SLM is a variable keyword that indicates the negative limit of the reaction coordinate (in bohrs).

SIGN is a variable keyword used to ensure the conventional definition of the sign of s, s < 0 for the reactant side and s > 0 for the product side, is followed. PRODUCT should be used if the eigenvector at the saddle point points toward the product side and REACTANT if the eigenvector points toward the reactant side.

INTEGRA is a variable keyword that indicates the integration method used to follow the reaction path. Options are: EULER, LQA, CLQA, and CUBE.

PRINTFREQ is a variable keyword that indicates that projected frequencies and eigenvectors will be printed along the MEP.

Restart

DIRDYVTST calculations should be restarted through the normal NWChem mechanism. The user needs to change the start directive to a restart directive and get rid of any information that will overwrite important information in the RTDB. The file.db and file.file30 need to be available for the calculation to restart properly.

Example

This is an example that creates the file30 file for POLYRATE for $H + H_2$. Note that the multiplicity is that of the entire supermolecule, a doublet. In this example, the initial energies, gradients, and Hessians are calculated at the UHF/3-21G level of theory and the singlepoint calculations are calculated at the MP2/cc-pVDZ level of theory with a tighter convergence threshold than the first SCF.

```
start h3test
```

```
basis
  h library 3-21G
end
basis singlepoint
  h library cc-pVDZ
```

end
scf uhf doublet thresh 1.0e-6 end
<pre>dirdyvtst autosym 0.001 theory scf input "scf\; uhf\; doublet\; thresh 1.0e-06\; end" sptheory mp2 basis singlepoint input \ "scf\; uhf\; doublet\; thresh 1.0e-07\; end" *GENERAL TITLE Test run: H+H2 reaction, Page-McIver CLQA algorithm, no restart</pre>
ATOMS 1 H 2 H 3 H END
SINGLEPOINT
*REACT1 GEOM 1 0.0 0.0 0.0 2 0.0 0.0 1.3886144 END
SPECIES LINRP
*REACT2 GEOM 3 0.0 0.0 190.3612132 END
SPECIES ATOMIC
*PROD2 GEOM 1 0.0 0.0 190.3612132 END
SPECIES ATOMIC
*PROD1
GEOM 2 0.0 0.0 1.3886144 3 0.0 0.0 0.0 END

SPECIES	LINRP		
*START			
GEOM 1 0.0 2 0.0 3 0.0 END	0.0 -1.76531973 0.0 0.0 0.0 1.76531973		
SPECIES	LINTS		
*PATH SSTEP 0 SSAVE 0 SLP 0 SLM -0 SCALEMASS INTEGRA end	.05 .05 .50 5 0.6718993 CLQA		
task dirdyvtst			

Examples

Release65:Sample

__NOTITLE__

Sample input files

Water SCF calculation and geometry optimization in a 6-31g basis

The Getting Started input file performs a geometry optimization in a single task. A single point SCF energy calculation is performed and then restarted to perform the optimization (both could of course be performed in a single task).

Job 1.Single point SCF energy

```
start h2o
title "Water in 6-31g basis set"
geometry units au
  0
         0.0000000
                       0.00000000
                                      0.0000000
  Н
         0.0000000
                       1.43042809
                                     -1.10715266
  Н
         0.00000000
                       -1.43042809
                                     -1.10715266
end
basis
  H library 6-31g
  0 library 6-31g
end
task scf
```

The final energy should be -75.983998.

Job 2.Restarting and perform a geometry optimization

```
restart h2o
title "Water geometry optimization"
task scf optimize
```

There is no need to specify anything that has not changed from the previous input deck, though it will do no harm to repeat it.

Compute the polarizability of Ne using finite field

Job 1.Compute the atomic energy

```
start ne
title "Neon"
geometry; ne 0 0 0; end
basis spherical
   ne library aug-cc-pvdz
end
scf; thresh 1e-10; end
task scf
```

The final energy should be -128.496350.

Job 2.Compute the energy with applied field

An external field may be simulated with point charges. The charges here apply a field of magnitude 0.01 atomic units to the atom at the origin. Since the basis functions have not been reordered by the additional centers we can also restart from the previous vectors, which is the default for a restart job.

```
restart ne
title "Neon in electric field"
geometry units atomic
   bq1 0 0 100 charge 50
   ne 0 0 0
   bq2 0 0 -100 charge -50
end
task scf
```

The final energy should be -128.496441, which together with the previous field-free result yields an estimate for the polarizability of 1.83 atomic units. Note that by default NWChem does not include the interaction between the two point charges in the total energy.

SCF energy of H₂CO using ECPs for C and O

The following will compute the SCF energy for formaldehyde with ECPs on the Carbon and Oxygen centers.

```
title "formaldehyde ECP deck"
start ecpchho
geometry units au
C 0.000000 0.000000 -1.025176
0 0.000000 0.000000 1.280289
H 0.000000 1.767475 -2.045628
H 0.000000 -1.767475 -2.045628
end
```

basis C SP 0.1675097360D+02 -0.7812840500D-01 0.3088908800D-01 0.2888377460D+01 -0.3741108860D+00 0.2645728130D+00 0.6904575040D+00 0.1229059640D+01 0.8225024920D+00 C SP 0.1813976910D+00 0.100000000D+01 0.100000000D+01 C D 0.800000000D+00 0.100000000D+01 C F 0.1000000000D+01 0.100000000D+01 0 SP 0.1842936330D+02 -0.1218775590D+00 0.5975796600D-01 0.4047420810D+01 -0.1962142380D+00 0.3267825930D+00 0.1093836980D+01 0.1156987900D+01 0.7484058930D+00 0 SP 0.2906290230D+00 0.100000000D+01 0.100000000D+01 0 D 0.800000000D+00 0.100000000D+01 0 F 0.1100000000D+01 0.100000000D+01 H S 0.1873113696D+02 0.3349460434D-01 0.2825394365D+01 0.2347269535D+00 0.6401216923D+00 0.8137573262D+00 H S 0.1612777588D+00 0.100000000D+01 end еср C nelec 2 C ul 1 80.000000 -1.6000000 1 30,000000 -0.40000002 0.5498205 -0.03990210 Сs 0 0.7374760 0.63810832 0 135.2354832 11.00916230 2 8.5605569 20.13797020 Ср 10.6863587 2 -3.24684280 2 23.4979897 0.78505765 0 nelec 2 0 ul 1 80.000000 -1.600000001 30.000000 -0.4000000 2 1.0953760 -0.06623814 0 s

	0	0.9212952	0.39552179
	0	28.6481971	2.51654843
	2	9.3033500	17.04478500
0 р			
	2	52.3427019	27.97790770
	2	30.7220233	-16.49630500
end			

```
scf
vectors input hcore
maxiter 20
end
```

task scf

This should produce the following output:

```
Final RHF results

Total SCF energy = -22.507927218024

One electron energy = -71.508730162974

Two electron energy = 31.201960019808

Nuclear repulsion energy = 17.798842925142
```

MP2 optimization and CCSD(T) on nitrogen

The following performs an MP2 geometry optimization followed by a CCSD(T) energy evaluation at the converged geometry. A Dunning correlation-consistent triple-zeta basis is used. The default of Cartesian basis functions must be overridden using the keyword spherical on the BASIS directive. The 1s core orbitals are frozen in both the MP2 and coupled-cluster calculations (note that these must separately specified). The final MP2 energy is -109.383276, and the CCSD(T) energy is -109.399662.

```
start n2
```

```
geometry
symmetry d2h
n 0 0 0.542
end
basis spherical
n library cc-pvtz
end
mp2
freeze core
end
task mp2 optimize
ccsd
freeze core
```

end

task ccsd(t)

Release65:Geometry examples

__NOTITLE___

Examples of geometries using symmetry

Below are examples of the use of the SYMMETRY directive in the compound GEOMETRY directive. The z axis is always the primary rotation axis. When in doubt about which axes and planes are used for the group elements, the keyword print may be added to the SYMMETRY directive to obtain this information.

C_s methanol

The σ_h plane is the xy plane.

geome	etry units angs	troms	
С	0.11931097	-0.66334875	0.0000000
Н	1.20599017	-0.87824237	0.0000000
Н	-0.32267592	-1.15740001	0.89812652
0	-0.01716588	0.78143468	0.0000000
Н	-1.04379735	0.88169812	0.0000000
sym	metry cs		
end			

C_{2v} water

The z axis is the C_2 axis and the σ_v may be either the xz or the yz planes.

D_{2h} acetylene

Although acetylene has symmetry $D_{\infty h}$ the subgroup D_{2h} includes all operations that interchange equivalent atoms which is what determines how much speedup you gain from using symmetry in building a Fock matrix.

The C_2 axes are the x, y, and z axes. The σ planes are the xy, xz and yz planes. Generally, the unique atoms are placed to use the z as the primary rotational axis and use the xz or yz planes as the σ plane.

```
geometry units au
symmetry group d2h
C 0.00000000 0.00000000 -1.115108538
```

H 0.00000000 0.00000000 -3.106737425 end

D_{2h} ethylene

The C_2 axes are the x, y, and z axes. The σ planes are the xy, xz and yz planes. Generally, the unique atoms are placed to use the z as the primary rotational axis and use the xz or yz planes as the σ plane.

```
geometry units angstroms
   C 0 0 0.659250
   H 0 0.916366 1.224352
   symmetry d2h
end
```

T_d methane

For ease of use, the primary C_3 axis should be the x=y=z axis. The 3 C_2 axes are the x, y, and z.

```
geometry units au

c 0.0000000 0.0000000 0.0000000

h 1.1828637 1.1828637 1.1828637

symmetry group Td

end
```

Ih buckminsterfullerene

One of the C_5 axes is the z axis and the point of inversion is the origin.

```
geometry units angstroms # Bonds = 1.4445, 1.3945
symmetry group Ih
c -1.2287651 0.0 3.3143121
end
```

S_4 porphyrin

The S_4 and C_2 rotation axis is the z axis. The reflection plane for the S_4 operation is the xy plane.

```
geometry units angstroms
   symmetry group s4
   fe
                            0.000 0.000
                     0.000
   h
                     2.242
                            6.496 -3.320
                     1.542 4.304 -2.811
   h
                     1.947
                            6.284 -2.433
   С
                     1.568 4.987 -2.084
   С
                     2.252 8.213 -1.695
   h
                     1.993 7.278 -1.458
   С
                     5.474 -1.041 -1.143
   h
                     1.234 4.676 -0.765
   с
```

h	7.738	-1.714	-0.606
С	0.857	3.276	-0.417
h	1.380	-4.889	-0.413
С	1.875	2.341	-0.234
h	3.629	3.659	-0.234
С	0.493	-2.964	-0.229
С	1.551	-3.933	-0.221
С	5.678	-1.273	-0.198
С	1.656	6.974	-0.144
С	3.261	2.696	-0.100
n	1.702	0.990	-0.035
end			

D_{3h} iron penta-carbonyl

The C_3 axis is the z axis. The σ_h plane is the xy plane. One of the perpendicular C_2 axes is the x=y axis. One of the σ_v planes is the plane containing the x=y axis and the z axis. (The other axes and planes are generated by the C_3 operation.)

```
geometry units au
  symmetry group d3h
  fe
             0.0
                          0.0
                                        0.0
             0.0
                           0.0
                                        3.414358
  с
             0.0
                          0.0
                                        5.591323
  0
             2.4417087
                          2.4417087
                                        0.0
  с
                          3.9810552
             3.9810552
                                        0.0
  0
end
```

D_{3d} sodium crown ether

The C_3 axis is the z axis. The point of inversion is the origin. One of the perpendicular C_2 axes is the x=y axis. One of the σ_d planes is the plane containing the -x=y axis and the z axis.

Note that the oxygen atom is rotated in the x-y plane 15 degrees away from the y-axis so that it lies in a mirror plane. There is a total of six atoms generated from the unique oxygen, in contrast to twelve from each of the carbon and hydrogen atoms.

```
geometry units au
  symmetry D3d
        .0000000000
 NA
                        .0000000000
                                       .0000000000
 0
       1.3384771885
                       4.9952647969
                                       .1544089284
 Н
       6.7342048019
                     -0.6723850379
                                      2.6581562148
 С
       6.7599180056
                     -0.4844977035
                                       .6136583870
       8.6497577017
                       0.0709194071
                                       .0345361934
 Н
```

end

C_{3v} ammonia

The C_3 axis is the z axis. One of the σ_v planes is the plane containing the x=y axis and the z axis.

```
geometry units angstroms
N 0 0 -0.055
H 0.665 0.665 -0.481
symmetry c3v
end
```

D_{6h} benzene

The C_6 axis is the z axis. The point of inversion is the origin. One of the 6 perpendicular C'_2 axes is the x=y axis. (-x=y works as a C''_2 axis.) The σ_h plane is the xy plane. The σ_d planes contain the C''_2 axis and the z axis. The σ_v planes contain the C''_2 axis and the z axis.

```
geometry units au
  C 1.855 1.855 0
  H 3.289 3.289 0
  symmetry D6h
end
```

 $C_{3h} BO_3H_3$

The C_3 axis is the z axis. The σ_h plane is the xy plane.

```
geometry units au
   b 0 0 0
   o 2.27238285 1.19464491 0.00000000
   h 2.10895420 2.97347707 0.00000000
   symmetry C3h
end
```

D_{5d} ferrocene

The C_5 axis is the z axis. The center of inversion is the origin. One of the perpendicular C_2 axes is the x axis. One of the σ_d planes is the yz plane.

```
geometry units angstroms
   symmetry d5d
   fe 0 0 0
    c 0 1.194 1.789
    h 0 2.256 1.789
end
```

 $C_{4v} SF_5Cl$

The C_4 axis is the z axis. The σ_v planes are the yz and the xz planes. The σ_d planes are: 1) the plane containing the x=y axis and the z axis and 2) the plane containing the -x=y axis and the z axis.

```
geometry units au
S 0.00000000 0.00000000 -0.14917600
Cl 0.00000000 0.00000000 4.03279700
F 3.13694200 0.00000000 -0.15321800
F 0.00000000 0.00000000 -3.27074500
symmetry C4v
end
```

C_{2h} trans-dichloroethylene

The C_2 axis is the z axis. The origin is the inversion center. The σ_h plane is the xy plane.

```
geometry units angstroms
   C  0.65051239 -0.08305064 0
   Cl 1.75249381  1.30491767 0
   H  1.14820954 -1.04789741 0
   symmetry C2h
end
```

 $D_{2d} CH_2CCH_2$

The C_2 axis is the z axis (z is also the S_4 axis). The x and y axes are the perpendicular C'_2 s. The σ_d planes are: 1) the plane containing the x=y axis and the z axis and 2) the plane containing the -x=y axis and the z axis.

```
geometry units angstroms
symmetry d2d
c 0 0 0
c 0 0 1.300
h 0.656 0.656 1.857
end
```

D_{5h} cyclopentadiene anion

The C_5 axis is the z axis (z is also the S_5 axis). The y axis is one of the perpendicular C_2 axes. The σ_h plane is the xy plane and one of the σ_d planes is the yz plane.

```
charge -1
geometry units angstroms
  symmetry d5h
  c 0 1.1853 0
   h 0 2.2654 0
end
```

D_{4h} gold tetrachloride

The C_4 axis is the z axis (z is also the S_4 axis). The C'_2 axes are the x and y axes and the C''_2 axes are the x=y axis and the x=-y axis. The inversion center is the origin. The σ_h plane is the xy plane. The σ_v planes are the xz and yz planes and the σ_d planes are 1) the plane containing the x=-y axis and the z axis and 2) the plane containing the x=y axis and the z axis.

```
geometry units au
Au 0 0 0
Cl 0 4.033 0
symmetry D4h
```

 end

Article Sources and Contributors

Release65:NWChem Documentation Source: http://nwchemweb.pnl.gov/index.php?oldid=6858 Contributors: Bert, Niri, Silvia

Release65:Capabilities Source: http://nwchemweb.pnl.gov/index.php?oldid=6720 Contributors: Bert, Silvia Compiling NWChem Source: http://nwchemweb.pnl.gov/index.php?oldid=6382 Contributors: Bert, Edoapra, Huub, Marat, Niri Release65:Getting Started Source: http://nwchemweb.pnl.gov/index.php?oldid=6722 Contributors: Bert, Silvia Release65:Top-level Source: http://nwchemweb.pnl.gov/index.php?oldid=6724 Contributors: Bert, Silvia Release65:Nwarch Source: http://nwchemweb.pnl.gov/index.php?oldid=6726 Contributors: Bert, Silvia Release65:Running Source: http://nwchemweb.pnl.gov/index.php?oldid=6728 Contributors: Bert, Silvia Release65:Charge Source: http://nwchemweb.pnl.gov/index.php?oldid=6730 Contributors: Bert, Silvia Release65:Geometry Source: http://nwchemweb.pnl.gov/index.php?oldid=6732 Contributors: Bert, Silvia Release65:Basis Source: http://nwchemweb.pnl.gov/index.php?oldid=6734 Contributors: Bert, Edoapra, Huub, Silvia Release65:ECP Source: http://nwchemweb.pnl.gov/index.php?oldid=6759 Contributors: Bert, Silvia Release65:Relativistic All-electron Approximations Source: http://nwchemweb.pnl.gov/index.php?oldid=6761 Contributors: Bert, Silvia Release65:Hartree-Fock Theory for Molecules Source: http://nwchemweb.pnl.gov/index.php?oldid=6764 Contributors: Bert, Edoapra, Huub, Silvia Release65:Density Functional Theory for Molecules Source: http://nwchemweb.pnl.gov/index.php?oldid=6766 Contributors: Bert, Edoapra, Huub, Niri, Silvia Release65:Excited-State Calculations Source: http://nwchemweb.pnl.gov/index.php?oldid=6768 Contributors: Bert, Niri, Silvia Release65:RT-TDDFT Source: http://nwchemweb.pnl.gov/index.php?oldid=6770 Contributors: Bert, Lopata, Silvia Release65:Plane-Wave Density Functional Theory Source: http://nwchemweb.pnl.gov/index.php?oldid=6772 Contributors: Bert, Silvia Release65:TCE Source: http://nwchemweb.pnl.gov/index.php?oldid=6774 Contributors: Bert, Karol, Silvia Release65:MP2 Source: http://nwchemweb.pnl.gov/index.php?oldid=6776 Contributors: Bert, Edoapra, Silvia Release65:CCSD Source: http://nwchemweb.pnl.gov/index.php?oldid=6778 Contributors: Bert, Edoapra, Silvia Release65:Multiconfiguration SCF Source: http://nwchemweb.pnl.gov/index.php?oldid=6780 Contributors: Bert, Silvia Release65:SELCI Source: http://nwchemweb.pnl.gov/index.php?oldid=6782 Contributors: Bert, Huub, Silvia Release65:Prepare Source: http://nwchemweb.pnl.gov/index.php?oldid=6787 Contributors: Bert, Silvia Release65:MD Source: http://nwchemweb.pnl.gov/index.php?oldid=6789 Contributors: Bert, Silvia Release65:Analysis Source: http://nwchemweb.pnl.gov/index.php?oldid=6791 Contributors: Bert, Silvia Release65:COSMO Solvation Model Source: http://nwchemweb.pnl.gov/index.php?oldid=6796 Contributors: Bert, Huub, Marat, Silvia Release65:SMD Model Source: http://nwchemweb.pnl.gov/index.php?oldid=6798 Contributors: Huub. Niri, Silvia Release65:VEM Model Source: http://nwchemweb.pnl.gov/index.php?oldid=6850 Contributors: Huub. Niri. Silvia Release65:ONIOM Source: http://nwchemweb.pnl.gov/index.php?oldid=6802 Contributors: Bert, Huub, Silvia Release65:OMMM Source: http://nwchemweb.pnl.gov/index.php?oldid=6804 Contributors: Bert. Silvia Release65:Bg Source: http://nwchemweb.pnl.gov/index.php?oldid=6806 Contributors: Bert, Niri, Silvia Release65:Constraints Source: http://nwchemweb.pnl.gov/index.php?oldid=6811 Contributors: Bert, Silvia Release65:Geometry Optimization Source: http://nwchemweb.pnl.gov/index.php?oldid=6813 Contributors: Bert, Edoapra, Silvia Release65:Hessians & Vibrational Frequencies Source: http://nwchemweb.pnl.gov/index.php?oldid=6815 Contributors: Bert, Huub, Silvia Release65:Nudged Elastic Band (NEB) and Zero Temperature String Methods Source: http://nwchemweb.pnl.gov/index.php?oldid=6817 Contributors: Bert, Bylaska, Silvia Release65:Properties Source: http://nwchemweb.pnl.gov/index.php?oldid=6822 Contributors: Bert, Niri, Silvia Release65:ESP Source: http://nwchemweb.pnl.gov/index.php?oldid=6824 Contributors: Bert, Edoapra, Silvia Release65:DPLOT Source: http://nwchemweb.pnl.gov/index.php?oldid=6826 Contributors: Bert, Edoapra, Huub, Niri, Silvia Release65:Electron Transfer Source: http://nwchemweb.pnl.gov/index.php?oldid=6831 Contributors: Bert, Silvia Release65:VSCF Source: http://nwchemweb.pnl.gov/index.php?oldid=6833 Contributors: Bert, Silvia Release65:DNTMC Source: http://nwchemweb.pnl.gov/index.php?oldid=6835 Contributors: Bert, Huub, Silvia Release65:CCCA Source: http://nwchemweb.pnl.gov/index.php?oldid=6837 Contributors: Bert, Silvia Release65:Python Source: http://nwchemweb.pnl.gov/index.php?oldid=6839 Contributors: Bert, Edoapra, Silvia Release65:Interface Source: http://nwchemweb.pnl.gov/index.php?oldid=6841 Contributors: Bert, Silvia Release65:Sample Source: http://nwchemweb.pnl.gov/index.php?oldid=6851 Contributors: Bert, Silvia Release65:Geometry examples Source: http://nwchemweb.pnl.gov/index.php?oldid=6853 Contributors: Bert, Silvia

Image Sources, Licenses and Contributors

 File:Zmat1.jpg
 Source: http://nwchemweb.pnl.gov/index.php?title=File:Zmat1.jpg
 unknownContributors: Huub van Dam, WikiSysop

 File:Zmat2.jpg
 Source: http://nwchemweb.pnl.gov/index.php?title=File:Zmat2.jpg
 unknownContributors: Huub van Dam, WikiSysop

 File:Zmat3.jpg
 Source: http://nwchemweb.pnl.gov/index.php?title=File:Zmat3.jpg
 unknownContributors: Huub van Dam, WikiSysop

File:RT_TDDFT_h2o_td_dipoles.png Source: http://nwchemweb.pnl.gov/index.php?title=File:RT_TDDFT_h2o_td_dipoles.png unknownContributors:

Lopata

File:RT_TDDFT_h2o_abs_spectrum.png Source: http://nwchemweb.pnl.gov/index.php?title=File:RT_TDDFT_h2o_abs_spectrum.png unknownContributors: Lopata

File:RT_TDDFT_h2o_resonant_spec_field.png Source: http://nwchemweb.pnl.gov/index.php?title=File:RT_TDDFT_h2o_resonant_spec_field.png unknownContributors: Lopata

File:RT_TDDFT_h2o_resonant_td.png Source: http://nwchemweb.pnl.gov/index.php?title=File:RT_TDDFT_h2o_resonant_td.png unknownContributors: Lopata

File:RT_TDDFT_tcne_td_charge.png Source: http://nwchemweb.pnl.gov/index.php?title=File:RT_TDDFT_tcne_td_charge.png unknownContributors: Lopata

 $file:s2-bomd.png \ Source: \ http://nwchemweb.pnl.gov/index.php?title=File:S2-bomd.png \ unknownContributors: \ Bylaska \ Saurce: \ http://nwchemweb.pnl.gov/index.php?title=File:S2-bomd.png \ unknownContributors: \ Bylaska \ Byla$

file:boron.png Source: http://nwchemweb.pnl.gov/index.php?title=File:Boron.png unknownContributors: Bylaska

file:diamond.png Source: http://nwchemweb.pnl.gov/index.php?title=File:Diamond.png unknownContributors: Bylaska

 $file: catom-pspw.nwout\ outributors:\ by lask a start outributor outributor$

file:diamondfcc.restricted_band.dat Source: http://nwchemweb.pnl.gov/index.php?title=File:Diamondfcc.restricted_band.dat unknownContributors: Bylaska

 File:Diamond-dos.dos.dat
 Source: http://nwchemweb.pnl.gov/index.php?title=File:Diamond-dos.dos.dat
 unknownContributors: Bylaska

 file:Brucite-small.jpg
 Source: http://nwchemweb.pnl.gov/index.php?title=File:Brucite-small.jpg
 unknownContributors: Bylaska

 File:ea-ip-initial-guess.png
 Source: http://nwchemweb.pnl.gov/index.php?title=File:Ea-ip-initial-guess.png
 unknownContributors: Bylaska